




FCC RF EXPOSURE REPORT

Applicant	: Measurement Specialties (China), Ltd.
Address	: No. 26 Langshan Road Shenzhen High-Tech Park (North) Nanshan District Shenzhen 518057 China
Equipment	: Wireless Vibration Sensor
Model No.	: 8511N-EX, 8511N-NX , 8531N-EX, 8531N-NX
Trade Name	: TE Connectivity
FCC ID.	: 2A85PA85X1N

I HEREBY CERTIFY THAT :

The sample was received on Oct.08, 2022 and the testing was completed on Oct. 24, 2022 at CerpPASS Technology Corp. The test result refers exclusively to the test presented test model / sample. Without written approval of CerpPASS Technology Corp., the test report shall not be reproduced except in full.

Approved by:


Leevin Li /Supervisor



Contents

1. Test Configuration of Equipment under Test..... 4

1.1 Feature of Equipment 4

1.2 General Information of Test..... 5

2. Radio Frequency Exposure 6



History of this test report

■ Original.

□ Additional attachment as following record:

Attachment No.	Issue Date	Description
DEFJ2209070	Oct. 31, 2022	Original



1. Test Configuration of Equipment under Test

1.1 Feature of Equipment

Equipment	Wireless Vibration Sensor
Model Name	8511N-EX,8511N-NX ,8531N-EX, 8531N-NX
Model Description	ATEX product: 8511N-EX is uniaxial accelerometer. 8531N-EX is triaxial accelerometer. Non-ATEX product: 8511N-NX is uniaxial accelerometer. 8531N-NX is triaxial accelerometer Model 8511N-EX and 8531N-EX were chosen for final test
Frequency Range	2400MHz-2483.5MHz
Modulation Type	GFSK
Data Rate	GFSK: 1Mbps, 2Mbps, 125Kbps, 500Kbps
Antenna Gain.	2.4dBi
Antenna Type	PIFA Antenna
Working Temperature	-40°C to +60°C
Operating Voltage	DC 3.6V from Battery

Note: For more details, please refer to the User's manual of the EUT.



1.2 General Information of Test

Test Site	CerpPASS Technology Corporation(CerpPASS Laboratory) Address: Room 102, No. 5, Xing'an Road, Chang'an Town, Dongguan City, Guangdong Province Tel: +86-769-8547-1212 Fax: +86-769-8547-1912
FCC Designation No.:	CN1288



2. Radio Frequency Exposure

Device category	☐ Portable (<20cm separation) ☒ Mobile (>20cm separation)
Exposure classification	☐ Occupational/Controlled exposure (S = 5mW/cm ²) ☒ General Population/Uncontrolled exposure (S=1mW/cm ²)
Antenna diversity	☒ Single antenna ☐ Multiple antennas ☐ Tx diversity ☐ Rx diversity ☐ Tx/Rx diversity
Evaluation applied	☒ MPE Evaluation* ☐ SAR Evaluation ☐ N/A

TEST RESULTS

No non-compliance noted.

Calculation

Given $E = \frac{\sqrt{30 \times P \times G}}{d}$ & $S = \frac{E^2}{3770}$

Where E = Field strength in Volts / meter
 P = Power in Watts
 G = Numeric antenna gain
 d = Distance in meters
 S = Power density in milliwatts / square centimeter

Combining equations and re-arranging the terms to express the distance as a function of the remaining variables yields:

$$S = \frac{30 \times P \times G}{3770d^2}$$

Changing to units of mW and cm, using:

$$P \text{ (mW)} = P \text{ (W)} / 1000 \text{ and}$$

$$d \text{ (cm)} = d \text{ (m)} / 100$$

Yields

$$S = \frac{30 \times (P/1000) \times G}{3770 \times (d/100)^2} = 0.0796 \times \frac{P \times G}{d^2} \text{ Equation 1}$$

Where d = Distance in cm
 P = Power in mW
 G = Numeric antenna gain
 S = Power density in mW / cm²

**Maximum Permissible Exposure**

Mode	Channel Frequency (MHz)	Max. Conducted output power (dBm)	Max. Tune up power (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)
Bluetooth LE	2402-2480	6.21	7.21	2.4	20	0.002

Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.

-----**End of the report** -----