

## MAXIMUM PERMISSIBLE EXPOSURE

KDB 447498 D01 Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies v06.

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

### EUT Specification

<b>FCC ID</b>	2A86W-N1
<b>EUT</b>	8 CH Wi-Fi Network Video Recorder
<b>Frequency band (Operating)</b>	<input type="checkbox"/> BT: 2.402GHz ~ 2.480GH <input checked="" type="checkbox"/> WLAN: 2.412GHz ~ 2.462GHz <input checked="" type="checkbox"/> RLAN: 5.180GHz ~ 5.240GHz <input checked="" type="checkbox"/> RLAN: 5.260GHz ~ 5.320GHz <input checked="" type="checkbox"/> RLAN: 5.500GHz ~ 5.700GHz <input checked="" type="checkbox"/> RLAN: 5.745GHz ~ 5.825GHz <input type="checkbox"/> Others:
<b>Device category</b>	<input type="checkbox"/> Portable (<20cm separation) <input checked="" type="checkbox"/> Mobile (>20cm separation) <input type="checkbox"/> Others: ___
<b>Exposure classification</b>	<input type="checkbox"/> Occupational/Controlled exposure <input checked="" type="checkbox"/> General Population/Uncontrolled exposure
<b>Antenna diversity</b>	<input type="checkbox"/> Single antenna <input checked="" type="checkbox"/> Multiple antennas <input type="checkbox"/> Tx diversity <input type="checkbox"/> Rx diversity <input type="checkbox"/> Tx/Rx diversity
<b>Max. output power</b>	module MT7628DAN: WiFi 2.4G ANT1: 14.89 dBm (0.0247W) WiFi 2.4G ANT2: 15.01 dBm (0.0249W) WiFi 2.4G MIMO: 16.97 dBm (0.0497W) module RTL8731BU: WiFi 2.4G: 14.64 dBm (0.0246W) WiFi 5.2G: 15.16 dBm (0.0246W) WiFi 5.3G: 15.54 dBm (0.0545W) WiFi 5.6G: 16.24 dBm (0.0501W) WiFi 5.8G: 16.53dBm (0.0607W)
<b>Antenna gain (Max)</b>	module MT7628DAN: WiFi 2.4G ANT1: 2.69dBi WiFi 2.4G ANT2: 2.69dBi

#### Shenzhen Anbotek Compliance Laboratory Limited

Address: 1/F., Building D, Sogood Science and Technology Park, Sanwei Community, Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China.  
 Tel: (86) 0755-26066440 Fax: (86) 0755-26014772 Email: service@anbotek.com



Hotline  
 400-003-0500  
 www.anbotek.com.cn



	module RTL8731BU: WiFi 2.4G: 2.10 dBi WiFi 5.2G: 4.45dBi WiFi 5.3G: 4.45dBi WiFi 5.6G: 4.90dBi WiFi 5.8G: 4.26dBi
<b>Evaluation applied</b>	<input checked="" type="checkbox"/> MPE Evaluation <input type="checkbox"/> SAR Evaluation

### Limits for Maximum Permissible Exposure(MPE)

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm <sup>2</sup> )	Average Time
<b>(A) Limits for Occupational/Control Exposures</b>				
300-1500	--	--	F/300	6
1500-100000	--	--	5	6
<b>(B) Limits for General Population/Uncontrol Exposures</b>				
300-1500	--	--	F/1500	30
1500-100000	--	--	1	30

### Shenzhen Anbotek Compliance Laboratory Limited

Address: 1/F., Building D, Sogood Science and Technology Park, Sanwei Community, Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China.  
 Tel: (86) 0755-26066440 Fax: (86) 0755-26014772 Email: service@anbotek.com



Hotline  
 400-003-0500  
[www.anbotek.com.cn](http://www.anbotek.com.cn)



## Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where

$P_d$  = Power density in mW/cm<sup>2</sup>

$P_{out}$  = output power to antenna in Mw

$G$  = gain of antenna in linear scale

$\pi$  = 3.1416

$R$  = distance between observation point and center of the radiator in cm

$P_d$  the limit of MPE. If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

## Max Measurement Result

Operating Mode	Measured Power	Tune up tolerance	Max. Tune up Power	Antenna Gain	Power density at 20cm	Power density Limits (mW/cm <sup>2</sup> )
	(dBm)	(dBm)	(dBm)	(dBi)	(mW/cm <sup>2</sup> )	
module MT7628DAN WiFi 2.4G ANT1	14.89	14.89 ±1	15.89	2.69	0.0144	1
module MT7628DAN WiFi 2.4G ANT2	15.01	15.01 ±1	16.01	2.69	0.0148	1
module RTL8731BU WiFi 2.4G	14.64	14.64 ±1	15.64	2.10	0.0118	1
module RTL8731BU WiFi 5.2G	15.16	15.16 ±1	16.16	4.45	0.0229	1
module RTL8731BU WiFi 5.3G	15.54	15.54 ±1	16.54	4.45	0.0250	1
module RTL8731BU WiFi 5.6G	16.24	16.24 ±1	17.24	4.90	0.0326	1
module RTL8731BU WiFi 5.8G	16.53	16.53 ±1	17.53	4.26	0.0301	1

### No. Applicable Simultaneous Transmission

1. module MT7628DAN WiFi 2.4G ANT1+module MT7628DAN WiFi 2.4G ANT2
2. module MT7628DAN WiFi 2.4G ANT1+module RTL8731BU WiFi 2.4G
3. module MT7628DAN WiFi 2.4G ANT1+module RTL8731BU WiFi 5.2G
4. module MT7628DAN WiFi 2.4G ANT1+module RTL8731BU WiFi 5.3G
5. module MT7628DAN WiFi 2.4G ANT1+module RTL8731BU WiFi 5.6G
6. module MT7628DAN WiFi 2.4G ANT1+module RTL8731BU WiFi 5.8G



7. module MT7628DAN WiFi 2.4G ANT2+module RTL873IBU WiFi 2.4G
8. module MT7628DAN WiFi 2.4G ANT2+module RTL873IBU WiFi 5.2G
9. module MT7628DAN WiFi 2.4G ANT2+module RTL873IBU WiFi 5.3G
10. module MT7628DAN WiFi 2.4G ANT2+module RTL873IBU WiFi 5.6G
11. module MT7628DAN WiFi 2.4G ANT2+module RTL873IBU WiFi 5.8G

### The Maximum simultaneous transmission for module MT7628DAN WiFi 2.4G ANT2+module RTL873IBU WiFi 5.8G:

$$\sum_i \frac{S_i}{S_{Limit,i}}$$

$$= S_{WiFi\ 2.4G\ ANT2}/S_{limit-2.4G} + S_{WiFi\ 5.8G}/S_{limit-5.8G}$$

$$= 0.0148/1 + 0.0301/1$$

$$= 0.0449$$

$$< 1.0$$

Result: No Standalone SAR test is required.

