

RF Test Data for Bluetooth LE (Conducted Measurements)

General Description of EUT	
Product Name:	AINote
Test Model:	B1051
Sample ID:	HC-C-202410-0003-01-02-2#
Environmental Conditions	
Temperature:	25.4°C
Relative Humidity:	42%RH
Test Voltage:	DC 3.85V
Test Engineer:	Jolin Lee
Note: For a more detailed features description, please refer to the report TBR-C-202410-0003-8 The report only show the worst case data.	

Contents


1. Duty Cycle	3
2. Maximum Conducted Peak Output Power	7
3. -6dB Bandwidth	11
4. Occupied Channel Bandwidth	15
5. Maximum Power Spectral Density Level	19
6. Band Edge	23
7. Conducted RF Spurious Emission	28
8. Restrict Band	35

1. Duty Cycle


Condition	Mode	Frequency (MHz)	Antenna	Duty Cycle (%)	Correction Factor (dB)	1/T (kHz)
NVNT	BLE 1Mbps	2402	Ant1	84.8	0.72	0.47
NVNT	BLE 1Mbps	2440	Ant1	85.2	0.7	0.47
NVNT	BLE 1Mbps	2480	Ant1	85.2	0.7	0.47
NVNT	BLE 2Mbps	2402	Ant1	45.2	3.45	0.88
NVNT	BLE 2Mbps	2440	Ant1	45.2	3.45	0.88
NVNT	BLE 2Mbps	2480	Ant1	45.2	3.45	0.88



Test Graphs

Duty Cycle NVNT BLE 1Mbps 2402MHz Ant1




Duty Cycle NVNT BLE 1Mbps 2440MHz Ant1






Duty Cycle NVNT BLE 2Mbps 2440MHz Ant1



Duty Cycle NVNT BLE 2Mbps 2480MHz Ant1




2. Maximum Conducted Peak Output Power


Condition	Mode	Frequency (MHz)	Antenna	Conducted Power (dBm)	Limit (dBm)	Verdict
NVNT	BLE 1Mbps	2402	Ant1	2.301	30	Pass
NVNT	BLE 1Mbps	2440	Ant1	1.954	30	Pass
NVNT	BLE 1Mbps	2480	Ant1	3.205	30	Pass
NVNT	BLE 2Mbps	2402	Ant1	3.571	30	Pass
NVNT	BLE 2Mbps	2440	Ant1	3.812	30	Pass
NVNT	BLE 2Mbps	2480	Ant1	3.53	30	Pass

Test Graphs


Power NVNT BLE 1Mbps 2402MHz Ant1




Power NVNT BLE 1Mbps 2440MHz Ant1




Power NVNT BLE 1Mbps 2480MHz Ant1




Power NVNT BLE 2Mbps 2402MHz Ant1



Power NVNT BLE 2Mbps 2440MHz Ant1



Power NVNT BLE 2Mbps 2480MHz Ant1




3. -6dB Bandwidth


Condition	Mode	Frequency (MHz)	Antenna	-6 dB Bandwidth (MHz)	Limit -6 dB Bandwidth (MHz)	Verdict
NVNT	BLE 1Mbps	2402	Ant1	0.65	0.5	Pass
NVNT	BLE 1Mbps	2440	Ant1	0.65	0.5	Pass
NVNT	BLE 1Mbps	2480	Ant1	0.65	0.5	Pass
NVNT	BLE 2Mbps	2402	Ant1	1.1	0.5	Pass
NVNT	BLE 2Mbps	2440	Ant1	1.07	0.5	Pass
NVNT	BLE 2Mbps	2480	Ant1	1.12	0.5	Pass



Test Graphs



-6dB Bandwidth NVNT BLE 1Mbps 2402MHz Ant1



-6dB Bandwidth NVNT BLE 1Mbps 2440MHz Ant1








4. Occupied Channel Bandwidth


Condition	Mode	Frequency (MHz)	Antenna	99% OBW (MHz)
NVNT	BLE 1Mbps	2402	Ant1	1.033
NVNT	BLE 1Mbps	2440	Ant1	1.032
NVNT	BLE 1Mbps	2480	Ant1	1.031
NVNT	BLE 2Mbps	2402	Ant1	2.041
NVNT	BLE 2Mbps	2440	Ant1	2.031
NVNT	BLE 2Mbps	2480	Ant1	2.053

Test Graphs


OBW NVNT BLE 1Mbps 2402MHz Ant1




OBW NVNT BLE 1Mbps 2440MHz Ant1




OBW NVNT BLE 1Mbps 2480MHz Ant1




OBW NVNT BLE 2Mbps 2402MHz Ant1



OBW NVNT BLE 2Mbps 2440MHz Ant1



OBW NVNT BLE 2Mbps 2480MHz Ant1




5. Maximum Power Spectral Density Level


Condition	Mode	Frequency (MHz)	Antenna	Max PSD (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
NVNT	BLE 1Mbps	2402	Ant1	-13.696	8	Pass
NVNT	BLE 1Mbps	2440	Ant1	-14.188	8	Pass
NVNT	BLE 1Mbps	2480	Ant1	-12.969	8	Pass
NVNT	BLE 2Mbps	2402	Ant1	-7.671	8	Pass
NVNT	BLE 2Mbps	2440	Ant1	-7.379	8	Pass
NVNT	BLE 2Mbps	2480	Ant1	-7.51	8	Pass



Test Graphs



PSD NVNT BLE 1Mbps 2402MHz Ant1



PSD NVNT BLE 1Mbps 2440MHz Ant1








6. Band Edge


Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	BLE 1Mbps	2402	Ant1	-56.56	-20	Pass
NVNT	BLE 1Mbps	2480	Ant1	-56.93	-20	Pass
NVNT	BLE 2Mbps	2402	Ant1	-56.82	-20	Pass
NVNT	BLE 2Mbps	2480	Ant1	-51.36	-20	Pass



Test Graphs



Band Edge NVNT BLE 1Mbps 2402MHz Ant1 Ref





Band Edge NVNT BLE 1Mbps 2402MHz Ant1 Emission










7. Conducted RF Spurious Emission


Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	BLE 1Mbps	2402	Ant1	-43.21	-20	Pass
NVNT	BLE 1Mbps	2440	Ant1	-42.95	-20	Pass
NVNT	BLE 1Mbps	2480	Ant1	-43.63	-20	Pass
NVNT	BLE 2Mbps	2402	Ant1	-38.75	-20	Pass
NVNT	BLE 2Mbps	2440	Ant1	-39.13	-20	Pass
NVNT	BLE 2Mbps	2480	Ant1	-40.45	-20	Pass

Test Graphs


Tx. Spurious NVNT BLE 1Mbps 2402MHz Ant1 Ref




Tx. Spurious NVNT BLE 1Mbps 2402MHz Ant1 Emission




Tx. Spurious NVNT BLE 1Mbps 2440MHz Ant1 Ref




Tx. Spurious NVNT BLE 1Mbps 2440MHz Ant1 Emission




Tx. Spurious NVNT BLE 1Mbps 2480MHz Ant1 Ref




Tx. Spurious NVNT BLE 1Mbps 2480MHz Ant1 Emission




Tx. Spurious NVNT BLE 2Mbps 2402MHz Ant1 Ref




Tx. Spurious NVNT BLE 2Mbps 2402MHz Ant1 Emission




Tx. Spurious NVNT BLE 2Mbps 2440MHz Ant1 Ref




Tx. Spurious NVNT BLE 2Mbps 2440MHz Ant1 Emission



Tx. Spurious NVNT BLE 2Mbps 2480MHz Ant1 Ref



Tx. Spurious NVNT BLE 2Mbps 2480MHz Ant1 Emission




8. Restrict Band


Condition	Mode	Frequency (MHz)	Antenna	Spur Freq (MHz)	Power (dBm)	Gain (dBi)	Duty Factor (dB)	E (dBuV/m)	Detector	Limit (dBuV/m)	Verdict
NVNT	BLE 1Mbps	2402	Ant1	2310	-58.46	2	-	38.8	Peak	74	Pass
NVNT	BLE 1Mbps	2402	Ant1	2310	-66	2	0.72	31.98	Average	54	Pass
NVNT	BLE 1Mbps	2402	Ant1	2311.44	-54.36	2	-	42.9	Peak	74	Pass
NVNT	BLE 1Mbps	2402	Ant1	2388.528	-65.34	2	0.72	32.64	Average	54	Pass
NVNT	BLE 1Mbps	2402	Ant1	2390	-59.59	2	-	37.67	Peak	74	Pass
NVNT	BLE 1Mbps	2402	Ant1	2390	-65.74	2	0.72	32.24	Average	54	Pass
NVNT	BLE 1Mbps	2480	Ant1	2483.5	-55.55	2	-	41.71	Peak	74	Pass
NVNT	BLE 1Mbps	2480	Ant1	2483.5	-64.16	2	0.7	33.8	Average	54	Pass
NVNT	BLE 1Mbps	2480	Ant1	2487.76	-54.06	2	-	43.2	Peak	74	Pass
NVNT	BLE 1Mbps	2480	Ant1	2484.136	-63.55	2	0.7	34.41	Average	54	Pass
NVNT	BLE 1Mbps	2480	Ant1	2500	-58.52	2	-	38.74	Peak	74	Pass
NVNT	BLE 1Mbps	2480	Ant1	2500	-65.07	2	0.7	32.89	Average	54	Pass
NVNT	BLE 2Mbps	2402	Ant1	2310	-58.27	2	-	38.99	Peak	74	Pass
NVNT	BLE 2Mbps	2402	Ant1	2310	-66.23	2	3.45	34.48	Average	54	Pass
NVNT	BLE 2Mbps	2402	Ant1	2356.272	-48.54	2	-	48.72	Peak	74	Pass
NVNT	BLE 2Mbps	2402	Ant1	2354.256	-59.82	2	3.45	40.89	Average	54	Pass
NVNT	BLE 2Mbps	2402	Ant1	2390	-52.6	2	-	44.66	Peak	74	Pass
NVNT	BLE 2Mbps	2402	Ant1	2390	-63.82	2	3.45	36.89	Average	54	Pass
NVNT	BLE 2Mbps	2480	Ant1	2483.5	-43.35	2	-	53.91	Peak	74	Pass
NVNT	BLE 2Mbps	2480	Ant1	2483.5	-54.5	2	3.45	46.21	Average	54	Pass
NVNT	BLE 2Mbps	2480	Ant1	2483.56	-43.1	2	-	54.16	Peak	74	Pass
NVNT	BLE 2Mbps	2480	Ant1	2483.512	-54.5	2	3.45	46.21	Average	54	Pass
NVNT	BLE 2Mbps	2480	Ant1	2500	-49.89	2	-	47.37	Peak	74	Pass
NVNT	BLE 2Mbps	2480	Ant1	2500	-61.9	2	3.45	38.81	Average	54	Pass

Test Graphs


Restrict Band NVNT BLE 1Mbps 2402MHz Ant1 Peak




Restrict Band NVNT BLE 1Mbps 2402MHz Ant1 Average




Restrict Band NVNT BLE 1Mbps 2480MHz Ant1 Peak




Restrict Band NVNT BLE 1Mbps 2480MHz Ant1 Average




Restrict Band NVNT BLE 2Mbps 2402MHz Ant1 Peak




Restrict Band NVNT BLE 2Mbps 2402MHz Ant1 Average



Restrict Band NVNT BLE 2Mbps 2480MHz Ant1 Peak



Restrict Band NVNT BLE 2Mbps 2480MHz Ant1 Average



-----END OF THE REPORT-----