

FCC ID: 2A8I3-BRPV4

RF Exposure Evaluation

According to KDB 447498 and part 2.1093, Unless specifically required by the *published RF* exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Test Exclusion Threshold condition(s), listed below, is (are) satisfied.

For 100 MHz to 6 GHz and test separation distances ≤ 5.0 mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:

[(max. power of channel, including tune-up tolerance, mW) / (min. test separation distance, mm)] $\cdot [\sqrt{f_{(GHz)}}] \le 3.0$ for 1-g SAR, and ≤ 7.5 for 10-g extremity SAR, where

f_(GHz) is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation. The result is rounded to one decimal place for comparison

Here,

2.4GWIFI-worst mode and channel					
Frequency	Max Power	Tune up tolerance (dBm)	Maximum tune-up		
(MHz)	(dBm)		(dBm)	(mW)	
802.11g- 2412MHz	8.237	8±1	9	7.943	

Maxtune-up Power (dBm)	Max tune-up Power (mW)	Frequency (MHz)	Min. distance (mm)	Calc. thresholds	limit
9	7.943	2412	5	2.467	3.0

BLE-worst mode and channel					
Frequency	Max Power	Tune up tolerance (dBm)	Maximum tune-up		
(MHz)	(dBm)		(dBm)	(mW)	
BLE- 2480MHz	-3.327	-3±1	-2	0.631	


-2	0.631	2480	5	0.199	3.0
Maxtune-up Power (dBm)	Max tune-up Power (mW)	Frequency (MHz)	Min. distance (mm)	Calc. thresholds	limit

Shenzhen ZKT Technolgy Co., Ltd.



















Simultaneous transmission mode	The sum of the ratios	SUM	Limit
2.4G WIFI + BT	2.467/3+0.199/3	0.889	1.0

conclusion : 0.889 < 1, So there is no sar requirement



Shenzhen ZKT Technolgy Co., Ltd. 1/F, No. 101, Building B, No. 6, Tangwei Community Industrial Avenue, Fuhai Street, Bao'an District, Shenzhen, China