

**FCC ID: 2A8IT001****Portable device**

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V06

The 1-g SAR and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq$  50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where:}$

- $f(\text{GHz})$  is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion.

**EDR:**

Modulation	Channel Freq. (GHz)	Conducted power (dBm)	Conducted power (mW)	Tune-up power (dBm)	Max tune-up power (dBm)	Max tune-up power (mW)	Distance (mm)	Result calculation	SAR Exclusion threshold	SAR test exclusion
GFSK	2.402	2.291	1.69	2 $\pm$ 1	3.00	2.00	<5	0.61847	3.00	YES
	2.441	2.877	1.94	2 $\pm$ 1	3.00	2.00	<5	0.62347	3.00	YES
	2.480	2.653	1.84	2 $\pm$ 1	3.00	2.00	<5	0.62843	3.00	YES
$\pi$ /4DQPSK	2.402	0.773	1.19	0 $\pm$ 1	1.00	1.26	<5	0.39023	3.00	YES
	2.441	1.239	1.33	1 $\pm$ 1	2.00	1.58	<5	0.49524	3.00	YES
	2.480	0.826	1.21	0 $\pm$ 1	1.00	1.26	<5	0.39651	3.00	YES

**Conclusion:**

For the max result :  $0.62843 \leq$  FCC Limit 3.0 for 1g SAR.