

Shenzhen SKYLink Technology Co.,Ltd

Antenna Specification for Approval

Customer Name: _____

Product Name: _____ Falcon1 Controller Antenna

Part NO.: _____ YMC.Controller.ANT1.V2.C113.187B.1

Write By: _____ zhangchanghua

Issued Date: _____ 2022-01-18

Edition: _____ V3.0

Customer

R&D Dept	Business Dept	Approved By

SKYLink

R&D Dept	Engineer Dept	Approval

● Specification Summary

A. Electrical Characteristics	
Frequency	2400MHz ~2500MHz
VSWR	<2.0
Efficiency	>50%
Peak Gain	2.6dbi
Impedance	50 Ohm
Polarization	Line
B. Material & Mechanical Characteristics	
Material of Radiator	Cu
Cable Type	1.13 Black
Connector Type	I
Dimension	At Attachment
Heat-durability	280±5°C, 10sec.
C. Environmental Characteristics	
Operation Temperature	- 20 °C ~ + 80 °C
Storage Temperature	- 30 °C ~ + 85 °C

THE NATIONAL

● Test Equipment & Conditions



1. Network Analyzers :

Agilent 8753D 5071B


Communications Test Set:

Agilent E5515C CMW500


2. 3D Chamber Test System




Phi axis test




Theta axis test



◆ Return Loss




◆ VSWR





◆ Gain & Efficiency

Freq (MHz)	Effi (%)	Gain (dBi)
2400	77.17	2.58
2410	74.07	2.25
2420	73.19	2.07
2430	72.35	1.99
2440	71.69	1.92
2450	67.15	1.65
2460	66.09	1.58
2470	65.11	1.48
2480	66.51	1.49
2490	70.58	1.62
2500	70.16	1.37


◆ Radiation Pattern







◆ Antenna Picture



◆ Reliability Test

Test Item		Test condition	Equipment	Specification	Result
1	Low Temp. Storage Test	Temperature: -30℃ , Time:48hrs Test condition: Placing antenna in a Low/High Temperature Chamber, keep the temp is 25℃ and humidity is 65% for one hour, then step-down the temp. to -30℃ in one hour, store antenna for 44 hours; step-up temp to 25℃,test antenna after 2 hours.	Temp.&Humi. Tester	No material deformation is allowed. Electronic Performance is ok .	PASS
2	High Temp./High Humid Storage Test	Temperature: 85℃ Humidity: 85% RH Time:48hrs Test condition: Placing antenna in a Low/High Temperature Chamber, keep the temp is 25℃ and humidity is 65% for one hour, then step-up the temp. to 80℃ and the humidity up to 85% in one hour, store antenna for 44 hours; step-down temp to 25℃,test antenna after 2 hours.	Temp.&Humi. Tester	No material deformation is allowed. Electronic Performance is ok .	PASS
3	Salt-Spray 6 pray Test	Placing antenna in the Salt-Spray Tester ,set the test condition , Temp: $35\pm 2^{\circ}\text{C}$ Humidity: 85% NaCl salt spray :$5\pm 1\%$.PH value :6.5~7.2 Test time:24hours	Salt-Spray Tester	No color change No appear rusting	PASS