



# TEST REPORT

Applicant: Shenzhen Weikesen Electronic Technology Co., Ltd.  
Address of Applicant: 1909, No. 2, Baolong Factory, Anbo Tech, No. 2, Baolong 4th Road, Longgang Dist., Shenzhen, China  
Manufacturer/Factory: Shenzhen Weikesen Electronic Technology Co., Ltd.  
Address of Manufacturer: 1909, No. 2, Baolong Factory, Anbo Tech, No. 2, Baolong 4th Road, Longgang Dist., Shenzhen, China  
Product Name: Mini PC  
Model No.: P2, B95, B100, B200, B300, B305, P1, P2, P3, P4, P5, P6, P7, E1, E2, E3, E4, E5, E6, E7, M6, M1, M2, M3, M4, M5, M7  
Trade Mark: BOSGAME  
IC: 33040-P2  
FCC ID: 2A8JR-P2  
Applicable standards: FCC CFR Title 47 Part 15 Subpart C Section 15.247  
RSS-Gen Issue 5, RSS-247 Issue 3  
Date of Test: Sep.07, 2024-Sep.11, 2024  
Date of report issued: Nov.04, 2024

*Remark:*

*The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full without prior written permission of the company.*

*The report would be invalid without specific stamp of test institute and the signatures of compiler and approver*

## Prepared By

Shenzhen ETR Standard Technology Co., Ltd.

Address: No.103, No.10, Phase I, Zone 3, Xinxing Industrial Park, Xinhe, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

Compiled by:

Project Engineer

Reviewed by:

Project Manager

Approved by:

Authorized Signature



### Report Revision History

Report No.	Description	Issue Date
ET-24091321E01	Original	Nov.04, 2024

# Contents

	Page
1. TEST SUMMARY .....	4
2. GENERAL INFORMATION .....	5
2.1 GENERAL DESCRIPTION OF EUT .....	5
2.2 TEST MODE .....	7
2.3 DESCRIPTION OF SUPPORT UNITS .....	7
2.4 DEVIATION FROM STANDARDS .....	7
2.5 ABNORMALITIES FROM STANDARD CONDITIONS .....	7
2.6 TEST FACILITY .....	7
2.7 TEST LOCATION .....	7
2.8 ADDITIONAL INSTRUCTIONS .....	7
3. TEST INSTRUMENTS LIST .....	8
4. TEST RESULTS AND MEASUREMENT DATA .....	9
4.1 ANTENNA REQUIREMENT .....	9
4.2 CONDUCTED EMISSIONS .....	10
4.3 DUTY CYCLE .....	13
4.4 CONDUCTED OUTPUT POWER&EIRP .....	15
4.5 6dB BANDWIDTH .....	16
4.6 POWER SPECTRAL DENSITY .....	19
4.7 BAND EDGES .....	21
<i>Conducted Emission Method</i> .....	21
4.8 SPURIOUS EMISSION .....	24
<i>Conducted Emission Method</i> .....	24
<i>Radiated Emission Method</i> .....	26
5. TEST SETUP PHOTO .....	33
6. EUT CONSTRUCTIONAL DETAILS .....	33

## 1. Test Summary

Test Item	Section	Result	Test by
Antenna requirement	FCC part 15.203/15.247 (c) RSS-Gen §6.8	Pass	/
AC Power Line Conducted Emission	FCC part 15.207 RSS-Gen §8.8	Pass	Qiao Li
Conducted Peak Output Power	FCC part 15.247 (b)(3) RSS-247 §5.4.d	Pass	Yvan Fan
6dB Bandwidth	FCC part 15.247 (a)(2) RSS-247 §5.2.a RSS-Gen § 6.7	Pass	Yvan Fan
Power Spectral Density	FCC part 15.247 (e) RSS-247 §5.2.b	Pass	Yvan Fan
Band Edge	FCC part 15.247(d) RSS-247 §5.5	Pass	Yvan Fan
Spurious Emission	FCC part 15.205/15.209 RSS-Gen §8.9 §8.10	Pass	Qiao Li

**Remarks:**

1. *Pass: The EUT complies with the essential requirements in the standard.*
2. *Test according to ANSI C63.10:2013 and RSS-Gen.*
3. *Note: Compliance determination rules*
  - 1). *The Compliance determination of test results does not take into account measurement uncertainty. Measurement results are determined based on regulatory limitations or requirements specified by the applicant/manufacturer. If measurement uncertainty is taken into account, the applicant/manufacturer will bear all possible risks of non-compliance.*
  - 2). *The measurement uncertainty please refer to each test result in the "Measurement Uncertainty"*

**Measurement Uncertainty**

Test Item	Measurement Uncertainty	Notes
Occupied Channel Bandwidth	±0.55%	(1)
RF output power, conducted	±0.99dB	(1)
Power Spectral Density, conducted	±0.61dB	(1)
Unwanted Emissions, conducted	±0.64dB	(1)
AC Power Line Conducted Emission	± 3.02dB	(1)
Radiated emissions 9K-30MHz	±3.98dB	(1)
Radiated emissions 30M- 1GHz	±4.32dB	(1)
Radiated emissions 1GHz-18GHz	±4.56dB	(1)
Radiated emissions 18GHz-40GHz	±4.59 dB	(1)

Note (1): The measurement uncertainty is for coverage factor of k=2 and a level of confidence of 95%.

## 2. General Information

### 2.1 General Description of EUT

Product Name:	Mini PC
Model No.:	P2, B95,B100,B200,B300,B305,P1,P2,P3,P4,P5,P6,P7,E1,E2,E3,E4,E5,E6,E7,M6M1,M2,M3,M4,M5
Difference of model(s)	All the model are the same circuit and RF module, except the model names,To differentiate between different sales Area.
Test Model:	P2
Hardware version:	N/A
Software version:	N/A
Sample(s) Status	Engineer sample
Operation Frequency:	2402MHz~2480MHz
Channel Numbers:	40
Channel separation:	2MHz
Modulation technology:	GFSK
Battery:	N/A
Adapter:	Model:SOY-1900630-410.8 Input:100-240VAC 50/60Hz Output: 19VDC 6.3A
Antenna Type:	FPC Antenna
Antenna gain:	0.06dBi(Declare by applicant) Note: Antenna information is provided by applicant, Testing lab is not responsible for the accuracy of the information.
Power supply:	DC 19V from adapter

Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2402 MHz	11	2422 MHz	21	2442 MHz	31	2462 MHz
2	2404 MHz	12	2424 MHz	22	2444 MHz	32	2464 MHz
3	2406 MHz	13	2426 MHz	23	2446 MHz	33	2466 MHz
4	2408 MHz	14	2428 MHz	24	2448 MHz	34	2468 MHz
5	2410 MHz	15	2430 MHz	25	2450 MHz	35	2470 MHz
6	2412 MHz	16	2432 MHz	26	2452 MHz	36	2472 MHz
7	2414 MHz	17	2434 MHz	27	2454 MHz	37	2474 MHz
8	2416 MHz	18	2436 MHz	28	2456 MHz	38	2476 MHz
9	2418 MHz	19	2438 MHz	29	2458 MHz	39	2478 MHz
10	2420 MHz	20	2440 MHz	30	2460 MHz	40	2480 MHz

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Test channel	Frequency (MHz)
Lowest channel	2402MHz
Middle channel	2440MHz
Highest channel	2480MHz

## 2.2 Test mode

Transmitting mode	Keep the EUT in continuously transmitting mode.
<i>Remark: During the test, the test voltage was tuned from 85% to 115% of the nominal rated supply voltage, and found that the worst case was under the nominal rated supply condition. So the report just shows that condition's data.</i>	

## 2.3 Description of Support Units

No.	Description	Manufacturer	Model	Serial Number
/	/	/	/	/

## 2.4 Deviation from Standards

None.
-------

## 2.5 Abnormalities from Standard Conditions

None.
-------

## 2.6 Test Facility

Test laboratory:	Shenzhen ETR Standard Technology Co., Ltd.
CNAS Registration Number:	L11864
A2LA Certificate Number:	6640.01
FCC Designation Number:	CN1326
FCC Test Firm Registration:	183064
IC Company Number:	28440

## 2.7 Test Location

All tests were performed at:	
Laboratory location:	No.103, No.10, Phase I, Zone 3, Xinxing Industrial Park, Xinhe, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China
Telephone:	+86 755 85259392

## 2.8 Additional Instructions

Test Software	DRTU.EXE
Power level setup	Default

### 3. Test Instruments list

Item	Equipment name	Manufacturer	Model	Serial No.	Calibration date	Due date
1	EMI Test Receiver	Rohde&schwarz	ESCi7	100605	2024.3.12	2025.3.11
2	EMI Test Receiver	Rohde&schwarz	ESCi3	102696	2024.3.12	2025.3.11
3	Loop Antenna	schwarabeck	FMZB 1519 B	FMZB 1519 B	2024.3.19	2026.3.18
4	Broadband antenna	schwarabeck	VULB9168	1064	2024.3.19	2026.3.18
5	Horn antenna	schwarabeck	BBHA9120D	9120D-1145	2024.3.19	2026.3.18
6	amplifier	EMtrace	RP01A	50117	2024.3.12	2025.3.11
7	Artificial power network	schwarabeck	NSLK8127	8127483	2024.3.12	2025.3.11
8	Artificial power network	ETS	3186/2NM	1132	2024.3.12	2025.3.11
9	10dB attenuator	HUBER+SUHNER	10dB	/	2024.3.12	2025.3.11
10	amplifier	Space-Dtronics	EWLAN0118G-P40	19113001	2024.3.12	2025.3.11
11	Filter	Xingbo	XBLBQ-GTA19	210410-3-1	2024.3.12	2025.3.11
12	Spectrum analyzer	KEYSIGHT	N9020A	MY55370280	2024.3.12	2025.3.11
13	Power detector box	MWRFtest	MW100-PSB	MW201020JYT	2024.3.12	2025.3.11
14	Power meter	Rohde&Schwarz	NRP-Z11	1138.3004.02-117725-vh	2024.3.12	2025.3.11
15	amplifier	SKET	LNPA_1840-50 (18-40GHz)	SK2019040302	2024.3.12	2025.3.11
16	Horn antenna	schwarabeck	BBHA 9170	946	2024.3.19	2026.3.18
17	Spectrum analyzer	Rohde&schwarz	FSU40	1166.1660K43	2024.3.12	2025.3.11
18	Temp. & Humidity Chamber	Jiecheng Instrument	QA-LP-80	20160705001	2024/4/23	2025/4/22

Note: the calibration interval of the above test instruments is 12 or 24 months and the calibrations are traceable to international system unit (SI).

Software Name	Manufacturer	Model	Version
RF test software	MWRFtest	MTS 8310	V2.0.0.0
Conducted test software	EZ-EMC	Farad	Ver.EMC-CON 3A1.1
Radiated test software	EZ-EMC	Farad	Ver.FA-03A2 RE




## 4. Test results and Measurement Data

### 4.1 Antenna requirement

<b>Standard requirement:</b>	FCC Part15 C Section 15.203 /247(c) ,RSS-Gen §6.8
<p><b>15.203 requirement:</b></p> <p>An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.</p> <p><b>15.247(c) (1)(i) requirement:</b></p> <p>(i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.</p> <p><b>RSS-Gen 6.8:</b></p> <p>The applicant for equipment certification shall provide a list of all antenna types that may be used with the transmitter, where applicable (i.e. for transmitters with detachable antenna), indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna. The test report shall demonstrate the compliance of the transmitter with the limit for maximum equivalent isotropically radiated power (e.i.r.p.) specified in the applicable RSS, when the transmitter is equipped with any antenna type, selected from this list.</p> <p>For expediting the testing, measurements may be performed using only the antenna with highest gain of each combination of transmitter and antenna type, with the transmitter output power set at the maximum level. However, the transmitter shall comply with the applicable requirements under all operational conditions and when in combination with any type of antenna from the list provided in the test report (and in the notice to be included in the user manual, provided below).</p>	
<b>EUT Antenna:</b>	
<p><i>The antenna is PCB antenna, the best case gain of the antenna is 0.06 dBi, reference to the appendix II for details.</i></p>	

### 4.2 Conducted Emissions


Test Requirement:	FCC Part15 C Section 15.207, RSS-Gen §8.8					
Test Method:	ANSI C63.10:2013					
Test Frequency Range:	150KHz to 30MHz					
Receiver setup:	RBW=9KHz, VBW=30KHz, Sweep time=auto					
Limit:	Frequency range (MHz)	Limit (dBuV)				
		Quasi-peak		Average		
	0.15-0.5	66 to 56*		56 to 46*		
	0.5-5	56		46		
	5-30	60		50		
* Decreases with the logarithm of the frequency.						
Test setup:	 <p><i>Remark: E.U.T: Equipment Under Test LISN: Line Impedance Stabilization Network Test table height=0.8m</i></p>					
Test procedure:	<ol style="list-style-type: none"> <li>1. The E.U.T and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment.</li> <li>2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs).</li> <li>3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10:2013 on conducted measurement.</li> </ol>					
Test Instruments:	Refer to section 3.0 for details					
Test mode:	Refer to section 2.2 for details					
Test environment:	Temp.:	24.3°C	Humid.:	44%	Press.:	1012mbar
Test voltage:	AC 120V, 60Hz					
Test results:	Pass					

*Remark:*

1. Both high voltage and low voltage have been tested, and the report only shows the worst case data with AC 120V/60Hz.
2. All mode have been tested, the report only shows the worst mode (2480MHz) data.


Measurement data

Line:



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.2353	35.72	9.82	45.54	62.26	-16.72	QP
2	0.2353	30.88	9.82	40.70	52.26	-11.56	AVG
3	0.3520	28.03	9.88	37.91	58.92	-21.01	QP
4	0.3520	15.94	9.88	25.82	48.92	-23.10	AVG
5	0.4148	30.89	9.90	40.79	57.55	-16.76	QP
6	0.4148	18.65	9.90	28.55	47.55	-19.00	AVG
7	0.4761	27.80	9.93	37.73	56.41	-18.68	QP
8	0.4761	19.94	9.93	29.87	46.41	-16.54	AVG
9	0.5406	30.61	9.94	40.55	56.00	-15.45	QP
10	0.5406	17.17	9.94	27.11	46.00	-18.89	AVG
11	0.6611	32.35	9.94	42.29	56.00	-13.71	QP
12	0.6611	19.45	9.94	29.39	46.00	-16.61	AVG

**Neutral:**




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.2400	34.99	9.82	44.81	62.10	-17.29	QP
2	0.2400	29.63	9.82	39.45	52.10	-12.65	AVG
3	0.4155	28.68	9.90	38.58	57.54	-18.96	QP
4	0.4155	19.44	9.90	29.34	47.54	-18.20	AVG
5	0.5414	30.98	9.94	40.92	56.00	-15.08	QP
6	0.5414	17.58	9.94	27.52	46.00	-18.48	AVG
7	0.6000	29.89	9.94	39.83	56.00	-16.17	QP
8	0.6000	18.21	9.94	28.15	46.00	-17.85	AVG
9	0.6629	32.85	9.94	42.79	56.00	-13.21	QP
10	0.6629	19.63	9.94	29.57	46.00	-16.43	AVG
11	1.0184	24.82	9.96	34.78	56.00	-21.22	QP
12	1.0184	9.97	9.96	19.93	46.00	-26.07	AVG

**Notes:**

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Level = Receiver Read level + Factor (Factor = LISN Factor + Cable Loss + Attenuator Factor)
4. If the average limit is met when using a quasi-peak detector receiver, the EUT shall be deemed to meet both limits and measurement with the average detector receiver is unnecessary.


### 4.3 Duty cycle

Test Method :	ANSI C63.10:2013	
Limit:	/	
Test setup:	 <p>The diagram illustrates the test setup. A Spectrum Analyzer is connected via a red cable to an E.U.T. (Equipment Under Test). Both are placed on a Non-Conducted Table. Below the table is a Ground Reference Plane.</p>	
Test Instruments:	Refer to section 3.0 for details	
Test mode:	Refer to section 2.2 for details	
Test environment:	Temp.: 23.5°C	Humid.: 54%RH
Test voltage:	DC 19V	
Test results:	Pass	


### Measurement Result

Test channel	Duty Cycle (%)	Correction Factor (dB)
Lowest	85.6	0.68
Middle	85.6	0.68
Highest	85.2	0.70


Test plot as follows:



Lowest channel




Middle channel



Highest channel

#### 4.4 Conducted Output Power&EIRP

Test Requirement :	FCC Part15 C Section 15.247 (b)(3) , RSS-247 §5.4.d	
Test Method :	ANSI C63.10:2013 and KDB558074 D01 15.247 Meas Guidance v05r02 and RSS-Gen	
Limit:	30dBm for conducted and 36dBm for EIRP	
Test setup:		
Test Instruments:	Refer to section 3.0 for details	
Test mode:	Refer to section 2.2 for details	
Test environment:	Temp.: 23.5°C	Humid.: 54%RH
Test voltage:	DC 19V	
Test results:	Pass	


#### Measurement Result

Test channel	Output Power (dBm)	Limit(dBm)	Result
Lowest	0.86	30.00	Pass
Middle	1.87		
Highest	1.69		

#### EIRP

Test channel	Peak Output Power (dBm)	Antenna Gain(dBi)	E.I.R.P (dBm)	Limit(dBm)	Result
Lowest	0.86	0.06	0.92	36.00	Pass
Middle	1.87	0.06	1.93		
Highest	1.69	0.06	1.75		

### 4.5 6dB Bandwidth

Test Requirement :	FCC Part15 C Section 15.247 (a)(2), RSS-247 §5.2.a	
Test Method :	ANSI C63.10:2013 and RSS-Gen	
Limit:	>500KHz	
Test setup:	 <p>The diagram illustrates the test setup. A Spectrum Analyzer is connected via a red cable to an E.U.T. (Equipment Under Test). Both are placed on a Non-Conducted Table. Below the table is a Ground Reference Plane.</p>	
Test Instruments:	Refer to section 3.0 for details	
Test mode:	Refer to section 2.2 for details	
Test environment:	Temp.: 23.5°C	Humid.: 54%RH
Test voltage:	DC19V	
Test results:	Pass	


### Measurement Result

Test channel	6dB Bandwidth (MHz)	Limit(KHz)	Result
Lowest	0.6303	>500	Pass
Middle	0.6351		
Highest	0.6627		


Test channel	99% Bandwidth (MHz)	Limit(KHz)	Result
Lowest	1.0471	/	Pass
Middle	1.0436		
Highest	1.0346		




Test plot as follows:




Lowest channel




Middle channel




Highest channel



Lowest channel




Middle channel



Highest channel


### 4.6 Power Spectral Density

Test Requirement:	FCC Part15 C Section 15.247 (e), RSS-247 §5.2.b	
Test Method:	ANSI C63.10:2013 and KDB558074 D01 15.247 Meas Guidance v05r02 And RSS-Gen	
Limit:	8dBm/3kHz	
Test setup:	 <p>The diagram illustrates the test setup. A Spectrum Analyzer is connected via a red cable to an E.U.T. (Equipment Under Test). Both are placed on a Non-Conducted Table. Below the table is a Ground Reference Plane.</p>	
Test Instruments:	Refer to section 3.0 for details	
Test mode:	Refer to section 2.2 for details	
Test environment:	Temp.: 23.5°C	Humid.: 54%RH
Test voltage:	DC 19V	
Test results:	Pass	


### Measurement Result

Test channel	Power Spectral Density (dBm/3kHz)	Limit(dBm/3kHz)	Result
Lowest	-14.197	8.00	Pass
Middle	-13.243		
Highest	-13.452		


Test plot as follows:



Lowest channel



Middle channel




Highest channel

### 4.7 Band edges


#### Conducted Emission Method

Test Requirement:	FCC Part15 C Section 15.247 (d), RSS-247 §5.5	
Test Method:	ANSI C63.10 and RSS-Gen	
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.	
Test setup:		
Test Instruments:	Refer to section 3.0 for details	
Test mode:	Refer to section 2.2 for details	
Test environment:	Temp.: 23.5°C	Humid.: 54%RH
Test voltage:	DC 19V	
Test results:	Pass	

Test plot as follows:




Lowest channel



Highest channel

**Radiated Emission Method**

Test Requirement:	FCC Part15 C Section 15.209 and 15.205, RSS-Gen §8.9 §8.10				
Test Method:	ANSI C63.10: 2013 and RSS-Gen				
Test Frequency Range:	All of the restrict bands were tested, only the worst band's (2310MHz to 2500MHz) data was showed.				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Value
	Above 1GHz	Peak Average	1MHz 1MHz	3MHz 3MHz	Peak Average
Limit:	Frequency		Limit (dBuV/m @3m)		Value
	Above 1GHz		54.00		Average
			74.00		Peak
Test setup:					
Test Procedure:	<ol style="list-style-type: none"> <li>1. The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.</li> <li>2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.</li> <li>3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.</li> <li>4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.</li> <li>5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.</li> <li>6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.</li> <li>7. The radiation measurements are performed in X, Y, Z axis positioning. And found the Y axis positioning which it is worse case, only the test worst case mode is recorded in the report.</li> </ol>				
Test Instruments:	Refer to section 3.0 for details				
Test mode:	Refer to section 2.2 for details				
Test environment:	Temp.: 23.5°C		Humid.: 54%RH		
Test voltage:	DC 19V				
Test results:	Pass				

**Measurement Result:**

Test channel:	Lowest
---------------	--------

**Peak value:**

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310.00	59.96	27.40	4.61	44.50	47.47	74.00	-26.53	Horizontal
2390.00	63.72	27.50	4.61	44.50	51.33	74.00	-22.67	Horizontal
2310.00	60.51	27.40	4.61	44.50	48.02	74.00	-25.98	Vertical
2390.00	64.25	27.50	4.61	44.50	51.86	74.00	-22.14	Vertical

**Average value:**

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310.00	49.22	27.40	4.61	44.50	36.73	54.00	-17.27	Horizontal
2390.00	52.87	27.50	4.61	44.50	40.48	54.00	-13.52	Horizontal
2310.00	52.48	27.40	4.61	44.50	39.99	54.00	-14.01	Vertical
2390.00	53.17	27.50	4.61	44.50	40.78	54.00	-13.22	Vertical

Test channel:	Highest
---------------	---------

**Peak value:**

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	67.54	27.90	4.84	44.90	55.38	74.00	-18.62	Horizontal
2500.00	61.38	27.90	4.84	44.90	49.22	74.00	-24.78	Horizontal
2483.50	68.20	27.90	4.84	44.90	56.04	74.00	-17.96	Vertical
2500.00	61.88	27.90	4.84	44.90	49.72	74.00	-24.28	Vertical

**Average value:**


Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	55.92	27.80	4.84	44.90	43.76	54.00	-10.24	Horizontal
2500.00	50.99	27.80	4.84	44.90	38.83	54.00	-15.17	Horizontal
2483.50	55.35	27.80	4.84	44.90	43.19	54.00	-10.81	Vertical
2500.00	50.90	27.80	4.84	44.90	38.74	54.00	-15.26	Vertical

**Remarks:**

1. *Level = Read level + Antenna Factor + Cable Loss – Preamplifier Factor*
2. *Emissions more than 20 dB below the limit do not need to be reported.*
3. *The pre-test were performed on lowest, middle and highest frequencies, only the worst case's (lowest and highest frequencies) data was showed.*

## 4.8 Spurious Emission



### Conducted Emission Method

Test Requirement:	FCC Part15 C Section 15.247 (d), RSS-Gen §8.9 §8.10	
Test Method:	ANSI C63.10-2013 and RSS-Gen	
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.	
Test setup:	 <p>The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T. (Equipment Under Test) via a red cable. Both are placed on a Non-Conducted Table, which is supported by a Ground Reference Plane.</p>	
Test Instruments:	Refer to section 3.0 for details	
Test mode:	Refer to section 2.2 for details	
Test environment:	Temp.: 23.5°C	Humid.: 54%RH
Test voltage:	DC 19V	
Test results:	Pass	





Test plot as follows:

Lowest channel





30MHz~26.5GHz

Middle channel



30MHz~26.5GHz


Highest channel



30MHz~26.5GHz

**Radiated Emission Method**

Test Requirement:	FCC Part15 C Section 15.209 , RSS-Gen §8.9 §8.10				
Test Method:	ANSI C63.10: 2013 and RSS-Gen				
Test Frequency Range:	9kHz to 25GHz				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Value
	9KHz-150KHz	Quasi-peak	200Hz	600Hz	Quasi-peak
	150KHz-30MHz	Quasi-peak	9KHz	30KHz	Quasi-peak
	30MHz-1GHz	Quasi-peak	120KHz	300KHz	Quasi-peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
Peak		1MHz	10Hz	Average	
Limit:	Frequency	Limit (uV/m)	Value	Measurement Distance	
	0.009MHz-0.490MHz	2400/F(KHz)	QP	300m	
	0.490MHz-1.705MHz	24000/F(KHz)	QP	300m	
	1.705MHz-30MHz	30	QP	30m	
	30MHz-88MHz	100	QP	3m	
	88MHz-216MHz	150	QP		
	216MHz-960MHz	200	QP		
	960MHz-1GHz	500	QP		
	Above 1GHz	500	Average		
5000		Peak			
Test setup:	For radiated emissions from 9kHz to 30MHz				
Test setup:	For radiated emissions from 30MHz to 1GHz				

	<p>For radiated emissions above 1GHz</p> 					
<p>Test Procedure:</p>	<ol style="list-style-type: none"> <li>1. The EUT was placed on the top of a rotating table (0.8m for below 1G and 1.5m for above 1G) above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.</li> <li>2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.</li> <li>3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.</li> <li>4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.</li> <li>5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.</li> <li>6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.</li> </ol>					
<p>Test Instruments:</p>	<p>Refer to section 3.0 for details</p>					
<p>Test mode:</p>	<p>Refer to section 2.2 for details</p>					
<p>Test voltage:</p>	<p>DC 19V</p>					
<p>Test environment:</p>	<p>Temp.:</p>	<p>23.5°C</p>	<p>Humid.:</p>	<p>54%</p>	<p>Press.:</p>	<p>1012mbar</p>
<p>Test results:</p>	<p>Pass</p>					

Remarks:

1. The report only shows the worst mode.
2. Pre-scan all kind of the place mode (X-axis, Y-axis, Z-axis), and found the Y-axis which it is worse case.

**Measurement Result:**


■ **9kHz~30MHz**

The emission from 9 kHz to 30MHz was pre-tested and found the result was 20dB lower than the limit, and according to 15.31(o) & RSS-Gen 6.13, the test result no need to reported.

■ Below 1GHz


All mode has been tested, the report only shows the worst mode (2480MHz) data.

Vertical:



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	43.0505	54.09	-21.09	33.00	40.00	-7.00	QP
2	148.4410	54.91	-20.68	34.23	43.50	-9.27	QP
3	194.4534	55.29	-23.22	32.07	43.50	-11.43	QP
4	253.8367	58.88	-22.19	36.69	46.00	-9.31	QP
5	543.2742	55.21	-13.01	42.20	46.00	-3.80	QP
6	989.5355	44.82	-3.45	41.37	54.00	-12.63	QP

**Horizontal:**



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	131.7577	45.97	-22.39	23.58	43.50	-19.92	QP
2	200.6881	57.17	-23.39	33.78	43.50	-9.72	QP
3	284.9767	59.07	-21.08	37.99	46.00	-8.01	QP
4	356.6758	51.16	-19.09	32.07	46.00	-13.93	QP
5	550.9480	53.36	-12.82	40.54	46.00	-5.46	QP
6	801.7863	46.66	-6.49	40.17	46.00	-5.83	QP

*Remarks:*

*Level = Receiver Reading + Factor*

*Factor = Antenna Factor + Cable Factor - Preamplifier Factor*

■ Above 1GHz

Test channel:	Lowest
---------------	--------

**Peak value:**

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4804.00	52.67	32.40	6.99	44.40	47.66	74.00	-26.34	Vertical
7206.00	48.39	36.60	8.15	42.30	50.84	74.00	-23.16	Vertical
9608.00	45.81	38.50	9.44	42.40	51.35	74.00	-22.65	Vertical
12010.00	*	--	--	--	--	74.00	--	Vertical
14412.00	*	--	--	--	--	74.00	--	Vertical
4804.00	53.12	32.40	6.99	44.40	48.11	74.00	-25.89	Horizontal
7206.00	48.12	36.60	8.15	42.30	50.57	74.00	-23.43	Horizontal
9608.00	46.34	38.50	9.44	42.40	51.88	74.00	-22.12	Horizontal
12010.00	*	--	--	--	--	74.00	--	Horizontal
14412.00	*	--	--	--	--	74.00	--	Horizontal

**Average value:**

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4804.00	41.78	32.10	6.99	45.70	36.77	54.00	-17.23	Vertical
7206.00	37.34	36.10	8.15	45.50	39.79	54.00	-14.21	Vertical
9608.00	34.81	38.30	9.44	46.20	40.35	54.00	-13.65	Vertical
12010.00	*	--	--	--	--	54.00	--	Vertical
14412.00	*	--	--	--	--	54.00	--	Vertical
4804.00	42.64	32.10	6.99	45.70	37.63	54.00	-16.37	Horizontal
7206.00	37.76	36.10	8.15	45.50	40.21	54.00	-13.79	Horizontal
9608.00	34.92	38.30	9.44	46.20	40.46	54.00	-13.54	Horizontal
12010.00	*	--	--	--	--	54.00	--	Horizontal
14412.00	*	--	--	--	--	54.00	--	Horizontal

Remarks:

1. Level = Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. “\*”, means this data is the too weak instrument of signal is unable to test.
3. Emissions more than 20 dB below the limit do not need to be reported.

Test channel:	Middle
---------------	--------

**Peak value:**

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4880.00	54.72	32.10	6.99	45.70	48.11	74.00	-25.89	Vertical
7320.00	50.90	36.80	8.15	45.50	50.35	74.00	-23.65	Vertical
9760.00	48.82	38.40	9.44	46.20	50.46	74.00	-23.54	Vertical
12200.00	*	--	--	--	--	74.00	--	Vertical
14640.00	*	--	--	--	--	74.00	--	Vertical
4880.00	54.49	32.10	6.99	45.70	47.88	74.00	-26.12	Horizontal
7320.00	51.01	36.80	8.15	45.50	50.46	74.00	-23.54	Horizontal
9760.00	48.27	38.40	9.44	46.20	49.91	74.00	-24.09	Horizontal
12200.00	*	--	--	--	--	74.00	--	Horizontal
14640.00	*	--	--	--	--	74.00	--	Horizontal

**Average value:**

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4880.00	44.48	32.10	6.99	45.70	37.87	54.00	-16.13	Vertical
7320.00	40.29	36.80	8.15	45.50	39.74	54.00	-14.26	Vertical
9760.00	39.15	38.40	9.44	46.20	40.79	54.00	-13.21	Vertical
12200.00	*	--	--	--	--	54.00	--	Vertical
14640.00	*	--	--	--	--	54.00	--	Vertical
4880.00	44.14	32.10	6.99	45.70	37.53	54.00	-16.47	Horizontal
7320.00	40.63	36.80	8.15	45.50	40.08	54.00	-13.92	Horizontal
9760.00	39.08	38.40	9.44	46.20	40.72	54.00	-13.28	Horizontal
12200.00	*	--	--	--	--	54.00	--	Horizontal
14640.00	*	--	--	--	--	54.00	--	Horizontal

Remarks:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Pre-amplifier Factor
2. “\*”, means this data is too weak instrument of signal is unable to test.
3. Emissions more than 20 dB below the limit do not need to be reported.

Test channel:	Highest
---------------	---------

**Peak value:**

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4960.00	53.86	32.70	6.99	45.70	47.85	74.00	-26.15	Vertical
7440.00	50.43	36.40	8.15	45.50	49.48	74.00	-24.52	Vertical
9920.00	48.85	38.00	9.44	46.20	50.09	74.00	-23.91	Vertical
12400.00	*	--	--	--	--	74.00	--	Vertical
14880.00	*	--	--	--	--	74.00	--	Vertical
4960.00	53.65	32.70	6.99	45.70	47.64	74.00	-26.36	Horizontal
7440.00	50.67	36.40	8.15	45.50	49.72	74.00	-24.28	Horizontal
9920.00	48.69	38.00	9.44	46.20	49.93	74.00	-24.07	Horizontal
12400.00	*	--	--	--	--	74.00	--	Horizontal
14880.00	*	--	--	--	--	74.00	--	Horizontal

**Average value:**

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4960.00	42.76	32.70	6.99	45.70	36.75	54.00	-17.25	Vertical
7440.00	40.29	36.40	8.15	45.50	39.34	54.00	-14.66	Vertical
9920.00	37.73	38.00	9.44	46.20	38.97	54.00	-15.03	Vertical
12400.00	*	--	--	--	--	54.00	--	Vertical
14880.00	*	--	--	--	--	54.00	--	Vertical
4960.00	43.22	32.70	6.99	45.70	37.21	54.00	-16.79	Horizontal
7440.00	40.21	36.40	8.15	45.50	39.26	54.00	-14.74	Horizontal
9920.00	38.23	38.00	9.44	46.20	39.47	54.00	-14.53	Horizontal
12400.00	*	--	--	--	--	54.00	--	Horizontal
14880.00	*	--	--	--	--	54.00	--	Horizontal

Remarks:

1. Level = Read level + Antenna Factor + Cable Loss – Pre-amplifier Factor
2. “\*”, means this data is the too weak instrument of signal is unable to test.
3. Emissions more than 20 dB below the limit do not need to be reported.



## 5. Test Setup Photo

Reference to the **appendix I** for details.

## 6. EUT Constructional Details

Reference to the **appendix II** for details.

-----End-----