

<b>Test report no.:</b> <i>Prüfbericht-Nr.:</i>	<b>CN238VDE 002</b>	<b>Order No.:</b> <i>Auftragsnr.:</i>	168374226	<b>Page 1 of 10</b> <i>Seite 1 von 10</i>
<b>Client reference no.:</b> <i>Kunden-Referenz-Nr.:</i>	N/A	<b>Order date:</b> <i>Auftragsdatum:</i>	2022-05-06	
<b>Client:</b> <i>Auftraggeber:</i>	Honeywell International Inc. 12 Clintonville Road, Northford, CT 06472, USA			
<b>Test item:</b> <i>Prüfgegenstand:</i>	Plant controller			
<b>Identification / Type no.:</b> <i>Bezeichnung / Typ-Nr.:</i>	IQ5-00-B-24, CPO-PC600-B, N-ADV-133-H-B, N-ADV-133-H-B-C, N-ADV-133-H-B-D			
<b>Order content:</b> <i>Auftrags-Inhalt:</i>	Test Report			
<b>Test specification</b> <i>Prüfgrundlage:</i>	47 CFR FCC Part 2.1091 RSS-102 Issue 5			
<b>Date of sample receipt:</b> <i>Wareneingangsdatum:</i>	2022-05-27	Please refer to Photo Document		
<b>Test sample no.:</b> <i>Prüfmuster-Nr.:</i>	A003262749-002 A003407648-001 A003589769-012			
<b>Testing period:</b> <i>Prüfzeitraum:</i>	2023-11-10 - 2023-11-10			
<b>Place of testing:</b> <i>Ort der Prüfung:</i>	Refer to section 2.1			
<b>Testing laboratory:</b> <i>Prüflaboratorium:</i>	TÜV Rheinland (Shenzhen) Co., Ltd.			
<b>Test result*:</b> <i>Prüfergebnis*:</i>	Pass			
<b>tested by:</b> <i>geprüft von:</i>	X <u>Breeze Jiang</u>			
<b>Date:</b> 2024-02-21 <i>Datum:</i>	Signed by: Breeze Jiang	<b>Issue date:</b> 2024-02-21 <i>Ausstellungsdatum:</i>	Signed by: Bell Hu	
<b>Position / Stellung:</b>	Expert/Sachverständige(r)	<b>Position / Stellung:</b>	Expert/Sachverständige(r)	
<b>Other:</b> <i>Sonstiges:</i>	FCC ID: 2A8LT-ADVBLE IC: 1609A-ADVBLE HVIN: 501003 PMN: IQ5-00-B-24, CPO-PC600-B, N-ADV-133-H-B, N-ADV-133-H-B-C, N-ADV-133-H-B-D			
<b>Condition of the test item at delivery:</b> <i>Zustand des Prüfgegenstandes bei Anlieferung:</i>	Test item complete and undamaged Prüfmuster vollständig und unbeschädigt			
* Legend:	P(ass) = passed a.m. test specification(s)	F(ail) = failed a.m. test specification(s)	N/A = not applicable	N/T = not tested
* Legende:	P(ass) = entspricht o.g. Prüfgrundlage(n)	F(ail) = entspricht nicht o.g. Prüfgrundlage(n)	N/A = nicht anwendbar	N/T = nicht getestet
<b>This test report only relates to the above mentioned test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.</b> <i>Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens.</i>				

V05

Test report no.: CN238VDE 002  
Prüfbericht-Nr.:

Page 2 of 10  
Seite 2 von 10

**Remarks**  
*Anmerkungen*

1	<p>The equipment used during the specified testing period was calibrated according to our test laboratory calibration program. The equipment fulfils the requirements included in the relevant standards. The traceability of the test equipment used is ensured by compliance with the regulations of our management system. Detailed information regarding test conditions, equipment and measurement uncertainty is available in the test laboratory and could be provided on request.</p> <p><i>Alle eingesetzten Prüfmittel waren zum angegebenen Prüfzeitraum gemäß eines festgelegten Kalibrierungsprogramms unseres Prüfhauses kalibriert. Sie entsprechen den in den Prüfprogrammen hinterlegten Anforderungen. Die Rückverfolgbarkeit der eingesetzten Prüfmittel ist durch die Einhaltung der Regelungen unseres Managementsystems gegeben.</i></p> <p><i>Detaillierte Informationen bezüglich Prüfkonditionen, Prüfequipment und Messunsicherheiten sind im Prüflabor vorhanden und können auf Wunsch bereitgestellt werden.</i></p>
2	<p>As contractually agreed, this document has been signed digitally only. TÜV Rheinland has not verified and unable to verify which legal or other pertaining requirements are applicable for this document. Such verification is within the responsibility of the user of this document. Upon request by its client, TÜV Rheinland can confirm the validity of the digital signature by a separate document. Such request shall be addressed to our Sales department. An environmental fee for such additional service will be charged.</p> <p><i>Wie vertraglich vereinbart, wurde dieses Dokument nur digital unterzeichnet. Der TÜV Rheinland hat nicht überprüft, welche rechtlichen oder sonstigen diesbezüglichen Anforderungen für dieses Dokument gelten. Diese Überprüfung liegt in der Verantwortung des Benutzers dieses Dokuments. Auf Verlangen des Kunden kann der TÜV Rheinland die Gültigkeit der digitalen Signatur durch ein gesondertes Dokument bestätigen. Diese Anfrage ist an unseren Vertrieb zu richten. Eine Umweltgebühr für einen solchen zusätzlichen Service wird erhoben.</i></p>
3	<p>Test clauses with remark of * are subcontracted to qualified subcontractors and described under the respective test clause in the report. Deviations of testing specification(s) or customer requirements are listed in specific test clause in the report.</p> <p><i>Prüfklausel mit der Note * wurden an qualifizierte Unterauftragnehmer vergeben und sind unter der jeweiligen Prüfklausel des Berichts beschrieben. Abweichungen von Prüfspezifikation(en) oder Kundenanforderungen sind in der jeweiligen Prüfklausel im Bericht aufgeführt.</i></p>
4	<p>The decision rule for statements of conformity, based on numerical measurement results, in this test report is based on the "Zero Guard Band Rule" and "Simple Acceptance" in accordance with ILAC G8:2019 and IEC Guide 115:2021, unless otherwise specified in the applied standard mentioned on Page 1 of this report or requested by the customer. This means that measurement uncertainty is not taken in account and hence also not declared in the test report. For additional information to the resulting risk based of this decision rule please refer to ILAC G8:2019.</p> <p><i>Die Entscheidungsregel für Konformitätserklärungen basierend auf numerischen Messergebnissen in diesem Prüfbericht basiert auf der "Null-Grenzwert-Regel" und der "Einfachen Akzeptanz" gemäß ILAC G8:2019 und IEC Guide 115:2021, es sei denn, in der auf Seite 1 dieses Berichts genannten angewandten Norm ist etwas anderes festgelegt oder vom Kunden gewünscht. Dies bedeutet, dass die Messunsicherheit nicht berücksichtigt wird und daher auch nicht im Prüfbericht angegeben wird. Zu weiteren Informationen bezueglich des Risikos durch diese Entscheidungsregel siehe ILAC G8:2019.</i></p>

**Prüfbericht - Nr.: CN238VDE 002**  
Test Report No.:

Seite 3 von 10  
Page 3 of 10

## TEST SUMMARY

### 3.1.1 RF EXPOSURE COMPLIANCE

RESULT: Pass

## CONTENTS

<b>1.</b>	<b>TEST SITES.....</b>	<b>5</b>
<b>1.1</b>	<b>TEST FACILITIES .....</b>	<b>5</b>
<b>1.2</b>	<b>TRACEABILITY .....</b>	<b>5</b>
<b>1.3</b>	<b>CALIBRATION.....</b>	<b>5</b>
<b>1.4</b>	<b>LOCATION OF ORIGINAL DATA .....</b>	<b>5</b>
<b>1.5</b>	<b>STATUS OF FACILITY USED FOR TESTING .....</b>	<b>5</b>
<b>2.</b>	<b>GENERAL PRODUCT INFORMATION .....</b>	<b>6</b>
<b>2.1</b>	<b>GENERAL DESCRIPTION .....</b>	<b>6</b>
<b>2.2</b>	<b>RATING AND SYSTEM DETAILS .....</b>	<b>6</b>
<b>3.</b>	<b>TEST RESULTS .....</b>	<b>7</b>
<b>3.1</b>	<b>TRANSMITTER REQUIREMENTS &amp; TEST SUITES.....</b>	<b>7</b>
3.1.1	<i>RF Exposure Compliance.....</i>	<i>7</i>
3.1.1.1	FCC Part 1.1310, Part 2.1091 .....	8
3.1.1.2	RSS-102 Exemption Limits for Routine Evaluation – RF Exposure Evaluation .....	9
<b>4.</b>	<b>LIST OF TABLES.....</b>	<b>10</b>

**Prüfbericht - Nr.: CN238VDE 002**  
Test Report No.:

Seite 5 von 10  
Page 5 of 10

## 1. TEST SITES

### 1.1 TEST FACILITIES

TÜV Rheinland (Shenzhen) Co., Ltd.

Address: No.362, Huanguan Middle Road, Songyuansha Community, Guanhu Subdistrict, Longhua District, Shenzhen 518110, Guangdong, China

FCC Registration No.: 694916

ISED wireless device testing laboratory: 25069

### 1.2 TRACEABILITY

All measurement equipment calibrations are traceable to NIST or where calibration is performed outside the United States, to equivalent nationally recognized standards organizations.

### 1.3 CALIBRATION

Equipment requiring calibration is calibrated periodically by the manufacturer or according to manufacturer's specifications. Additionally all equipment is verified for proper performance on a regular basis using in house standards or comparisons.

### 1.4 LOCATION OF ORIGINAL DATA

The original copies of all test data taken during actual testing were attached at Appendixes of this report and delivered to the applicant. A copy has been retained in the TÜV Rheinland (Shenzhen) file for certification follow-up purposes.

### 1.5 STATUS OF FACILITY USED FOR TESTING

The TÜV Rheinland (Shenzhen) Co., Ltd. facility located at No.362, Huanguan Middle Road, Songyuansha Community, Guanhu Subdistrict, Longhua District, Shenzhen 518110, Guangdong, China is listed on the US Federal Communications Commission list of facilities approved to perform measurements.

**Prüfbericht - Nr.: CN238VDE 002**

Test Report No.:

Seite 6 von 10

Page 6 of 10

## 2. GENERAL PRODUCT INFORMATION

### 2.1 GENERAL DESCRIPTION

The Product is plant controller which supports Bluetooth (Low Energy) technology.  
For details refer to the User Manual, Technical Description and Circuit Diagram.

### 2.2 RATING AND SYSTEM DETAILS

Table 1: Technical Specification of EUT

General Information of EUT	Value
Kind of Equipment:	Plant controller
Type Designation:	IQ5-00-B-24, CPO-PC600-B, N-ADV-133-H-B, N-ADV-133-H-B-C, N-ADV-133-H-B-D
FCC ID:	2A8LT-ADVBLE
IC:	1609A-ADVBLE
PMN:	IQ5-00-B-24, CPO-PC600-B, N-ADV-133-H-B, N-ADV-133-H-B-C, N-ADV-133-H-B-D
HVIN:	501003
Operating Voltage:	DC 20V-30V or AC 19.2V-30V
Testing Voltage:	AC 24V or DC 24V (via AC/DC or AC/AC adapter)
Operating Temperature Range:	-25°C ~ 60°C

## 3. TEST RESULTS

### 3.1 TRANSMITTER REQUIREMENTS & TEST SUITES

#### 3.1.1 RF Exposure Compliance

**RESULT:**

**Pass**

Test standard	:	RSS-102 Issue 5 FCC Part 2.1091
Limit	:	Table 1 of 47 CFR FCC Part 1.1310 Section 2.5.2 of RSS-102 Issue 5
Kind of test site	:	Shielded room

This device is mobile device, and the applicant declares that the minimum separation distance is greater than 20cm. Therefore MPE measurement or computational modelling should be used to determine compliance.

MPE Calculation is based on the conducted power, and considering maximum power and Antenna gain. The following formula is used to MPE evaluation.

$$Pd = \frac{P_{out} * G}{4R^2\pi}$$

Where

$P_d$  = power density in mW/cm<sup>2</sup> or W/m<sup>2</sup>

$P_{out}$  = output power to antenna in mW or W

$G_{num}$  = Antenna gain in numeric

$\pi$  = 3.14159

R = Distance between observation point and the center of radiator in cm or m

**Prüfbericht - Nr.: CN238VDE 002**

Test Report No.:

Seite 8 von 10

Page 8 of 10

**3.1.1.1 FCC Part 1.1310, Part 2.1091**

According to ANSI/IEEE C95.1-1992, the criteria listed in Table 1 shall be used to evaluate the environmental impact of human exposure to radio frequency (RF) radiation as specified in §1.1310.

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
<b>(A) Limits for Occupational/Controlled Exposures</b>				
0.3-3.0	614	1.63	*(100)	6
3.0-30	1842/f	4.89/f	*(900/f <sup>2</sup> )	6
30-300	61.4	0.163	1.0	6
300-1500			f/300	6
1500-100.000			5	6
<b>(B) Limits for General Population/Uncontrolled Exposure</b>				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30-300	27.5	0.073	0.2	30
300-1500			f/1500	30
1500-100.000			1.0	30

**Table 2: Test Results of RF Exposure Calculations for FCC**

Operating Mode	Max. EIRP incl. tune-up (dBm)	Distance (cm)	MPE Pd (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )	Verdict
Bluetooth	9.42	20	0.0017	1.0	Pass

1. RF Output Power above: Refer to test report CN238VDE 001.
2. EIRP= Conducted power + Directional Gain



### 3.1.1.2 RSS-102 Exemption Limits for Routine Evaluation – RF Exposure Evaluation

RF exposure evaluation is required if the separation distance between the user and/or bystander and the device's radiating element is greater than 20 cm, except when the device operates as follows:

- below 20 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 1 W (adjusted for tune-up tolerance);
- at or above 20 MHz and below 48 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than  $4.49/f^{0.5}$  W (adjusted for tune-up tolerance), where  $f$  is in MHz;
- at or above 48 MHz and below 300 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 0.6 W (adjusted for tune-up tolerance);
- at or above 300 MHz and below 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than  $1.31 \times 10^{-2} f^{0.6834}$  W (adjusted for tune-up tolerance), where  $f$  is in MHz;
- at or above 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 5 W (adjusted for tune-up tolerance).

In these cases, the information contained in the RF exposure technical brief may be limited to information that demonstrates how the e.i.r.p. was derived.

**Table 3: Test Results of RF Exposure Calculations for ISED**

Operating Mode	Max. EIRP incl. tune-up (dBm)	Distance (cm)	Maximum EIRP (W)	Threshold power (W)	Verdict
Bluetooth	9.42	20	0.0087	2.68	Pass

Note: The maximum EIRP lower than the threshold power in section 2.5.2, thus compliant.

1. RF Output Power above: Refer to test report CN238VDE 001.
2. EIRP= Conducted power + Directional Gain

## 4. LIST OF TABLES

Table 1: Technical Specification of EUT .....	6
Table 2: Test Results of RF Exposure Calculations for FCC.....	8
Table 3: Test Results of RF Exposure Calculations for ISED.....	9