

Just Show It

Now, Let' s Get Started

1. Insert 3V Lithium battery in the battery compartment on the back of Geshowit hand unit.

Press the gesture button on the remoter to display the corresponding gesture light of the HAND LIGHT and resume the cover.(If the hand unit does not light up, roll the battery around)

2. Clean the area where you would like to stick your hand light.(If the surface is freezing cold, please DO NOT attach the hand unit)

3. Tear off the tape' s cover of the hand unit and remote, and place them to your desired places.

Please place your remoter on a safe location that is convenient to control while driving according to your wants.

4. The Battery of the remote is repeale. Pop the back cover of the remote open with the accompanying pin through the slot, then we can replace the CR2032 battery.

FCC Requirement

Any changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions:

- (1) this device may not cause harmful interference, and
- (2) this device must accept any interference received, including interference that may cause undesired operation.

Note: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses, and can radiate radio frequency energy, and if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.