


[TestMode: TX mid channel]; [Polarity: Vertical]



Site: Polarization: **Vertical** Temperature: (C)
 Limit: FCC Part15 (PK) Power: Humidity: %RH
 EUT: GEEK ONE
 M/N: AMP06
 Mode: BT TX-M
 Note: TX-1


No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		2398.250	43.07	-1.14	41.93	74.00	-32.07	peak	
2		4884.000	40.05	4.37	44.42	74.00	-29.58	peak	
3		7326.000	38.23	8.21	46.44	74.00	-27.56	peak	
4		9768.000	37.38	11.31	48.69	74.00	-25.31	peak	
5		11410.500	38.11	13.63	51.74	74.00	-22.26	peak	
6	*	12256.500	38.77	13.89	52.66	74.00	-21.34	peak	

*:Maximum data x:Over limit !:over margin

(Reference Only)

Test Result: Pass

[TestMode: TX high channel]; [Polarity: Horizontal]



Site: Polarization: **Horizontal** Temperature: (C)
 Limit: FCC Part15 (PK) Power: Humidity: %RH
 EUT: GEEK ONE
 M/N: AMP06
 Mode: BT TX-H
 Note: TX-1


No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		2480.500	45.16	-2.05	43.11	74.00	-30.89	peak	
2		4960.000	40.34	5.42	45.76	74.00	-28.24	peak	
3		7740.000	39.20	8.76	47.96	74.00	-26.04	peak	
4		9920.000	35.72	11.69	47.41	74.00	-26.59	peak	
5		11293.000	38.80	13.58	52.38	74.00	-21.62	peak	
6	*	12350.500	38.61	13.88	52.49	74.00	-21.51	peak	

*:Maximum data x:Over limit !:over margin

(Reference Only)

Test Result: Pass

[TestMode: TX high channel]; [Polarity: Vertical]



Site: Polarization: **Vertical** Temperature: (C)
 Limit: FCC Part15 (PK) Power: Humidity: %RH
 EUT: GEEK ONE
 M/N: AMP06
 Mode: BT TX-H
 Note: TX-1

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		1893.000	48.36	-4.80	43.56	74.00	-30.44	peak	
2		4149.000	40.67	3.95	44.62	74.00	-29.38	peak	
3		4960.000	38.80	5.42	44.22	74.00	-29.78	peak	
4		7440.000	38.25	8.48	46.73	74.00	-27.27	peak	
5		9920.000	35.62	11.69	47.31	74.00	-26.69	peak	
6	*	11915.750	38.66	13.86	52.52	74.00	-21.48	peak	


*:Maximum data x:Over limit !:over margin

(Reference Only)

Test Result: Pass

Test engineer sample no: RX-1


[TestMode: TX below 1G]; [Polarity: Horizontal]



*:Maximum data x:Over limit !:over margin

Test Result: Pass


[TestMode: TX below 1G]; [Polarity: Vertical]



*:Maximum data x:Over limit !:over margin

Test Result: Pass

[TestMode: TX low channel]; [Polarity: Horizontal]




Site: Polarization: **Horizontal** Temperature: (C)
 Limit: FCC Part15 (PK) Power: Humidity: %RH
 EUT: GEEK ONE
 M/N: AMP06
 Mode: BT TX-L
 Note: RX-1

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		2410.000	43.42	-1.26	42.16	74.00	-31.84	peak	
2		4804.000	41.18	4.05	45.23	74.00	-28.77	peak	
3		7206.000	39.33	7.93	47.26	74.00	-26.74	peak	
4		9608.000	37.64	10.90	48.54	74.00	-25.46	peak	
5	*	11398.750	39.25	13.63	52.88	74.00	-21.12	peak	
6		12409.250	38.65	13.88	52.53	74.00	-21.47	peak	

*:Maximum data x:Over limit !:over margin <Reference Only

Test Result: Pass

[TestMode: TX low channel]; [Polarity: Vertical]



Site: _____ Polarization: **Vertical** Temperature: (C)
 Limit: FCC Part15 (PK) Power: _____ Humidity: %RH
 EUT: GEEK ONE
 M/N: AMP06
 Mode: BT TX-L
 Note: RX-1


No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		
1		2468.750	43.68	-1.91	41.77	74.00	-32.23	peak	
2		4804.000	39.49	4.05	43.54	74.00	-30.46	peak	
3		7206.000	38.66	7.93	46.59	74.00	-27.41	peak	
4		9608.000	38.31	10.90	49.21	74.00	-24.79	peak	
5	*	10999.250	39.81	13.45	53.26	74.00	-20.74	peak	
6		12632.500	38.62	13.86	52.48	74.00	-21.52	peak	

*:Maximum data x:Over limit l:over margin

<Reference Only

Test Result: Pass

[TestMode: TX mid channel]; [Polarity: Horizontal]



Site: Polarization: **Horizontal** Temperature: (C)
 Limit: FCC Part15 (PK) Power: Humidity: %RH
 EUT: GEEK ONE
 M/N: AMP06
 Mode: BT TX-M
 Note: RX-1


No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		1587.500	46.87	-5.56	41.31	74.00	-32.69	peak	
2		4884.000	39.40	4.37	43.77	74.00	-30.23	peak	
3		7326.000	38.13	8.21	46.34	74.00	-27.66	peak	
4		9768.000	36.86	11.31	48.17	74.00	-25.83	peak	
5		11340.000	38.78	13.60	52.38	74.00	-21.62	peak	
6	*	12667.750	38.97	13.87	52.84	74.00	-21.16	peak	

*:Maximum data x:Over limit !:over margin

<Reference Only

Test Result: Pass

[TestMode: TX mid channel]; [Polarity: Vertical]



Site: Polarization: **Vertical** Temperature: (C)
 Limit: FCC Part15 (PK) Power: Humidity: %RH
 EUT: GEEK ONE
 M/N: AMP06
 Mode: BT TX-M
 Note: RX-1


No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		1916.500	47.13	-4.74	42.39	74.00	-31.61	peak	
2		3455.750	42.90	-1.42	41.48	74.00	-32.52	peak	
3		4884.000	39.95	4.37	44.32	74.00	-29.68	peak	
4		7326.000	39.21	8.21	47.42	74.00	-26.58	peak	
5		9768.000	38.60	11.31	49.91	74.00	-24.09	peak	
6	*	11915.750	39.99	13.86	53.85	74.00	-20.15	peak	

*:Maximum data x:Over limit !:over margin

<Reference Only

Test Result: Pass

[TestMode: TX high channel]; [Polarity: Horizontal]



Site	Polarization: Horizontal	Temperature: (C)
Limit: FCC Part15 (PK)	Power:	Humidity: %RH
EUT: GEEK ONE		
M/N: AMP06		
Mode: BT TX-H		
Note: RX-1		


No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		2410.000	42.04	-1.26	40.78	74.00	-33.22	peak	
2		4090.250	42.58	2.63	45.21	74.00	-28.79	peak	
3		4960.000	38.75	5.42	44.17	74.00	-29.83	peak	
4		7440.000	38.63	8.48	47.11	74.00	-26.89	peak	
5		9920.000	36.66	11.69	48.35	74.00	-25.65	peak	
6	*	11786.500	39.00	13.81	52.81	74.00	-21.19	peak	

*:Maximum data x:Over limit !:over margin

<Reference Only

Test Result: Pass

[TestMode: TX high channel]; [Polarity: Vertical]



Site	Polarization: Vertical	Temperature: (C)
Limit: FCC Part15 (PK)	Power:	Humidity: %RH
EUT: GEEK ONE		
M/N: AMP06		
Mode: BT TX-H		
Note: RX-1		

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		1869.500	47.18	-4.88	42.30	74.00	-31.70	peak	
2		4960.000	38.53	5.42	43.95	74.00	-30.05	peak	
3		7440.000	38.33	8.48	46.81	74.00	-27.19	peak	
4		9920.000	36.68	11.69	48.37	74.00	-25.63	peak	
5		11340.000	38.99	13.60	52.59	74.00	-21.41	peak	
6	*	12397.500	38.77	13.88	52.65	74.00	-21.35	peak	

*:Maximum data x:Over limit !:over margin

<Reference Only

Test Result: Pass

Remark:

1. Final Level = Receiver Read level + Correct factor
2. Correct factor = Antenna Factor + Cable Loss – Preamplifier Factor
3. The emission levels of other frequencies are very lower than the limit and not show in test report.

BlueAsia

17 RADIATED EMISSIONS WHICH FALL IN THE RESTRICTED BANDS

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 6.10.5
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Jozu
Temperature	25°C
Humidity	60%

17.1 LIMITS

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

17.2 BLOCK DIAGRAM OF TEST SETUP



17.3 PROCEDURE

- For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.

Remark 1: $Level = Read\ Level + Cable\ Loss + Antenna\ Factor - Preamp\ Factor$


Remark 2: For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.

BlueAsia

17.4 TEST DATA

Test engineer sample no: TX-1

[TestMode: TX low channel]; [Polarity: Horizontal]



Site	Polarization: Horizontal	Temperature: (C)
Limit: FCC Part15 (PK)	Power:	Humidity: %RH
EUT: GEEK ONE		
M/N: AMP06		
Mode: BT TX-L		
Note: TX-1		


No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		
1		2310.000	42.78	-4.27	38.51	74.00	-35.49	peak	
2	*	2390.000	44.45	-3.82	40.63	74.00	-33.37	peak	

*:Maximum data x:Over limit !:over margin

<Reference Only

Test Result: Pass

[TestMode: TX low channel]; [Polarity: Vertical]



Site	Polarization: Vertical	Temperature: (C)
Limit: FCC Part15 (PK)	Power:	Humidity: %RH
EUT: GEEK ONE		
M/N: AMP06		
Mode: BT TX-L		
Note: TX-1		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		
1		2310.000	42.84	-4.27	38.57	74.00	-35.43	peak	
2	*	2390.000	44.22	-3.82	40.40	74.00	-33.60	peak	


*:Maximum data x:Over limit !:over margin

(Reference Only)

Test Result: Pass

[TestMode: TX high channel]; [Polarity: Horizontal]

Radiated Emission Measurement



Site: Polarization: **Horizontal** Temperature: (C)
Limit: FCC Part15 (PK) Power: Humidity: %RH
EUT: GEEK ONE
M/N: AMP06
Mode: BT TX-H
Note: TX-1

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		
1		2483.500	54.33	-3.96	50.37	74.00	-23.63	peak	
2	*	2483.500	40.32	-3.96	36.36	54.00	-17.64	AVG	
3		2500.000	42.41	-4.00	38.41	74.00	-35.59	peak	


*:Maximum data x:Over limit !:over margin

(Reference Only)

Test Result: Pass

[TestMode: TX high channel]; [Polarity: Vertical]

Radiated Emission Measurement



Site	Polarization: Vertical	Temperature: (C)
Limit: FCC Part15 (PK)	Power:	Humidity: %RH
EUT: GEEK ONE		
M/N: AMP06		
Mode: BT TX-H		
Note: TX-1		

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	*	2483.500	43.77	-3.96	39.81	74.00	-34.19	peak	
2		2500.000	42.45	-4.00	38.45	74.00	-35.55	peak	


*:Maximum data x:Over limit !:over margin

(Reference Only)

Test Result: Pass

Test engineer sample no: RX-1

[TestMode: TX low channel]; [Polarity: Horizontal]



Site	Polarization: Horizontal	Temperature: (C)
Limit: FCC Part15 (PK)	Power:	Humidity: %RH
EUT: GEEK ONE		
M/N: AMP06		
Mode: BT TX-L		
Note: RX-1		


No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		
1		2310.000	42.16	-4.27	37.89	74.00	-36.11	peak	
2	*	2390.000	43.66	-3.82	39.84	74.00	-34.16	peak	

*:Maximum data x:Over limit !:over margin

<Reference Only

Test Result: Pass

[TestMode: TX low channel]; [Polarity: Vertical]




Site	Polarization: Vertical	Temperature: (C)
Limit: FCC Part15 (PK)	Power:	Humidity: %RH
EUT: GEEK ONE		
M/N: AMP06		
Mode: BT TX-L		
Note: RX-1		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		
1		2310.000	42.54	-4.27	38.27	74.00	-35.73	peak	
2	*	2390.000	43.66	-3.82	39.84	74.00	-34.16	peak	

*:Maximum data x:Over limit !:over margin <Reference Only

Test Result: Pass

[TestMode: TX high channel]; [Polarity: Horizontal]



Site	Polarization: Horizontal	Temperature: (C)
Limit: FCC Part15 (PK)	Power:	Humidity: %RH
EUT: GEEK ONE		
M/N: AMP06		
Mode: BT TX-H		
Note: RX-1		


No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		
1	*	2483.500	51.53	-3.96	47.57	74.00	-26.43	peak	
2		2500.000	42.88	-4.00	38.88	74.00	-35.12	peak	

*:Maximum data x:Over limit l:over margin

<Reference Only

Test Result: Pass

[TestMode: TX high channel]; [Polarity: Vertical]



Site	Polarization: Vertical	Temperature: (C)
Limit: FCC Part15 (PK)	Power:	Humidity: %RH
EUT: GEEK ONE		
M/N: AMP06		
Mode: BT TX-H		
Note: RX-1		

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	*	2483.500	44.89	-3.96	40.93	74.00	-33.07	peak	
2		2500.000	43.89	-4.00	39.89	74.00	-34.11	peak	

*:Maximum data x:Over limit l:over margin

<Reference Only

Test Result: Pass

Remark:

1. Final Level = Receiver Read level + Correct factor
2. Correct factor = Antenna Factor + Cable Loss – Preamplifier Factor
3. The emission levels of other frequencies are very lower than the limit and not show in test report.

BlueAsia


18 CONDUCTED BAND EDGES MEASUREMENT

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 7.8.8 & Section 11.13.3.2
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Jozu
Temperature	25°C
Humidity	60%

18.1 LIMITS

Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).
---------------	--

18.2 BLOCK DIAGRAM OF TEST SETUP



18.3 TEST DATA

Pass: Please Refer To Appendix: Appendix1 For Details

BlueAsia


19 DWELL TIME

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 7.8.4
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Jozu
Temperature	25°C
Humidity	60%

19.1 LIMITS

Frequency(MHz)	Limit
902-928	0.4S within a 20S period(20dB bandwidth<250kHz)
	0.4S within a 10S period(20dB bandwidth≥250kHz)
2400-2483.5	0.4S within a period of 0.4S multiplied by the number of hopping channels
5725-5850	0.4S within a 30S period

19.2 BLOCK DIAGRAM OF TEST SETUP



19.3 TEST DATA

Pass: Please Refer To Appendix: Appendix1 For Details

BlueAsia


20 HOPPING CHANNEL NUMBER

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 7.8.3
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Jozu
Temperature	25°C
Humidity	60%

20.1 LIMITS

Frequency range(MHz)	Number of hopping channels (minimum)
902-928	50 for 20dB bandwidth <250kHz
	25 for 20dB bandwidth ≥250kHz
2400-2483.5	15
5725-5850	75

20.2 BLOCK DIAGRAM OF TEST SETUP



20.3 TEST DATA

Pass: Please Refer To Appendix: Appendix1 For Details


21 APPENDIX

21.1 TEST ENGINEER SAMPLE NO: TX-1

Maximum Conducted Output Power

Condition	Mode	Frequency (MHz)	Antenna	Conducted Power (dBm)	Limit (dBm)	Verdict
NVNT	1-DH1	2402	Ant1	0.829	21	Pass
NVNT	1-DH1	2441	Ant1	0.849	21	Pass
NVNT	1-DH1	2480	Ant1	0.929	21	Pass
NVNT	2-DH1	2402	Ant1	2.593	21	Pass
NVNT	2-DH1	2441	Ant1	2.508	21	Pass
NVNT	2-DH1	2480	Ant1	2.657	21	Pass
NVNT	3-DH1	2402	Ant1	2.985	21	Pass
NVNT	3-DH1	2441	Ant1	2.867	21	Pass
NVNT	3-DH1	2480	Ant1	3.041	21	Pass

Power NVNT 1-DH1 2402MHz Ant1



Power NVNT 1-DH1 2441MHz Ant1