



FCC RF Test Report

APPLICANT : Repairify, Inc.
EQUIPMENT : Diagnostic Tool
BRAND NAME : asTech®
MODEL NAME : AIO-5700-4G
FCC ID : 2A8NIAAI14G
STANDARD : FCC Part 15 Subpart C §15.247
CLASSIFICATION : (DSS) Spread Spectrum Transmitter
TEST DATE(S) : Mar. 25, 2024 ~ Apr. 28, 2024

This product installed a RF module (Brand Name: Quectel, Model Name: SC668S-NA, FCC ID: XMR2022SC668SNA) during the test, only Conducted Power, AC Conducted Emission and RSE test items are tested in this report, all the other test results are leveraged from module RF report.

We, Sporton International Inc. (Kunshan), would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. (Kunshan), the test report shall not be reproduced except in full.

Jason Jia



Approved by: Jason Jia

Sportun International Inc. (Kunshan)
No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300
People's Republic of China



TABLE OF CONTENTS

REVISION HISTORY.....	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION.....	5
1.1 Applicant	5
1.2 Manufacturer.....	5
1.3 Product Feature of Equipment Under Test.....	5
1.4 Product Specification of Equipment Under Test.....	5
1.5 Modification of EUT	5
1.6 Testing Location	6
1.7 Test Software.....	6
1.8 Applicable Standards.....	6
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST.....	7
2.1 Carrier Frequency Channel	7
2.2 Test Mode.....	8
2.3 Connection Diagram of Test System.....	9
2.4 Support Unit used in test configuration and system.....	9
2.5 EUT Operation Test Setup	9
3 TEST RESULT	10
3.1 Output Power Measurement.....	10
3.2 Radiated Band Edges and Spurious Emission Measurement	12
3.3 AC Conducted Emission Measurement.....	16
3.4 Antenna Requirements.....	18
4 LIST OF MEASURING EQUIPMENT.....	19
5 MEASUREMENT UNCERTAINTY	20
APPENDIX A. AC CONDUCTED EMISSION TEST RESULT	
APPENDIX B. RADIATED SPURIOUS EMISSION	
APPENDIX C. DUTY CYCLE PLOTS	
APPENDIX D. SETUP PHOTOGRAPHS	



REVISION HISTORY



SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
-	15.247(a)(1)	Number of Channels	$\geq 15\text{Chs}$	Pass	1
-	15.247(a)(1)	Hopping Channel Separation	$\geq 2/3 \text{ of } 20\text{dB BW}$	Pass	1
-	15.247(a)(1)	Dwell Time of Each Channel	$\leq 0.4\text{sec in } 31.6\text{sec period}$	Pass	1
-	15.247(a)(1)	20dB Bandwidth	-	Report only	1
-	-	99% Bandwidth	-	Report only	1
3.1	15.247(b)(1)	Peak Output Power	$\leq 125 \text{ mW}$	Pass	-
-	15.247(d)	Conducted Band Edges	$\leq 20\text{dBc}$	Pass	1
-	15.247(d)	Conducted Spurious Emission	$\leq 20\text{dBc}$	Pass	1
3.2	15.247(d)	Radiated Band Edges and Radiated Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 10.38 dB at 44.550 MHz
3.3	15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 12.02 dB at 0.341 MHz
3.4	15.203 & 15.247(b)	Antenna Requirement	15.203 & 15.247(b)	Pass	-

Remark 1: The conducted test results were leveraged from module RF report which can refer to Report No. 311713A.

Conformity Assessment Condition:

1. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacturer who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
2. The measurement uncertainty please refer to each test result in the section "Measurement Uncertainty"

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.



1 General Description

1.1 Applicant

Repairify, Inc.

5700 Tennyson PKWY, STE 600, Plano, TX 75024

1.2 Manufacturer

Launch Tech Co., Ltd.

Launch Industrial Park, North of Wuhe Avenue, Banxuegang, Longgang, Shenzhen 518031

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Diagnostic Tool
Brand Name	asTech®
Model Name	AIO-5700-4G
FCC ID	2A8NIAAI14G
IMEI Code	Conducted: 865696060076162/866914028793748 Conduction: 865696060076162/866914028793748 Radiation: 865696060076063/866914028793730
HW Version	V1.2
SW Version	SC668SNANAR02A05_BP01.001V02_QDM550
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx/Rx Frequency Range	2402 MHz ~ 2480 MHz
Number of Channels	79
Carrier Frequency of Each Channel	2402+n*1 MHz; n=0~78
Maximum Output Power to Antenna	Bluetooth BR(1Mbps) : 6.56 dBm (0.0045 W) Bluetooth EDR (2Mbps) : 8.22 dBm (0.0066 W) Bluetooth EDR (3Mbps) : 8.62 dBm (0.0073 W)
Antenna Type / Gain	IFA Antenna with gain 1.71 dBi
Type of Modulation	Bluetooth BR (1Mbps) : GFSK Bluetooth EDR (2Mbps) : π/4-DQPSK Bluetooth EDR (3Mbps) : 8-DPSK

1.5 Modification of EUT

No modifications are made to the EUT during all test items.



1.6 Testing Location

Sportun International Inc. (Kunshan) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

Test Firm	Sportun International Inc. (Kunshan)		
Test Site Location	No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China TEL : +86-512-57900158		
Test Site No.	Sportun Site No.	FCC Designation No.	FCC Test Firm Registration No.
	CO01-KS 03CH08-KS TH01-KS	CN1257	314309

1.7 Test Software

Item	Site	Manufacturer	Name	Version
1.	TH01-KS	Tonscend	JS1120-3 test system China_210602	3.3.10
2.	03CH08-KS	AUDIX	E3	210616
3.	CO01-KS	AUDIX	E3	6.2009-8-24

1.8 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 15 Subpart C §15.247
- FCC KDB 558074 D01 15.247 Meas Guidance v05r02
- ANSI C63.10-2013

Remark: All test items were verified and recorded according to the standards and without any deviation during the test.



2 Test Configuration of Equipment Under Test

2.1 Carrier Frequency Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	0	2402	27	2429	54	2456
	1	2403	28	2430	55	2457
	2	2404	29	2431	56	2458
	3	2405	30	2432	57	2459
	4	2406	31	2433	58	2460
	5	2407	32	2434	59	2461
	6	2408	33	2435	60	2462
	7	2409	34	2436	61	2463
	8	2410	35	2437	62	2464
	9	2411	36	2438	63	2465
	10	2412	37	2439	64	2466
	11	2413	38	2440	65	2467
	12	2414	39	2441	66	2468
	13	2415	40	2442	67	2469
	14	2416	41	2443	68	2470
	15	2417	42	2444	69	2471
	16	2418	43	2445	70	2472
	17	2419	44	2446	71	2473
	18	2420	45	2447	72	2474
	19	2421	46	2448	73	2475
	20	2422	47	2449	74	2476
	21	2423	48	2450	75	2477
	22	2424	49	2451	76	2478
	23	2425	50	2452	77	2479
	24	2426	51	2453	78	2480
	25	2427	52	2454	-	-
	26	2428	53	2455	-	-




2.2 Test Mode

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (Y plane) were recorded in this report, and the worst mode of radiated spurious emissions is Bluetooth 3Mbps mode, and recorded in this report.
- b. AC power line Conducted Emission was tested under maximum output power.

The following summary table is showing all test modes to demonstrate in compliance with the standard.

Summary table of Test Cases								
Test Item	Data Rate / Modulation							
	Bluetooth BR 1Mbps GFSK	Bluetooth EDR 2Mbps $\pi/4$ -DQPSK	Bluetooth EDR 3Mbps 8-DPSK					
Conducted Test Cases	Mode 1: CH00_2402 MHz Mode 2: CH39_2441 MHz Mode 3: CH78_2480 MHz	Mode 4: CH00_2402 MHz Mode 5: CH39_2441 MHz Mode 6: CH78_2480 MHz	Mode 7: CH00_2402 MHz Mode 8: CH39_2441 MHz Mode 9: CH78_2480 MHz					
Radiated Test Cases	Bluetooth EDR 3Mbps 8-DPSK							
	Mode 1: CH00_2402 MHz Mode 2: CH39_2441 MHz Mode 3: CH78_2480 MHz							
AC Conducted Emission	Mode 1 : Band 26 RX(Middle)+ BT Link+ WLAN Link(2.4G)+ USB cable TYPE-C(from Adapter)							
Remark:								
1. For radiated test cases, the worst mode data rate 3Mbps was reported only, because this data rate has the highest RF output power at preliminary tests, and no other significantly frequencies found in conducted spurious emission.								

2.3 Connection Diagram of Test System



2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	Anritus	MT8821C	N/A	N/A	Unshielded, 1.8m
2.	Notebook	Lenovo	G480	QDS-BRCM1050I	N/A	AC I/P: Unshielded, 1.8 m DC O/P: Shielded, 1.8 m
3.	Bluetooth Earphone	Lenovo	thinkplus-BH3	N/A	N/A	N/A
4.	WLAN AP	D-link	DIR-655	KA21R655B1	N/A	Unshielded, 1.8m
5.	SD Card	Kingston	8GB	N/A	N/A	N/A

2.5 EUT Operation Test Setup

For Bluetooth function, the engineering test program was provided and enabled to make EUT connect with Bluetooth base station to continuous transmit.

For AC power line conducted emissions, the EUT was set to connect with the WLAN AP under large package sizes transmission.

3 Test Result

3.1 Output Power Measurement

3.1.1 Limit of Output Power

The maximum peak conducted output power of the intentional radiator shall not exceed the following:

For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band 0.125 watts.


3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.5.
1. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
2. Set to the maximum power setting and enable the EUT transmit continuously.
3. Measure the conducted output power with cable loss and record the results in the test report.
4. Measure and record the results in the test report.

3.1.4 Test Setup





3.1.5 Test Result of Peak Output Power

DH	CH.	NTX	Peak Power (dBm)	Power Limit (dBm)	Test Result
DH1	0	1	6.47	20.97	Pass
	39	1	6.16	20.97	Pass
	78	1	6.56	20.97	Pass

2DH	CH.	NTX	Peak Power (dBm)	Power Limit (dBm)	Test Result
2DH1	0	1	8.16	20.97	Pass
	39	1	8.05	20.97	Pass
	78	1	8.22	20.97	Pass

3DH	CH.	NTX	Peak Power (dBm)	Power Limit (dBm)	Test Result
3DH1	0	1	8.54	20.97	Pass
	39	1	8.48	20.97	Pass
	78	1	8.62	20.97	Pass

Note: Power setting is default.



3.2 Radiated Band Edges and Spurious Emission Measurement

3.2.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.




3.2.3 Test Procedures

1. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
2. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
3. For each suspected emission, the EUT was arranged to its worst case and then tune the Antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.
4. Set to the maximum power setting and enable the EUT transmit continuously.
5. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 kHz for $f < 1$ GHz, RBW=1MHz for $f > 1$ GHz ; VBW \geq RBW; Sweep = auto; Detector function = peak; Trace = max hold for peak
 - (3) For average measurement: use duty cycle correction factor method per 15.35(c).
Duty cycle = On time/100 milliseconds
On time = $N_1 \cdot L_1 + N_2 \cdot L_2 + \dots + N_{n-1} \cdot L_{n-1} + N_n \cdot L_n$
Where N_1 is number of type 1 pulses, L_1 is length of type 1 pulses, etc.
Average Emission Level = Peak Emission Level + $20 \cdot \log(\text{Duty cycle})$
6. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
7. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
8. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than peak limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.


Note: The average levels were calculated from the peak level corrected with duty cycle correction factor (-24.79dB) derived from $20 \log(\text{dwell time}/100\text{ms})$. This correction is only for signals that hop with the fundamental signal, such as band-edge and harmonic. Other spurious signals that are independent of the hopping signal would not use this correction.

3.2.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz





3.2.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and semi-Anechoic chamber, and the result came out very similar.

3.2.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix B.

3.2.7 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic or 40GHz, whichever is lower)

Please refer to Appendix B.

3.2.8 Duty cycle correction factor for average measurement

Please refer to Appendix C.



3.3 AC Conducted Emission Measurement

3.3.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.3.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

3.3.4 Test Setup



3.3.5 Test Result of AC Conducted Emission

Please refer to Appendix A.



3.4 Antenna Requirements

3.4.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

3.4.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.4.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101040	10Hz~40GHz	Oct. 11, 2023	Apr. 28, 2024	Oct. 10, 2024	Conducted (TH01-KS)
Pulse Power Senor	Anritsu	MA2411B	0917070	300MHz~40GHz	Jan. 02, 2024	Apr. 28, 2024	Jan. 01, 2025	Conducted (TH01-KS)
Power Meter	Anritsu	ML2495A	1005002	50MHz Bandwidth	Jan. 02, 2024	Apr. 28, 2024	Jan. 01, 2025	Conducted (TH01-KS)
EMI Test Receiver	Keysight	N9038A	MY564000 23	3Hz~8.5GHz; Max 30dBm	Jan. 04, 2024	Apr. 17, 2024	Jan. 03, 2025	Radiation (03CH08-KS)
Spectrum Analyzer	R&S	FSV40	101932	10kHz~40GHz; Max 30dBm	Oct. 10, 2023	Apr. 17, 2024	Oct. 09, 2024	Radiation (03CH08-KS)
Loop Antenna	R&S	HFH2-Z2E	101125	9kHz~30MHz	Oct. 10, 2023	Apr. 17, 2024	Oct. 09, 2024	Radiation (03CH08-KS)
Bilog Antenna	TESEQ& VGT	CBL 61110	59915	30MHz-1GHz	Aug. 12, 2023	Apr. 17, 2024	Aug. 11, 2024	Radiation (03CH08-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	75959	1GHz~18GHz	Mar. 01, 2024	Apr. 17, 2024	Feb. 28, 2025	Radiation (03CH08-KS)
high gain Amplifier	EM	EM01G18GA	060845	1Ghz-18Ghz	Jan. 05, 2024	Apr. 17, 2024	Jan. 04, 2025	Radiation (03CH08-KS)
SHF-EHF Horn	Com-power	AH-840	101070	18GHz~40GHz	Jan. 05, 2024	Apr. 17, 2024	Jan. 04, 2025	Radiation (03CH08-KS)
Amplifier	SONOMA	310N	413741	9KHz-1GHz	Jan. 05, 2024	Apr. 17, 2024	Jan. 04, 2025	Radiation (03CH08-KS)
Amplifier	EM	EM01G18GA	060834	1Ghz-18Ghz	Oct. 10, 2023	Apr. 17, 2024	Oct. 09, 2024	Radiation (03CH08-KS)
Amplifier	MITEQ	EM18G40GG A	060728	18~40GHz	Jan. 04, 2024	Apr. 17, 2024	Jan. 03, 2025	Radiation (03CH08-KS)
AC Power Source	Chroma	61601	616010002 473	N/A	NCR	Apr. 17, 2024	NCR	Radiation (03CH08-KS)
Turn Table	EM	EM 1000-T	N/A	0~360 degree	NCR	Apr. 17, 2024	NCR	Radiation (03CH08-KS)
Antenna Mast	EM	EM 1000-A	N/A	1 m~4 m	NCR	Apr. 17, 2024	NCR	Radiation (03CH08-KS)
EMI Receiver	R&S	ESCI7	100768	9kHz~7GHz;	May 16, 2023	Mar. 25, 2024	May 15, 2024	Conduction (CO01-KS)
AC LISN (for auxiliary equipment)	MessTec	AN3016	060103	9kHz~30MHz	Oct. 11, 2023	Mar. 25, 2024	Oct. 10, 2024	Conduction (CO01-KS)
AC LISN	MessTec	AN3016	060105	9kHz~30MHz	May 16, 2023	Mar. 25, 2024	May 15, 2024	Conduction (CO01-KS)
AC Power Source	Chroma	61602	ABP00000 0811	AC 0V~300V, 45Hz~1000Hz	Oct. 11, 2023	Mar. 25, 2024	Oct. 10, 2024	Conduction (CO01-KS)

NCR: No Calibration Required



5 Measurement Uncertainty

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.10-2013. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Conducted Measurement

Conducted Power	± 0.46 dB
-----------------	---------------

Uncertainty of AC Conducted Emission Measurement (0.15 MHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_{c(y)}$)	2.84 dB
--	---------

Uncertainty of Radiated Emission Measurement (9 KHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_{c(y)}$)	3.32 dB
--	---------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_{c(y)}$)	6.28 dB
--	---------

Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_{c(y)}$)	4.90 dB
--	---------


Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_{c(y)}$)	5.26 dB
--	---------

----- THE END -----

Appendix A. AC Conducted Emission Test Results

Test Engineer :	Amos Zhang	Temperature :	25.3~26.2°C
		Relative Humidity :	38~40%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		




Site : CO01-KS
Condition : 15C RSS247-QP LISN-060105-L 2023 LINE

	Freq	Level	Over Limit	Limit	Read Line	LISN Level	Cable Factor	Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	dB	
1	0.188	45.65	-18.46	64.11	35.21	0.03	10.41	QP	
2	0.188	32.75	-21.36	54.11	22.31	0.03	10.41	Average	
3	0.471	42.01	-14.48	56.49	31.79	-0.02	10.24	QP	
4	0.471	28.81	-17.68	46.49	18.59	-0.02	10.24	Average	
5	0.755	39.55	-16.45	56.00	29.51	-0.08	10.12	QP	
6	0.755	28.55	-17.45	46.00	18.51	-0.08	10.12	Average	
7	1.449	40.46	-15.54	56.00	30.50	-0.12	10.08	QP	
8	1.449	28.46	-17.54	46.00	18.50	-0.12	10.08	Average	
9	16.312	42.56	-17.44	60.00	31.50	-0.19	11.25	QP	
10 *	16.312	37.36	-12.64	50.00	26.30	-0.19	11.25	Average	
11	20.486	39.60	-20.40	60.00	28.60	-0.36	11.36	QP	
12	20.486	33.90	-16.10	50.00	22.90	-0.36	11.36	Average	



Test Engineer :	Amos Zhang	Temperature :	25.3~26.2°C
Test Voltage :	120Vac / 60Hz	Relative Humidity :	38~40%
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		



Site : CO01-KS
Condition : 15C RSS247-QP LISN-060105-N 2023 NEUTRAL

Freq MHz	Level dB μ V	Over Limit dB	Limit Line dB μ V	Read Line dB μ V	LISN Factor dB	Cable Loss dB		Remark
						Cable Loss dB	Remark	
1	0.252	46.56	-15.13	61.69	36.19	0.00	10.37	QP
2	0.252	36.66	-15.03	51.69	26.29	0.00	10.37	Average
3 *	0.341	47.16	-12.02	59.18	36.90	-0.05	10.31	QP
4	0.341	35.46	-13.72	49.18	25.20	-0.05	10.31	Average
5	0.538	43.33	-12.67	56.00	33.20	-0.07	10.20	QP
6	0.538	29.73	-16.27	46.00	19.60	-0.07	10.20	Average
7	0.735	43.26	-12.74	56.00	33.20	-0.07	10.13	QP
8	0.735	28.26	-17.74	46.00	18.20	-0.07	10.13	Average
9	1.381	40.57	-15.43	56.00	30.60	-0.11	10.08	QP
10	1.381	28.57	-17.43	46.00	18.60	-0.11	10.08	Average
11	16.055	43.40	-16.60	60.00	32.30	-0.14	11.24	QP
12	16.055	37.70	-12.30	50.00	26.60	-0.14	11.24	Average

Note:

1. Level(dB μ V) = Read Level(dB μ V) + LISN Factor(dB) + Cable Loss(dB)
2. Over Limit(dB) = Level(dB μ V) - Limit Line(dB μ V)



Appendix B. Radiated Spurious Emission Test Data

Test Engineer :	Koi Ji			Relative Humidity :	41~42%
				Temperature :	22~23°C



Radiated Spurious Emission Test Modes

Mode	Band (MHz)	Antenna	Modulation	Channel	Frequency	Data Rate	RU	Remark
Mode 1	2400-2483.5	3	Bluetooth EDR_8-DPSK	00	2402	3Mbps	-	-
Mode 2	2400-2483.5	3	Bluetooth EDR_8-DPSK	39	2441	3Mbps	-	-
Mode 3	2400-2483.5	3	Bluetooth EDR_8-DPSK	78	2480	3Mbps	-	-



Summary of each worse mode


Mode	Modulation	Ch.	Freq. (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol.	Peak Avg.	Result	Remark
1	Bluetooth EDR_8-DPSK	00	2358.62	54.97	74.00	-19.03	H	PEAK	Pass	Band Edge
1	Bluetooth EDR_8-DPSK	00	4804.00	40.22	74.00	-33.78	V	PEAK	Pass	Harmonic
2	Bluetooth EDR_8-DPSK	39	-	-	-	-	-	-	-	Band Edge
2	Bluetooth EDR_8-DPSK	39	7323.00	42.20	74.00	-31.80	H	PEAK	Pass	Harmonic
3	Bluetooth EDR_8-DPSK	78	2483.78	59.49	74.00	-14.51	H	PEAK	Pass	Band Edge
3	Bluetooth EDR_8-DPSK	78	7440.00	42.75	74.00	-31.25	H	PEAK	Pass	Harmonic




Mode	1																																																																																											
	Band Edge																																																																																											
	2400-2483.5_Bluetooth EDR_8-DPSK_CH00_2402MHz																																																																																											
ANT	3																																																																																											
Pol.	Horizontal	Fundamental																																																																																										
Peak	 <table><thead><tr><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr></thead><tbody><tr><td>MHz</td><td>dBuV/m</td><td>dBuV/m</td><td>dB</td><td>dBuV</td><td>dB/m</td><td>dB</td><td>dB</td><td>cm deg</td></tr><tr><td>1</td><td>2358.62</td><td>54.97</td><td>74.00</td><td>-19.03</td><td>38.89</td><td>32.32</td><td>8.78</td><td>30.94 6.00 100 229 PEAK</td></tr><tr><td>2</td><td>2358.62</td><td>30.18</td><td>54.00</td><td>-23.82</td><td>14.10</td><td>32.32</td><td>8.78</td><td>30.94 6.00 100 229 AVERAGE</td></tr></tbody></table>	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm deg	1	2358.62	54.97	74.00	-19.03	38.89	32.32	8.78	30.94 6.00 100 229 PEAK	2	2358.62	30.18	54.00	-23.82	14.10	32.32	8.78	30.94 6.00 100 229 AVERAGE	 <table><thead><tr><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr></thead><tbody><tr><td>MHz</td><td>dBuV/m</td><td>dBuV/m</td><td>dB</td><td>dBuV</td><td>dB/m</td><td>dB</td><td>dB</td><td>cm deg</td></tr><tr><td>1</td><td>2402.00</td><td>101.26</td><td>-----</td><td>-----</td><td>84.99</td><td>32.40</td><td>8.88</td><td>30.93 6.00 100 229 PEAK</td></tr><tr><td>2</td><td>2402.00</td><td>76.47</td><td>-----</td><td>-----</td><td>68.20</td><td>32.40</td><td>8.88</td><td>30.93 6.00 100 229 AVERAGE</td></tr></tbody></table>	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm deg	1	2402.00	101.26	-----	-----	84.99	32.40	8.88	30.93 6.00 100 229 PEAK	2	2402.00	76.47	-----	-----	68.20	32.40	8.88	30.93 6.00 100 229 AVERAGE
Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																				
Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor																																																																																					
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm deg																																																																																				
1	2358.62	54.97	74.00	-19.03	38.89	32.32	8.78	30.94 6.00 100 229 PEAK																																																																																				
2	2358.62	30.18	54.00	-23.82	14.10	32.32	8.78	30.94 6.00 100 229 AVERAGE																																																																																				
Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																				
Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor																																																																																					
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm deg																																																																																				
1	2402.00	101.26	-----	-----	84.99	32.40	8.88	30.93 6.00 100 229 PEAK																																																																																				
2	2402.00	76.47	-----	-----	68.20	32.40	8.88	30.93 6.00 100 229 AVERAGE																																																																																				





Mode	1																																																																																	
	Band Edge																																																																																	
	2400-2483.5_Bluetooth EDR_8-DPSK_CH00_2402MHz																																																																																	
ANT	3																																																																																	
Pol.	Vertical	Fundamental																																																																																
Peak	 <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Factor</th><th></th></tr></thead><tbody><tr><td>1</td><td>2347.57</td><td>54.68</td><td>74.00</td><td>-19.32</td><td>38.67</td><td>32.28</td><td>8.67</td><td>30.94</td><td>6.00 102 245 PEAK</td></tr><tr><td>2</td><td>2347.57</td><td>29.89</td><td>54.00</td><td>-24.11</td><td>13.88</td><td>32.28</td><td>8.67</td><td>30.94</td><td>6.00 102 245 AVERAGE</td></tr></tbody></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor	Factor		1	2347.57	54.68	74.00	-19.32	38.67	32.28	8.67	30.94	6.00 102 245 PEAK	2	2347.57	29.89	54.00	-24.11	13.88	32.28	8.67	30.94	6.00 102 245 AVERAGE	 <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Factor</th><th></th></tr></thead><tbody><tr><td>1</td><td>2402.00</td><td>101.24</td><td>-----</td><td>-----</td><td>84.97</td><td>32.40</td><td>8.80</td><td>30.93</td><td>6.00 102 245 PEAK</td></tr><tr><td>2</td><td>2402.00</td><td>76.45</td><td>-----</td><td>-----</td><td>60.18</td><td>32.40</td><td>8.80</td><td>30.93</td><td>6.00 102 245 AVERAGE</td></tr></tbody></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor	Factor		1	2402.00	101.24	-----	-----	84.97	32.40	8.80	30.93	6.00 102 245 PEAK	2	2402.00	76.45	-----	-----	60.18	32.40	8.80	30.93	6.00 102 245 AVERAGE
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																									
Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor	Factor																																																																										
1	2347.57	54.68	74.00	-19.32	38.67	32.28	8.67	30.94	6.00 102 245 PEAK																																																																									
2	2347.57	29.89	54.00	-24.11	13.88	32.28	8.67	30.94	6.00 102 245 AVERAGE																																																																									
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																									
Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor	Factor																																																																										
1	2402.00	101.24	-----	-----	84.97	32.40	8.80	30.93	6.00 102 245 PEAK																																																																									
2	2402.00	76.45	-----	-----	60.18	32.40	8.80	30.93	6.00 102 245 AVERAGE																																																																									













Mode	3																																																																																
	Band Edge																																																																																
	2400-2483.5_Bluetooth EDR_8-DPSK_CH78_2480MHz																																																																																
ANT	3																																																																																
Pol.	Horizontal	Fundamental																																																																															
Peak																																																																																	
	<table border="1"><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Factor</th><th></th></tr></thead><tbody><tr><td>1</td><td>2483.78</td><td>59.49</td><td>74.00</td><td>-14.51</td><td>43.18</td><td>32.40</td><td>8.88</td><td>30.97</td><td>6.00</td></tr><tr><td>2</td><td>2483.78</td><td>34.70</td><td>54.00</td><td>-19.30</td><td>18.39</td><td>32.40</td><td>8.88</td><td>30.97</td><td>6.00</td></tr></tbody></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor	Factor		1	2483.78	59.49	74.00	-14.51	43.18	32.40	8.88	30.97	6.00	2	2483.78	34.70	54.00	-19.30	18.39	32.40	8.88	30.97	6.00	<table border="1"><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Factor</th><th></th></tr></thead><tbody><tr><td>1</td><td>2480.00</td><td>100.43</td><td>-----</td><td>-----</td><td>84.12</td><td>32.40</td><td>8.88</td><td>30.97</td><td>6.00</td></tr><tr><td>2</td><td>2480.00</td><td>75.64</td><td>-----</td><td>-----</td><td>59.33</td><td>32.40</td><td>8.88</td><td>30.97</td><td>6.00</td></tr></tbody></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor	Factor		1	2480.00	100.43	-----	-----	84.12	32.40	8.88	30.97	6.00	2	2480.00	75.64	-----	-----	59.33	32.40	8.88	30.97
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																								
Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor	Factor																																																																									
1	2483.78	59.49	74.00	-14.51	43.18	32.40	8.88	30.97	6.00																																																																								
2	2483.78	34.70	54.00	-19.30	18.39	32.40	8.88	30.97	6.00																																																																								
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																								
Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor	Factor																																																																									
1	2480.00	100.43	-----	-----	84.12	32.40	8.88	30.97	6.00																																																																								
2	2480.00	75.64	-----	-----	59.33	32.40	8.88	30.97	6.00																																																																								




Mode	3																																																																																	
	Band Edge																																																																																	
	2400-2483.5_Bluetooth EDR_8-DPSK_CH78_2480MHz																																																																																	
ANT	3																																																																																	
Pol.	Vertical	Fundamental																																																																																
																																																																																		
Peak	<table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr></thead><tbody><tr><td>1</td><td>2493.39</td><td>55.34</td><td>74.00</td><td>-18.66</td><td>39.04</td><td>32.40</td><td>8.87</td><td>30.97</td><td>6.00 147 249 PEAK</td></tr><tr><td>2</td><td>2493.39</td><td>30.55</td><td>54.00</td><td>-23.45</td><td>14.25</td><td>32.40</td><td>8.87</td><td>30.97</td><td>6.00 147 249 AVERAGE</td></tr></tbody></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor		1	2493.39	55.34	74.00	-18.66	39.04	32.40	8.87	30.97	6.00 147 249 PEAK	2	2493.39	30.55	54.00	-23.45	14.25	32.40	8.87	30.97	6.00 147 249 AVERAGE	<table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr></thead><tbody><tr><td>1</td><td>2480.00</td><td>98.69</td><td>-----</td><td>-----</td><td>82.38</td><td>32.40</td><td>8.88</td><td>30.97</td><td>6.00 147 249 PEAK</td></tr><tr><td>2</td><td>2480.00</td><td>73.90</td><td>-----</td><td>-----</td><td>57.59</td><td>32.40</td><td>8.88</td><td>30.97</td><td>6.00 147 249 AVERAGE</td></tr></tbody></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor		1	2480.00	98.69	-----	-----	82.38	32.40	8.88	30.97	6.00 147 249 PEAK	2	2480.00	73.90	-----	-----	57.59	32.40	8.88	30.97	6.00 147 249 AVERAGE
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																									
Freq	Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor																																																																										
1	2493.39	55.34	74.00	-18.66	39.04	32.40	8.87	30.97	6.00 147 249 PEAK																																																																									
2	2493.39	30.55	54.00	-23.45	14.25	32.40	8.87	30.97	6.00 147 249 AVERAGE																																																																									
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																									
Freq	Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor																																																																										
1	2480.00	98.69	-----	-----	82.38	32.40	8.88	30.97	6.00 147 249 PEAK																																																																									
2	2480.00	73.90	-----	-----	57.59	32.40	8.88	30.97	6.00 147 249 AVERAGE																																																																									




Mode	Harmonic																																																																																																									
2400-2483.5_Bluetooth EDR_8-DPSK_CH78_2480MHz																																																																																																										
ANT	3																																																																																																									
Pol.	Horizontal						Vertical																																																																																																			
Peak																																																																																																										
Avg	<table border="1"> <thead> <tr> <th rowspan="2">Freq</th> <th colspan="2">Limit</th> <th>Read</th> <th>Ant</th> <th>Cable</th> <th>Preamp</th> <th>Aux</th> <th>APos</th> <th>TPos</th> <th colspan="2">Remark</th> </tr> <tr> <th>MHz</th> <th>dBuV/m</th> <th>dBuV/m</th> <th>dB</th> <th>dBuV</th> <th>dB/m</th> <th>dB</th> <th>dB</th> <th>cm</th> <th>deg</th> <th></th> </tr> </thead> <tbody> <tr> <td>1</td> <td>4960.00</td> <td>39.86</td> <td>74.00</td> <td>-34.14</td> <td>58.95</td> <td>34.24</td> <td>12.07</td> <td>65.40</td> <td>0.00</td> <td>--</td> <td>-- PEAK</td> </tr> <tr> <td>2</td> <td>7440.00</td> <td>42.75</td> <td>74.00</td> <td>-31.25</td> <td>56.93</td> <td>35.80</td> <td>15.21</td> <td>65.19</td> <td>0.00</td> <td>--</td> <td>-- PEAK</td> </tr> </tbody> </table>						Freq	Limit		Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg		1	4960.00	39.86	74.00	-34.14	58.95	34.24	12.07	65.40	0.00	--	-- PEAK	2	7440.00	42.75	74.00	-31.25	56.93	35.80	15.21	65.19	0.00	--	-- PEAK	<table border="1"> <thead> <tr> <th rowspan="2">Freq</th> <th colspan="2">Limit</th> <th>Read</th> <th>Ant</th> <th>Cable</th> <th>Preamp</th> <th>Aux</th> <th>APos</th> <th>TPos</th> <th colspan="2">Remark</th> </tr> <tr> <th>MHz</th> <th>dBuV/m</th> <th>dBuV/m</th> <th>dB</th> <th>dBuV</th> <th>dB/m</th> <th>dB</th> <th>dB</th> <th>cm</th> <th>deg</th> <th></th> </tr> </thead> <tbody> <tr> <td>1</td> <td>4960.00</td> <td>40.72</td> <td>74.00</td> <td>-33.28</td> <td>59.81</td> <td>34.24</td> <td>12.07</td> <td>65.40</td> <td>0.00</td> <td>--</td> <td>-- PEAK</td> </tr> <tr> <td>2</td> <td>7440.00</td> <td>42.03</td> <td>74.00</td> <td>-31.97</td> <td>56.21</td> <td>35.80</td> <td>15.21</td> <td>65.19</td> <td>0.00</td> <td>--</td> <td>-- PEAK</td> </tr> </tbody> </table>						Freq	Limit		Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg		1	4960.00	40.72	74.00	-33.28	59.81	34.24	12.07	65.40	0.00	--	-- PEAK	2	7440.00	42.03	74.00	-31.97	56.21	35.80	15.21	65.19	0.00	--	-- PEAK
Freq	Limit		Read	Ant	Cable	Preamp		Aux	APos	TPos	Remark																																																																																															
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																
1	4960.00	39.86	74.00	-34.14	58.95	34.24	12.07	65.40	0.00	--	-- PEAK																																																																																															
2	7440.00	42.75	74.00	-31.25	56.93	35.80	15.21	65.19	0.00	--	-- PEAK																																																																																															
Freq	Limit		Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																
1	4960.00	40.72	74.00	-33.28	59.81	34.24	12.07	65.40	0.00	--	-- PEAK																																																																																															
2	7440.00	42.03	74.00	-31.97	56.21	35.80	15.21	65.19	0.00	--	-- PEAK																																																																																															
Peak																																																																																																										
Avg																																																																																																										

Note: Only the worst case has assessed 18G ~25GHz to test.




Appendix C. Duty Cycle Plots

3DH5 on time (One Pulse) Plot on Channel 00



3DH5 on time (Count Pulses) Plot on Channel 00



Note:

1. Worst case Duty cycle = on time/100 milliseconds = $2 * 2.88 / 100 = 5.76 \%$
2. Worst case Duty cycle correction factor = $20 * \log(\text{Duty cycle}) = -24.79 \text{ dB}$
3. 3DH5 has the highest duty cycle worst case and is reported.