

TEST REPORT

Product Name : Wireless Gaming Headphones
Brand Mark :  **MONSTER®**
Model No. : Monster Airmars XKT10 Pro
Report Number : BLA-EMC-202303-A13402
FCC ID : 2A8PV-QSMT10P
Date of Sample Receipt : 2023/3/29
Date of Test : 2023/3/29 to 2023/4/11
Date of Issue : 2023/4/11
Test Standard : 47 CFR Part 15, Subpart C 15.247
Test Result : Pass

Prepared for:

Shenzhen Information Infinity Co., Ltd.
Block a,CleanSunshine Garden,15Keji Second Road Songpingshan
community, XiliStreet,Nanshan District, Shenzhen

Prepared by:

BlueAsia of Technical Services(Shenzhen) Co.,Ltd.
Building C, No. 107, Shihuan Road, Shiyuan Sub-District, Baoan District,
Shenzhen, Guangdong Province, China
TEL: +86-755-23059481

Compiled by:



Review by:



Approved by:



Date:

2023/4/11



REPORT REVISE RECORD

Version No.	Date	Description
00	2023/4/11	Original

BlueAsia

TABLE OF CONTENTS

1	TEST SUMMARY	5
2	GENERAL INFORMATION	6
3	GENERAL DESCRIPTION OF E.U.T.	6
4	TEST ENVIRONMENT	7
5	TEST MODE	7
6	MEASUREMENT UNCERTAINTY	7
7	DESCRIPTION OF SUPPORT UNIT	8
8	LABORATORY LOCATION	8
9	TEST INSTRUMENTS LIST	9
10	ANTENNA REQUIREMENT	11
10.1	CONCLUSION	11
11	CONDUCTED SPURIOUS EMISSIONS	12
11.1	LIMITS	12
11.2	BLOCK DIAGRAM OF TEST SETUP	12
11.3	TEST DATA	13
12	20DB BANDWIDTH	14
12.1	BLOCK DIAGRAM OF TEST SETUP	14
12.2	TEST DATA	14
13	CONDUCTED PEAK OUTPUT POWER	15
13.1	LIMITS	15
13.2	BLOCK DIAGRAM OF TEST SETUP	15
13.3	TEST DATA	16
14	CONDUCTED EMISSIONS AT AC POWER LINE (150KHZ-30MHZ)	17
14.1	LIMITS	17
14.2	BLOCK DIAGRAM OF TEST SETUP	17
14.3	PROCEDURE	17
14.4	TEST DATA	19
15	RADIATED SPURIOUS EMISSIONS	21
15.1	LIMITS	21

15.2	BLOCK DIAGRAM OF TEST SETUP	22
15.3	PROCEDURE	22
15.4	TEST DATA	24
16	RADIATED EMISSIONS WHICH FALL IN THE RESTRICTED BANDS	32
16.1	LIMITS	32
16.2	BLOCK DIAGRAM OF TEST SETUP	33
16.3	PROCEDURE	33
16.4	TEST DATA	35
17	CONDUCTED BAND EDGES MEASUREMENT	39
17.1	LIMITS	39
17.2	BLOCK DIAGRAM OF TEST SETUP	39
17.3	TEST DATA	40
18	DWELL TIME	41
18.1	LIMITS	41
18.2	BLOCK DIAGRAM OF TEST SETUP	41
18.3	TEST DATA	42
19	HOPPING CHANNEL NUMBER	43
19.1	LIMITS	43
19.2	BLOCK DIAGRAM OF TEST SETUP	43
19.3	TEST DATA	43
20	CARRIER FREQUENCIES SEPARATION	44
20.1	LIMITS	44
20.2	BLOCK DIAGRAM OF TEST SETUP	44
20.3	TEST DATA	44
21	APPENDIX	45
APPENDIX A: PHOTOGRAPHS OF TEST SETUP		83
APPENDIX B: PHOTOGRAPHS OF EUT		85

1 TEST SUMMARY

Test item	Test Requirement	Test Method	Class/Severity	Result
Antenna Requirement	47 CFR Part 15, Subpart C 15.247	N/A	47 CFR Part 15, Subpart C 15.203 & 15.247(c)	Pass
Conducted Spurious Emissions	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.6 & Section 11.11	47 CFR Part 15, Subpart C 15.247(d)	Pass
20dB Bandwidth	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.7	47 CFR Part 15, Subpart C 15.247(a)(1)	Pass
Conducted Peak Output Power	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.5	47 CFR Part 15, Subpart C 15.247(b)(3)	Pass
Conducted Emissions at AC Power Line (150kHz-30MHz)	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.2	47 CFR Part 15, Subpart C 15.207	Pass
Radiated Spurious Emissions	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.4,6.5,6.6	47 CFR Part 15, Subpart C 15.209 & 15.247(d)	Pass
Radiated Emissions which fall in the restricted bands	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.10.5	47 CFR Part 15, Subpart C 15.209 & 15.247(d)	Pass
Conducted Band Edges Measurement	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.8 & Section 11.13.3.2	47 CFR Part 15, Subpart C 15.247(d)	Pass
Dwell Time	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.4	47 CFR Part 15, Subpart C 15.247a(1)(iii)	Pass
Hopping Channel Number	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.3	47 CFR Part 15, Subpart C 15.247a(1)(iii)	Pass
Carrier Frequencies Separation	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.2	47 CFR Part 15, Subpart C 15.247a(1)	Pass

2 GENERAL INFORMATION

Applicant	Shenzhen Information Infinity Co., Ltd.
Address	Block a,CleanSunshine Garden,15Keji Second Road Songpingshan community, XiliStreet,Nanshan Distric, Shenzhen
Manufacturer	Shenzhen Information Infinity Co., Ltd.
Address	Block a,CleanSunshine Garden,15Keji Second Road Songpingshan community, XiliStreet,Nanshan Distric, Shenzhen
Factory	Shenzhen Information Infinity Co., Ltd.
Address	Block a,CleanSunshine Garden,15Keji Second Road Songpingshan community, XiliStreet,Nanshan Distric, Shenzhen
Product Name	Wireless Gaming Headphones
Test Model No.	Monster Airmars XKT10 Pro

3 GENERAL DESCRIPTION OF E.U.T.

Hardware Version	BSX-J205- V1.3
Software Version	ME139-V06
Operation Frequency:	2402MHz-2480MHz
Modulation Type:	GFSK, pi/4DQPSK
Channel Spacing:	1MHz
Number of Channels:	79
Antenna Type:	Chip Antenna
Antenna Gain:	1.15dBi (Provided by the applicant)

4 TEST ENVIRONMENT

Environment	Temperature	Voltage
Normal	25°C	3.7Vdc

5 TEST MODE

TEST MODE	TEST MODE DESCRIPTION
Transmitting mode	Keep the EUT in continuously transmitting mode with modulation. (hopping and non hopping mode all have been tested, non hopping mode is worse case for RE)
Remark: Full battery is used during all test except ac conducted emission, DH1,DH3, DH5 all have been tested, during the test, GFSK, Pi/4QPSK modulation were all pre-scanned only GFSK worse case is reported.	

6 MEASUREMENT UNCERTAINTY

Parameter	Expanded Uncertainty (Confidence of 95%)
Radiated Emission(9kHz-30MHz)	±4.34dB
Radiated Emission(30Mz-1000MHz)	±4.24dB
Radiated Emission(1GHz-18GHz)	±4.68dB
AC Power Line Conducted Emission(150kHz-30MHz)	±3.45dB

Parameter	Expanded Uncertainty (Confidence of 95%)
Occupied Channel Bandwidth	±5 %
RF output power, conducted	±1.5 dB
Power Spectral Density, conducted	±3.0 dB
Unwanted Emissions, conducted	±3.0 dB
Temperature	±3 °C
Supply voltages	±3 %
Time	±5 %
Unwanted Radiated Emission (30MHz ~ 1000MHz)	±4.35 dB
Unwanted Radiated Emission (1GHz ~ 18GHz)	±4.44 dB

7 DESCRIPTION OF SUPPORT UNIT

Device Type	Manufacturer	Model Name	Serial No.	Remark
AC Adapter	UGREEN	CD112	N/A	N/A

8 LABORATORY LOCATION

All tests were performed at:
BlueAsia of Technical Services(Shenzhen) Co.,Ltd.
Building C, No. 107, Shihuan Road, Shiyao Sub-District, Baoan District, Shenzhen, Guangdong Province,
China
Telephone: TEL: +86-755-28682673 FAX: +86-755-28682673

9 TEST INSTRUMENTS LIST

Test Equipment Of Radiated Spurious Emissions					
Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Chamber 1	SKET	966	N/A	2020/11/10	2023/11/9
Chamber 2	SKET	966	N/A	2021/07/20	2024/07/19
Spectrum	R&S	FSP40	100817	2022/09/15	2023/09/14
Receiver	R&S	ESR7	101199	2022/09/15	2023/09/14
Receiver	R&S	ESPI7	101477	2022/07/16	2023/07/15
broadband Antenna	Schwarzbeck	VULB9168	00836 P:00227	2022/09/15	2023/09/14
Horn Antenna	Schwarzbeck	BBHA9120D	01892 P:00331	2022/09/13	2025/09/12
Amplifier	SKET	LNPA_30M01G-30	SK2021060801	2022/07/16	2023/07/15
Amplifier	SKET	PA-000318G-45	N/A	2022/09/13	2023/09/12
Amplifier	SKET	LNPA_18G40G-50	SK2022071301	2022/07/14	2023/07/13
Filter group	SKET	2.4G/5G Filter group r	N/A	2022/07/16	2023/07/15
EMI software	EZ	EZ-EMC	EEMC-3A1	N/A	N/A
Loop antenna	SCHNARZBECK	FMZB1519B	00102	2022/9/14	2025/9/13
Controller	SKET	N/A	N/A	N/A	N/A
Coaxial Cable	BlueAsia	BLA-XC-02	N/A	N/A	N/A
Coaxial Cable	BlueAsia	BLA-XC-03	N/A	N/A	N/A
Coaxial Cable	BlueAsia	BLA-XC-01	N/A	N/A	N/A

Test Equipment Of Conducted Emissions at AC Power Line (150kHz-30MHz)

Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Shield room	SKET	833	N/A	2020/11/25	2023/11/24
Receiver	R&S	ESPI3	101082	2022/09/14	2023/09/13
LISN	R&S	ENV216	3560.6550.15	2022/09/14	2023/09/13
LISN	AT	AT166-2	AKK1806000003	2022/09/14	2023/09/13
ISN	TESEQ	ISNT8-cat6	53580	2022/09/14	2023/09/13
Single-channel vehicle artificial power network	Schwarzbeck	NNBM 8124	01045	2022/08/17	2023/08/16
Single-channel vehicle artificial power network	Schwarzbeck	NNBM 8124	01075	2022/08/17	2023/08/16
EMI software	EZ	EZ-EMC	EEMC-3A1	N/A	N/A

Test Equipment Of RF Conducted Test

Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Spectrum	R&S	FSP40	100817	2022/09/15	2023/09/14
Spectrum	Agilent	N9020A	MY49100060	2022/09/07	2023/09/06
Spectrum	KEYSIGHT	N9030A	MY52350152	2022/07/01	2023/06/30
Spectrum	KEYSIGHT	N9010A	MY54330814	2022/07/01	2023/06/30
Signal Generator	Agilent	N5182A	MY47420955	2022/09/07	2023/09/06
Signal Generator	Agilent	E8257D	MY44320250	2022/07/01	2023/06/30
Signal Generator	Agilent	N5181A	MY46240904	2022/08/02	2023/08/01
Signal Generator	R&S	CMW500	132429	2022/09/07	2023/09/06
BluetoothTester	Anritsu	MT8852B	06262047872	2022/09/07	2023/09/06
Power probe	DARE	RPR3006W	14I00889SN042	2022/09/07	2023/09/06
DCPowersupply	zhaoxin	KXN-305D	20K305D1221363	2022/09/14	2023/09/13
DCPowersupply	zhaoxin	RXN-1505D	19R1505D050168	2022/09/14	2023/09/13
2.4GHz/5GHz RF Test software	MTS	MTS 8310	Version 2.0.0.0	N/A	N/A
Audio Analyzer	Audioprecision	N/A	ATSI-41094	2022/7/1	2023/6/30

10 ANTENNA REQUIREMENT

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	N/A

10.1 CONCLUSION

Standard Requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit permanently attached antenna or of an so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

EUT Antenna:

The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is 1.15dBi.


11 CONDUCTED SPURIOUS EMISSIONS

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 7.8.6 & Section 11.11
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Jozu
Temperature	25°C
Humidity	60%

11.1 LIMITS

Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).
---------------	--

11.2 BLOCK DIAGRAM OF TEST SETUP



11.3 TEST DATA


Pass: Please Refer To Appendix: Appendix1 For Details

BlueAsia

12 20DB BANDWIDTH

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 7.8.7
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Jozu
Temperature	25℃
Humidity	60%

12.1 BLOCK DIAGRAM OF TEST SETUP



12.2 TEST DATA

Pass: Please Refer To Appendix: Appendix1 For Details


13 CONDUCTED PEAK OUTPUT POWER

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 7.8.5
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Jozu
Temperature	25℃
Humidity	60%

13.1 LIMITS

Frequency range(MHz)	Output power of the intentional radiator(watt)
902-928	1 for ≥ 50 hopping channels
	0.25 for $25 \leq$ hopping channels < 50
	1 for digital modulation
2400-2483.5	1 for ≥ 75 non-overlapping hopping channels
	0.125 for all other frequency hopping systems
	1 for digital modulation
5725-5850	1 for frequency hopping systems and digital modulation

13.2 BLOCK DIAGRAM OF TEST SETUP



13.3 TEST DATA

Pass: Please Refer To Appendix: Appendix1 For Details

BlueAsia

14 CONDUCTED EMISSIONS AT AC POWER LINE (150KHZ-30MHZ)


Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 6.2
Test Mode (Pre-Scan)	BT mode
Test Mode (Final Test)	BT mode
Tester	Jozu
Temperature	25℃
Humidity	60%

14.1 LIMITS

Frequency of emission(MHz)	Conducted limit(dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

14.2 BLOCK DIAGRAM OF TEST SETUP



14.3 PROCEDURE


- 1) The mains terminal disturbance voltage test was conducted in a shielded room.
- 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50ohm/50H + 5ohm linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.

- 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane,
- 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.
- 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.

Remark: $LISN = Read\ Level + Cable\ Loss + LISN\ Factor$

14.4 TEST DATA

[TestMode: BT mode]; [Line: Line] ;[Power:AC120V/60Hz]



Site: Phase: **L1** Temperature: (C)
Limit: FCC Class B Conduction(QP) Power: Humidity: %RH
EUT: Wireless Gaming Headphones
M/N: Monster Airmars XKT10 Pro
Mode: TX mode
Note:

No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1	0.4940	29.78	10.08	39.86	56.10	-16.24	QP	
2 *	0.4940	21.77	10.08	31.85	46.10	-14.25	AVG	
3	0.9780	23.40	10.11	33.51	56.00	-22.49	QP	
4	0.9780	15.78	10.11	25.89	46.00	-20.11	AVG	
5	2.3060	20.21	10.28	30.49	56.00	-25.51	QP	
6	2.3060	13.89	10.28	24.17	46.00	-21.83	AVG	
7	4.1779	13.26	10.08	23.34	56.00	-32.66	QP	
8	4.1779	12.35	10.08	22.43	46.00	-23.57	AVG	
9	8.2500	11.76	10.08	21.84	60.00	-38.16	QP	
10	8.2500	5.72	10.08	15.80	50.00	-34.20	AVG	
11	18.3660	7.89	9.99	17.88	60.00	-42.12	QP	
12	18.3660	1.82	9.99	11.81	50.00	-38.19	AVG	
13	18.3660	1.82	9.99	11.81	50.00	-38.19	AVG	


*:Maximum data x:Over limit !:over margin

⟨Reference Only⟩

Test Result: Pass

[TestMode: BT mode]; [Line: Nutral] ;[Power:AC120V/60Hz]

Conducted Emission Measurement



Site: Phase: **N** Temperature: (C)
Limit: FCC Class B Conduction(QP) Power: Humidity: %RH
EUT: Wireless Gaming Headphones
M/N: Monster Airmars XKT10 Pro
Mode: TX mode
Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.5140	32.90	10.05	42.95	56.00	-13.05	QP	
2	*	0.5140	30.07	10.05	40.12	46.00	-5.88	AVG	
3		1.2980	22.60	10.04	32.64	56.00	-23.36	QP	
4		1.2980	16.55	10.04	26.59	46.00	-19.41	AVG	
5		2.3900	21.93	10.07	32.00	56.00	-24.00	QP	
6		2.3900	15.23	10.07	25.30	46.00	-20.70	AVG	
7		4.6860	18.51	9.84	28.35	56.00	-27.65	QP	
8		4.6860	12.41	9.84	22.25	46.00	-23.75	AVG	
9		12.9460	5.33	9.99	15.32	60.00	-44.68	QP	
10		12.9460	-0.46	9.99	9.53	50.00	-40.47	AVG	
11		19.4100	9.30	10.01	19.31	60.00	-40.69	QP	
12		19.4100	4.11	10.01	14.12	50.00	-35.88	AVG	

*:Maximum data x:Over limit !:over margin

(Reference Only)

Test Result: Pass

15 RADIATED SPURIOUS EMISSIONS


Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 6.4,6.5,6.6
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Jozu
Temperature	25℃
Humidity	60%

15.1 LIMITS

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

15.2 BLOCK DIAGRAM OF TEST SETUP



15.3 PROCEDURE

- For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.


- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.

Remark:

- 1) For emission below 1GHz, through pre-scan found the worst case is the lowest channel. Only the worst case is recorded in the report.
- 2) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:
Final Test Level = Receiver Reading + Antenna Factor + Cable Factor - Preamplifier Factor
- 3) Scan from 9kHz to 25GHz, the disturbance above 12.75GHz and below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported. fundamental frequency is blocked by filter, and only spurious emission is shown.
- 4) For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.

15.4 TEST DATA


[TestMode: TX below 1G]; [Polarity: Horizontal]



*:Maximum data x:Over limit !:over margin

Test Result: Pass

[TestMode: TX below 1G]; [Polarity: Vertical]




*:Maximum data x:Over limit !:over margin

Test Result: Pass

Above 1GHz:

[TestMode: TX low channel]; [Polarity: Horizontal]



Site: Polarization: **Horizontal** Temperature: (C)
Limit: FCC Part15 (PK) Power: Humidity: %RH
EUT: Wireless Gaming Headphones
M/N: Monster Airmars XKT10 Pro
Mode: TX-L
Note:


No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		4804.000	40.10	4.05	44.15	74.00	-29.85	peak	
2		5700.000	40.62	6.81	47.43	74.00	-26.57	peak	
3		7206.000	39.43	7.93	47.36	74.00	-26.64	peak	
4		8038.250	40.61	8.91	49.52	74.00	-24.48	peak	
5		9608.000	38.30	10.90	49.20	74.00	-24.80	peak	
6	*	11880.500	39.06	13.85	52.91	74.00	-21.09	peak	

*:Maximum data x:Over limit !:over margin

(Reference Only)

Test Result: Pass

[TestMode: TX low channel]; [Polarity: Vertical]



Site: Polarization: **Vertical** Temperature: (C)
Limit: FCC Part15 (PK) Power: Humidity: %RH
EUT: Wireless Gaming Headphones
M/N: Monster Airmars XKT10 Pro
Mode: TX-L
Note:


No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		4804.000	39.78	4.05	43.83	74.00	-30.17	peak	
2		6017.250	42.60	3.97	46.57	74.00	-27.43	peak	
3		7206.000	39.15	7.93	47.08	74.00	-26.92	peak	
4		8214.500	39.93	9.00	48.93	74.00	-25.07	peak	
5		9608.000	37.43	10.90	48.33	74.00	-25.67	peak	
6	*	11234.250	38.77	13.55	52.32	74.00	-21.68	peak	

*:Maximum data x:Over limit !:over margin

⟨Reference Only

Test Result: Pass

[TestMode: TX mid channel]; [Polarity: Horizontal]



Site: Polarization: **Horizontal** Temperature: (C)
Limit: FCC Part15 (PK) Power: Humidity: %RH
EUT: Wireless Gaming Headphones
M/N: Monster Airmars XKT10 Pro
Mode: TX-M
Note:


No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		4882.000	39.92	4.37	44.29	74.00	-29.71	peak	
2		5782.250	40.15	6.77	46.92	74.00	-27.08	peak	
3		7323.000	38.27	8.21	46.48	74.00	-27.52	peak	
4		8238.000	40.04	9.00	49.04	74.00	-24.96	peak	
5		9764.000	37.06	11.30	48.36	74.00	-25.64	peak	
6	*	11363.500	39.65	13.62	53.27	74.00	-20.73	peak	

*:Maximum data x:Over limit !:over margin

(Reference Only)

Test Result: Pass

[TestMode: TX mid channel]; [Polarity: Vertical]



Site: Polarization: **Vertical** Temperature: (C)
Limit: FCC Part15 (PK) Power: Humidity: %RH
EUT: Wireless Gaming Headphones
M/N: Monster Airmars XKT10 Pro
Mode: TX-M
Note:


No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		4882.000	39.78	4.37	44.15	74.00	-29.85	peak	
2		5993.750	39.90	7.04	46.94	74.00	-27.06	peak	
3		7323.000	39.36	8.21	47.57	74.00	-26.43	peak	
4		8273.250	41.65	9.03	50.68	74.00	-23.32	peak	
5		9764.000	37.04	11.30	48.34	74.00	-25.66	peak	
6	*	11328.250	39.19	13.59	52.78	74.00	-21.22	peak	

*:Maximum data x:Over limit !:over margin

⟨Reference Only

Test Result: Pass

[TestMode: TX high channel]; [Polarity: Horizontal]



Site: Polarization: **Horizontal** Temperature: (C)
Limit: FCC Part15 (PK) Power: Humidity: %RH
EUT: Wireless Gaming Headphones
M/N: Monster Airmars XKT10 Pro
Mode: TX-H
Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		3902.250	41.22	0.71	41.93	74.00	-32.07	peak	
2		4959.750	41.56	5.42	46.98	74.00	-27.02	peak	
3		7440.000	38.06	8.48	46.54	74.00	-27.46	peak	
4		8249.750	40.62	9.01	49.63	74.00	-24.37	peak	
5		9920.000	37.33	11.69	49.02	74.00	-24.98	peak	
6	*	11269.500	38.19	13.57	51.76	74.00	-22.24	peak	

*:Maximum data x:Over limit !:over margin

⟨Reference Only

Test Result: Pass