

RF Exposure evaluation

FCC ID: 2A8QK-P08

1. Reference

According to §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to §1.1310 and §2.1091 RF exposure is calculated.

KDB 662911 D01: Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies

2. Limit

Limits for Maximum Permissible Exposure (MPE)/Controlled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	6
3.0 – 30	1842/f	4.89/f	(900/f ²)*	6
30 – 300	61.4	0.163	1.0	6
300 – 1500	/	/	f/300	6
1500 – 100,000	/	/	5	6

Limits for Maximum Permissible Exposure (MPE)/Uncontrolled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	30
3.0 – 30	824/f	2.19/f	(180/f ²)*	30
30 – 300	27.5	0.073	0.2	30
300 – 1500	/	/	f/1500	30
1500 – 100,000	/	/	1.0	30

F=frequency in MHz

*=Plane-wave equivalent power density

3. MPE Calculation Method

Predication of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S=PG/4\pi R^2$$

Where: S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna

4. Result

As declared by the Applicant, the EUT is a wireless device used in a fix application, at least 20 cm from any body part of the user or nearby persons; from the maximum EUT RF output power, the minimum separation distance, $r = 20\text{cm}$.

Manufacturing tolerance

2.4G WIFI			
802.11b			
Channel	2412	2442	2462
Target (dBm)	17	17	17
Tolerance \pm (dB)	1.0	1.0	1.0
802.11g			
Channel	2412	2442	2462
Target (dBm)	11	11	11
Tolerance \pm (dB)	1.0	1.0	1.7
802.11n(HT20)			
Channel	2412	2442	2462
Target (dBm)	11	11	11
Tolerance \pm (dB)	1.0	1.0	1.0
802.11n(HT40)			
Channel	2422	2442	2452
Target (dBm)	12	12	11
Tolerance \pm (dB)	1.0	1.0	1.0
Bluetooth			
Channel	2402	2441	2480
Target (dBm)	0	0	0
Tolerance \pm (dB)	1.0	1.0	1.0
5G WIFI			
802.11a			
Channel	5180	5200	5240
Target (dBm)	13	12	12
Tolerance \pm (dB)	1.0	1.0	1.0
802.11n(HT20)			

Channel	5180	5200	5240
Target (dBm)	13	12	12
Tolerance \pm (dB)	1.0	1.0	1.0
802.11n(HT40)			
Channel	5190	5230	
Target (dBm)	13	12	
Tolerance \pm (dB)	1.0	1.0	

2.4G WIFI (Antenna gain:2.06dBi)	Max. Output Power with Tolerance (dBm)	Max. Output Power (mW)	Antenna Gain (Numeric)	Power Density At 20 cm (mW/cm ²)	Power Density Limit FCC (mW/cm ²)	Test Results
	18.00	63.0957	1.6069	0.0202	1.0000	PASS
Bluetooth (Antenna gain:-0.68dBi)	Max. Output Power with Tolerance (dBm)	Max. Output Power (mW)	Antenna Gain (Numeric)	Power Density At 20 cm (mW/cm ²)	Power Density Limit FCC (mW/cm ²)	Test Results
	0.00	1.0000	0.8551	0.0002	1.0000	PASS
5G WIFI (Antenna gain:2.49dBi)	Max. Output Power with Tolerance (dBm)	Max. Output Power (mW)	Antenna Gain (Numeric)	Power Density At 20 cm (mW/cm ²)	Power Density Limit FCC (mW/cm ²)	Test Results
	14.00	25.1189	1.7742	0.0089	1.0000	PASS

Simultaneous transmission MPE

Max.Power Density 2.4G WIFI (mW/cm ²)	Max.Power Density 5.1G WIFI (mW/cm ²)	Max.Power Density BT (mW/cm ²)	Max.sum of the MPE ratios	Limit	Test Results
0.0202	0.0089	0.0002	0.0293	1	PASS

5. Conclusion

The SAR evaluation is not required.