

Shenzhen SKYLink Technology Co.,Ltd

Antenna Specification for Approval

Customer Name: _____

Product Name: _____ 2.4G _____ WIFI Antenna _____

Part NO.: _____ GDU RC SEE. WIFI. C081. 200B. 3 _____

Write By: _____ Damon Cui _____

Issued Date: _____ 2024. 07. 18 _____

Customer

R&D Dept	Business Dept	Approved By

SKYLink

R&D Dept	Engineer Dept	Approval

● Specification Summary

A. Electrical Characteristics	
Frequency	2400MHz ~2500MHz 5150MHz ~5850MHz
VSWR	<3.0
Efficiency	>30%
Peak Gain	0.8dbi
Impedance	50 Ohm
Polarization	Line
B. Material & Mechanical Characteristics	
Material of Radiator	Cu
Cable Type	0.81MM Black
Connector Type	3
Dimension	At Attachment
Heat-durability	280±5°C, 10sec.
C. Environmental Characteristics	
Operation Temperature	- 20 °C ~ + 80 °C
Storage Temperature	- 30 °C ~ + 85 °C

● Test Equipment & Conditions




1. Network Analyzers :

Agilent 8753D 5071B


Communications Test Set:

Agilent E5515C CMW500


2. 3D Chamber Test System



◆ Return Loss




◆ VSWR




◆ Gain & Efficiency



Freq (MHz)	Effi (%)	Gain (dBi)	Freq (MHz)	Effi (%)	Gain (dBi)
2400	44.84	0.17	5150	31.3	0.61
2410	42.33	-0.27	5200	30.13	0.81
2420	42	-0.11	5250	39.15	0.3
2430	42.85	-0.06	5300	37.49	-0.3
2440	40.25	-0.46	5350	39.04	0.35
2450	36.59	-0.66	5400	38.69	0.49
2460	34.93	-0.72	5450	38.4	0.82
2470	36.31	-0.58	5500	38.44	0.8
2480	35.89	-0.66	5550	35.06	0.27
2490	36.16	-0.5	5600	32.57	-0.06
2500	33.95	-0.59	5650	33.9	-0.2
			5700	30.33	-0.19
			5750	31.14	-0.07
			5800	30.73	0.02
			5850	30.8	-0.03

◆ Radiation Pattern







5500.000MHz




5500.000MHz H





5500.000MHz E1




5500.000MHz E2




5850.000MHz




5850.000MHz H




5850.000MHz E1



5850.000MHz E2



◆ Antenna Picture



◆ Reliability Test

Test Item		Test condition	Equipment	Specification	Result
1	Low Temp. Storage Test	Temperature: -30℃, Time:48hrs Test condition: Placing antenna in a Low/High Temperature Chamber, keep the temp is 25℃ and humidity is 65% for one hour, then step-down the temp. to -30℃ in one hour, store antenna for 44 hours; step-up temp to 25℃,test antenna after 2 hours.	Temp.&Humi. Tester	No material deformation is allowed. Electronic Performance is ok .	PASS
2	High Temp./High Humid Storage Test	Temperature: 85℃ Humidity: 85% RH Time:48hrs Test condition: Placing antenna in a Low/High Temperature Chamber, keep the temp is 25℃ and humidity is 65% for one hour, then step-up the temp. to 80℃ and the humidity up to 85% in one hour, store antenna for 44 hours; step-down temp to 25℃,test antenna after 2 hours.	Temp.&Humi. Tester	No material deformation is allowed. Electronic Performance is ok .	PASS
3	Salt-Spray 6 pray Test	Placing antenna in the Salt-Spray Tester ,set the test condition , Temp: 35±2℃ Humidity: 85% NaCl salt spray :5 ±1 %.PH value :6.5~7.2 Test time:24hours	Salt-Spray Tester	No color change No appear rusting	PASS