Request for Modular Approval

Date: February 24, 2023

Subject: Manufacturer's Declaration for	🖂 - Modular Approval	🗆 - Split Modular Approval
	□ - Limited Modular Approv	al 🗆 - Limited Split Modular Approval

Confidentiality Request for: _____

8 Basic Requirements – FCC Part 15.212(a)(1) For Itoms Marked (NO(*)) the Limited Module Description Must be Filled Out on the Following Poges			
	For Items Marked "NO(*)", the Limited Module Description Must be Filled Out on the F Modular Approval Requirement		ges ement Met
1.	The modular transmitter must have its own RF shielding. This is intended to ensure that the module does not have to rely upon the shielding provided by the device into which it is installed in order for all modular transmitter emissions to comply with FCC limits. It is also intended to prevent coupling between the RF circuitry of the module and any wires or circuits in the device into which the module is installed. Such coupling may result in non-compliant operation. The physical crystal and tuning capacitors may be located external to the shielded radio elements. 15.212(a)(1)(i)	⊠ - YES	- NO(*)
	Details: The module contains a metal shield which covers all RF components and circuitry. The s side of the board. See photo provided with this application.	hield is locate	ed on the top
2.	The modular transmitter must have buffered modulation/data inputs (if such inputs are provided) to ensure that the module will comply with FCC requirements under conditions of excessive data rates or over-modulation. 15.212(a)(1)(ii)	🛛 - YES	□ - NO(*)
	Details: Data to the modulation circuit is buffered on the module; please refer to the operation filed with this application for full description.	nal descriptio	n document
3.	The modular transmitter must have its own power supply regulation on the module. This is intended to ensure that the module will comply with FCC requirements regardless of the design of the power supplying circuitry in the device into which the module is installed. 15.212(a)(1)(iii)	🖾 - YES	□ - NO(*)
	Details: The module contains its own power supply regulation and the rf reference oscillator is com Please refer to the schematics and operational description documents filed with this application for		
4.	The modular transmitter must comply with the antenna and transmission system requirements of §§ 15.203, 15.204(b), 15.204(c), 15.212(a), and 2.929(b). The antenna must either be permanently attached or employ a "unique" antenna coupler (at all connections between the module and the antenna, including the cable). The "professional installation" provision of § 15.203 is not applicable to modules but can apply to limited modular approvals under paragraph 15.212(b). 15.212(a)(1)(iv)	🖾 - YES	- NO(*)
	Details: The module connects to its antenna via using an UFL type connector. This antenna conn connector. The antenna tested was a PIFA type and the data sheet is included in the application.	ector is a non	standard
5.	The modular transmitter must be tested in a stand-alone configuration, i.e., the module must not be inside another device during testing. This is intended to demonstrate that the module is capable of complying with Part 15 emission limits regardless of the device into which it is eventually installed. Unless the transmitter module will be battery powered, it must comply with the AC line conducted requirements found in Section 15.207. AC or DC power lines and data input/output lines connected to the module must not contain ferrites, unless they will be marketed with the module (see Section 15.27(a)). The length of these lines shall be length typical of actual use or, if that length is unknown, at least 10 centimeters to insure that there is no coupling between the case of the module and supporting equipment. Any accessories, peripherals, or support equipment connected to the module during testing shall be unmodified or commercially available (see Section 15.31(i)). $15.212(a)(1)(v)$	🛛 - YES	□ - NO(*)
	Details: Test data contained in this application is for the device tested as a stand-alone device PC. See test set-up photographs filed with this application.	connected ex	ternally to a

Modular Approval Requirement	Require	Requirement Met	
6. The modular transmitter must be labeled with its own FCC ID number, or use an electron display (see KDB Publication 784748). If using a permanently affixed label with its own FCC ID number, if the FCC ID is not visible when the module is installed inside another device, then the outside of the device into which the module is installed must also display a label referring to the enclosed module. This exterior label can use wording such as the following: "Contains Transmitter Module FCC ID: XYZMODEL1" or "Contains FCC ID: XYZMODEL1." Any similar wording that expresses the same meaning may be used. The Grantee may either provide such a label, an example of which must be included in the application for equipment authorization, or, must provide adequate instructions along with the module which explain this requirement. In the latter case, a copy of these instructions must be included in the application for equipment authorization.	🛛 - YES	□ - NO(*)	
If the modular transmitter uses an electronic display of the FCC identification number, the information must be readily accessible and visible on the modular transmitter or on the device in which it is installed. If the module is installed inside another device, then the outside of the device into which the module is installed must display a label referring to the enclosed module. This exterior label can use wording such as the following: "Contains FCC certified transmitter module(s)." Any similar wording that expresses the same meaning may be used. The user manual must include instructions on how to access the electronic display. A copy of these instructions must be included in the application for equipment authorization. 15.212(a)(1)(vi)			
Details: The module is appropriately labeled (refer to the label and label location drawings contained within this application). Information to the integrator of this device regarding the labeling requirements for the host system is contained in the instructions provided with the module.			
7. The modular transmitter must comply with all specific rule or operating requirements applicable to the transmitter, including all the conditions provided in the integration instructions by the grantee. A copy of these instructions must be included in the application for equipment authorization. For example, there are very strict operational and timing requirements that must be met before a transmitter is authorized for operation under Section 15.231. For instance, data transmission is prohibited, except for operation under Section 15.231(e), in which case there are separate field strength level and timing requirements. Compliance with these requirements must be assured. 15.212(a)(1)(vii)	🛛 - YES	□ - NO(*)	
Details: The module complies with FCC Part 15C requirements. Instructions to the OEM installer are provided in the installation manual filed with this application.>			
8. The modular transmitter must comply with any applicable RF exposure requirements. For example, FCC Rules in Sections 2.1091, 2.1093 and specific Sections of Part 15, including 15.319(i), 15.407(f), 15.253(f) and 15.255(g), require that Unlicensed PCS, UNII and millimeter wave devices perform routine environmental evaluation for RF Exposure to demonstrate compliance. In addition, spread spectrum transmitters operating under Section 15.247 are required to address RF Exposure compliance in accordance with Section 15.247(b)(4). Modular transmitters approved under other Sections of Part 15, when necessary, may also need to address certain RF Exposure concerns, typically by providing specific installation and operating instructions for users, installers and other interested parties to ensure compliance. 15.212(a)(1)(viii)	🛛 - YES	□ - NO(*)	
Details: The module meets the requirements for a mobile/portable device that may be used at separation 12mm from the human body. Refer to the RF Exposure test report submitted with this application.	n distances of	more than	

Limited Module Description – When Applicable

* If a module does NOT meet one or more of the above 8 requirements, the applicant may request Limited Modular Approval (LMA). This Limited Modular Approval (LMA) is applied with the understanding that the applicant will demonstrate and will retain control over the final installation of the device, such that compliance of the end product is always assured. The operating condition(s) for the LMA; the module is only approved for use when installed in devices produced by grantee. A description regarding how control of the end product, into which the module will be installed, will be maintained by the applicant/manufacturer, such that full compliance of the end product is always ensured should be provided here.

Details: N/A

	Software Considerations – KDB 594280 / KDB 442812 (One of the following 2 items must be applied)			
Requirement	Requirement Requirement Met			
 For <u>non-Software Defined Radio</u> transmitter modules where software is used to ensure compliance of the device, technical description must be provided about how such control is implemented to ensure prevention of third-party modification; see KDB Publication 594280. 	 Provided in Separate Cover Letter 	🗆 - N/A		
Details: <example adjusted="" application.="" be="" by="" cannot="" cover="" device="" filed="" firmware="" letter="" modified="" of="" or="" the="" this="" with="" –=""></example>	the end user as described in a	separate		
2. For <u>Software Defined Radio (SDR)</u> devices, transmitter module applications must provide a software security description; see KDB Publication 442812.	 Provided in Separate Cover Letter 	🖾 - N/A		
Details: N/A				

Split Modular Requirements			
Requirement	Provided in Manual		
 For split modular transmitters, specific descriptions for secure communications between front-end and control sections, including authentication and restrictions on third-party modifications; also, instructions to third-party integrators on how control is maintained. 	Provided in Separate Cover Letter	🖾 - N/A	
Details: N/A			

OEM Integration Manual Guidance – KDB 996369 D03 Section 2			
Clear and Specific Instructions Describing the Conditions, Limitations, and Procedures for third-parties to use and/or integrate the module into a host device.			
Requirement			
itegan entent		🖾 - No,	
Is this module intended for sale to third parties?	🗆 - YES	If No, and LMA applies, the applicant not make the following detailed info pu needs to be basic integration instruction the information below must still be inc description. If the applicant wishes to k this will require a separate statement co module is not for sale to third partie instructions are internal confide	blic. However there still as for a users manual and cluded in the operational eep this info confidential, over letter explaining the as and that integration
Items	required to be in the man	ual – See KDB 996369 D03, Section 2	
As of May 1, 2019, the FCC requ applicants should include informa For example information on tr grantees own products and not i	nires ALL the following inf ation in their instructions f ace antenna design could in intended for sale to third p	formation to be in the installation manual for all these items indicating clearly when ndicate "Not Applicable". Also if a modu arties, the user instructions may not need iption, but this should include a cover let	they are not applicable. le is limited to only a to be detailed and the
1. List of applicable FCC rules. K	DB 996369 D03. Section 2.	2	
	lated to the transmitter.		
	as limits on antennas, cable ional installation info	loss, reduction of power for point to point	
limiting condition b. When RF expose that compliance 4. Trace antenna designs. KDB 9	 a. Describe alternative means that the grantee uses to verify the host meets the necessary limiting conditions b. When RF exposure evaluation is necessary, state how control will be maintained such that compliance is ensured, such as Class II for new hosts, etc. Crace antenna designs. KDB 996369 D03, Section 2.5 		
design verification confidential, the provided in the c	Modular Approval (MA) or LMA.		
a. Clearly and explicitly state conditions that allow host manufacturers to use the module. Two types of instructions are necessary: first to the host manufacturer to define conditions (mobile, portable – xx cm from body) and second additional text needed to be provided to the end user in the host product manuals.			
a. Advice to host integrators that they need to provide a physical or e-label stating Therefore the information shown to the left is found in the theory of operation.			a separate cover letter. Therefore the information shown to the left is found in the
8. Information on test modes and a a. Test modes that clarifications near	should be taken into conside cessary for stand-alone and s tion on how to configure test	nts. KDB 996369 D03, Section 2.9 eration by host integrators including simultaneous configurations. t modes for evaluation	

Sincerely,

By:

0 /Vice President____ (Signature/Title¹)

<u>Jay Moulton, RF Exposure Lab</u> (Print name)