1 Cover Page

RF Exposure Evaluation Report

Application No.:	KSCR2208001543CO
FCC ID:	2A8XYZDYDKBL0311100
IC:	29457-ZDYDKBLK7
Applicant:	SHANGHAI ZHIDA TECHNOLOGY DEVELOPMENT CO., LTD.
Address of Applicant:	Room 1001-1, No127, Guotong Road, Yangpu, Shanghai, CHINA 200433
Manufacturer:	SHANGHAI ZHIDA TECHNOLOGY DEVELOPMENT CO., LTD.
Address of Manufacturer:	Room 1001-1, No127, Guotong Road, Yangpu, Shanghai, CHINA 200433
Factory:	Anhui Zhida ZhongDing Vehicle Charging Equipment CO., LTD.
Address of Factory:	Floors 1-2, Building B15, Science Park, Xuancheng economic and technological development zone, Anhui Province, China
Equipment Under Test (EUT):	
EUT Name:	ZHIDA GLOBAL STANDARD AC CHARGING PILE
Model No.:	ZDYDKBL0311100,ZDYDKAL0200000
Standard(s) :	FCC Rules 47 CFR §2.1091 KDB 447498 D04 interim General RF Exposure Guidance v01 RSS-102 Issue 5 Amendment 1 (February 2, 2021)
Date of Receipt:	2022-08-29
Date of Test:	2022-09-24 to 2022-12-09
Date of Issue:	2022-12-10
Test Result:	**Pass***

* In the configuration tested, the EUT complied with the standards specified above.

Eric Lin
Laboratory Manager

No.10, Weiye Road, Innovation Park, Kunshan, Jiangsu, China 215300 t(86-512)57355888 f(86-512)57370818 www.sgsgroup.com.cn
中国・江苏・昆山市留学生创业园伟业路10号 邮编 215300 t(86-512)57355888 f(86-512)57370818 sgs.china@sgs.com

Revision Record			
Version	**Description**	**Date**	**Remark**
00	Original	2022-12-10	/

Authorized for issue by:				
		Tommie Tang		
		Tommie_Tang / Project Engineer		
		Eric Lin		
		Eric Lin / Reviewer		

No.10, Weiye Road, Innovation Park, Kunshan, Jiangsu, China 215300 t(86-512)57355888 f(86-512)57370818 www.sgsgroup.com.cn
中国・江苏・昆山市留学生创业园伟业路10号 邮编 215300 t(86-512)57355888 f(86-512)57370818 sgs.china@sgs.com

2 Contents

No.10, Weiye Road, Innovation Park, Kunshan, Jiangsu, China 215300 t(86-512)57355888 f(86-512)57370818 www.sgsgroup.com.cn
中国・江苏・昆山市留学生创业园伟业路10号 邮编 215300 t(86-512)57355888 f(86-512)57370818 sgs.china@sgs.com

3 General Information

3.1 General Description of E.U.T.

Power supply:	AC 240V,32A,60Hz

3.2 Technical Specifications

13.56MHz

Operation Frequency		13.56MHz
Modulation Technique:		ASK
Antenna Type:		Loop antenna
Serial Number:	ZDYDKBL0311100	ZDYDKBL
	ZDYDKAL0200000	ZDYDKAL
Firmware Version:		ZDAC-32A-433HS-IEC-SAE-V1.0.04

2.4G WIFI (ESP-WROOM-32)

Operation Frequency:	802.11b/g/n(HT20): 2412MHz to 2462MHz; 802.11n(HT40): 2422MHz to 2452MHz
Modulation Type:	802.11b: DSSS (CCK, DQPSK, DBPSK); 802.11g/n: OFDM (64QAM, 16QAM, QPSK, BPSK)
Number of Channels:	802.11b/g/n(HT20):11; 802.11n(HT40):7
Channel Spacing:	5MHz
Antenna Type:	PCB Antenna
Antenna Gain:	2dBi (Provided by manufacturer)

BT (ESP-WROOM-32)

Operation Frequency:	2402MHz to 2480MHz
Modulation Type:	GFSK, pi/4DQPSK, 8DPSK
Number of Channels:	79
Channel Spacing:	1MHz

No.10, Weiye Road, Innovation Park, Kunshan, Jiangsu, China 215300 t(86-512)57355888 f(86-512)57370818 www.sgsgroup.com.cn
中国・江苏・昆山市留学生创业园伟业路10号 邮编 215300 t(86-512)57355888 f(86-512)57370818 sgs.china@sgs.com

Spectrum Spread Technology:	Frequency Hopping Spread Spectrum(FHSS)
Antenna Type:	PCB Antenna
Antenna Gain:	2dBi (Provided by manufacturer)

BLE (ESP-WROOM-32)

Operation Frequency:	2402MHz to 2480MHz
Modulation Type:	GFSK
Number of Channels:	40
Channel Spacing:	2MHz
Antenna Type:	PCB Antenna
Antenna Gain:	2dBi (Provided by manufacturer)

3G&4G:

Frequency Band	WCDMA Band: II,IV,V LTE Band: 2,4,5,12,13,14,66,71
Output power(dBm)	25dBm
Antenna Type	FPC Antenna
Antenna Gain:	WCDMA Band II: -0.13dBi(Provided by the manufacturer) WCDMA Band IV: 1.11dBi(Provided by the manufacturer) WCDMA Band V: -1.99dBi(Provided by the manufacturer) LTE Band 2: -0.13dBi(Provided by the manufacturer) LTE Band 4: 1.11dBi(Provided by the manufacturer) LTE Band 5: -1.99dBi(Provided by the manufacturer) LTE Band 12: -2.65dBi(Provided by the manufacturer) LTE Band 13: -2.65dBi(Provided by the manufacturer) LTE Band 14: -2.65dBi(Provided by the manufacturer) LTE Band 66: 1.11dBi(Provided by the manufacturer) LTE Band 71: -2.65dBi(Provided by the manufacturer)

No.10, Weiye Road, Innovation Park, Kunshan, Jiangsu, China 215300 t(86-512)57355888 f(86-512)57370818 www.sgsgroup.com.cn
中国・江苏・昆山市留学生创业园伟业路10号 邮编 215300 t(86-512)57355888 f(86-512)57370818 sgs.china@sgs.com

3.3 Test Location

All tests were performed at:

Compliance Certification Services (Kunshan) Inc.

No.10 Weiye Rd, Innovation park, Eco&Tec, Development Zone, Kunshan City, Jiangsu, China.

Tel: +86 512 5735 5888 Fax: +86 512 5737 0818

No tests were sub-contracted.

Note:

1. SGS is not responsible for wrong test results due to incorrect information (e.g., max. internal working frequency, antenna gain, cable loss, etc) is provided by the applicant. (If applicable).

2. SGS is not responsible for the authenticity, integrity and the validity of the conclusion based on results of the data provided by applicant. (If applicable).

3.4 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **A2LA (Certificate No. 2541.01)**

Compliance Certification Services (Kunshan) Inc. is accredited by the American Association for Laboratory Accreditation (A2LA). Certificate No. 2541.01.

- **FCC (Designation Number: CN1172)**

Compliance Certification Services Inc. has been recognized as an accredited testing laboratory.

Designation Number: CN1172.

- **ISED (CAB Identifier: CN0072)**

Compliance Certification Services (Kunshan) Inc. has been recognized by Innovation, Science and Economic Development (ISED) Canada as an accredited testing laboratory.

CAB Identifier: 2324E

- **VCCI (Member No.: 1938)**

The 3m and 10m Semi-anechoic chamber and Shielded Room of Compliance Certification Services (Kunshan) Inc. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-20134, R-11600, C-11707, T-11499, G-10216 respectively.

4 Test Standards and Limits

4.1 FCC Radiofrequency radiation exposure limits

Test exemptions apply for devices used in general population/uncontrolled exposure environments, according to the SAR-based, or MPE-based exemption thresholds.

4.2 Blanket 1 mW Blanket Exemption

The 1 mW Blanket Exemption of §1.1307(b)(3)(i)(A) applies for single fixed, mobile, and portable RF sources with available maximum time-averaged power of no more than 1 mW, regardless of separation distance.

The 1-mW blanket exemption applies at separation distances less than 0.5 cm, including where there is no separation. This exemption shall not be used in conjunction with other exemption criteria other than those for multiple RF sources in paragraph §1.1307(b)(3)(ii)(A).

The 1-mW exemption is independent of service type and covers the full range of 100 kHz to 100 GHz, but it shall not be used in conjunction with other exemption criteria or in devices with higher-power transmitters operating in the same time-averaging period. Exposure from such higher-power transmitters would invalidate the underlying assumption that exposure from the lower-power transmitter is the only contributor to SAR in the relevant volume of tissue.

4.3 MPE-based Exemption

General frequency and separation-distance dependent MPE-based effective radiated power (ERP) thresholds are in Table B.1 [Table 1 of §1.1307(b)(1)(i)(C)] to support an exemption from further evaluation from 300 kHz through 100 GHz.

Table B.1—Thresholds For Single RF Sources Subject to Routine Environmental Evaluation

RF Source Frequency			Minimum Distance			Threshold ERP
f_L MHz		f_H MHz	$\lambda_L / 2\pi$		$\lambda_H / 2\pi$	W
0.3	–	1.34	159 m	–	35.6 m	1,920 R^2
1.34	–	30	35.6 m	–	1.6 m	3,450 R^2/f^2
30	–	300	1.6 m	–	159 mm	3.83 R^2
300	–	1,500	159 mm	–	31.8 mm	0.0128 R^2f
1,500	–	100,000	31.8 mm	–	0.5 mm	19.2R^2
Subscripts L and H are low and high; λ is wavelength. From §1.1307(b)(3)(i)(C), modified by adding Minimum Distance columns.						

No.10, Weiye Road, Innovation Park, Kunshan, Jiangsu, China 215300 t(86-512)57355888 f(86-512)57370818 www.sgsgroup.com.cn
中国・江苏・昆山市留学生创业园伟业路10号 邮编 215300 t(86-512)57355888 f(86-512)57370818 sgs.china@sgs.com

The table applies to any RF source (i.e. single fixed, mobile, and portable transmitters) and specifies power and distance criteria for each of the five frequency ranges used for the MPE limits. These criteria apply at separation distances from any part of the radiating structure of at least λ/2π. The thresholds are based on the general population MPE limits with a single perfect reflection, outside of the reactive near-field, and in the main beam of the radiator.

For mobile devices that are not exempt per Table B.1 [Table 1 of §1.1307(b)(1)(i)(C)] at distances from 20 cm to 40 cm and in 0.3 GHz to 6 GHz, evaluation of compliance with the exposure limits in §1.1310 is necessary if the ERP of the device is greater than ERP_{20cm} in Formula (B.1) [repeated from §2.1091(c)(1); also in §1.1307(b)(1)(i)(B)].

$$P_{\text{th}}\ (\text{mW}) = ERP_{20\ \text{cm}}\ (\text{mW}) = \begin{cases} 2040f & 0.3\ \text{GHz} \le f < 1.5\ \text{GHz} \\ 3060 & 1.5\ \text{GHz} \le f \le 6\ \text{GHz} \end{cases} \qquad (\text{B.1})$$

If the ERP is not easily obtained, then the available maximum time-averaged power may be used (i.e., without consideration of ERP only if the physical dimensions of the radiating structure(s) do not exceed the electrical length of λ/4 or if the antenna gain is less than that of a half-wave dipole.

SAR-based exemptions are constant at separation distances between 20 cm and 40 cm to avoid discontinuities in the threshold when transitioning between SAR-based and MPE-based exemption criteria at 40 cm, considering the importance of reflections.

Limit calculation			
Frequency range	Frequency(MHz)	R(λ/2π)(m)	Threshold ERP(W)
300~1500MHz	**915**	0.0522	0.032
1500~100000MHz	**2462**	0.0194	0.007

4.4 SAR-based Exemption

SAR-based thresholds are derived based on frequency, power, and separation distance of the RF source. The formula defines the thresholds in general for either available maximum time-averaged power or maximum time-averaged ERP, whichever is greater.

If the ERP of a device is not easily determined, such as for a portable device with a small form factor, the applicant may use the available maximum time-averaged power exclusively if the device antenna or radiating structure does not exceed an electrical length of λ/4.

As for devices with antennas of length greater than λ/4 where the gain is not well defined, but always less than that of a half-wave dipole (length λ/2), the available maximum time-averaged power generated by the device may be used in place of the maximum time-averaged ERP, where that value is not known.

No.10, Weiye Road, Innovation Park, Kunshan, Jiangsu, China 215300 t(86-512)57355888 f(86-512)57370818 www.sgsgroup.com.cn
中国・江苏・昆山市留学生创业园伟业路10号 邮编 215300 t(86-512)57355888 f(86-512)57370818 sgs.china@sgs.com

The separation distance is the smallest distance from any part of the antenna or radiating structure for all persons, during operation at the applicable ERP. In the case of mobile or portable devices, the separation distance is from the outer housing of the device where it is closest to the antenna.

The SAR-based exemption formula of §1.1307(b)(3)(i)(B), repeated here as Formula (B.2), applies for single fixed, mobile, and portable RF sources with available maximum time-averaged power or effective radiated power (ERP), whichever is greater, of less than or equal to the threshold P_{th} (mW).

This method shall only be used at separation distances from 0.5 cm to 40 cm and at frequencies from 0.3 GHz to 6 GHz (inclusive). P_{th} is given by Formula (B.2).

$$P_{\text{th}}\,(\text{mW}) = \begin{cases} ERP_{20\text{ cm}}(d/20\text{ cm})^{x} & d \le 20\text{ cm} \\ ERP_{20\text{ cm}} & 20\text{ cm} < d \le 40\text{ cm} \end{cases} \qquad \text{(B.2)}$$

where

$$x = -\log_{10}\left(\frac{60}{ERP_{20\text{ cm}}\sqrt{f}}\right)$$

and f is in GHz, d is the separation distance (cm), and ERP_{20cm} is per Formula (B.1).

Example values shown in Table B.2 are for illustration only.

Table B.2—Example Power Thresholds (mW)

Frequency (MHz)	Distance(mm)									
	5	10	15	20	25	30	35	40	45	50
300	39	65	88	110	129	148	166	184	201	217
450	22	44	67	89	112	135	158	180	203	226
835	9	25	44	66	90	116	145	175	207	240
1900	3	12	26	44	66	92	122	157	195	236
2450	3	10	22	38	59	83	111	143	179	219
3600	2	8	18	32	49	71	96	125	158	195
5800	1	6	14	25	40	58	80	106	136	169

No.10, Weiye Road, Innovation Park, Kunshan, Jiangsu, China 215300 t(86-512)57355888 f(86-512)57370818 www.sgsgroup.com.cn
中国・江苏・昆山市留学生创业园伟业路10号 邮编 215300 t(86-512)57355888 f(86-512)57370818 sgs.china@sgs.com

For 13.56MHz device, the limit of worse case is 1mW.

2.4G WIFI

Limit calculation				
Frequency range(GHz)	Frequency(GHz)	X	Distance(cm)	Pth (mW)
1.5~6	**2.462**	1.903	**20**	**3060.000**

BT/BLE

Limit calculation				
Frequency range(GHz)	Frequency(GHz)	X	Distance(cm)	Pth (mW)
1.5~6	**2.48**	1.905	**20**	**3060.000**

3G/4G

Limit calculation				
Frequency range(GHz)	Frequency(GHz)	X	Distance(cm)	Pth (mW)
0.3~1.5	**0.7905**	1.378	**20**	**1612.620**
1.5~6	**1.7107**	1.824	**20**	**3060.000**

No.10, Weiye Road, Innovation Park, Kunshan, Jiangsu, China 215300 t(86-512)57355888 f(86-512)57370818 www.sgsgroup.com.cn
中国・江苏・昆山市留学生创业园伟业路10号 邮编 215300 t(86-512)57355888 f(86-512)57370818 sgs.china@sgs.com

4.5 IC Radiofrequency radiation exposure limits:

According to RSS-102 section 2.5.2, RF exposure evaluation is required if the separation distance between the user and/or bystander and the device's radiating element is greater than 20 cm, except when the device operates as follows:

below 20 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 1 W (adjusted for tune-up tolerance);

• at or above 20 MHz and below 48 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than $4.49/f^{0.5}$ W (adjusted for tune-up tolerance), where f is in MHz;

• at or above 48 MHz and below 300 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 0.6 W (adjusted for tune-up tolerance);

• at or above 300 MHz and below 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than $1.31 \times 10^{-2}\ f^{0.6834}$ W (adjusted for tune-up tolerance), where f is in MHz;

• at or above 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 5 W (adjusted for tune-up tolerance).

For 13.56MHz device, the limit of worse case is 1W
For 2.4G WIFI, the limit is 2.68W
For BT/BLE, the limit is 2.68W
For 3G/4G, the limit is 1.25W

No.10, Weiye Road, Innovation Park, Kunshan, Jiangsu, China 215300 t(86-512)57355888 f(86-512)57370818 www.sgsgroup.com.cn
中国・江苏・昆山市留学生创业园伟业路10号 邮编 215300 t(86-512)57355888 f(86-512)57370818 sgs.china@sgs.com

5 Measurement and Calculation

5.1 Maximum transmit power

13.56MHz:

The Power Data please refer to the RF Test Report KSCR220800154301

53.85 dBuV/m@3m = 0.0001W

2.4G WIFI (ESP-WROOM-32)

The power of 2.4G WIFI base on the certificate module of ESP-WROOM-32,

FCC ID is: 2AC7Z-ESPWROOM32, IC ID is: 21098-ESPWROOM32,

The Max Conducted Output Power is 17dBm (50.12mW).

BT/BLE (ESP-WROOM-32)

The power of BT base on the certificate module of ESP-WROOM-32,

FCC ID is: 2AC7Z-ESPWROOM32, IC ID is: 21098-ESPWROOM32,

The Max Conducted Output Power is 8dBm (6.31mW).

3G/4G (ESP-WROOM-32)

The power of BLE base on the certificate module of EC25-AF,

FCC ID is: XMR201808EC25AF, IC ID is: 10224A-2018EC25AF,

The Max Conducted Output Power is 25dBm (316.23mW).

No.10, Weiye Road, Innovation Park, Kunshan, Jiangsu, China 215300 t(86-512)57355888 f(86-512)57370818 www.sgsgroup.com.cn
中国・江苏・昆山市留学生创业园伟业路10号 邮编 215300 t(86-512)57355888 f(86-512)57370818 sgs.china@sgs.com

5.2 MPE Calculation

For FCC:

For 13.56MHz:
0.0001W< 1mW.

For 2.4G WIFI:
The Max Conducted Output Power is 50.12mW. The best case gain of the antenna is 2dBi.

2dBi logarithmic terms convert to numeric result is nearly 1.58.

According to the formula. calculate the EIRP test result:

EIRP= P x G = 50.12 mW x 1.58 = 79.19mW < 3060mW

For BT/BLE:
The Max Conducted Output Power is 6.31mW. The best case gain of the antenna is 2dBi.

2dBi logarithmic terms convert to numeric result is nearly 1.58.

According to the formula. calculate the EIRP test result:

EIRP= P x G = 6.31 mW x 1.58 = 9.97mW < 3060mW

For 3G/4G:
The Max Conducted Output Power is 316.23mW. The best case gain of the antenna is1.11dBi.

1.11dBi logarithmic terms convert to numeric result is nearly 1.29.

According to the formula. calculate the EIRP test result:

EIRP= P x G = 316.23 mW x 1.63 = 515.45mW < 1612.62mW

The 2.4G WIFI and BT/BLE and 3G/4G and 13.56MHz can transmit simultaneously, and 79.19/3060+9.97/3060+515.45/1612.62+0.1/1=0.45<1, so the device is to qualify for SAR test exemption.

Remark: we used the maximum power between the conducted power and ERP/EIRP to perform RF exposure exemption evaluation.

So the device is exclusion from SAR test.

No.10, Weiye Road, Innovation Park, Kunshan, Jiangsu, China 215300 t(86-512)57355888 f(86-512)57370818 www.sgsgroup.com.cn
中国・江苏・昆山市留学生创业园伟业路10号 邮编 215300 t(86-512)57355888 f(86-512)57370818 sgs.china@sgs.com

For IC:

For 13.56MHz:
0.0001W< 1W.

For 2.4G WIFI:
The Max Conducted Output Power is 50.12mW. The best case gain of the antenna is 2dBi.

2dBi logarithmic terms convert to numeric result is nearly 1.58.

According to the formula. calculate the EIRP test result:

EIRP= P x G = 50.12 mW x 1.58 = 79.19mW < 2.68W

For BT/BLE:
The Max Conducted Output Power is 6.31mW. The best case gain of the antenna is 2dBi.

2dBi logarithmic terms convert to numeric result is nearly 1.58.

According to the formula. calculate the EIRP test result:

EIRP= P x G = 6.31 mW x 1.58 = 9.97mW < 2.68W

For 3G/4G:
The Max Conducted Output Power is 316.23mW. The best case gain of the antenna is1.11dBi.

1.11dBi logarithmic terms convert to numeric result is nearly 1.29.

According to the formula. calculate the EIRP test result:

EIRP= P x G = 316.23 mW x 1.63 = 515.45mW < 1.25W

The 2.4G WIFI and BT/BLE and 3G/4G and 13.56MHz can transmit simultaneously, and 79.19/2680+9.97/2680+515.45/1250+0.0001/1=0.45<1, so the device is to qualify for SAR test exemption.

--End of the Report--

No.10, Weiye Road, Innovation Park, Kunshan, Jiangsu, China 215300 t(86-512)57355888 f(86-512)57370818 www.sgsgroup.com.cn
中国・江苏・昆山市留学生创业园伟业路10号 邮编 215300 t(86-512)57355888 f(86-512)57370818 sgs.china@sgs.com