APPENDIX REPORT

Project No.	SHT2211065401EW	Radio Specification	Bluetooth BLE
Test sample No.	YPHT22110654005	Model No.	BJM-20
Start test date	2023-01-09	Finish date	2023-01-09
Temperature	24.1℃	Humidity	54%
Test Engineer	Xiaoxiao Li	Auditor	Xiaodong Zhao

Appendix clause	Test item	Result
A	Peak Output Power	PASS
B	Power Spectral Density	PASS
C	6 dB Bandwidth	PASS
D	99% Occupied Bandwidth	PASS
E	Duty cycle	PASS
F	Band edge and Spurious Emissions (conducted)	PASS

Appendix A：Peak Output Power

Type	Channel	Peak Output power (dBm)	Average Output power (dBm)	Limit (dBm)	Result
BT-BLE	00	-2.86	-2.90	≤ 30.00	Pass
	19	-2.38	-2.69		
	39	-3.02	-3.03		

CH00	
CH19	
CH39	

Appendix B：Power Spectral Density

Type	Channel	Power Spectral Density(dBm/3KHz)	Limit (dBm/3KHz)	Result
BT-BLE	00	-17.89	≤8.00	Pass
	19	-18.07		
	39	-18.50		

CH00	
CH19	
CH39	

Appendix C：6dB bandwidth

Type	Channel	6dB Bandwidth(kHz)	Limit (kHz)	Result
BT-BLE	00	796.00	≥500	Pass
	19	782.00		
	39	792.00		

CH00	
CH19	
CH39	

Appendix D：99% Occupied Bandwidth

Type	Channel	99% Occupied Bandwidth(MHz)	Limit (kHz)	Result
BT-BLE	00	1.04	-	Pass
	19	1.05		
	39	1.05		

CH00	
CH19	
CH39	

Appendix E：Duty cycle

Test Frequency （MHz）	$T_{on\ time}$ for single burst (ms)	T_{period} (ms)	Duty cycle	$1/T_{on\ time}$ (kHz)
2440	0.39	0.62	62.9%	2.6



Appendix F：Band edge and Spurious Emissions (conducted)

Test Item:	Band edge
CH00	
CH39	

Test Item:	SE
CH00 Reference level	
CH00 30MHz~1000MHz	
CH00 1GHz~26GHz	

CH19 Reference level	
CH19 30MHz~1000MHz	
CH19 1GHz~26GHz	

CH39 Reference level	
CH39 30MHz~1000MHz	
CH39 1GHz~26GHz	

--------End of Report--------