


Product specification

Quick Reference Data

	Antenna module on the system board	
Frequenc Range	2400 ~ 2500MHz	
Ant. Port Input Pwr. (dBm)	0 (Typ. BT class 2 output power)	
Tot. Rad. Pwr. (dBm)	-1.2 (Input pwr – loss pwr)	
Peak EIRP(dBm)	2.99	
Directivity (dBi)	1 (all direction antenna)	
Efficiency (dB)	1 5.8 %	
Gain (dBi)	2.99 (Peak Gain XZ-plane)	
Maximum Power (dBm)	2.99(XZ-plane)	
Minimum Power (dBm)	-18.71(XZ-plane)	
Avg. Power (dBm)	-0.6(XZ-plane)	
Input Impedence(ohm)	50	
Polarization Type	V ertical & H orizontal	
V . S .W . R	< 1.4	

All the technical data and information contained herein are subject to change without prior notice

Antenna Layout & module on the system board




Antenna Gain

Gain Table

Unit in dBi @2.44GHz	XY-plane	XZ-plane	YZ-plane	Efficiency
	Peak	Peak	Peak	
Module Board	2.68	2.99	2.85	1 5.8 %



蓝牙2.4G板载天线

20230105




晶振16M


The Environment of Antenna Radiation Pattern




3D radiation pattern diagram




XY-plane



XZ-plane



YZ-plane



Manufacturer :

Lenze Technology Co.,LTD

Address :

26c newspaper west tower, 6008 shennan Avenue,Futian
District, Shenzhen City, Guangdong Province,China