

Test report No:  
NIE: 72872RAN.007A1

## Assessment report

### RF EXPOSURE REPORT ACCORDING TO FCC 47 CFR Part 2.1091; FCC 47 CFR Part 1.1307 FCC 47 CFR Part 1.1310

(*) Identification of item under evaluation	Central Unit 2 - LatAm variant
(*) Trademark	Verisure
(*) Model and /or type reference	GW-CU2L
(*) Other identification of the product	FCC ID: 2A93W-GW-CU2L IC: Not provided HW version: A5 SW version: 1.8.26
(*) Features	Central processing, Ethernet, Wi-Fi, Cellular, DECT, ISM
(*) Manufacturer	Verisure Sàrl Chemin Jean-Baptiste Vandelle 3 1290 Versoix (Switzerland)
Test method requested, standard	FCC 47 CFR Part 2.1091 Radiofrequency radiation exposure evaluation: mobile devices. FCC 47 CFR Part 1.1307: Actions that may have a significant environmental effect, for which Environmental Assessments (EAs) must be prepared. FCC 47 CFR Part 1.1310: Radiofrequency radiation exposure limits.
Summary	IN COMPLIANCE
Approved by (name / position & signature)	Miguel Lacave Antennas Lab Manager
Date of issue	2023-09-27
Report template No	FAN36_02 (*) "Data provided by the client"

# Index

Competences and guarantees .....	3
General conditions .....	3
Data provided by the client.....	3
Identification of the client.....	3
Document history .....	3
Appendix A: FCC RF Exposure assessment result .....	4
General description of the device under evaluation .....	5
Evaluation Results.....	7
Appendix B: FCC RF Exposure information .....	8
RF Exposure determination of exemption.....	9

## Competences and guarantees

In order to assure the traceability to other national and international laboratories, DEKRA Testing and Certification, S.A.U. has a calibration and maintenance program for its measurement equipment.

DEKRA Testing and Certification, S.A.U. guarantees the reliability of the data presented in this report, which is the result of the measurements and the tests performed to the item under test on the date and under the conditions stated on the report and, it is based on the knowledge and technical facilities available at DEKRA Testing and Certification, S.A.U. at the time of performance of the test.

DEKRA Testing and Certification, S.A.U. is liable to the client for the maintenance of the confidentiality of all information related to the item under test and the results of the test.

The results presented in this Assessment Report apply only to the particular item under test established in this document.

**IMPORTANT:** No parts of this report may be reproduced or quoted out of context, in any form or by any means, except in full, without the previous written permission of DEKRA Testing and Certification, S.A.U.

## General conditions

1. This report is only referred to the item that has undergone the assessment.
2. This report does not constitute or imply on its own an approval of the product by the Certification Bodies or competent Authorities.
3. This document is only valid if complete; no partial reproduction can be made without previous written permission of DEKRA Testing and Certification, S.A.U.
4. This test report cannot be used partially or in full for publicity and/or promotional purposes without previous written permission of DEKRA Testing and Certification, S.A.U. and the Accreditation Bodies

## Data provided by the client

The following data has been provided by the client:

1. Information relating to the description of the sample ("Identification of the item under evaluation", "Trademark", "Model and/or type reference", "General description of the device", "Other identification of the product").
2. Maximum output power, maximum antenna gain and use distance information.
3. The device under evaluation consists of a Central Unit 2 - LatAm variant. Central Unit of the alarm suite. It acts as the main hub and gateway.

DEKRA Testing and Certification S.A.U. declines any responsibility with respect to the information provided by the client and that may affect the validity of results.

## Identification of the client

Verisure Sàrl  
Chemin Jean-Baptiste Vandelle 3 1290 Versoix (Switzerland)

## Document history

Report number	Date	Description
72872RAN.007	2023-09-07	First release
72872RAN.007A1	2023-09-27	Second release. Applicable UMTS V and LTE Band 5 exposure limits updated from §1.1307(b)(3).i.(C) to §1.1307(b)(3).i.(B) limit. This modification test report cancels and replaces the test report 72872RAN.007.

## Appendix A: FCC RF Exposure assessment result

## General description of the device under evaluation

---

**Description and technologies:** the device under evaluation consists of a Central Unit 2 - LatAm variant. Central Unit of the alarm suite. It acts as the main hub and gateway.

**Antennas:** the device supports several antennas for the Wi-Fi, Cellular, DECT, ISM transmitting technologies:

- Cellular: Total 2 antennas – Main Cellular antenna (Transmit/Receive) and Diversity cellular antenna (Receive)
- Wi-Fi: Total 2 antennas – Wi-Fi antenna #1 combined 2.4GHz and 5GHz (Transmit/Receive) and Wi-Fi antenna #2 combined 2.4GHz and 5GHz (Transmit/Receive)
- SRD: Total 3 antennas – ISM antenna #1 (Transmit/Receive) and ISM antenna #2 - #3 (Receive)
- DECT: Total 2 antennas – DECT antenna #1 (Transmit/Receive) and DECT antenna #2 (Transmit/Receive)

**Evaluation Distance:** according to the manufacturer, during its normal use, the separation distance between the radiating structures of the device and nearby users will be greater than 20 cm. In order to perform the assessment a conservative evaluation distance of 20 cm has been used.

**Maximum output power and antenna gain values:**

- Values corresponding to cellular maximum output power have been declared by the device manufacturer (maximum output power values stated in module manufacturer´s datasheet).
- Values corresponding to Wi-Fi 2.4 GHz and SRD conducted output power have been measured and stated into DEKRA Testing and Certification, S.A.U. test report num. 72872RRF001.
- Values corresponding to Wi-Fi 5 GHz conducted output power have been measured and stated into DEKRA Testing and Certification, S.A.U. test report num. 72872RRF002.
- Values corresponding to DECT conducted output power have been measured and stated into cetecom advanced GmbH, test report num. 1-4862\_22-01-03.
- Values corresponding to antenna gain have been declared by the device manufacturer (maximum peak gain stated in antenna manufacturer´s datasheet).

The following table shows the information provided above:

Technology / Mode	Operating Band	Frequency under evaluation (MHz)	Channel Bandwidth (MHz)	Maximum Conducted Output Power (Incl. Tune-Up) (dBm)	Duty Cycle (%)	Time Averaged Conducted Power (dBm)	Antenna peak gain (dBi)	Maximum Averaged E.R.P (dBm)	Maximum Averaged E.R.P (mW)	Maximum Averaged E.I.R.P (dBm)	Maximum Averaged E.I.R.P (mW)
GSM	850	824 - 849	0.200	35.00	12.50	25.97	2.20	26.02	399.86	28.17	656.01
GPRS 1TX	850	824 - 849	0.200	35.00	12.50	25.97	2.20	26.02	399.86	28.17	656.01
GPRS 2TX	850	824 - 849	0.200	35.00	25.00	28.98	2.20	29.03	799.72	31.18	1312.02
GPRS 3TX	850	824 - 849	0.200	33.20	37.50	28.94	2.20	28.99	792.56	31.14	1300.26
GPRS 4TX	850	824 - 849	0.200	32.00	50.00	28.99	2.20	29.04	801.62	31.19	1315.13
GSM	1900	1850 - 1910	0.200	32.00	12.50	22.97	2.20	23.02	200.41	25.17	328.78
GPRS 1TX	1900	1850 - 1910	0.200	32.00	12.50	22.97	2.20	23.02	200.41	25.17	328.78
GPRS 2TX	1900	1850 - 1910	0.200	32.00	25.00	25.98	2.20	26.03	400.81	28.18	657.57
GPRS 3TX	1900	1850 - 1910	0.200	30.20	37.50	25.94	2.20	25.99	397.22	28.14	651.68
GPRS 4TX	1900	1850 - 1910	0.200	29.00	50.00	25.99	2.20	26.04	401.76	28.19	659.13
UMTS	II	1850 - 1910	5.000	25.00	100.00	25.00	2.20	25.05	319.89	27.20	524.81
UMTS	IV	1710 - 1755	5.000	25.00	100.00	25.00	2.20	25.05	319.89	27.20	524.81
UMTS	V	824 - 849	5.000	25.00	100.00	25.00	2.20	25.05	319.89	27.20	524.81
LTE	2	1850 - 1910	1.4/3/5/10/15/20	26.00	100.00	26.00	2.20	26.05	402.72	28.20	660.69
LTE	4	1710 - 1755	1.4/3/5/10/15/20	26.00	100.00	26.00	2.20	26.05	402.72	28.20	660.69
LTE	5	824 - 849	1.4/3/5/10	26.00	100.00	26.00	2.20	26.05	402.72	28.20	660.69
LTE	7	2500 - 2570	5/10/15/20	26.00	100.00	26.00	2.20	26.05	402.72	28.20	660.69
802.11b/g/n (SISO)	2.4 GHz	2412 - 2484	20.000	14.63	100.00	14.63	2.20	14.68	29.38	16.83	48.19
802.11b/g/n (MIMO)	2.4 GHz	2412 - 2484	20.000	14.05	100.00	14.05	4.77	16.67	46.45	18.82	76.21
802.11a/n/ac (SISO)	5 GHz	5150 - 5850	20/40/80	15.90	100.00	15.90	5.00	18.75	74.99	20.90	123.03
802.11a/n/ac (MIMO)	5 GHz	5150 - 5850	20/40/80	15.33	100.00	15.33	7.12	20.30	107.15	22.45	175.79
SRD	ISM	917.5 - 925.5	0.609	11.96	100.00	11.96	0.30	10.11	10.26	12.26	16.83
DECT	1900	1921.536 - 1928.448	1.500	19.50	100.00	19.50	1.50	18.85	76.74	21.00	125.89

**Table 1:** Equipment specifications

## Evaluation Results

### RF Exposure Exemption evaluation:

Technology / Mode	Operating Band	Frequency under evaluation (MHz)	Distance (cm)	Maximum Averaged E.R.P (mW)	§1.1307(b)(3).i.(C) Exposure Limit (mW)	§ 1.1307(b)(3).i.(B) Exposure Limit (mW)	Verdict for exemption § 1.1307(b)(3).i
GSM/GPRS	850	824 - 849	20.00	801.62	-	1680.96	Pass
GSM/GPRS	1900	1850 - 1910	20.00	401.76	768.00	-	Pass
UMTS	II	1850 - 1910	20.00	319.89	768.00	-	Pass
UMTS	IV	1710 - 1755	20.00	319.89	768.00	-	Pass
UMTS	V	824 - 849	20.00	319.89	-	1680.96	Pass
LTE	2	1850 - 1910	20.00	402.72	768.00	-	Pass
LTE	4	1710 - 1755	20.00	402.72	768.00	-	Pass
LTE	5	824 - 849	20.00	402.72	-	1680.96	Pass
LTE	7	2500 - 2570	20.00	402.72	768.00	-	Pass
802.11b/g/n (SISO)	2.4 GHz	2412 - 2484	20.00	29.38	768.00	-	Pass
802.11b/g/n (MIMO)	2.4 GHz	2412 - 2484	20.00	46.45	768.00	-	Pass
802.11a/n/ac (SISO)	5 GHz	5150 - 5850	20.00	74.99	768.00	-	Pass
802.11a/n/ac (MIMO)	5 GHz	5150 - 5850	20.00	107.15	768.00	-	Pass
SRD	ISM	917.5 - 925.5	20.00	10.26	469.76	-	Pass
DECT	1900	1921.536 - 1928.448	20.00	76.74	768.00	-	Pass

**Table 2:** FCC Exemption Evaluation Results

The computed value(s) are below the exemption limit(s), so these modes meet the requirements stated in FCC 47 CFR Part 1.1307.

### Simultaneous transmission assessment:

Simultaneous technologies and modes	Result ( $\sum$ of Pout/Pmax ratios)	Verdict ( $\sum \leq 1$ )
GPRS 4TX 850 + 802.11b/g/n (MIMO) (UL MIMO) 2.4 GHz + 802.11a/n/ac (MIMO) (UL MIMO) 5 GHz + SRD ISM + DECT 1900	0.80	Pass

**Table 3:** Simultaneous Transmission assessment

## Appendix B: FCC RF Exposure information



## RF Exposure determination of exemption

According to FCC 47 CFR §1.1307 (b)(3) Determination of exemption:

(i) For single RF sources (i.e., any single fixed RF source, mobile device, or portable device, as defined in paragraph (b)(2), a single RF source is exempt if:

(A) The available maximum time-averaged power is no more than 1 mW, regardless of separation distance. This exemption may not be used in conjunction with other exemption criteria other than those in paragraph (b)(3)(ii)(A) of this section. Medical implant devices may only use this exemption and that in paragraph (b)(3)(ii)(A);

(B) Or the available maximum time-averaged power or effective radiated power (ERP), whichever is greater, is less than or equal to the threshold  $P_{th}$  (mW) described in the following formula. This method shall only be used at separation distances (cm) from 0.5 centimeters to 40 centimeters and at frequencies from 0.3 GHz to 6 GHz (inclusive).  $P_{th}$  is given by:

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

Where

$$x = -\log_{10} \left( \frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right) \text{ and } f \text{ is in GHz;}$$

and

$$ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

$d$  = the separation distance (cm);

(C) Or using Table 1 and the minimum separation distance ( $R$  in meters) from the body of a nearby person for the frequency ( $f$  in MHz) at which the source operates, the ERP (watts) is no more than the calculated value prescribed for that frequency. For the exemption in Table 1 to apply,  $R$  must be at least  $\lambda/2\pi$ , where  $\lambda$  is the free-space operating wavelength in meters. If the ERP of a single RF source is not easily obtained, then the available maximum time-averaged power may be used in lieu of ERP if the physical dimensions of the radiating structure(s) do not exceed the electrical length of  $\lambda/4$  or if the antenna gain is less than that of a half-wave dipole (1.64 linear value).

TABLE 1 TO §1.1307(b)(3)(i)(C)—SINGLE RF SOURCES SUBJECT TO ROUTINE ENVIRONMENTAL EVALUATION

RF Source frequency (MHz)	Threshold ERP (watts)
0.3-1.34	$1,920 R^2$ .
1.34-30	$3,450 R^2/f^2$ .
30-300	$3.83 R^2$ .
300-1,500	$0.0128 R^2 f$ .
1,500-100,000	$19.2R^2$ .

(ii) For multiple RF sources: Multiple RF sources are exempt if:

(A) The available maximum time-averaged power of each source is no more than 1 mW and there is a separation distance of two centimeters between any portion of a radiating structure operating and the nearest portion of any other radiating structure in the same device, except if the sum of multiple sources is less than 1 mW during the time-averaging period, in which case they may be treated as a single source (separation is not required). This exemption may not be used in conjunction with other exemption criteria other than those in paragraph (b)(3)(i)(A) of this section. Medical implant devices may only use this exemption and that in paragraph (b)(3)(i)(A).

(B) in the case of fixed RF sources operating in the same time-averaging period, or of multiple mobile or portable RF sources within a device operating in the same time averaging period, if the sum of the fractional contributions to the applicable thresholds is less than or equal to 1 as indicated in the following equation.

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure\ Limit_k} \leq 1$$

Where:

a = number of fixed, mobile, or portable RF sources claiming exemption using paragraph (b)(3)(i)(B) of this section for P<sub>th</sub>, including existing exempt transmitters and those being added.

b = number of fixed, mobile, or portable RF sources claiming exemption using paragraph (b)(3)(i)(C) of this section for Threshold ERP, including existing exempt transmitters and those being added.

c = number of existing fixed, mobile, or portable RF sources with known evaluation for the specified minimum distance including existing evaluated transmitters.

P<sub>i</sub> = the available maximum time-averaged power or the ERP, whichever is greater, for fixed, mobile, or portable RF source i at a distance between 0.5 cm and 40 cm (inclusive).

P<sub>th,i</sub> = the exemption threshold power (P<sub>th</sub>) according to paragraph (b)(3)(i)(B) of this section for fixed, mobile, or portable RF source i.

ERP<sub>j</sub> = the ERP of fixed, mobile, or portable RF source j.

ERP<sub>th,j</sub> = exemption threshold ERP for fixed, mobile, or portable RF source j, at a distance of at least λ/2π according to the applicable formula of paragraph (b)(3)(i)(C) of this section.

Evaluated<sub>k</sub> = the maximum reported SAR or MPE of fixed, mobile, or portable RF source k either in the device or at the transmitter site from an existing evaluation at the location of exposure.

Exposure Limit<sub>k</sub> = either the general population/uncontrolled maximum permissible exposure (MPE) or specific absorption rate (SAR) limit for each fixed, mobile, or portable RF source k, as applicable from §1.1310 of this chapter.

The available maximum time-averaged power or effective radiated power (ERP), can be calculated using the following formula to assess compliance with the Exemption Limits:

$$P_{E.I.R.P.} = P_T + G_T - L_C$$

Where:

P<sub>T</sub> = transmitter time-averaged output power (including Duty Cycle and tune-up tolerance, if applicable)

G<sub>T</sub> = gain of the transmitting antenna

L<sub>C</sub> = signal attenuation in the connecting cable between the transmitter and the antenna if applicable

$$P_{E.R.P.} = P_{E.I.R.P.} - 2.15 \text{ dB}$$