



# RADIO TEST REPORT

**FCC ID** : 2A95Z20231001  
**Equipment** : TRUE BALLISTIC Chronograph  
**Brand Name** : FX Airguns, FX outdoors  
**Model Name** : TRUE BALLISTIC Chronograph  
**Applicant** : EXC Taiwan Co Ltd  
No 8-9, Xinhe Rd, Daya District, Taichung city  
40863, Taiwan  
**Manufacturer** : EXC Taiwan Co Ltd  
No 8-9, Xinhe Rd, Daya District, Taichung city  
40863, Taiwan  
**Standard** : 47 CFR FCC Part 15.247

The product was received on Feb. 21, 2023, and testing was started from Feb. 22, 2023 and completed on Mar. 09, 2023. We, Sporton International Inc. Hsinchu Laboratory, would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.10-2013 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. Hsinchu Laboratory, the test report shall not be reproduced except in full.

Approved by: Sam Chen

**Sportun International Inc. Hsinchu Laboratory**  
No.8, Ln. 724, Bo'ai St., Zhubei City, Hsinchu County 302010, Taiwan (R.O.C.)



## Table of Contents

<b>History of this test report.....</b>	<b>3</b>
<b>Summary of Test Result.....</b>	<b>4</b>
<b>1 General Description .....</b>	<b>5</b>
1.1 Information.....	5
1.2 Applicable Standards .....	7
1.3 Testing Location Information.....	7
1.4 Measurement Uncertainty .....	7
<b>2 Test Configuration of EUT.....</b>	<b>8</b>
2.1 Test Channel Mode .....	8
2.2 The Worst Case Measurement Configuration.....	8
2.3 EUT Operation during Test .....	9
2.4 Accessories .....	10
2.5 Support Equipment.....	10
2.6 Test Setup Diagram .....	11
<b>3 Transmitter Test Result .....</b>	<b>13</b>
3.1 AC Power-line Conducted Emissions .....	13
3.2 DTS Bandwidth.....	15
3.3 Maximum Conducted Output Power .....	16
3.4 Power Spectral Density .....	19
3.5 Emissions in Non-restricted Frequency Bands .....	21
3.6 Emissions in Restricted Frequency Bands.....	22
<b>4 Test Equipment and Calibration Data .....</b>	<b>26</b>

**Appendix A. Test Results of AC Power-line Conducted Emissions****Appendix B. Test Results of DTS Bandwidth****Appendix C. Test Results of Maximum Conducted Output Power****Appendix D. Test Results of Power Spectral Density****Appendix E. Test Results of Emissions in Non-restricted Frequency Bands****Appendix F. Test Results of Emissions in Restricted Frequency Bands****Appendix G. Test Photos****Photographs of EUT v01**



## History of this test report



## Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
1.1.2	15.203	Antenna Requirement	PASS	-
3.1	15.207	AC Power-line Conducted Emissions	PASS	-
3.2	15.247(a)	DTS Bandwidth	PASS	-
3.3	15.247(b)	Maximum Conducted Output Power	PASS	-
3.4	15.247(e)	Power Spectral Density	PASS	-
3.5	15.247(d)	Emissions in Non-restricted Frequency Bands	PASS	-
3.6	15.247(d)	Emissions in Restricted Frequency Bands	PASS	-

**Conformity Assessment Condition:**

1. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacturer who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
2. The measurement uncertainty please refer to each test result in the chapter "Measurement Uncertainty".

**Disclaimer:**

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.

Reviewed by: Sam Chen

Report Producer: Sophia Shiung



## 1 General Description

### 1.1 Information

#### 1.1.1 RF General Information

Frequency Range (MHz)	Bluetooth Mode	Ch. Frequency (MHz)	Channel Number
2400-2483.5	LE	2402-2480	0-39 [40]

Band	Mode	BWch (MHz)	Nant
2.4-2.4835GHz	BT-LE(1Mbps)	1.0	1TX

Note:

- Bluetooth LE uses a GFSK modulation.
- BWch is the nominal channel bandwidth.

#### 1.1.2 Antenna Information

Ant.	Port		Brand	Model Name	Antenna Type	Connector	Gain (dBi)	
	WLAN 24GHz	Bluetooth					WLAN 24GHz	Bluetooth
1	1	-	EXC	#EX080424001	Patch Antenna	N/A	19.6	-
2	-	1	EXC	#EXBL01L001	PCB Antenna	N/A	-	3.05

Note 1: The above information was declared by manufacturer.

Note 2: **For 24GHz function (1TX/1RX):**

Only Port 1 can be used as transmitting/receiving antenna.

**For bluetooth function (1TX/1RX):**

Only Port 1 can be used as transmitting/receiving antenna.

#### 1.1.3 Mode Test Duty Cycle

Mode	DC	DCF(dB)	T(s)	VBW(Hz) $\geq 1/T$
BT-LE(1Mbps)	0.923	0.35	1.09m	1k

Note:

- DC is Duty Cycle.
- DCF is Duty Cycle Factor.



#### 1.1.4 EUT Operational Condition

EUT Power Type	Powered by Battery or from system via USB cable		
Function	<input type="checkbox"/>	Point-to-multipoint	<input checked="" type="checkbox"/> Point-to-point
Test Software Version	Default		
Support Mode	<input checked="" type="checkbox"/>	LE 1M PHY: 1 Mb/s	
	<input type="checkbox"/>	LE Coded PHY (S=2): 500 Kb/s	
	<input type="checkbox"/>	LE Coded PHY (S=8): 125 Kb/s	
	<input type="checkbox"/>	LE 2M PHY: 2 Mb/s	

Note: The above information was declared by manufacturer.



## 1.2 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ◆ 47 CFR FCC Part 15.247
- ◆ ANSI C63.10-2013

The following reference test guidance is not within the scope of accreditation of TAF.

- ◆ FCC KDB 558074 D01 v05r02
- ◆ FCC KDB 414788 D01 v01r01

## 1.3 Testing Location Information

Testing Location Information				
Test Lab. : Sporton International Inc. Hsinchu Laboratory				
Hsinchu (TAF: 3787)	ADD: No.8, Ln. 724, Bo'ai St., Zhubei City, Hsinchu County 302010, Taiwan (R.O.C.) TEL: 886-3-656-9065	FAX: 886-3-656-9085		
		Test site Designation No. TW3787 with FCC.		
		Conformity Assessment Body Identifier (CABID) TW3787 with ISED.		

Test Condition	Test Site No.	Test Engineer	Test Environment (°C / %)	Test Date
RF Conducted	TH01-CB	Jeff Wu	22.2~23.1 / 61~68	Feb. 24, 2023
Radiated < 1GHz	03CH04-CB	Chris Li	21.6~22.2 / 62~65	Feb. 22, 2023~ Mar. 08, 2023
Radiated > 1GHz	03CH03-CB		21.9~22 / 62~69	
AC Conduction	CO01-CB	Elvin Yeh	22~23 / 50~51	Mar. 09, 2023

## 1.4 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2)

Test Items	Uncertainty	Remark
Conducted Emission (150kHz ~ 30MHz)	3.4 dB	Confidence levels of 95%
Radiated Emission (9kHz ~ 30MHz)	3.4 dB	Confidence levels of 95%
Radiated Emission (30MHz ~ 1,000MHz)	5.6 dB	Confidence levels of 95%
Radiated Emission (1GHz ~ 18GHz)	5.2 dB	Confidence levels of 95%
Radiated Emission (18GHz ~ 40GHz)	4.7 dB	Confidence levels of 95%
Conducted Emission	3.2 dB	Confidence levels of 95%
Output Power Measurement	0.8 dB	Confidence levels of 95%
Power Density Measurement	3.2 dB	Confidence levels of 95%
Bandwidth Measurement	2.0 %	Confidence levels of 95%



## 2 Test Configuration of EUT

### 2.1 Test Channel Mode

Mode	Power Setting
BT-LE(1Mbps)	-
2402MHz	Default
2440MHz	Default
2480MHz	Default

### 2.2 The Worst Case Measurement Configuration

The Worst Case Mode for Following Conformance Tests	
<b>Tests Item</b>	AC power-line conducted emissions
<b>Condition</b>	AC power-line conducted measurement for line and neutral Test Voltage: 120Vac / 60Hz
<b>Operating Mode</b>	Normal Link
1	EUT + Powered from system via USB cable

The Worst Case Mode for Following Conformance Tests	
<b>Tests Item</b>	DTS Bandwidth Maximum Conducted Output Power Power Spectral Density Emissions in Non-restricted Frequency Bands
<b>Test Condition</b>	Conducted measurement at transmit chains



The Worst Case Mode for Following Conformance Tests	
<b>Tests Item</b>	Emissions in Restricted Frequency Bands
<b>Test Condition</b>	Radiated measurement If EUT consist of multiple antenna assembly (multiple antenna are used in EUT regardless of spatial multiplexing MIMO configuration), the radiated test should be performed with highest antenna gain of each antenna type.
<b>Operating Mode &lt; 1GHz</b>	CTX After evaluating, EUT in Y axis was the worst case. So the measurement will follow this same test configuration.
1	EUT in Y axis_Bluetooth + Powered from battery
2	EUT in Y axis_Bluetooth + Powered from system via USB cable
3	EUT in Y axis_24GHz + Powered from system via USB cable
For operating, mode 3 is the worst case and it was record in this test report.	
<b>Operating Mode &gt; 1GHz</b>	CTX After evaluating, EUT in Y axis was the worst case. So the measurement will follow this same test configuration.
1	EUT in Y axis

The Worst Case Mode for Following Conformance Tests	
<b>Tests Item</b>	Simultaneous Transmission Analysis - Co-location RF Exposure Evaluation
<b>Operating Mode</b>	
1	24GHz + Bluetooth

Refer to Sporton Test Report No.: FA311054 for Co-location RF Exposure Evaluation.

## 2.3 EUT Operation during Test

For Normal Link Mode:

During the test, the EUT operation to normal function.

For CTX Mode:

The EUT was programmed to be in continuously transmitting mode.



## 2.4 Accessories

<b>Accessories</b>			
<b>Power</b>	<b>Brand</b>	<b>Model</b>	<b>Rating</b>
Rechargeable Li-ion battery*2	SANYO	INR18650A260A-1S1P	DC 3.6V - 2.6Ah
<b>Others</b>			
USB cable*1: Shielded,:1m			
Base bracket*1			

## 2.5 Support Equipment

For AC Conduction:

<b>Support Equipment</b>				
<b>No.</b>	<b>Equipment</b>	<b>Brand Name</b>	<b>Model Name</b>	<b>FCC ID</b>
A	Type-C NB	DELL	E6430	N/A
B	iPhone 12	Apple	A2403	BCG-E3544A
C	Earphone	SHYARO CHI	MIC-04	N/A
D	Mouse	Logitech	M-U0026	N/A


For Radiated:

<b>Support Equipment</b>				
<b>No.</b>	<b>Equipment</b>	<b>Brand Name</b>	<b>Model Name</b>	<b>FCC ID</b>
A	NB	Lenovo	L440	N/A

For RF Conducted: N/A

## 2.6 Test Setup Diagram


Test Setup Diagram – AC Line Conducted Emission Test



Item	Connection	Shielded	Length
1	USB cable	Yes	1m
2	Power cable	No	1.5m
3	Audio cable	No	1.2m
4	USB cable	Yes	1.8m

**Test Setup Diagram - Radiated Test**

AC MAIN



Item	Connection	Shielded	Length
1	USB cable	Yes	1m
2	Power cable	No	1m



### 3 Transmitter Test Result

#### 3.1 AC Power-line Conducted Emissions

##### 3.1.1 AC Power-line Conducted Emissions Limit

AC Power-line Conducted Emissions Limit		
Frequency Emission (MHz)	Quasi-Peak	Average
0.15-0.5	66 - 56 *	56 - 46 *
0.5-5	56	46
5-30	60	50

Note 1: \* Decreases with the logarithm of the frequency.

##### 3.1.2 Measuring Instruments


Refer a test equipment and calibration data table in this test report.

##### 3.1.3 Test Procedures

Test Method
▪ Refer as ANSI C63.10-2013, clause 6.2 for AC power-line conducted emissions.

### 3.1.4 Test Setup

#### AC Power-line Conducted Emissions



1—Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 cm to 40 cm long.

2—The I/O cables that are not connected to an accessory shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.

3—EUT connected to one LISN. Unused LISN measuring port connectors shall be terminated in  $50\ \Omega$  loads. LISN may be placed on top of, or immediately beneath, reference ground plane.

3.1—All other equipment powered from additional LISN(s).

3.2—A multiple-outlet strip may be used for multiple power cords of non-EUT equipment.

3.3—LISN at least 80 cm from nearest part of EUT chassis.

4—Non-EUT components of EUT system being tested.

5—Rear of EUT, including peripherals, shall all be aligned and flush with edge of tabletop.

6—Edge of tabletop shall be 40 cm removed from a vertical conducting plane that is bonded to the ground plane.

7—Antenna can be integral or detachable. If detachable, then the antenna shall be attached for this test.

#### 1.1.1. Measurement Results Calculation

The measured Level is calculated using:

- Corrected Reading: LISN Factor (LISN) + Attenuator (AT/AUX) + Cable Loss (CL) + Read Level (Raw) = Level
- Margin = -Limit + Level

### 3.1.5 Test Result of AC Power-line Conducted Emissions

Refer as Appendix A



## 3.2 DTS Bandwidth

### 3.2.1 6dB Bandwidth Limit

6dB Bandwidth Limit
<b>Systems using digital modulation techniques:</b>
▪ 6 dB bandwidth $\geq$ 500 kHz.


### 3.2.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

### 3.2.3 Test Procedures

Test Method
▪ For the emission bandwidth shall be measured using one of the options below:
<input checked="" type="checkbox"/> Refer as FCC KDB 558074, clause 8.2 & C63.10 clause 11.8.1 Option 1 for 6 dB bandwidth measurement.
<input type="checkbox"/> Refer as FCC KDB 558074, clause 8.2 & C63.10 clause 11.8.2 Option 2 for 6 dB bandwidth measurement.
<input type="checkbox"/> Refer as ANSI C63.10, clause 6.9.1 for occupied bandwidth testing.

### 3.2.4 Test Setup



### 3.2.5 Test Result of Emission Bandwidth

Refer as Appendix B



### 3.3 Maximum Conducted Output Power

#### 3.3.1 Maximum Conducted Output Power Limit

Maximum Conducted Output Power Limit	
	<ul style="list-style-type: none"><li>▪ If <math>G_{TX} \leq 6 \text{ dBi}</math>, then <math>P_{Out} \leq 30 \text{ dBm}</math> (1 W)</li></ul>
	<ul style="list-style-type: none"><li>▪ Point-to-multipoint systems (P2M): If <math>G_{TX} &gt; 6 \text{ dBi}</math>, then <math>P_{Out} = 30 - (G_{TX} - 6) \text{ dBm}</math></li></ul>
	<ul style="list-style-type: none"><li>▪ Point-to-point systems (P2P): If <math>G_{TX} &gt; 6 \text{ dBi}</math>, then <math>P_{Out} = 30 - (G_{TX} - 6)/3 \text{ dBm}</math></li></ul>
	<ul style="list-style-type: none"><li>▪ Smart antenna system (SAS):<ul style="list-style-type: none"><li>- Single beam: If <math>G_{TX} &gt; 6 \text{ dBi}</math>, then <math>P_{Out} = 30 - (G_{TX} - 6)/3 \text{ dBm}</math></li><li>- Overlap beam: If <math>G_{TX} &gt; 6 \text{ dBi}</math>, then <math>P_{Out} = 30 - (G_{TX} - 6)/3 \text{ dBm}</math></li><li>- Aggregate power on all beams: If <math>G_{TX} &gt; 6 \text{ dBi}</math>, then <math>P_{Out} = 30 - (G_{TX} - 6)/3 + 8\text{dB dBm}</math></li></ul></li></ul>

$P_{Out}$  = maximum peak conducted output power or maximum conducted output power in dBm,

$G_{TX}$  = the maximum transmitting antenna directional gain in dBi.

#### 3.3.2 Measuring Instruments


Refer a test equipment and calibration data table in this test report.



### 3.3.3 Test Procedures

Test Method	
▪ Maximum Peak Conducted Output Power	
<input type="checkbox"/>	Refer as FCC KDB 558074, clause 8.3.1.1 & C63.10 clause 11.9.1.1 (RBW $\geq$ EBW method).
<input type="checkbox"/>	Refer as FCC KDB 558074, clause 8.3.1.3 & C63.10 clause 11.9.1.3 (peak power meter).
▪ Maximum Conducted Output Power	
[duty cycle $\geq$ 98% or external video / power trigger]	
<input type="checkbox"/>	Refer as FCC KDB 558074, clause 8.3.2.2 & C63.10 clause 11.9.2.2.2 Method AVGSA-1.
<input type="checkbox"/>	Refer as FCC KDB 558074, clause 8.3.2.2 & C63.10 clause 11.9.2.2.3 Method AVGSA-1A. (alternative)
duty cycle < 98% and average over on/off periods with duty factor	
<input type="checkbox"/>	Refer as FCC KDB 558074, clause 8.3.2.2 & C63.10 clause 11.9.2.2.4 Method AVGSA-2.
<input type="checkbox"/>	Refer as FCC KDB 558074, clause 8.3.2.2 & C63.10 clause 11.9.2.2.5 Method AVGSA-2A (alternative)
<input type="checkbox"/>	Refer as FCC KDB 558074, clause 8.3.2.2 & C63.10 clause 11.9.2.2.6 Method AVGSA-3
<input type="checkbox"/>	Refer as FCC KDB 558074, clause 8.3.2.2 & C63.10 clause 11.9.2.2.7 Method AVGSA-3A (alternative)
Measurement using a power meter (PM)	
<input type="checkbox"/>	Refer as FCC KDB 558074, clause 8.3.2.3 & C63.10 clause 11.9.2.3.1 Method AVGPM (using an RF average power meter).
<input checked="" type="checkbox"/>	Refer as FCC KDB 558074, clause 8.3.2.3 & C63.10 clause 11.9.2.3.2 Method AVGPM-G (using an gate RF average power meter).
▪ For conducted measurement.	
<input type="checkbox"/>	If the EUT supports multiple transmit chains using options given below: Refer as FCC KDB 662911, In-band power measurements. Using the measure-and-sum approach, measured all transmit ports individually. Sum the power (in linear power units e.g., mW) of all ports for each individual sample and save them.
	▪ If multiple transmit chains, EIRP calculation could be following as methods: $P_{total} = P_1 + P_2 + \dots + P_n$ (calculated in linear unit [mW] and transfer to log unit [dBm]) $EIRP_{total} = P_{total} + DG$

### 3.3.4 Test Setup





### **3.3.5 Test Result of Maximum Conducted Output Power**

Refer as Appendix C



## 3.4 Power Spectral Density

### 3.4.1 Power Spectral Density Limit

Power Spectral Density Limit
▪ Power Spectral Density (PSD)≤8 dBm/3kHz

### 3.4.2 Measuring Instruments


Refer a test equipment and calibration data table in this test report.

### 3.4.3 Test Procedures

Test Method
▪ Peak power spectral density procedures that the same method as used to determine the conducted output power. If maximum peak conducted output power was measured to demonstrate compliance to the output power limit, then the peak PSD procedure below (Method PKPSD) shall be used. If maximum conducted output power was measured to demonstrate compliance to the output power limit, then one of the average PSD procedures shall be used, as applicable based on the following criteria (the peak PSD procedure is also an acceptable option).
<input checked="" type="checkbox"/> Refer as FCC KDB 558074, clause 8.4 & C63.10 clause 11.10 Method Max. PSD. [duty cycle ≥ 98% or external video / power trigger]
▪ For conducted measurement.
▪ If The EUT supports multiple transmit chains using options given below:
<input type="checkbox"/> Option 1: Measure and sum the spectra across the outputs. Refer as FCC KDB 662911, In-band power spectral density (PSD). Sample all transmit ports simultaneously using a spectrum analyzer for each transmit port. Where the trace bin-by-bin of each transmit port summing can be performed. (i.e., in the first spectral bin of output 1 is summed with that in the first spectral bin of output 2 and that from the first spectral bin of output 3, and so on up to the NTX output to obtain the value for the first frequency bin of the summed spectrum.). Add up the amplitude (power) values for the different transmit chains and use this as the new data trace.
<input type="checkbox"/> Option 2: Measure and sum spectral maxima across the outputs. With this technique, spectra are measured at each output of the device at the required resolution bandwidth. The maximum value (peak) of each spectrum is determined. These maximum values are then summed mathematically in linear power units across the outputs. These operations shall be performed separately over frequency spans that have different out-of-band or spurious emission limits,
<input type="checkbox"/> Option 3: Measure and add $10 \log(N)$ dB, where N is the number of transmit chains. Refer as FCC KDB 662911, In-band power spectral density (PSD). Performed at each transmit chains and each transmit chains shall be compared with the limit have been reduced with $10 \log(N)$ . Or each transmit chains shall be add $10 \log(N)$ to compared with the limit.



### 3.4.4 Test Setup



### 3.4.5 Test Result of Power Spectral Density

Refer as Appendix D



### 3.5 Emissions in Non-restricted Frequency Bands

#### 3.5.1 Emissions in Non-restricted Frequency Bands Limit

Un-restricted Band Emissions Limit	
RF output power procedure	Limit (dBc)
Peak output power procedure	20
Average output power procedure	30

Note 1: If the peak output power procedure is used to measure the fundamental emission power to demonstrate compliance to requirements, then the peak conducted output power measured within any 100 kHz outside the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum measured in-band peak PSD level.

Note 2: If the average output power procedure is used to measure the fundamental emission power to demonstrate compliance to requirements, then the power in any 100 kHz outside of the authorized frequency band shall be attenuated by at least 30 dB relative to the maximum measured in-band average PSD level.


#### 3.5.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

#### 3.5.3 Test Procedures

Test Method
▪ Refer as FCC KDB 558074, clause 8.5 for unwanted emissions into non-restricted bands.

#### 3.5.4 Test Setup



#### 3.5.5 Test Result of Emissions in Non-restricted Frequency Bands

Refer as Appendix E



## 3.6 Emissions in Restricted Frequency Bands

### 3.6.1 Emissions in Restricted Frequency Bands Limit

Restricted Band Emissions Limit			
Frequency Range (MHz)	Field Strength (uV/m)	Field Strength (dBuV/m)	Measure Distance (m)
0.009~0.490	2400/F(kHz)	48.5 - 13.8	300
0.490~1.705	24000/F(kHz)	33.8 - 23	30
1.705~30.0	30	29	30
30~88	100	40	3
88~216	150	43.5	3
216~960	200	46	3
Above 960	500	54	3

Note 1: Test distance for frequencies at or above 30 MHz, measurements may be performed at a distance other than the limit distance provided they are not performed in the near field and the emissions to be measured can be detected by the measurement equipment. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse of linear distance for field-strength measurements, inverse of linear distance-squared for power-density measurements).

Note 2: Test distance for frequencies at below 30 MHz, measurements may be performed at a distance closer than the EUT limit distance; however, an attempt should be made to avoid making measurements in the near field. When performing measurements below 30 MHz at a closer distance than the limit distance, the results shall be extrapolated to the specified distance by either making measurements at a minimum of two or more distances on at least one radial to determine the proper extrapolation factor or by using the square of an inverse linear distance extrapolation factor (40 dB / decade). The test report shall specify the extrapolation method used to determine compliance of the EUT.

Note 3: Using the distance of 1m during the test for above 18 GHz, and the test value to correct for the distance factor at 3m.

### 3.6.2 Measuring Instruments


Refer a test equipment and calibration data table in this test report.




### 3.6.3 Test Procedures

<b>Test Method</b>	
<ul style="list-style-type: none"><li>▪ The average emission levels shall be measured in [duty cycle <math>\geq</math> 98 or duty factor].</li></ul>	
<ul style="list-style-type: none"><li>▪ Refer as ANSI C63.10, clause 6.10.3 band-edge testing shall be performed at the lowest frequency channel and highest frequency channel within the allowed operating band.</li></ul>	
<ul style="list-style-type: none"><li>▪ For the transmitter unwanted emissions shall be measured using following options below:</li></ul>	
<ul style="list-style-type: none"><li>▪ Refer as FCC KDB 558074, clause 8.6 for unwanted emissions into restricted bands.</li></ul>	<ul style="list-style-type: none"><li><input type="checkbox"/> Refer as FCC KDB 558074, clause 8.6 &amp; C63.10 clause 11.12.2.5.1(trace averaging for duty cycle <math>\geq</math>98%).</li></ul>
	<ul style="list-style-type: none"><li><input type="checkbox"/> Refer as FCC KDB 558074, clause 8.6 &amp; C63.10 clause 11.12.2.5.2(trace averaging + duty factor).</li></ul>
	<ul style="list-style-type: none"><li><input checked="" type="checkbox"/> Refer as FCC KDB 558074, clause 8.6 &amp; C63.10 clause 11.12.2.5.3(Reduced VBW<math>\geq</math>1/T).</li></ul>
	<ul style="list-style-type: none"><li><input type="checkbox"/> Refer as ANSI C63.10, clause 11.12.2.5.3 (Reduced VBW). VBW <math>\geq</math> 1/T, where T is pulse time.</li></ul>
	<ul style="list-style-type: none"><li><input type="checkbox"/> Refer as ANSI C63.10, clause 7.5 average value of pulsed emissions.</li></ul>
	<ul style="list-style-type: none"><li><input checked="" type="checkbox"/> Refer as FCC KDB 558074, clause 8.6 &amp; C63.10 clause 11.12.2.4 measurement procedure peak limit.</li></ul>
	<ul style="list-style-type: none"><li>▪ For the transmitter band-edge emissions shall be measured using following options below:</li></ul>
<ul style="list-style-type: none"><li>▪ Refer as FCC KDB 558074 clause 8.7 &amp; c63.10 clause 11.13.1, When the performing peak or average radiated measurements, emissions within 2 MHz of the authorized band edge may be measured using the marker-delta method described below.</li></ul>	<ul style="list-style-type: none"><li>▪ Refer as FCC KDB 558074, clause 8.7 (ANSI C63.10, clause 6.10.6) for marker-delta method for band-edge measurements.</li></ul>
	<ul style="list-style-type: none"><li>▪ Refer as FCC KDB 558074, clause 8.7 for narrower resolution bandwidth (100kHz) using the band power and summing the spectral levels (i.e., 1 MHz).</li></ul>
	<ul style="list-style-type: none"><li>▪ For conducted unwanted emissions into restricted bands (absolute emission limits). Devices with multiple transmit chains using options given below: (1) Measure and sum the spectra across the outputs or (2) Measure and add <math>10 \log(N)</math> dB</li></ul>
<ul style="list-style-type: none"><li>▪ For FCC KDB 662911 The methodology described here may overestimate array gain, thereby resulting in apparent failures to satisfy the out-of-band limits even if the device is actually compliant. In such cases, compliance may be demonstrated by performing radiated tests around the frequencies at which the apparent failures occurred.</li></ul>	

### 3.6.4 Test Setup





### 3.6.5 Measurement Results Calculation

The measured Level is calculated using:

Corrected Reading: Antenna factor (AF) + Cable loss (CL) + Read level (Raw) - Preamp factor (PA)(if applicable) = Level.

### 3.6.6 Emissions in Restricted Frequency Bands (Below 30MHz)

There is a comparison data of both open-field test site and alternative test site - semi-Anechoic chamber according to KDB414788 Radiated Test Site, and the result came out very similar.

All amplitude of spurious emissions that are attenuated by more than 20 dB below the permissible value has no need to be reported.

The radiated emissions were investigated from 9 kHz or the lowest frequency generated within the device, up to the 10th harmonic or 40 GHz, whichever is appropriate.

### 3.6.7 Test Result of Emissions in Restricted Frequency Bands

Refer as Appendix F



## 4 Test Equipment and Calibration Data

Instrument	Brand	Model No.	Serial No.	Characteristics	Calibration Date	Calibration Due Date	Remark
EMI Receiver	Agilent	N9038A	My52260123	9kHz ~ 8.4GHz	Feb. 20, 2023	Feb. 19, 2024	Conduction (CO01-CB)
LISN	F.C.C.	FCC-LISN-50-16-2	04083	150kHz ~ 100MHz	Feb. 16, 2023	Feb. 15, 2024	Conduction (CO01-CB)
LISN	Schwarzbeck	NSLK 8127	8127647	9kHz ~ 30MHz	Apr. 12, 2022	Apr. 11, 2023	Conduction (CO01-CB)
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100430	9kHz ~ 30MHz	Feb. 09, 2023	Feb. 08, 2024	Conduction (CO01-CB)
COND Cable	Woken	Cable	Low cable-CO01	9kHz ~ 30MHz	Oct. 18, 2022	Oct. 17, 2023	Conduction (CO01-CB)
Software	SPORTON	SENSE	V5.10	-	N.C.R.	N.C.R.	Conduction (CO01-CB)
Loop Antenna	Teseq	HLA 6120	24155	9kHz - 30 MHz	May 14, 2022	May 13, 2023	Radiation (03CH04-CB)
3m Semi Anechoic Chamber NSA	TDK	SAC-3M	03CH04-CB	30 MHz ~ 1 GHz	Aug. 02, 2022	Aug. 01, 2023	Radiation (03CH04-CB)
BILOG ANTENNA with 6 dB attenuator	Schaffner & EMCI	CBL6112B & N-6-06	22021&AT-N06 07	30MHz ~ 1GHz	Oct. 08, 2022	Oct. 07, 2023	Radiation (03CH04-CB)
Pre-Amplifier	EMCI	EMC330N	980391	20MHz ~ 3GHz	May 19, 2022	May 18, 2023	Radiation (03CH04-CB)
Spectrum Analyzer	R&S	FSP40	100142	9kHz~40GHz	Mar. 28, 2022	Mar. 27, 2023	Radiation (03CH04-CB)
EMI Test Receiver	R&S	ESCS	826547/017	9kHz ~ 2.75GHz	Jun. 17, 2022	Jun. 16, 2023	Radiation (03CH04-CB)
RF Cable-low	Woken	RG402	Low Cable-03+67	30MHz – 1GHz	Oct. 03, 2022	Oct. 02, 2023	Radiation (03CH04-CB)
Test Software	SPORTON	SENSE	V5.10	-	N.C.R.	N.C.R.	Radiation (03CH04-CB)
3m Semi Anechoic Chamber VSWR	TDK	SAC-3M	03CH03-CB	1GHz ~18GHz 3m	May 05, 2022	May 04, 2023	Radiation (03CH03-CB)
Horn Antenna	ETS • Lindgren	3115	6821	750MHz~18GHz	Feb. 03, 2023	Feb. 02, 2024	Radiation (03CH03-CB)
Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170252	15GHz ~ 40GHz	Aug. 22, 2022	Aug. 21, 2023	Radiation (03CH03-CB)
Pre-Amplifier	Agilent	8449B	3008A02097	1GHz ~ 26.5GHz	Jul. 01, 2022	Jun. 30, 2023	Radiation (03CH03-CB)
Pre-Amplifier	SGH	SGH184	20221107-3	18GHz ~ 40GHz	Nov. 16, 2022	Nov. 15, 2023	Radiation (03CH03-CB)
Spectrum Analyzer	R&S	FSP40	100019	9kHz ~ 40GHz	Jun. 10, 2022	Jun. 09, 2023	Radiation (03CH03-CB)



Instrument	Brand	Model No.	Serial No.	Characteristics	Calibration Date	Calibration Due Date	Remark
RF Cable-high	Woken	RG402	High Cable-20+29	1GHz ~ 18GHz	Oct. 03, 2022	Oct. 02, 2023	Radiation (03CH03-CB)
RF Cable-high	Woken	RG402	High Cable-29	1GHz ~ 18GHz	Oct. 03, 2022	Oct. 02, 2023	Radiation (03CH03-CB)
High Cable	Woken	WCA0929M	40G#5+6	1GHz ~ 40 GHz	Dec. 07, 2022	Dec. 06, 2023	Radiation (03CH03-CB)
High Cable	Woken	WCA0929M	40G#5	1GHz ~ 40 GHz	Dec. 07, 2022	Dec. 06, 2023	Radiation (03CH03-CB)
High Cable	Woken	WCA0929M	40G#6	1GHz ~ 40 GHz	Dec. 07, 2022	Dec. 06, 2023	Radiation (03CH03-CB)
Test Software	SPORTON	SENSE	V5.10	-	N.C.R.	N.C.R.	Radiation (03CH03-CB)
Spectrum analyzer	R&S	FSV40	100979	9kHz~40GHz	May 27, 2022	May 26, 2023	Conducted (TH01-CB)
Switch	SPTCB	SP-SWI	SWI-01	1 GHz ~26.5 GHz	Oct. 04, 2022	Oct. 03, 2023	Conducted (TH01-CB)
RF Cable-high	Woken	RG402	High Cable-06	1 GHz ~ 18 GHz	Oct. 03, 2022	Oct. 02, 2023	Conducted (TH01-CB)
RF Cable-high	Woken	RG402	High Cable-07	1 GHz ~ 18 GHz	Oct. 03, 2022	Oct. 02, 2023	Conducted (TH01-CB)
RF Cable-high	Woken	RG402	High Cable-08	1 GHz ~ 18 GHz	Oct. 03, 2022	Oct. 02, 2023	Conducted (TH01-CB)
RF Cable-high	Woken	RG402	High Cable-09	1 GHz ~ 18 GHz	Oct. 03, 2022	Oct. 02, 2023	Conducted (TH01-CB)
RF Cable-high	Woken	RG402	High Cable-10	1 GHz ~ 18 GHz	Oct. 03, 2022	Oct. 02, 2023	Conducted (TH01-CB)
RF Cable-high	Woken	RG402	High Cable-30	1 GHz ~ 18 GHz	Oct. 03, 2022	Oct. 02, 2023	Conducted (TH01-CB)
Power Sensor	Anritsu	MA2411B	1339408	300MHz~40GHz	Sep. 12, 2022	Sep. 11, 2023	Conducted (TH01-CB)
Power Meter	Anritsu	ML2495A	1517009	300MHz~40GHz	Sep. 12, 2022	Sep. 11, 2023	Conducted (TH01-CB)
Test Software	SPORTON	SENSE	V5.10	-	N.C.R.	N.C.R.	Conducted (TH01-CB)

Note: Calibration Interval of instruments listed above is one year.

NCR means Non-Calibration required.





## Conducted Emissions at Powerline

## Appendix A

### Summary

Mode	Result	Type	Freq (Hz)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Condition
Mode 1	Pass	QP	150k	49.56	66.00	-16.44	Neutral

**Mode 1**


**Mode 1**


**Summary**


Mode	Max-N dB (Hz)	Max-OBW (Hz)	ITU-Code	Min-N dB (Hz)	Min-OBW (Hz)
2.4-2.4835GHz	-	-	-	-	-
BT-LE(1Mbps)	806.25k	1.72M	1M72F1D	752.5k	1.684M

Max-N dB = Maximum 6dB down bandwidth; Max-OBW = Maximum 99% occupied bandwidth;  
Min-N dB = Minimum 6dB down bandwidth; Min-OBW = Minimum 99% occupied bandwidth


**Result**

Mode	Result	Limit (Hz)	Port 1-N dB (Hz)	Port 1-OBW (Hz)
BT-LE(1Mbps)	-	-	-	-
2402MHz	Pass	500k	752.5k	1.684M
2440MHz	Pass	500k	806.25k	1.696M
2480MHz	Pass	500k	803.75k	1.72M

Port X-N dB = Port X 6dB down bandwidth;  
Port X-OBW = Port X 99% occupied bandwidth

**BT-LE(1Mbps)**
**2402MHz**

**EBW-DTS**


24/02/2023

**BT-LE(1Mbps)**
**2440MHz**

**EBW-DTS**

24/02/2023

## BT-LE(1Mbps)

2480MHz





## Average Power-DTS

## Appendix C

### Summary

Mode	Power (dBm)	Power (W)
2.4-2.4835GHz	-	-
BT-LE(1Mbps)	5.36	0.00344

**Result**

Mode	Result	Gain (dBi)	Power (dBm)	Power Limit (dBm)
BT-LE(1Mbps)	-	-	-	-
2402MHz	Pass	3.05	5.36	30.00
2440MHz	Pass	3.05	4.08	30.00
2480MHz	Pass	3.05	2.07	30.00

DG = Directional Gain; Port X = Port X output power

**Summary**

Mode	PD (dBm/RBW)
2.4-2.4835GHz	-
BT-LE(1Mbps)	-19.73

RBW = 3kHz;

**Result**

Mode	Result	Gain (dBi)	PD (dBm/RBW)	PD Limit (dBm/RBW)
BT-LE(1Mbps)	-	-	-	-
2402MHz	Pass	3.05	-19.73	8.00
2440MHz	Pass	3.05	-20.38	8.00
2480MHz	Pass	3.05	-21.78	8.00

DG = Directional Gain; RBW = 3kHz;


PD = trace bin-by-bin of each transmits port summing can be performed maximum power density; Port X = Port X Power Density;

### **BT-LE(1Mbps)**

**2402MHz**

**PSD**

24/02/2023




### **BT-LE(1Mbps)**

**2440MHz**

**PSD**

24/02/2023




**BT-LE(1Mbps)**

**PSD**

**2480MHz**

24/02/2023



**Summary**


Mode	Result	Ref (Hz)	Ref (dBm)	Limit (dBm)	Freq (Hz)	Level (dBm)	Port								
2.4-2.4835GHz	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
BT-LE(1Mbps)	Pass	2.40184G	-6.37	-36.37	2.03455G	-54.16	2.4G	-45.13	2.4G	-44.16	2.50182G	-51.51	7.20527G	-37.83	1

**Result**


Mode	Result	Ref (Hz)	Ref (dBm)	Limit (dBm)	Freq (Hz)	Level (dBm)	Port								
BT-LE(1Mbps)	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
2402MHz	Pass	2.40184G	-6.37	-36.37	2.03455G	-54.16	2.4G	-45.13	2.4G	-44.16	2.50182G	-51.51	7.20527G	-37.83	1
2440MHz	Pass	2.40184G	-6.37	-36.37	1.84538G	-53.26	2.39796G	-51.23	2.4G	-55.48	2.50186G	-51.04	21.45399G	-47.05	1
2480MHz	Pass	2.40184G	-6.37	-36.37	1.24025G	-49.28	2.39236G	-51.47	2.4G	-57.18	2.50126G	-51.29	21.6199G	-46.98	1

**BT-LE(1Mbps)**
**2402MHz**
**CSEndB-DTS**

24/02/2023


 Port 1

**BT-LE(1Mbps)**
**2440MHz**
**CSEndB-DTS**

24/02/2023

 Port 1



**BT-LE(1Mbps)**
**2480MHz**
**CSENdB-DTS**

24/02/2023


Port 1 


**Summary**

Mode	Result	Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Condition
Mode 3	Pass	QP	61.04M	36.39	40.00	-3.61	Horizontal


**Mode 3**


Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB/m)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	Raw (dBuV/m)	AF (dB/m)	CL (dB)	PA
PK	45.52M	28.68	40.00	-11.32	-14.66	3	Vertical	294	1.00	-	43.34	16.14	0.75	31.55
PK	62.01M	35.78	40.00	-4.22	-17.82	3	Vertical	91	1.00	"Worst"	53.60	12.94	0.88	31.64
PK	89.17M	28.05	43.50	-15.45	-16.40	3	Vertical	241	1.25	-	44.45	14.25	1.04	31.69
PK	172.59M	37.72	43.50	-5.78	-14.60	3	Vertical	211	1.00	-	52.32	15.70	1.43	31.73
PK	182.29M	34.08	43.50	-9.42	-14.94	3	Vertical	316	1.00	-	49.02	15.32	1.47	31.73
PK	531.49M	36.35	46.00	-9.65	-5.61	3	Vertical	231	1.25	-	41.96	24.08	2.47	32.16

**Mode 3**



**Summary**

Mode	Result	Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
2.4-2.4835GHz	-	-	-	-	-	-	-	-	-	-	-
BT-LE(1Mbps)	Pass	AV	4.95994G	49.62	54.00	-4.38	3	Horizontal	332	1.60	-

**BT-LE(1Mbps)**
**2402MHz\_TX**



EUT Y\_1TX  
Setting Default  
03-C-E-5

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)	
PK	2.3674G	60.70	74.00	-13.30	28.53	3	Vertical	316	1.88	-	28.20	3.97	-	
AV	2.3676G	44.98	54.00	-9.02	12.81	3	Vertical	316	1.88	-	28.20	3.97	-	
PK	2.4018G	92.57	Inf	-Inf	60.37	3	Vertical	316	1.88	-	28.20	4.00	-	
AV	2.402G	90.92	Inf	-Inf	58.72	3	Vertical	316	1.88	-	28.20	4.00	-	

**BT-LE(1Mbps)**
**2402MHz\_TX**


EUT Y\_1TX  
Setting Default  
03-C-E-5

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)	
PK	2.3674G	61.71	74.00	-12.29	29.54	3	Horizontal	30	2.24	-	28.20	3.97	-	
AV	2.3674G	44.87	54.00	-9.13	12.70	3	Horizontal	30	2.24	-	28.20	3.97	-	
PK	2.4018G	93.39	Inf	-Inf	61.19	3	Horizontal	30	2.24	-	28.20	4.00	-	
AV	2.402G	91.77	Inf	-Inf	59.57	3	Horizontal	30	2.24	-	28.20	4.00	-	


**BT-LE(1Mbps)**
**2402MHz\_TX**


EUT Y\_1TX  
Setting Default  
03-C-E-5

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)	
PK	4.8046G	51.57	74.00	-22.43	46.57	3	Vertical	332	2.08	-	33.40	6.50	34.90	
AV	4.8042G	42.66	54.00	-11.34	37.66	3	Vertical	332	2.08	-	33.40	6.50	34.90	


**BT-LE(1Mbps)**

**2402MHz\_TX**




EUT Y\_1TX  
Setting Default  
03-C-E-5

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)
PK	4.80442G	53.00	74.00	-21.00	48.00	3	Horizontal	340	1.78	-	33.40	6.50	34.90
AV	4.80406G	45.14	54.00	-8.86	40.14	3	Horizontal	340	1.78	-	33.40	6.50	34.90

**BT-LE(1Mbps)**
**2440MHz\_TX**



EUT Y\_1TX  
Setting Default  
03-C-E-5

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)	
PK	2.3596G	56.77	74.00	-17.23	24.61	3	Vertical	316	2.02	-	28.20	3.96	-	
AV	2.3436G	45.00	54.00	-9.00	12.90	3	Vertical	316	2.02	-	28.16	3.94	-	
PK	2.4404G	90.59	Inf	-Inf	58.35	3	Vertical	316	2.02	-	28.20	4.04	-	
AV	2.44G	89.04	Inf	-Inf	56.80	3	Vertical	316	2.02	-	28.20	4.04	-	
PK	2.4924G	57.70	74.00	-16.30	25.16	3	Vertical	316	2.02	-	28.45	4.09	-	
AV	2.49G	45.29	54.00	-8.71	12.76	3	Vertical	316	2.02	-	28.44	4.09	-	

**BT-LE(1Mbps)**
**2440MHz\_TX**



EUT Y\_1TX  
Setting Default  
03-C-E-5

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)	
PK	2.35G	56.75	74.00	-17.25	24.60	3	Horizontal	28	2.16	-	28.20	3.95	-	
AV	2.3476G	45.06	54.00	-8.94	12.92	3	Horizontal	28	2.16	-	28.19	3.95	-	
PK	2.4396G	90.44	Inf	-Inf	58.20	3	Horizontal	28	2.16	-	28.20	4.04	-	
AV	2.44G	88.90	Inf	-Inf	56.66	3	Horizontal	28	2.16	-	28.20	4.04	-	
PK	2.4928G	56.93	74.00	-17.07	24.38	3	Horizontal	28	2.16	-	28.46	4.09	-	
AV	2.4968G	45.15	54.00	-8.85	12.57	3	Horizontal	28	2.16	-	28.48	4.10	-	

**BT-LE(1Mbps)**
**2440MHz\_TX**



EUT Y\_1TX  
Setting Default  
03-C-E-58

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)	
PK	4.86986G	52.68	74.00	-21.32	47.53	3	Vertical	173	2.96	-	33.52	6.53	34.90	
AV	4.86992G	48.54	54.00	-5.46	43.39	3	Vertical	173	2.96	-	33.52	6.53	34.90	
PK	7.3209G	54.40	74.00	-19.60	44.01	3	Vertical	0	1.80	-	36.84	8.70	35.15	
AV	7.32054G	42.32	54.00	-11.68	31.93	3	Vertical	0	1.80	-	36.84	8.70	35.15	

**BT-LE(1Mbps)**
**2440MHz\_TX**



EUT Y\_1TX  
Setting Default  
03-C-E-5

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)	
PK	4.8806G	55.14	74.00	-18.86	49.91	3	Horizontal	343	1.58	-	33.58	6.54	34.89	
AV	4.88G	48.22	54.00	-5.78	42.99	3	Horizontal	343	1.58	-	33.58	6.54	34.89	
PK	7.32666G	53.67	74.00	-20.33	43.27	3	Horizontal	0	1.55	-	36.85	8.70	35.15	
AV	7.32084G	41.22	54.00	-12.78	30.83	3	Horizontal	0	1.55	-	36.84	8.70	35.15	

**BT-LE(1Mbps)**
**2480MHz\_TX**



EUT Y\_1TX  
Setting Default  
03-C-E-5

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)	
PK	2.4802G	88.95	Inf	-Inf	56.49	3	Vertical	315	2.18	-	28.38	4.08	-	
AV	2.48G	87.35	Inf	-Inf	54.89	3	Vertical	315	2.18	-	28.38	4.08	-	
PK	2.4922G	58.97	74.00	-15.03	26.43	3	Vertical	315	2.18	-	28.45	4.09	-	
AV	2.4964G	45.31	54.00	-8.69	12.73	3	Vertical	315	2.18	-	28.48	4.10	-	

**BT-LE(1Mbps)**
**2480MHz\_TX**



EUT Y\_1TX  
Setting Default  
03-C-E-5

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)	
PK	2.4802G	87.90	Inf	-Inf	55.44	3	Horizontal	25	2.31	-	28.38	4.08	-	
AV	2.48G	86.25	Inf	-Inf	53.79	3	Horizontal	25	2.31	-	28.38	4.08	-	
PK	2.492G	58.84	74.00	-15.16	26.30	3	Horizontal	25	2.31	-	28.45	4.09	-	
AV	2.4924G	45.33	54.00	-8.67	12.79	3	Horizontal	25	2.31	-	28.45	4.09	-	

**BT-LE(1Mbps)**
**2480MHz\_TX**


EUT Y\_1TX  
Setting Default  
03-C-E-5

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)	
PK	4.95934G	54.51	74.00	-19.49	49.20	3	Vertical	16	3.00	-	33.62	6.58	34.89	
AV	4.95994G	47.13	54.00	-6.87	41.82	3	Vertical	16	3.00	-	33.62	6.58	34.89	
PK	7.43892G	55.67	74.00	-18.33	45.07	3	Vertical	354	1.80	-	36.98	8.82	35.20	
AV	7.44066G	44.50	54.00	-9.50	33.90	3	Vertical	354	1.80	-	36.98	8.82	35.20	

**BT-LE(1Mbps)**
**2480MHz\_TX**


EUT Y\_1TX  
Setting Default  
03-C-E-5

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)	
PK	4.95994G	56.27	74.00	-17.73	50.96	3	Horizontal	332	1.60	-	33.62	6.58	34.89	
AV	4.95994G	49.62	54.00	-4.38	44.31	3	Horizontal	332	1.60	-	33.62	6.58	34.89	
PK	7.44006G	54.29	74.00	-19.71	43.69	3	Horizontal	-0	2.06	-	36.98	8.82	35.20	
AV	7.44084G	42.34	54.00	-11.66	31.74	3	Horizontal	-0	2.06	-	36.98	8.82	35.20	