



## Shenzhen Huaxia Testing Technology Co., Ltd.

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

Telephone: +86-755-26648640  
Fax: +86-755-26648637  
Website: [www.cqa-cert.com](http://www.cqa-cert.com)

Report Template Version: V05  
Report Template Revision Date: 2021-11-03

# RF Exposure Evaluation Report

**Report No.:** CQASZ20230200111E-03

**Applicant:** Shenzhen Micro Kitchen Technology Co., Ltd.

**Address of Applicant:** 118, Building 18, Maker Town, No. 4109, Liuxian Avenue, Pingshan Community, Taoyuan Street, Nanshan District, Shenzhen

**Equipment Under Test (EUT):**

**EUT Name:** Affordable Hot Food Vending Machine

**Model No.:** X1

**Test Model No.:** X1

**Brand Name:** 库盒

**FCC ID:** 2A978-X1

**Standards:** 47 CFR Part 1.1307

47 CFR Part 1.1310

447498 D04 Interim General RF Exposure Guidance v01

**Date of Receipt:** 2023-02-03

**Date of Test:** 2023-02-03 to 2023-02-21

**Date of Issue:** 2023-04-10

**Test Result:** **PASS\***

**\*In the configuration tested, the EUT complied with the standards specified above**

**Tested By:** lewis zhou

( Lewis Zhou )

**Reviewed By:** Timo Lei

( Timo Lei )

**Approved By:** Jack Ai

( Jack Ai )



## 1 Version

### Revision History Of Report

Report No.	Version	Description	Issue Date
CQASZ20230200111E-03	Rev.01	Initial report	2023-04-10

## 2 Contents

	Page
<b>1 VERSION</b> .....	2
<b>2 CONTENTS</b> .....	3
.....	3
<b>3 GENERAL INFORMATION</b> .....	4
3.1 CLIENT INFORMATION .....	4
3.2 GENERAL DESCRIPTION OF EUT .....	4
3.3 GENERAL DESCRIPTION OF BT CLASSIC .....	4
3.4 GENERAL DESCRIPTION OF 2.4G WIFI CLASSIC .....	5
<b>4 MPE EVALUATION</b> .....	6
4.1 RF EXPOSURE COMPLIANCE REQUIREMENT .....	6
4.1.1 <i>Limits</i> .....	6
4.1.2 <i>Test Procedure</i> .....	6
4.1.3 <i>EUT RF Exposure</i> .....	7

### 3 General Information

#### 3.1 Client Information

Applicant:	Shenzhen Micro Kitchen Technology Co., Ltd.
Address of Applicant:	118, Building 18, Maker Town, No. 4109, Liuxian Avenue, Pingshan Community, Taoyuan Street, Nanshan District, Shenzhen
Manufacturer:	Foshan Kujie Intelligent Equipment Technology Co., Ltd.
Address of Manufacturer:	Area 5A, 5th Floor, Building 2, No. 55 Huanzhen North Road, Shunjiang Community, Beijiao Town, Shunde District, Foshan City, Guangdong Province
Factory:	Foshan Kujie Intelligent Equipment Technology Co., Ltd.
Address of Factory:	Area 5A, 5th Floor, Building 2, No. 55 Huanzhen North Road, Shunjiang Community, Beijiao Town, Shunde District, Foshan City, Guangdong Province

#### 3.2 General Description of EUT

Product Name:	Affordable Hot Food Vending Machine
Model No.:	X1
Test Model No.:	X1
Trade Mark:	库盒
Software Version:	Android 10.1
Hardware Version:	15
EUT Power Supply:	MODEL:ADP-96H24 INPUT:100-240V~ 50/60Hz 1.5A OUTPUT:24V-- 4A

#### 3.3 General Description of BT Classic

Operation Frequency:	2402MHz~2480MHz
Bluetooth Version:	Bluetooth Spec 5.0
Modulation Technique:	Frequency Hopping Spread Spectrum(FHSS)
Modulation Type:	GFSK, π/4DQPSK, 8DPSK
Number of Channel:	79
Transfer Rate:	1Mbps/2Mbps/3Mbps
Hopping Channel Type:	Adaptive Frequency Hopping systems
Sample Type:	<input checked="" type="checkbox"/> Mobile <input type="checkbox"/> Portable
Antenna Type:	Sucker antenna
Antenna Gain:	1dBi

### 3.4 General Description of 2.4G WIFI Classic

Operation Frequency:	2412MHz~2462MHz
Type of Modulation:	IEEE for 802.11b: DSSS(CCK,DQPSK,DBPSK) IEEE for 802.11g : OFDM(64QAM, 16QAM, QPSK, BPSK) IEEE for 802.11n(HT20 and HT40) : OFDM (64QAM, 16QAM, QPSK, BPSK)
Number of Channel:	IEEE 802.11b/g, IEEE 802.11n HT20: 11 Channels IEEE 802.11n HT40: 7 Channels
Channel Separation:	5MHz
Transfer Rate:	IEEE for 802.11b: 1Mbps/2Mbps/5.5Mbps/11Mbps IEEE for 802.11g : 6Mbps/9Mbps/12Mbps/18Mbps/24Mbps/36Mbps/48Mbps/54Mbps IEEE for 802.11n(HT20) : 6.5Mbps/13Mbps/19.5Mbps/26Mbps/39Mbps/52Mbps/58.5Mbps/65Mbps IEEE for 802.11n(HT40) : 13.5Mbps/27Mbps/40.5Mbps/54Mbps/81Mbps/108Mbps/121.5Mbps/135Mbps
Sample Type:	<input checked="" type="checkbox"/> Mobile <input type="checkbox"/> Portable
Antenna Type:	Sucker antenna
Antenna Gain:	1dBi

Note:

The above parameters will directly affect the test results. The information is provided by the applicant.

## 4 MPE Evaluation

### 4.1 RF Exposure Compliance Requirement

#### 4.1.1 Limits

The table applies to any RF source (i.e., single fixed, mobile, and portable transmitters) and specifies power and distance criteria for each of the five frequency ranges used for the MPE limits. These criteria apply at separation distances from any part of the radiating structure of at least  $\lambda/2\pi$ . The thresholds are based on the general population MPE limits with a single perfect reflection, outside of the reactive near-field, and in the main beam of the radiator. For mobile devices that are not exempt per Table B.1 [Table 1 of § 1.1307(b)(1)(i)(C)] at distances from 20 cm to 40 cm and in 0.3 GHz to 6 GHz, evaluation of compliance with the exposure limits in § 1.1310 is necessary if the ERP of the device is greater than ERP<sub>20cm</sub> in Formula (B.1) [repeated from § 2.1091(c)(1) and § 1.1307(b)(1)(i)(B)].

$$P_{th} \text{ (mW)} = ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

If the ERP is not easily obtained, then the available maximum time-averaged power may be used (i.e., without consideration of ERP only if the physical dimensions of the radiating structure(s) do not exceed the electrical length of  $\lambda/4$  or if the antenna gain is less than that of a half-wave Dipole).

SAR-based exemptions are constant at separation distances between 20 cm and 40 cm to avoid discontinuities in the threshold when transitioning between SAR-based and MPE-based exemption criteria at 40 cm, considering the importance of reflections.

#### 4.1.2 Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

### 4.1.3 EUT RF Exposure

#### 1) For BT Classic

##### Measurement Data

GFSK mode					
Test channel	EIRP (dBm)	ERP (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
				(dBm)	(mW)
Lowest(2402MHz)	0.64	-1.51	-1.5±1	-0.5	0.89
Middle(2441MHz)	2.21	0.06	0.5±1	1.5	1.41
Highest(2480MHz)	1.62	-0.53	-0.5±1	0.5	1.12
π/4DQPSK mode					
Test channel	EIRP (dBm)	ERP (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
				(dBm)	(mW)
Lowest(2402MHz)	0.97	-1.18	-1.0±1	0	1
Middle(2441MHz)	2.71	0.56	0.5±1	1.5	1.41
Highest(2480MHz)	1.99	-0.16	-0.5±1	0.5	1.12
8DPSK mode					
Test channel	EIRP (dBm)	ERP (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
				(dBm)	(mW)
Lowest(2402MHz)	1.38	-0.77	-0.5±1	0.5	1.12
Middle(2441MHz)	2.78	0.63	0.5±1	1.5	1.41
Highest(2480MHz)	2.3	0.15	0.5±1	1.5	1.41

The ERP of this product is less than 3060mW

Note: 1) Refer to report No. CQASZ20230200111E-02 for EUT test Max Conducted Peak Output Power value.

2) EUT's module is more than 20cm away from the human body.

**2) For 2.4G WIFI Classic**
**Measurement Data**

11B mode					
Test channel	EIRP (dBm)	ERP (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
				(dBm)	(mW)
Lowest(2412MHz)	9.91	7.76	7.5±1	8.5	7.08
Middle(2437MHz)	11.05	8.9	9.0±1	10.0	10
Highest(2462MHz)	10.78	8.63	8.5±1	9.5	8.91
11G mode					
Test channel	EIRP (dBm)	ERP (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
				(dBm)	(mW)
Lowest(2412MHz)	3.93	1.78	1.5±1	2.5	1.78
Middle(2437MHz)	5.58	3.43	3.5±1	4.5	2.82
Highest(2462MHz)	5.95	3.8	3.5±1	4.5	2.82
11N20 mode					
Test channel	EIRP (dBm)	ERP (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
				(dBm)	(mW)
Lowest(2412MHz)	3.52	1.37	1.5±1	2.5	1.78
Middle(2437MHz)	5.47	3.32	3.5±1	4.5	2.82
Highest(2462MHz)	5.99	3.84	4.0±1	5.0	3.16
11N40 mode					
Test channel	EIRP (dBm)	ERP (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
				(dBm)	(mW)
Lowest(2422MHz)	4.15	2	2.0±1	3.0	2
Middle(2437MHz)	5.22	3.07	3.0±1	4.0	2.51
Highest(2452MHz)	5.74	3.59	3.5±1	4.5	2.82

The ERP of this product is less than 3060mW

Note: 1) Refer to report No. CQASZ20230200111E-01 for EUT test Max Conducted Peak Output Power value.  
2) EUT's module is more than 20cm away from the human body.

\*\*\* END OF REPORT \*\*\*