

Maximum Permissible Exposure Report

Product Information

EUT : Tablet PC

Model Number : T30,T30A,T30B

Model Declaration : All the same except for the model name

Test Model : T30

Power Supply : DC 5V by adapter

Hardware version : MT8183

Software version : Android 12

Sample ID : TZ230204035-2#&TZ230204035-4#

Bluetooth

Bluetooth Version : V5.0

Operation Frequency : 2402- 2480 MHz

Channel Number : 79 Channels for Bluetooth BR/EDR(DSS)
40 Channels for BLE (DTS)

Modulation Technology : GFSK, $\pi/4$ -DQPSK, 8-DPSK for Bluetooth BR/EDR (DSS)
GFSK for BLE (DTS)

Data Rates : Bluetooth BR/EDR (DSS): 1/2/3Mbps
BLE (DTS): 1Mbps

Antenna Type And Gain : Internal Antenna 1:
2.16dBi

WiFi

WLAN : Supported IEEE 802.11a/b/g/n/ac

IEEE 802.11b:2412-2462MHz
IEEE 802.11g:2412-2462MHz
IEEE 802.11n HT20:2412-2462MHz / 5180-5240MHz / 5745-5825MHz

WLAN FCC Operation : IEEE 802.11n HT40: 2422-2452MHz / 5190-5230MHz / 5755-5795MHz
Frequency : IEEE 802.11a: 5180-5240MHz / 5745-5825MHz
IEEE 802.11ac VHT20: 5180-5240MHz / 5745-5825MHz
IEEE 802.11ac VHT40: 5190-5230MHz / 5755-5795MHz
IEEE 802.11ac VHT80: 5210MHz / 5775MHz

WLAN Channel Number : 11 Channels for 2412-2462MHz(IEEE 802.11b/g/n HT20)
7 Channels for 2422-2452MHz(IEEE 802.11n HT40)
4 Channels for 5180-5240MHz (IEEE 802.11a/ac VHT20/n HT20)
2 Channels for 5190-5230MHz (IEEE 802.11ac VHT40/n HT40)
1 Channels for 5210MHz (IEEE 802.11ac VHT80)
5 Channels for 5745-5825MHz(IEEE 802.11a/ac VHT20/n HT20)
2 Channels for 5755-5795MHz(IEEE 802.11ac VHT40/n HT40)
1 Channels for 5775MHz(IEEE 802.11ac VHT80)

WLAN Modulation : IEEE 802.11b: DSSS(CCK,DQPSK,DBPSK)
Technology : IEEE 802.11g: OFDM (64QAM, 16QAM, QPSK, BPSK)
IEEE 802.11n: OFDM (64QAM, 16QAM, QPSK, BPSK)
IEEE 802.11a: OFDM (64QAM, 16QAM, QPSK, BPSK)
IEEE 802.11ac: OFDM (256QAM, 64QAM, 16QAM, QPSK, BPSK)

Antenna Type And Gain : 2.16dBi (Max.), for TX/RX (WLAN 2.4G Band)
2.1dBi (Max.), for TX/RX (WLAN 5.2G Band)
2.27dBi (Max.), for TX/RX (WLAN 5.8G Band)

Note 1: Antenna position refer to EUT Photos.

Note 2: the above information was supplied by the applicant.

1. RADIO FREQUENCY EXPOSURE

Limit

According to section 4.3.1 of KDB 447498 D01 General RF Exposure Guidance v06, SAR evaluation is required if the separation distance between the user and/or bystander and the antenna and/or radiating element of the device is less than or equal to 20 cm, except when the device operates at or below the applicable output power level (adjusted for tune-up tolerance) for the specified separation distance defined in Appendix A.

Appendix A

SAR Test Exclusion Thresholds for 100 MHz – 6 GHz and ≤ 50 mm

MHz	5	10	15	20	25	mm
150	39	77	116	155	194	SAR Test Exclusion Threshold (mW)
300	27	55	82	110	137	
450	22	45	67	89	112	
835	16	33	49	66	82	
900	16	32	47	63	79	
1500	12	24	37	49	61	
1900	11	22	33	44	54	
2450	10	19	29	38	48	
3600	8	16	24	32	40	
5200	7	13	20	26	33	
5400	6	13	19	26	32	
5800	6	12	19	25	31	
MHz	30	35	40	45	50	mm
150	232	271	310	349	387	SAR Test Exclusion Threshold (mW)
300	164	192	219	246	274	
450	134	157	179	201	224	
835	98	115	131	148	164	
900	95	111	126	142	158	
1500	73	86	98	110	122	
1900	65	76	87	98	109	
2450	57	67	77	86	96	
3600	47	55	63	71	79	
5200	39	46	53	59	66	
5400	39	45	52	58	65	
5800	37	44	50	56	62	

Conducted Power

2.4G Band:
Bluetooth(BDR+EDR)

TestMode	Antenna	Channel	Result[dBm]
DH5	Ant1	2402	6.29
		2441	6.98
		2480	6.62
2DH5	Ant1	2402	5.94
		2441	7.12
		2480	6.16
3DH5	Ant1	2402	6.69
		2441	6.62
		2480	6.19

Bluetooth(BLE)

TestMode	Antenna	Channel	Result[dBm]
BLE_1M	Ant1	2402	3.21
		2440	5.11
		2480	2.52

WiFi 2.4GHz Band

TestMode	Antenna	Channel	Result[dBm]
11B	Ant1	2412	6.86
		2437	7.19
		2462	6.83
11G	Ant1	2412	6.26
		2437	6.82
		2462	6.52
11N20SISO	Ant1	2412	6.13
		2437	6.68
		2462	6.50
11N40SISO	Ant1	2422	6.90
		2437	6.57
		2452	6.09

5G Band
UNII-1 Band

TestMode	Antenna	Channel	Result[dBm]
11A	Ant1	5180	5.66
		5200	5.55
		5240	5.41
11N20SISO	Ant1	5180	5.45
		5200	5.44
		5240	5.20
11N40SISO	Ant1	5190	5.18
		5230	5.57
11AC20SISO	Ant1	5180	5.64
		5200	5.44
		5240	5.25
11AC40SISO	Ant1	5190	5.22
		5230	5.65
11AC80SISO	Ant1	5210	5.51

UNII-3 Band

TestMode	Antenna	Channel	Result[dBm]
11A	Ant1	5745	4.64
		5785	4.76
		5825	4.48
11N20SISO	Ant1	5745	4.48
		5785	4.65
		5825	4.31
11N40SISO	Ant1	5755	4.36
		5795	3.87
11AC20SISO	Ant1	5745	4.42
		5785	4.65
		5825	4.34
11AC40SISO	Ant1	5755	4.33
		5795	3.84
11AC80SISO	Ant1	5775	4.28

Manufacturing Tolerance**Bluetooth(BDR+EDR)**

GFSK (Peak)			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	6.0	6.5	6.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
$\pi/4$ -DQPSK (Peak)			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	5.5	6.5	5.5
Tolerance $\pm$ (dB)	1.0	1.0	1.0
8-DPSK (Peak)			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	6.0	6.0	5.5
Tolerance $\pm$ (dB)	1.0	1.0	1.0

Bluetooth(BLE)

GFSK(1Mbps) (Peak)			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	2.5	4.5	2.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0

WiFi 2.4GHz Band – Antenna 1

IEEE 802.11b(Average)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	6.5	6.5	6.5
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11g (Average)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	6.0	6.5	6.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11n HT20 (Average)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	5.5	6.0	6.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11n HT40 (Average)			
Channel	Channel 3	Channel 6	Channel 9
Target (dBm)	6.5	6.0	5.5
Tolerance $\pm$ (dB)	1.0	1.0	1.0

UNII-1 Band – Antenna 1

IEEE 802.11a (Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	5.0	5.0	5.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11n HT20 (Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	5.0	5.0	4.5
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11ac VHT20 (Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	5.0	5.0	5.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11n HT40 (Average)			
Channel	Channel 38	Channel 46	--
Target (dBm)	4.5	5.0	--
Tolerance $\pm$ (dB)	1.0	1.0	--
IEEE 802.11ac VHT40 (Average)			
Channel	Channel 38	Channel 46	--
Target (dBm)	4.5	5.0	--
Tolerance $\pm$ (dB)	1.0	1.0	--
IEEE 802.11ac VHT80 (Average)			
Channel	Channel 42	--	--
Target (dBm)	5.0	--	--
Tolerance $\pm$ (dB)	1.0	--	--

UNII-3 Band – Antenna 1

IEEE 802.11a (Average)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	4.0	4.5	4.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11n HT20 (Average)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	4.0	4.0	4.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11ac VHT20 (Average)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	4.0	4.0	4.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11n HT40 (Average)			
Channel	Channel 151	Channel 159	--
Target (dBm)	4.0	3.5	--
Tolerance $\pm$ (dB)	1.0	1.0	--
IEEE 802.11ac VHT40 (Average)			
Channel	Channel 151	Channel 159	--
Target (dBm)	4.0	3.5	--
Tolerance $\pm$ (dB)	1.0	1.0	--
IEEE 802.11ac VHT80 (Average)			
Channel	Channel 155	--	--
Target (dBm)	4.0	--	--
Tolerance $\pm$ (dB)	1.0	--	--

Measurement Results

Bluetooth(BLE)

Test Mode	Channel Frequency (MHz)	Max. Tune Up Power (dBm, Peak)	Max. Eirp including Tune Up (dBm, Peak)	Max. Eirp including Tune Up (mW, Peak)	Exemption Limit (mW)
GFSK(1Mbps)	2402	3.50	5.66	3.68	10
	2440	5.50	7.66	5.83	10
	2480	3.00	5.16	3.28	10

Bluetooth(BDR+EDR)

Test Mode	Channel Frequency (MHz)	Max. Tune Up Power (dBm, Peak)	Max. Eirp including Tune Up (dBm, Peak)	Max. Eirp including Tune Up (mW, Peak)	Exemption Limit (mW)
GFSK	2402	7.00	9.16	8.24	10
	2440	7.50	9.66	9.25	10
	2480	7.00	9.16	8.24	10
$\pi/4$ -DQPSK	2402	6.50	8.66	7.35	10
	2440	7.50	9.66	9.25	10
	2480	6.50	8.66	7.35	10
8-DPSK	2402	7.00	9.16	8.24	10
	2440	7.00	9.16	8.24	10
	2480	6.50	8.66	7.35	10

WiFi 2.4GHz Band – Ant 1

Test Mode	Channel Frequency (MHz)	Max. Tune Up Power (dBm, Peak)	Max. Eirp including Tune Up (dBm, Peak)	Max. Eirp including Tune Up (mW, Peak)	Exemption Limit (mW)
IEEE 802.11b	2412	7.50	9.66	9.25	10
	2437	7.50	9.66	9.25	10
	2462	7.50	9.66	9.25	10
IEEE 802.11g	2412	7.00	9.16	8.24	10
	2437	7.50	9.66	9.25	10
	2462	7.00	9.16	8.24	10
IEEE 802.11n HT20	2412	6.50	8.66	7.35	10
	2437	7.00	9.16	8.24	10
	2462	7.00	9.16	8.24	10
IEEE 802.11n HT40	2422	7.50	9.66	9.25	10
	2437	7.00	9.16	8.24	10
	2452	6.50	8.66	7.35	10

UNII-1 Band – Ant 1

Test Mode	Channel Frequency (MHz)	Max. Tune Up Power (dBm, Peak)	Max. Eirp including Tune Up (dBm, Peak)	Max. Eirp including Tune Up (mW, Peak)	Exemption Limit (mW)
IEEE 802.11a	5180	6.00	8.10	6.46	7
	5200	6.00	8.10	6.46	7
	5240	6.00	8.10	6.46	7
IEEE 802.11n HT20	5180	6.00	8.10	6.46	7
	5200	6.00	8.10	6.46	7
	5240	5.50	7.60	5.75	7
IEEE 802.11n HT40	5190	5.50	7.60	5.75	7
	5230	6.00	8.10	6.46	7
IEEE 802.11ac VHT20	5180	6.00	8.10	6.46	7
	5200	6.00	8.10	6.46	7
	5240	6.00	8.10	6.46	7
IEEE 802.11ac VHT40	5190	5.50	7.60	5.75	7
	5230	6.00	8.10	6.46	7
IEEE 802.11ac VHT80	5210	6.00	8.10	6.46	7

UNII-3 Band – Ant 1

Test Mode	Channel Frequency (MHz)	Max. Tune Up Power (dBm, Peak)	Max. Eirp including Tune Up (dBm, Peak)	Max. Eirp including Tune Up (mW, Peak)	Exemption Limit (mW)
IEEE 802.11a	5745	5.00	7.27	5.33	6
	5785	5.50	7.77	5.98	6
	5825	5.00	7.27	5.33	6
IEEE 802.11n HT20	5745	5.00	7.27	5.33	6
	5785	5.00	7.27	5.33	6
	5825	5.00	7.27	5.33	6
IEEE 802.11n HT40	5755	5.00	7.27	5.33	6
	5795	4.50	6.77	4.75	6
IEEE 802.11ac VHT20	5745	5.00	7.27	5.33	6
	5785	5.00	7.27	5.33	6
	5825	5.00	7.27	5.33	6
IEEE 802.11ac VHT40	5755	5.00	7.27	5.33	6
	5795	4.50	6.77	4.75	6
IEEE 802.11ac VHT80	5775	5.00	7.27	5.33	6

Remark:

The antenna gain of the EUT for BT is 2.16dBi (Max), 2.4g WLAN is 2.16dBi (Max), 5.2G WLAN is 2.10dBi (Max), 5.8G WLAN is 2.27dBi (Max). The Maximum Eirp is used for Routine Evaluation Exemption according to section 4.3.1 of KDB 447498 D01.

So, the SAR evaluation is not required.

-----THE END OF REPORT-----