

# Powercore Technology Co., Ltd.

## MPE ASSESSMENT REPORT

**Report Type:**

FCCC MPE assessment report

**Model:**

ADC002C130C130, ADC002C160C130,  
ADC002C160C160, ADC002C190C160,  
ADC002C190C190

**REPORT NUMBER:**

230501370SHA-002

**ISSUE DATE:**

August 1, 2023

**DOCUMENT CONTROL NUMBER:**

TTRFFCCMPE-01\_V1 © 2018 Intertek



**Applicant:** Powercore Technology Co., Ltd.  
4th Floor, Jiangsu Science and Technology Finance Building, No.21  
Andemen Street, Yuhuatai District, Nanjing City, Jiangsu Province, P.R. China

**Manufacturer:** Powercore Technology Co., Ltd.  
4th Floor, Jiangsu Science and Technology Finance Building, No.21  
Andemen Street, Yuhuatai District, Nanjing City, Jiangsu Province, P.R. China


**Factory:** Powercore Technology Co., Ltd.  
Zone A, No.1 Yuansi Road, Jiangbei New District, Nanjing City, Jiangsu  
Province, P.R. China

**FCC ID:** 2A98K-ADC002

**SUMMARY:**

The equipment complies with the requirements according to the following standard(s) or Specification:

KDB447498 D01 General RF Exposure Guidance v06  
FCC Part2.1091, FCC Part2.1093 FCC Part1.1307(b)

**PREPARED BY:**

---

Project Engineer  
Sky Yang

**REVIEWED BY:**

---

Reviewer  
Eric Li

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

**TEST REPORT****Revision History**

Report No.	Version	Description	Issued Date
230501370SHA-002	Rev. 01	Initial issue of report	August 1, 2023

**TEST REPORT****1 GENERAL INFORMATION****1.1 Description of Equipment Under Test (EUT)**

Product name:	DC Electric Vehicle Charging Station
Type/Model:	ADC002C130C130, ADC002C160C130, ADC002C160C160, ADC002C190C160, ADC002C190C190
Description of EUT:	The EUT is electric vehicle DC charger. It contains two certified modules, the WIFI/Bluetooth module FCC ID is 2AC7Z-ESPWROOM32UE(grant date:01/25/2022), the LTE module FCC ID is XMR201903EG25G. All models are electric identical except the rated power.
Rating:	ADC002C130C130: Input: 480VAC±10%, 50/60Hz, 76A Output: 150-1000VDC, 200ADC, 60kW Max ADC002C160C130: Input: 480VAC±10%, 50/60Hz, 114A Output: 150-1000VDC, 200ADC, 90kW Max ADC002C160C160: Input: 480VAC±10%, 50/60Hz, 152A Output: 150-1000VDC, 200ADC, 120kW Max ADC002C190C160: Input: 480VAC±10%, 50/60Hz, 190A Output: 150-1000VDC, 200ADC, 150kW Max ADC002C190C190: Input: 480VAC±10%, 50/60Hz, 228A Output: 150-1000VDC, 200ADC, 180kW Max
EUT type:	<input type="checkbox"/> Table top <input checked="" type="checkbox"/> Floor standing
Software Version:	-
Hardware Version:	-
Serial numbers:	0230510-29
Sample received date:	May 10, 2023
Date of test:	May 29, 2023 ~ June 9, 2023

**1.2 Technical Specification**

Frequency Range:	13.56 MHz ~ 13.56 MHz
Modulation:	ASK
Antenna:	PCB antenna

**TEST REPORT****1.3 Description of Test Facility**

Name:	Intertek Testing Services Shanghai
Address:	Building 86, No. 1198 Qinzhou Road(North), Shanghai 200233, P.R. China
Telephone:	86 21 61278200
Telefax:	86 21 54262353

The test facility is recognized, certified, or accredited by these organizations:	CNAS Accreditation Lab Registration No. CNAS L0139
	FCC Accredited Lab Designation Number: CN0175
	IC Registration Lab CAB identifier.: CN0014
	VCCI Registration Lab Member No.: 3598 (Registration No.: R-14243, G-10845, C-14723, T-12252)
	A2LA Accreditation Lab Certificate Number: 3309.02

**TEST REPORT****2 MPE Assessment****Test result:** Pass**2.1 MPE Assessment Limit****Mobile device exposure for standalone operations:**

According to §1.1310, the limit for general population/uncontrolled exposures

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

Note: Limit for 13.56MHz is 60.77 V/m

Mobile device exposure for simultaneous transmission operations: **the sum of the MPE ratios for all simultaneously transmitting antennas incorporated in a host device is ≤ 1.0**

## TEST REPORT

### 2.2 Assessment Results

Power density (S) is calculated according to the formula:

$$S = P / (4\pi R^2)$$

Where S = power density in mW/cm<sup>2</sup>

P = Radiated transmit power in mW

R = distance (cm)

As we can see from the test report 230501370SHA-001:

52.1dBuV/m@3m, @20cm=@3m+40log(3/0.2)=99.14dBuV/m=0.091V/m<60.77.

The power for WIFI module refers to certificate of FCC ID: 2AC7Z- ESPWROOM32UE

The power for LTE module refers to certificate of FCC ID: XMR201903EG25G

The calculations in the table below use the highest gain of antenna for client EUT. These calculations represent worst case in terms of the exposure levels.

Frequency Range (MHz)	EIRP (dBm)		Antenna Gain (dBi)	R (cm)	S (mW/cm <sup>2</sup> )	Limits (mW/cm <sup>2</sup> )
WIFI 2.4G	19.92	98.18	4	20	0.0195	1.0000
BT	11.59	14.42	4	20	0.0029	1.0000
BLE	8.81	7.60	4	20	0.0015	1.0000
GSM850	28.10	645.65	2.29	20	0.1284	0.5495
GSM1900	24.40	275.42	1.59	20	0.0548	1.0000
WCDMA Band II	26.59	456.04	1.59	20	0.0907	1.0000
WCDMA Band IV	27.00	501.19	2.00	20	0.0997	1.0000
WCDMA Band V	27.29	535.80	2.29	20	0.1066	0.5509
LTE Band 2	26.59	456.04	1.59	20	0.0907	1.0000
LTE Band 4	27.00	501.19	2.00	20	0.0997	1.0000
LTE Band 5	27.29	535.80	2.29	20	0.1066	0.5498
LTE Band 7	28.00	630.96	3.00	20	0.1255	1.0000
LTE Band 12	28.26	669.88	3.26	20	0.1333	0.4665
LTE Band 13	29.45	881.05	4.45	20	0.1753	0.5197
LTE Band 25	26.59	456.04	1.59	20	0.0907	1.0000
LTE Band 26(814-824)	27.53	566.24	2.53	20	0.1126	0.5431
LTE Band 26(824-849)	27.53	566.24	2.53	20	0.1126	0.5498
LTE Band 38	27.06	508.16	2.06	20	0.1011	1.0000
LTE Band 41	28.00	630.96	3.00	20	0.1255	1.0000

Note: 1 mW/cm<sup>2</sup> from 1.310 Table 1.

RFID, LTE and WIFI can transmit simultaneously, so the maximum rate of MPE is,  
 $0.091/60.77+0.0195/1+0.1753/0.5197=0.358 < 1.0$ .

**TEST REPORT**

## **Appendix I**

Definition below must be outlined in the User Manual:

To satisfy FCC RF exposure requirements, a separation distance of 20 cm or more should be maintained between the antenna of this device and persons during device operation.

To ensure compliance, operations at closer than this distance is not recommended.

\*\*\*\*\*END\*\*\*\*\*