Coil Antenna 3 (Watch) Specifications

			Material no. 0					
Material no.	OJD DZ-RC24-K8.1-L12MM			SPEC NO	2022040	20220402002 Version		01
◆、外形尺寸	F A					(Unit: mm)		
						Α	24.0	±1.0
						В	13.5	
				I		C 7.		2.2
						D	1.2	±0.05
						E	2.0	±1.0
						F	12.0	±2.0
		D				J	0.1	±0.1
	B C			1		J	2.3	±0.2(With film thickness)
				1				Remark
						(1) Wire diameter: 0.08*24P twisted wire, single double winding method		
						(2) The coil	is wound 1	13 times
						(3) add bac	k glue at th	ne bottom
						(4) Whether the starting and tail lines are crossed:		
			\underline{H}			both (5) N52-7 4	*2 2 strong	magnetic field,2700GS, is
				- -		placed in the middle of the coil		f the coil
						(6) Whether both	r the startir	ng and tail lines are crossed:
♦、Electrical cl	haracteristics:							
Parameter	Specifications		Test conditions		Test equipment		ent	Antenna gain
L(W1)		±5% μΗ	1	00KHz/1V @ 25℃	■TH2816B ■CH-502BC ■TH1816B			0
DCR(W1)	<120 >20	mΩ min	1	00KHz/1V				
◆、Temperatur			ļ <u>.</u>		1		J	
Operating temperature	-40℃~ 125℃							
temperature	123 0							
◆、List of Mate	erials:							
S/N	Product name	Material specifications		Supplier		Rema		ark
1	Disk	24*2.3 Soft magnetic						
2	Stranded wire	0.08*24P				Stranded wire		ed wire
3	3 m adhesive	20 3M				Green tape		
4	Strong N52 magnetic	7.4*2.2				Magnet		met
		107H				Environmental protection tin		

Environmental protection glue

Environmental protection glue

6

7

 ${\tt Glue}$

Glue

Xanthan gum

Super glue