

1 Version

Revision History Of Report

Report No.	Version	Description	Issue Date
CQASZ20240901999E-04	Rev.01	Initial report	2024-11-04

2 Contents

	Page
1 VERSION	2
2 CONTENTS	3
.....	3
3 GENERAL INFORMATION	4
3.1 CLIENT INFORMATION	4
3.2 GENERAL DESCRIPTION OF EUT	4
3.3 GENERAL DESCRIPTION OF BT CLASSIC	4
3.4 GENERAL DESCRIPTION OF BLE	4
3.5 GENERAL DESCRIPTION OF 5.8G CUSTOM	5
4 MPE EVALUATION	6
4.1 RF EXPOSURE COMPLIANCE REQUIREMENT	6
4.1.1 <i>Limits</i>	6
4.1.2 <i>Test Procedure</i>	6
4.1.3 <i>EUT RF Exposure</i>	7

3 General Information

3.1 Client Information

Applicant:	Ultimea Technology (Shenzhen) Limited
Address of Applicant:	20th Floor, Building 4, Tianan Cloud Park, Bantian St., Longgang District, Shenzhen, China
Manufacturer:	Ultimea Technology (Shenzhen) Limited
Address of Manufacturer:	20th Floor, Building 4, Tianan Cloud Park, Bantian St., Longgang District, Shenzhen, China

3.2 General Description of EUT

Product Name:	Apollo S90 9.1 Channel Dolby Atmos Detachable Lighting Soundbar, Apollo S90 9.1 Channel Detachable Lighting Soundbar with Dolby Atmos
Model No.:	U3820
Test Model No.:	U3820
Trade Mark:	ULTIMEA
Software Version:	0.1
Hardware Version:	0.1
Power Supply:	Model:SMS-00180300-S38 Input:100-240V~50/60Hz 1.5A Output:18V 3.0A 54W
	Model:FX48U-180300C Input:100-240V~50/60Hz 1.0A Output:18V 3.0A 54W

3.3 General Description of BT Classic

Operation Frequency:	2402MHz~2480MHz
Bluetooth Version:	Bluetooth Spec 5.4
Modulation Technique:	Frequency Hopping Spread Spectrum(FHSS)
Modulation Type:	GFSK, $\pi/4$ DQPSK, 8DPSK
Number of Channel:	79
Transfer Rate:	1Mbps/2Mbps/3Mbps
Hopping Channel Type:	Adaptive Frequency Hopping systems
Sample Type:	<input checked="" type="checkbox"/> Mobile <input type="checkbox"/> Portable <input type="checkbox"/> Fix Location
Antenna Type:	FPC antenna
Antenna Gain:	2.64dBi
Cable loss:	1.0 dB

3.4 General Description of BLE

Operation Frequency:	2402MHz~2480MHz
Bluetooth Version:	Bluetooth Spec 5.4
Modulation Type:	GFSK
Number of Channel:	40

Transfer Rate:	1Mbps/2Mbps
Sample Type:	<input checked="" type="checkbox"/> Mobile <input type="checkbox"/> Portable <input type="checkbox"/> Fix Location
Antenna Type:	FPC antenna
Antenna Gain:	2.64dBi
Cable loss:	1.0 dB

3.5 General Description of 5.8G custom

Operation Frequency:	5729MHz ~ 5847MHz
Modulation Type:	GFSK
Number of Channel:	119
Sample Type:	<input checked="" type="checkbox"/> Mobile <input type="checkbox"/> Portable <input type="checkbox"/> Fix Location
Antenna Type:	FPC antenna
Antenna Gain:	ANT1:4.41dBi ANT2:2.07dBi
Cable loss:	1.0 dB

Note:

The above parameters will directly affect the test results. The information is provided by the applicant.

4 MPE Evaluation

4.1 RF Exposure Compliance Requirement

4.1.1 Limits

The table applies to any RF source (i.e., single fixed, mobile, and portable transmitters) and specifies power and distance criteria for each of the five frequency ranges used for the MPE limits. These criteria apply at separation distances from any part of the radiating structure of at least $\lambda/2\pi$. The thresholds are based on the general population MPE limits with a single perfect reflection, outside of the reactive near-field, and in the main beam of the radiator. For mobile devices that are not exempt per Table B.1 [Table 1 of § 1.1307(b)(1)(i)(C)] at distances from 20 cm to 40 cm and in 0.3 GHz to 6 GHz, evaluation of compliance with the exposure limits in § 1.1310 is necessary if the ERP of the device is greater than ERP_{20cm} in Formula (B.1) [repeated from § 2.1091(c)(1) and § 1.1307(b)(1)(i)(B)].

$$P_{th} \text{ (mW)} = ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

If the ERP is not easily obtained, then the available maximum time-averaged power may be used (i.e., without consideration of ERP only if the physical dimensions of the radiating structure(s) do not exceed the electrical length of $\lambda/4$ or if the antenna gain is less than that of a half-wave Dipole.

SAR-based exemptions are constant at separation distances between 20 cm and 40 cm to avoid discontinuities in the threshold when transitioning between SAR-based and MPE-based exemption criteria at 40 cm, considering the importance of reflections.

4.1.2 Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

4.1.3 EUT RF Exposure

1) For BT Classic

Output Power Into Antenna & RF Exposure Evaluation Distance:

Measurement Data

GFSK mode					
Test channel	EIRP (dBm)	ERP (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
				(dBm)	(mW)
Lowest(2402MHz)	7.35	5.20	5.0±1	6.0	3.98
Middle(2441MHz)	7.35	5.20	5.0±1	6.0	3.98
Highest(2480MHz)	8.27	6.12	6.0±1	7.0	5.01
π/4DQPSK mode					
Test channel	EIRP (dBm)	ERP (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
				(dBm)	(mW)
Lowest(2402MHz)	7.38	5.23	5.0±1	6.0	3.98
Middle(2441MHz)	7.31	5.16	5.0±1	6.0	3.98
Highest(2480MHz)	8.4	6.25	6.0±1	7.0	5.01
8DPSK mode					
Test channel	EIRP (dBm)	ERP (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
				(dBm)	(mW)
Lowest(2402MHz)	7.34	5.19	5.0±1	6.0	3.98
Middle(2441MHz)	7.27	5.12	5.0±1	6.0	3.98
Highest(2480MHz)	8.27	6.12	6.0±1	7.0	5.01

The ERP of this product is less than 3060mW

Note: 1) Refer to report No. CQASZ20240901999E-01 for EUT test Max Conducted Peak Output Power value.

2) EUT's module is more than 20cm away from the human body.

2) For BLE

Output Power Into Antenna & RF Exposure Evaluation Distance:

Measurement Data

GFSK mode(1Mbps)					
Test channel	EIRP (dBm)	ERP (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
				(dBm)	(mW)
Lowest(2402MHz)	7.28	5.13	5.0±1	6.0	3.98
Middle(2440MHz)	7.25	5.10	5.0±1	6.0	3.98
Highest(2480MHz)	8.23	6.08	6.0±1	7.0	5.01
GFSK mode(2Mbps)					
Test channel	EIRP (dBm)	ERP (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
				(dBm)	(mW)
Lowest(2402MHz)	7.40	5.25	5.5±1	6.5	4.47
Middle(2440MHz)	7.44	5.29	5.5±1	6.5	4.47
Highest(2480MHz)	8.43	6.28	6.0±1	7.0	5.01

The ERP of this product is less than 3060mW

Note: 1) Refer to report No. CQASZ20240901999E-02 for EUT test Max Conducted Peak Output Power value.

2) EUT's module is more than 20cm away from the human body.

3) For 5.8G custom

$$EIRP = E_{Meas} + 20 \log(d_{Meas}) - 104.7$$

where

EIRP is the equivalent isotropically radiated power, in dBm
 E_{Meas} is the field strength of the emission at the measurement distance, in dB μ V/m
 d_{Meas} is the measurement distance, in m

Channel	EIRP (dBm)	ERP (dBm)	Maximum tune-up Power (mW)	Exclusion threshold (mW)
Lowest (5729MHz)	0.89	-1.26	0.75	3060
Middle (5788MHz)	-0.63	-2.78	0.53	
Highest (5847MHz)	-0.21	-2.36	0.58	

Remark: The Max Peak Output Power data refer to report Report No.:CQASZ20240901999E-03.

$$BT+BLE+5.8GWIFI=5.01/3060+5.01/3060+0.53/3060=0.003 \leq 1$$

*** END OF REPORT ***