



## Shenzhen Huaxia Testing Technology Co., Ltd.

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

Telephone: +86-755-26648640  
Fax: +86-755-26648637  
Website: [www.cqa-cert.com](http://www.cqa-cert.com)

Report Template Version: V05  
Report Template Revision Date: 2021-11-03

# RF Exposure Evaluation Report

**Report No.:** CQASZ20240500869E-02

**Applicant:** Shenzhen Rinocloud Technology Co., Ltd.

**Address of Applicant:** Building 6, 2003, Cloud Park Phase II, Gangtou Community, Bantian Street, Longgang District, Shenzhen

**Equipment Under Test (EUT):**

**EUT Name:** Bluetooth module

**Model No.:** XY2612-T5, XY2616-T5-IPEX

**Test Model No.:** XY2612-T5

**Brand Name:** N/A

**FCC ID:** 2A9TO-XY2612-T5

**Standards:** 47 CFR Part 1.1307

47 CFR Part 1.1310

447498 D04 Interim General RF Exposure Guidance v01

**Date of Receipt:** 2024-05-21

**Date of Test:** 2024-05-21 to 2024-05-30

**Date of Issue:** 2024-06-11

**Test Result:** PASS\*

\*In the configuration tested, the EUT complied with the standards specified above

**Tested By:**

lewis zhou

( Lewis Zhou )

**Reviewed By:**

Timo Lei

( Timo Lei )

**Approved By:**

Alex

( Alex Wang )



## 1 Version

### Revision History Of Report

Report No.	Version	Description	Issue Date
CQASZ20240500869E-02	Rev.01	Initial report	2024-06-11

## 2 Contents

	Page
<b>1 VERSION</b> .....	2
<b>2 CONTENTS</b> .....	3
.....	3
<b>3 GENERAL INFORMATION</b> .....	4
3.1 CLIENT INFORMATION .....	4
3.2 GENERAL DESCRIPTION OF EUT .....	4
3.3 GENERAL DESCRIPTION OF BLE .....	4
<b>4 MPE EVALUATION</b> .....	5
4.1 RF EXPOSURE COMPLIANCE REQUIREMENT .....	5
4.1.1 <i>Limits</i> .....	5
4.1.2 <i>Test Procedure</i> .....	5
4.1.3 <i>EUT RF Exposure</i> .....	6

### 3 General Information

#### 3.1 Client Information

Applicant:	Shenzhen Rinocloud Technology Co ., Ltd .
Address of Applicant:	Building 6, 2003, Cloud Park Phase II, Gangtou Community, Bantian Street, Longgang District, Shenzhen
Manufacturer:	Shenzhen Rinocloud Technology Co ., Ltd .
Address of Manufacturer:	Building 6, 2003, Cloud Park Phase II, Gangtou Community, Bantian Street, Longgang District, Shenzhen
Factory:	Shenzhen Rinocloud Technology Co ., Ltd .
Address of Factory:	Building 6, 2003, Cloud Park Phase II, Gangtou Community, Bantian Street, Longgang District, Shenzhen

#### 3.2 General Description of EUT

Product Name:	Bluetooth module
Model No.:	XY2612-T5, XY2616-T5-IPEx
Test Model No.:	XY2612-T5
Trade Mark:	N/A
Software Version:	XY2612_T5_V2.0
Hardware Version:	XY2612_T5_V02
EUT Power Supply:	Power supply DC3.3V

#### 3.3 General Description of BLE

Operation Frequency:	2402MHz~2480MHz
Bluetooth Version:	Bluetooth Spec 5.3
Modulation Type:	GFSK
Number of Channel:	40
Transfer Rate:	1Mbps
Sample Type:	<input checked="" type="checkbox"/> Mobile <input type="checkbox"/> Portable
Antenna Type:	PCB antenna
Antenna Gain:	3.5dBi

Note:

The above parameters will directly affect the test results. The information is provided by the applicant.

## 4 MPE Evaluation

### 4.1 RF Exposure Compliance Requirement

#### 4.1.1 Limits

The table applies to any RF source (i.e., single fixed, mobile, and portable transmitters) and specifies power and distance criteria for each of the five frequency ranges used for the MPE limits. These criteria apply at separation distances from any part of the radiating structure of at least  $\lambda/2\pi$ . The thresholds are based on the general population MPE limits with a single perfect reflection, outside of the reactive near-field, and in the main beam of the radiator. For mobile devices that are not exempt per Table B.1 [Table 1 of § 1.1307(b)(1)(i)(C)] at distances from 20 cm to 40 cm and in 0.3 GHz to 6 GHz, evaluation of compliance with the exposure limits in § 1.1310 is necessary if the ERP of the device is greater than ERP<sub>20cm</sub> in Formula (B.1) [repeated from § 2.1091(c)(1) and § 1.1307(b)(1)(i)(B)].

$$P_{th} \text{ (mW)} = ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

If the ERP is not easily obtained, then the available maximum time-averaged power may be used (i.e., without consideration of ERP only if the physical dimensions of the radiating structure(s) do not exceed the electrical length of  $\lambda/4$  or if the antenna gain is less than that of a half-wave Dipole).

SAR-based exemptions are constant at separation distances between 20 cm and 40 cm to avoid discontinuities in the threshold when transitioning between SAR-based and MPE-based exemption criteria at 40 cm, considering the importance of reflections.

#### 4.1.2 Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

**4.1.3 EUT RF Exposure****1) For BLE****Measurement Data**

Test channel	EIRP (dBm)	ERP (dBm)	Tune up tolerance (dBm)	GFSK mode	
				(dBm)	(mW)
Lowest(2402MHz)	2.70	0.55	0.5±1	1.5	1.41
Middle(2440MHz)	2.60	0.45	0.5±1	1.5	1.41
Highest(2480MHz)	3.40	1.25	1.5±1	2.5	1.78

The ERP of this product is less than 3060mW

Note: 1) Refer to report No. CQASZ20240500869E-01 for EUT test Max Conducted Peak Output Power value.  
2) EUT's module is more than 20cm away from the human body.

\*\*\* END OF REPORT \*\*\*