

115.00 mm

TECLOMAN

Firefly Pro

Name: Battery System

Model/Nominal Voltage/Nominal Energy/Output Power

- Firefly Pro-H3/153.6V/7.5kWh/7.5kW
- Firefly Pro-H4/204.8V/10.0kWh/10.0kW
- Firefly Pro-H5/256.0V/12.5kWh/12.5kW
- Firefly Pro-H6/307.2V/15.0kWh/15.0kW
- Firefly Pro-H7/358.4V/17.5kWh/17.5kW
- Firefly Pro-H8/409.6V/20.0kWh/20.0kW

*During operation,don't put product in direct sunshine,rain shower, condensation environment.

*pendant le fonctionnement, ne mettez pas le produit sous le soleil direct, douche de pluie, environnement de condensation.



<http://www.tecloman.com>

Max.Continuous Current(A):

50

0~+50

Charging Operation Temperature(°C):

-20~+50

Discharging Operation Temperature(°C):

IP55

Enclosure:

Class I

Protection Level:

Maximum Short Circuit Current: 5000A Duration : 0.1ms
FCC ID:2A9WV-FIREFLY-PRO

*This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

*Cet appareil est conforme à la partie 15 de norme de la FCC. Son fonctionnement est soumis aux deux conditions suivantes: (1) cet appareil ne doit pas causer d'interférences nuisibles, et(2) cet appareil doit accepter toute interférence reçue, y compris les interférences susceptibles de provoquer un fonctionnement indésirable.

Serial Number

WIFI SSID

MADE IN CHINA



