


## Instructions of remote

Name:433.92MHZ RF remote control

Model:RC-001

### Remote connect process:

1. Pull out the insulation sheet.



2. Long press the connect button on the motor. Indicate light flash red light.



Long press the  
connect button



Indicate light  
flash red light

3. Press any button on the remote.



Press any button  
of them

4. Indicate light stop flashing. It means connected success!



Indicate light stop flashing  
connected success!

## Change battery process:

1. Use a coin or something like that, Rotate the battery cover from “close” to “open” until it faces the arrow.



2. Move the battery cover, take out the battery.



3. Put new battery in the remote, Cover the battery cover.



Caution: Any changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.