



Report No.: PTC23060810101E-FC02

# FCC TEST REPORT

## FCC ID: 2A9YKCWWTWSCENEWH

Product	:	Smart Wi-Fi Room Controller
Model Name	:	CWW-TW-SCENE-WH, Wiz33
Brand	:	N/A
Report No.	:	PTC23060810101E-FC02

### Prepared for

Pure Edge Lighting LLC.

1718 W. Fullerton Ave Chicago Illinois, 60614, United States

### Prepared by

Precise Testing & Certification Co., Ltd.

Building 1, No. 6, Tongxin Road, Dongcheng Street, Dongguan, Guangdong, China.



## TEST RESULT CERTIFICATION

Applicant's name : Pure Edge Lighting LLC.

Address : 1718 W. Fullerton Ave Chicago Illinois, 60614, United States

Manufacturer's name : NIE-TECH Co., Ltd

Address : Jinlian commercial center 9001, Jinxiu road No.2, Changan Town, Dongguan City, GuangDong Prov., CHINA

Product name : Smart Wi-Fi Room Controller

Model name : CWW-TW-SCENE-WH, Wiz33

Test procedure : FCC CFR47 Part 1.1307(b)(1)

Test Date : Jun. 09, 2023 to Jun. 17, 2023

Date of Issue : Jun. 28, 2023

Test Result : PASS

This device described above has been tested by PTC, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of PTC, this document may be altered or revised by PTC, personal only, and shall be noted in the revision of the document.

Test Engineer:

A handwritten signature in black ink that reads "Simon Pu".

Simon Pu / Engineer

Technical Manager:

A handwritten signature in black ink that reads "Ronnie Liu".

Ronnie Liu / Manager



## Contents

	<b>Page</b>
<b>2 TEST SUMMARY .....</b>	<b>4</b>
<b>3 GENERAL INFORMATION .....</b>	<b>5</b>
3.1 GENERAL DESCRIPTION OF E.U.T.....	5
<b>4 RF EXPOSURE .....</b>	<b>6</b>
4.1 REQUIREMENTS.....	6
4.2 THE PROCEDURES / LIMIT .....	6
4.3 MPE CALCULATION METHOD .....	7
4.4 TEST RESULT .....	7



## 2 Test Summary

Test Items	Test Requirement	Result
Maximum Permissible Exposure (Exposure of Humans to RF Fields)	15.247 (i)	PASS
Remark:		
N/A: Not Applicable		



### 3 General Information

#### 3.1 General Description of E.U.T.

Product Name	:	Smart Wi-Fi Room Controller
Model Name	:	CWW-TW-SCENE-WH
Additional model	:	Wiz33
Model difference	:	Different model names
Specification	:	802.11b/g/n HT20
Operation Frequency	:	2412-2462MHz for 802.11b/g/ n(HT20)
Number of Channel	:	11 channels for 802.11b/g/ n(HT20)
Type of Modulation	:	DSSS with DBPSK/DQPSK/CCK for 802.11b; OFDM with BPSK/QPSK/16QAM/64QAM for 802.11g/n;
Antenna installation	:	PCB antenna
Antenna Gain	:	2.72 dBi
Power supply	:	Input: AC 120V 60Hz
Hardware Version	:	N/A
Software Version	:	N/A



## 4 RF Exposure

Test Requirement : FCC Part 1.1307(b)(1)

Evaluation Method : KDB 447498 D01 General RF Exposure Guidance v06

### 4.1 Requirements

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2 m normally can be maintained between the user and the device.

### 4.2 The procedures / limit

(A) Limits for Occupational / Controlled Exposure

Frequency Range	Electric Field	Magnetic Field	Power Density (S)	Averaging Time
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-100,000			5	6

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range	Electric Field	Magnetic Field	Power Density (S)	Averaging Time
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: f = frequency in MHz ; \*Plane-wave equivalent power density



#### 4.3 MPE Calculation Method

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: } P_d \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric field (V/m)

P = Peak RF output power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$P_d = \frac{30 \times P \times G}{377 \times d^2} \theta \varphi$$

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained

#### 4.4 Test Result

Mode	Antenna Gain (numeric)	Max. Peak Output Power (dBm)	Tune up tolerance (dBm)	Max Tune Up Power (mW)	Power Density (mW/cm <sup>2</sup> )	Limit of Power Density (mW/cm <sup>2</sup> )	Result
2462	1.87	16.83	17±1	0.063096	0.234817	1	Pass

\*\*\*\*\*THE END REPORT\*\*\*\*\*