



MPE/RF EXPOSURE REPORT

FCC CFR 47 Part 1.1310

Report No.: XCOL01-U5 Rev A

Company: XCOM Labs.

Model Name: XCOM 632 5G RRU

MPE/RF EXPOSURE REPORT

Company Name: XCOM Labs.

Model Name: XCOM 632 5G RRU

To: FCC CFR 47 Part 1.1310

Report Serial No.: XCOL01-U5 Rev A

This report supersedes: None

Applicant: XCOM Labs.
9450 Carroll Park Dr.
San Diego, California 92121
USA

Issue Date: 19th January 2023

This Test Report is Issued Under the Authority of:

MiCOM Labs, Inc.
575 Boulder Court
Pleasanton California 94566
USA
Phone: +1 (925) 462-0304
Fax: +1 (925) 462-0306
www.micomlabs.com



MiCOM Labs is an ISO 17025 Accredited Testing Laboratory

1. MAXIMUM PERMISSABLE EXPOSURE

Calculations for Maximum Permissible Exposure Levels

Power Density = Pd (mW/cm²) = EIRP/(4*π*d²)

EIRP = P * G

P = Peak output power (mW)

G = Antenna numeric gain (numeric)

d = Separation distance (cm)

Numeric Gain = 10 ^ (G (dBi)/10)

FCC CFR 47 Part 1.1310 Power Density Limits for General Population/Uncontrolled Exposure:

1.34 – 30 MHz Plane Wave Power Density = (180/f²) mW/cm²

300-1,500 MHz; Power Density = f/1500 mW/cm²

1,500-100,000 MHz; Power Density = 1.0 mW/cm²

The calculations in the table below use the highest measured conducted power values together with the antenna gain specified for the EUT. These calculations represent worst case in terms of the exposure levels.

Specification - Maximum Permissible Exposure Limits.

The Limit is defined in Table 1 of FCC §1.1310.

Freq. Band (MHz)	Ant Gain (dBi)	Numeric Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Calculated Power Density (mW/cm ²) @ 20cm	Power Density Limit (mW/cm ²)	Min Calculated safe distance for Limit (cm)
CBSD; 3625.0	6.0	3.98	23.05	201.84	0.16	1.00	8.00

Note 1: for mobile or fixed location transmitters the minimum separation distance is 20cm, even if calculations indicate the MPE distance to be less.



575 Boulder Court
Pleasanton, California 94566, USA
Tel: +1 (925) 462 0304
Fax: +1 (925) 462 0306
www.micomlabs.com