

# RF EXPOSURE REPORT

**REPORT NO.:** SA131111C01

MODEL NO.: DWW100

FCC ID: 2AA2U-DWW100

**RECEIVED:** Nov. 11, 2013

**ISSUED:** Nov. 29, 2013

**APPLICANT:** Cal-Comp Electronics & Communications Company

Limited

ADDRESS: 3th FL., No. 99, Sec. 5, Nanjing E. Rd., Taipei, 105

**ISSUED BY:** Bureau Veritas Consumer Products Services

(H.K.) Ltd., Taoyuan Branch

LAB ADDRESS: No. 19, Hwa Ya 2nd Rd, Wen Hwa Tsuen, Kwei

Shan Hsiang, Taoyuan Hsien 333, Taiwan,

R.O.C.

This report should not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification



# **TABLE OF CONTENTS**

RE	ELEASE CONTROL RECORD	3
1.	CERTIFICATION	4
2.	RF EXPOSURE	5
	2.1 LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)	
	2.2 MPE CALCULATION FORMULA	5
	2.3 CLASSIFICATION	5
	2.4 CALCULATION RESULT OF MAXIMUM CONDUCTED POWER	6



## **RELEASE CONTROL RECORD**

ISSUE NO.	D. REASON FOR CHANGE	
SA131111C01	Original release	Nov. 29, 2013

Report No.: SA131111C01 3 of 6 Report Format Version 5.0.0



#### 1. CERTIFICATION

**PRODUCT:** Canvio wireless adapter

MODEL: DWW100 BRAND: TOSHIBA

**APPLICANT:** Cal-Comp Electronics & Communications Company Limited

**TEST SAMPLE:** Identical Prototype

STANDARDS: FCC Part 2 (Section 2.1091)

FCC OET Bulletin 65, Supplement C (01-01)

**IEEE C95.1** 

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch,** and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY: , DATE: Nov. 29, 2013

Gina Liu / Specialist

**APPROVED BY**: , **DATE**: Nov. 29, 2013

Roy Wu / Manager



#### 2. RF EXPOSURE

### 2.1 LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

FREQUENCY RANGE (MHz)	ELECTRIC FIELD STRENGTH (V/m)	MAGNETIC FIELD STRENGTH (A/m)	POWER DENSITY (mW/cm²)	AVERAGE TIME (minutes)					
LIMITS FOR GENERAL POPULATION / UNCONTROLLED EXPOSURE									
300-1500			F/1500	30					
1500-100,000			1.0	30					

F = Frequency in MHz

#### 2.2 MPE CALCULATION FORMULA

Pd = (Pout\*G) / (4\*pi\*r2)

where

Pd = power density in mW/cm2

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

#### 2.3 CLASSIFICATION

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.



## 2.4 CALCULATION RESULT OF MAXIMUM CONDUCTED POWER

Frequency Band (MHz)	Conducted Avg. Power (dBm)	Antenna Gain (dBi)	E.I.R.P. (mW)	Power Density (mW/cm²)	Limit (mW/cm²)
2412-2462	17.56	1	57.02	0.011	1.0