

## 10 Appendix A - General Product Information

### Radiofrequency radiation exposure evaluation

This exposure evaluation is intended for **FCC ID: 2AA2X-15000282**

According to KDB 447498 D01v06 section 4.3.1, For frequencies between 100 MHz to 6GHz and test separation distances  $\leq 50$  mm, the Numeric threshold is determined as:

Step a)

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR

>> The fundamental frequency of the EUT is 2405-2480MHz,  
the test separation distance is  $\leq 50$ mm.  
(Manufacturer specified the separation distance is: 20mm)

Step b)

>> Numeric threshold (2405MHz),  $\text{mW} / 20\text{mm} * \sqrt{2.402\text{GHz}} \leq 3.0$   
Numeric threshold (2405MHz)  $\leq 38.713\text{mW}$

>> Numeric threshold (2445MHz),  $\text{mW} / 20\text{mm} * \sqrt{2.440\text{GHz}} \leq 3.0$   
Numeric threshold (2445MHz)  $\leq 38.411\text{mW}$


>> Numeric threshold (2480MHz),  $\text{mW} / 20\text{mm} * \sqrt{2.480\text{GHz}} \leq 3.0$   
Numeric threshold (2480MHz)  $\leq 38.100\text{mW}$

>> The power (measured + tune up tolerance) of EUT at 2405MHz is:  $-1.60\text{dBm} = 0.692\text{mW}$   
The power (measured + tune up tolerance) of EUT at 2445MHz is:  $-2.42\text{dBm} = 0.573\text{mW}$   
The power (measured + tune up tolerance) of EUT at 2480MHz is:  $-1.76\text{dBm} = 0.667\text{mW}$

Which is smaller than the Numeric threshold.


Therefore, the device is exempt from stand-alone SAR test requirements.

Reviewed by:



Eric LI  
EMC Project Manager

Prepared by:

Hosea CHAN  
EMC Project Engineer