

**RF Exposure**

The equipment under test (EUT) is a Gaming Speaker Set with BT 5.3 EDR function operating in 2402-2480MHz. The EUT is powered by DC 5V. For more detail information pls. refer to the user manual.

**Standalone SAR evaluation for BT function**

Bluetooth Version: V5.3 EDR

Antenna Type: Integral antenna

Antenna Gain: -0.58 dBi max

Modulation Type: GFSK,  $\pi/4$  -DQPSK and 8-DPSK

The nominal conducted output power specified: -0.5dBm (+/-1dB).

The nominal radiated output power (e.i.r.p) specified: -1.08dBm (+/- 1dB).

The maximum conducted output power for the EUT is 0.25dBm in the frequency 2480MHz which is within the production variation.

The minimum conducted output power for the EUT is -1.05dBm in the frequency 2402MHz which is within the production variation.

According to FCC Part 2.1091, this unlicensed transmitting devices is categorically excluded from routine environmental evaluation for RF exposure prior to equipment authorization or use, According to the KDB 447498 and OET 65, the simple calculation as below:

The source-based time averaged maximum radiated power = -0.5dBm+1dB  
= 0.5dBm = 1.122mW

At the distance (R) of 20cm to 40cm and in 0.3 GHz to 6 GHz, MPE Exclusion Threshold Level:

$$P_{th} \text{ (mW)} = ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

The MPE limit is 3060mW for general population and uncontrolled exposure in the 2.4GHz frequency range according to FCC Part 1.1307. As the measured power density at 20cm from the transmitter is lower than the MPE limit, the compliance to the MPE limit can be ensured by indicating the minimum 20cm separation between the transmitter's radiating structure and body of the user or nearby persons.