

RF Exposure Report

Report No.: SABCIB-WTW-P22010514

FCC ID: 2AA3N-TTR03

Test Model: PLTN-TTR01-3

Received Date: Jan. 14, 2022

Test Date: Jan. 28 ~ Apr. 28, 2022

Issued Date: May 19, 2022

Applicant: Peloton Interactive Inc.

Address: 125 W 25th Street, 11th Floor, New York, NY, 10001, USA

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

Lin Kou Laboratories

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

Test Location: No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City

33383, TAIWAN

FCC Registration / 788550 / TW0003

Designation Number:





This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth ourfindings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.

Report No.: SABCIB-WTW-P22010514 Page No. 1 / 6 Report Format Version: 6.1.1



Table of Contents

Relea	se Control Record	. 3
1	Certificate of Conformity	. 4
2	RF Exposure	. 4
2.2	Limits for Maximum Permissible Exposure (MPE)	. 5
3	Calculation Result of Maximum Conducted Power	. 5



Release Control Record

Issue No.	Description	Date Issued
SABCIB-WTW-P22010514	Original release	May 19, 2022



1 Certificate of Conformity

Product: Peloton Tablet

Brand: PELOTON

Test Model: PLTN-TTR01-3

Sample Status: Engineering sample

Applicant: Peloton Interactive Inc.

Test Date: Jan. 28 ~ Apr. 28, 2022

Standards: FCC Part 2 (Section 2.1091)

References Test KDB 447498 D01 General RF Exposure Guidance v06

Guidance:

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

Prepared by : _______, Date: _______, May 19, 2022

Polly Chien / Specialist

Approved by: , Date: May 19, 2022

Jeremy Lin / Project Engineer



2 RF Exposure

2.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Magnetic Field Strength (V/m) Strength (A/m)		Power Density (mW/cm²)	Average Time (minutes)		
Limits For General Population / Uncontrolled Exposure						
300-1500			F/1500	30		
1500-100,000			1.0	30		

F = Frequency in MHz

2.2 MPE Calculation Formula

 $Pd = (Pout*G) / (4*pi*r^2)$

where

Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

pi = 3.1416

r = distance between observation point and center of the radiator in cm

2.3 Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.

3 Calculation Result of Maximum Conducted Power

For WLAN and BT

Frequency Band (MHz)	Max. AV Power (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm²)	Limit (mW/cm²)		
	WLAN						
2412-2462	24.31	3.06	20	0.109	1		
5180-5240	20.26	4.51	20	0.060	1		
5260-5320	20.58	4.51	20	0.064	1		
5500-5700	23.91	4.51	20	0.138	1		
5745-5825	26.42	4.51	20	0.246	1		
ВТ							
2402-2480	13.17	-0.19	20	0.004	1		
BT LE							
2402-2480	5.48	-0.19	20	0.001	1		

Note:

2.4GHz: Directional Gain = $10 \log[(10^{G1/20} + 10^{G2/20} + \cdots + 10^{GN/20})^2/2] = 3.06dBi$ 5GHz: Directional Gain = $10 \log[(10^{G1/20} + 10^{G2/20} + \cdots + 10^{GN/20})^2/2] = 4.51dBi$

Report No.: SABCIB-WTW-P22010514 Page No. 5 / 6 Report Format Version: 6.1.1



For ANT+

Frequency Band		Electric field	EIRP Power	Power Density	Limit
(MHz)		(dBuV/m) @0.2m	(dBm)	(mW/cm²)	(mW/cm²)
2402-2480	73.33	96.85	-21.901	0.000001	1

Note:

- 1. $73.33 + 20\log(3/0.2) = 96.85dBuV/m$
- 2. Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

Conclusion:

The formula of calculated the MPE is:

CPD1 / LPD1 + CPD2 / LPD2 +etc. < 1

CPD = Calculation power density

LPD = Limit of power density

WLAN 2.4G + WLAN 5G = 0.109 / 1 + 0.246 / 1 = 0.355

WLAN 5G + BT = 0.246 / 1 + 0.004 / 1 = 0.250

WLAN 5G + ANT+ = 0.246 / 1 + 0.000001 / 1 = 0.246001

Therefore the maximum calculations of above situations are less than the "1" limit.

---END---