



MET Laboratories, Inc. *Safety Certification - EMI - Telecom Environmental Simulation*

914 WEST PATAPSCO AVENUE • BALTIMORE, MARYLAND 21230-3432 • PHONE (410) 354-3300 • FAX (410) 354-3313

33439 WESTERN AVENUE • UNION CITY, CALIFORNIA 94587 • PHONE (510) 489-6300 • FAX (510) 489-6372

3162 BELICK STREET • SANTA CLARA, CA 95054 • PHONE (408) 748-3585 • FAX (510) 489-6372

13301 MCCALLEN PASS • AUSTIN, TEXAS 78753 • PHONE (512) 287-2500 • FAX (512) 287-2513

December 13, 2013

Blacksumac, Inc.
126 York Street Suite 400
Ottawa, ON Canada K1N 5T5

Dear Heather McIntosh,

Enclosed is the EMC Wireless test report for compliance testing of the Blacksumac, Inc., Piper as tested to the requirements of Title 47 of the CFR, Ch. 1 (10-1-06 ed.), Part 15, Subpart B and ICES-003, Issue 5 August 2012 for a Class B Digital Device, and FCC Part 15 Subpart C and RSS-210, Issue 8, Dec. 2010 for Intentional Radiators.

Thank you for using the services of MET Laboratories, Inc. If you have any questions regarding these results or if MET can be of further service to you, please feel free to contact me.

Sincerely yours,
MET LABORATORIES, INC.

Jennifer Warnell
Documentation Department

Reference: (\Blacksumac, Inc.\EMC39564-FCC247 Rev. 1)

Certificates and reports shall not be reproduced except in full, without the written permission of MET Laboratories, Inc.

Electromagnetic Compatibility Criteria Test Report

for the

**Blacksumac, Inc.
Piper**

Tested under
the FCC Certification Rules
contained in
Title 47 of the CFR, Parts 15 Subpart B & ICES-003
for Class B Digital Devices
&
15.247 Subpart C & RSS-210, Issue 8, Dec. 2010
for Intentional Radiators

MET Report: EMC39564-FCC247 Rev. 1

December 13, 2013

Prepared For:

**Blacksumac, Inc.
126 York Street Suite 400
Ottawa, ON Canada K1N 5T5**

Prepared By:
MET Laboratories, Inc.
914 W. Patapsco Ave.
Baltimore, MD 21230

Electromagnetic Compatibility Criteria Test Report

for the

**Blacksumac, Inc.
Piper**

Tested under
the FCC Certification Rules
contained in
Title 47 of the CFR, Parts 15 Subpart B & ICES-003
for Class B Digital Devices
&
15.247 Subpart C & RSS-210, Issue 8, Dec. 2010
for Intentional Radiators



Benjamin Taylor, Project Engineer
Electromagnetic Compatibility Lab



Jennifer Warnell
Documentation Department

Engineering Statement: The measurements shown in this report were made in accordance with the procedures indicated, and the emissions from this equipment were found to be within the limits applicable. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them. It is further stated that upon the basis of the measurements made, the equipment tested is capable of operation in accordance with the requirements of the FCC Rules Parts 15B, 15.247 and Industry Canada standards ICES-003, Issue 5 August 2012, RSS-210, Issue 8, Dec. 2010 under normal use and maintenance.



Asad Bajwa,
Director, Electromagnetic Compatibility Lab

Report Status Sheet

Revision	Report Date	Reason for Revision
∅	November 7, 2013	Initial Issue.
1	December 13, 2013	Revised to reflect engineer corrections.

Table of Contents

I.	Executive Summary	1
	A. Purpose of Test	2
	B. Executive Summary	2
II.	Equipment Configuration	3
	A. Overview	4
	B. References	5
	C. Test Site	5
	D. Description of Test Sample	5
	E. Equipment Configuration	6
	F. Support Equipment	6
	G. Mode of Operation	7
	H. Method of Monitoring EUT Operation	7
	I. Modifications	7
	a) Modifications to EUT	7
	b) Modifications to Test Standard	7
	J. Disposition of EUT	7
III.	Electromagnetic Compatibility Criteria for Unintentional Radiators	8
	§ 15.107(a) Conducted Emissions Limits	9
	§ 15.109(a) Radiated Emissions Limits	13
IV.	Electromagnetic Compatibility Criteria for Intentional Radiators	17
	§ 15.203 Antenna Requirement	18
	§ 15.207(a) Conducted Emissions Limits	19
	§ 15.247(a)(a) 6 dB and 99% Bandwidth	23
	§ 15.247(b) Peak Power Output	31
	§ 15.247(d) Radiated Spurious Emissions Requirements and Band Edge	36
	§ 15.247(d) RF Conducted Spurious Emissions Requirements and Band Edge	63
	§ 15.247(e) Peak Power Spectral Density	67
	§ 15.247(i) Maximum Permissible Exposure	78
V.	Test Equipment	79
VI.	Certification & User's Manual Information	81
	A. Certification Information	82
	B. Label and User's Manual Information	86
VII.	ICES-003 Procedural & Labeling Requirements	88

List of Tables

Table 1. Executive Summary of EMC Part 15.247 Compliance Testing	2
Table 2. EUT Summary Table.....	4
Table 3. References	5
Table 4. Equipment Configuration	6
Table 5. Support Equipment.....	6
Table 6. Conducted Limits for Radio Frequency Devices calculated from FCC Part 15 Subsections 15.107(a) (b).....	9
Table 7. Conducted Emissions - Voltage, AC Power, Phase Line (120 VAC, 60 Hz).....	10
Table 8. Conducted Emissions - Voltage, AC Power, Neutral Line (120 VAC, 60 Hz).....	11
Table 9. Radiated Emissions Limits calculated from FCC Part 15, §15.109 (a) (b)	13
Table 10. Radiated Emissions Limits, Test Results, 30 MHz – 1 GHz, FCC Limits	14
Table 11. Radiated Emissions Limits, Test Results, ICES-003 Limits	15
Table 12. Conducted Limits for Intentional Radiators from FCC Part 15 § 15.207(a)	19
Table 13. Conducted Emissions, 15.207(a), Phase Line, Test Results	20
Table 14. Conducted Emissions, 15.207(a), Neutral Line, Test Results	21
Table 15. 6 dB Occupied Bandwidth, Test Results	24
Table 16. 99% Occupied Bandwidth, Test Results	24
Table 17. Output Power Requirements from §15.247(b)	31
Table 18. Peak Power Output, Test Results	32
Table 19. Restricted Bands of Operation.....	36
Table 20. Radiated Emissions Limits Calculated from FCC Part 15, § 15.209 (a)	37
Table 21. Peak Power Spectral Density, Test Results	68
Table 22. Test Equipment List	80

List of Plots

Plot 1. Conducted Emission, Phase Line Plot	10
Plot 2. Conducted Emission, Neutral Line Plot.....	11
Plot 3. Radiated Emissions, 30 MHz - 1 GHz, FCC Limits	14
Plot 4. Radiated Emissions, ICES-003 Limits.....	15
Plot 5. Conducted Emissions, 15.207, Phase Line	20
Plot 6. Conducted Emissions, 15.207, Neutral Line.....	21
Plot 7. 6 dB Occupied Bandwidth, Low Channel, 802.11b.....	25
Plot 8. 6 dB Occupied Bandwidth, Mid Channel, 802.11b	25
Plot 9. 6 dB Occupied Bandwidth, High Channel, 802.11b	25
Plot 10. 6 dB Occupied Bandwidth, Low Channel, 802.11g.....	26
Plot 11. 6 dB Occupied Bandwidth, Mid Channel, 802.11g	26
Plot 12. 6 dB Occupied Bandwidth, High Channel, 802.11g	26
Plot 13. 6 dB Occupied Bandwidth, Low Channel, 802.11n.....	27
Plot 14. 6 dB Occupied Bandwidth, Mid Channel, 802.11n	27
Plot 15. 6 dB Occupied Bandwidth, High Channel, 802.11n	27
Plot 16. 99% Occupied Bandwidth, Low Channel, 802.11b	28
Plot 17. 99% Occupied Bandwidth, Mid Channel, 802.11b.....	28
Plot 18. 99% Occupied Bandwidth, High Channel, 802.11b	28
Plot 19. 99% Occupied Bandwidth, Low Channel, 802.11g	29
Plot 20. 99% Occupied Bandwidth, Mid Channel, 802.11g.....	29
Plot 21. 99% Occupied Bandwidth, High Channel, 802.11g	29
Plot 22. 99% Occupied Bandwidth, Low Channel, 802.11n	30
Plot 23. 99% Occupied Bandwidth, Mid Channel, 802.11n.....	30
Plot 24. 99% Occupied Bandwidth, High Channel, 802.11n	30
Plot 25. Peak Power Output, Low Channel, 802.11b	33

Plot 26. Peak Power Output, Mid Channel, 802.11b.....	33
Plot 27. Peak Power Output, High Channel, 802.11b	33
Plot 28. Peak Power Output, Low Channel, 802.11g.....	34
Plot 29. Peak Power Output, Mid Channel, 802.11g.....	34
Plot 30. Peak Power Output, High Channel, 802.11g	34
Plot 31. Peak Power Output, Low Channel, 802.11n.....	35
Plot 32. Peak Power Output, Mid Channel, 802.11n.....	35
Plot 33. Peak Power Output, High Channel, 802.11n	35
Plot 34. Radiated Spurious Emissions, Low Channel, 802.11b, 30 MHz – 1 GHz.....	38
Plot 35. Radiated Spurious Emissions, Low Channel, 802.11b, 1 GHz – 18 GHz, Peak under Average	38
Plot 36. Radiated Spurious Emissions, Low Channel, 802.11b, 1 GHz – 18 GHz, 7237 MHz, Average	38
Plot 37. Radiated Spurious Emissions, Mid Channel, 802.11b, 30 MHz – 1 GHz.....	39
Plot 38. Radiated Spurious Emissions, Mid Channel, 802.11b, 1 GHz – 18 GHz, Peak under Average	39
Plot 39. Radiated Spurious Emissions, High Channel, 802.11b, 30 MHz – 1 GHz	40
Plot 40. Radiated Spurious Emissions, High Channel, 802.11b, 1 GHz – 18 GHz, Peak under Average.....	40
Plot 41. Radiated Spurious Emissions, Low Channel, 802.11g, 30 MHz – 1 GHz.....	41
Plot 42. Radiated Spurious Emissions, Low Channel, 802.11g, 1 GHz – 18 GHz, Peak under Average	41
Plot 43. Radiated Spurious Emissions, Mid Channel, 802.11g, 30 MHz – 1 GHz.....	42
Plot 44. Radiated Spurious Emissions, Mid Channel, 802.11g, 1 GHz – 18 GHz, Peak under Average	42
Plot 45. Radiated Spurious Emissions, High Channel, 802.11g, 30 MHz – 1 GHz	43
Plot 46. Radiated Spurious Emissions, High Channel, 802.11g, 1 GHz – 18 GHz, Peak under Average.....	43
Plot 47. Radiated Spurious Emissions, Low Channel, 802.11n, 30 MHz – 1 GHz.....	44
Plot 48. Radiated Spurious Emissions, Low Channel, 802.11n, 1 GHz – 18 GHz, Peak under Average	44
Plot 49. Radiated Spurious Emissions, Mid Channel, 802.11n, 30 MHz – 1 GHz.....	45
Plot 50. Radiated Spurious Emissions, Mid Channel, 802.11n, 1 GHz – 18 GHz, Peak under Average	45
Plot 51. Radiated Spurious Emissions, High Channel, 802.11n, 30 MHz – 1 GHz	46
Plot 52. Radiated Spurious Emissions, High Channel, 802.11n, 1 GHz – 18 GHz, Peak under Average.....	46
Plot 52. Radiated Band Edge, Low Channel, 802.11b, Peak.....	47
Plot 52. Radiated Band Edge, Low Channel, 802.11b, Average.....	47
Plot 52. Radiated Band Edge, High Channel, 802.11b, Peak.....	48
Plot 52. Radiated Band Edge, High Channel, 802.11b, Average	48
Plot 52. Radiated Band Edge, Low Channel, 802.11g, Peak.....	49
Plot 52. Radiated Band Edge, Low Channel, 802.11g, Average.....	49
Plot 52. Radiated Band Edge, High Channel, 802.11g, Peak.....	50
Plot 52. Radiated Band Edge, High Channel, 802.11g, Average	50
Plot 52. Radiated Band Edge, Low Channel, 802.11n, Peak.....	51
Plot 52. Radiated Band Edge, Low Channel, 802.11n, Average.....	51
Plot 52. Radiated Band Edge, High Channel, 802.11n, Peak	52
Plot 52. Radiated Band Edge, High Channel, 802.11n, Average	52
Plot 53. Radiated Spurious Emissions, Low Channel, 802.11b, 30 MHz – 1 GHz, 900 MHz TX.....	53
Plot 54. Radiated Spurious Emissions, Low Channel, 802.11b, 1 GHz – 18 GHz, 900 MHz TX	53
Plot 55. Radiated Spurious Emissions, Mid Channel, 802.11b, 30 MHz – 1 GHz, 900 MHz TX	54
Plot 56. Radiated Spurious Emissions, Mid Channel, 802.11b, 1 GHz – 18 GHz, 900 MHz TX.....	54
Plot 57. Radiated Spurious Emissions, High Channel, 802.11b, 30 MHz – 1 GHz, 900 MHz TX	55
Plot 58. Radiated Spurious Emissions, High Channel, 802.11b, 1 GHz – 18 GHz, 900 MHz TX.....	55
Plot 59. Radiated Spurious Emissions, Low Channel, 802.11g, 30 MHz – 1 GHz, 900 MHz TX.....	56
Plot 60. Radiated Spurious Emissions, Low Channel, 802.11g, 1 GHz – 18 GHz, 900 MHz TX	56
Plot 61. Radiated Spurious Emissions, Mid Channel, 802.11g, 30 MHz – 1 GHz, 900 MHz TX	57
Plot 62. Radiated Spurious Emissions, Mid Channel, 802.11g, 1 GHz – 18 GHz, 900 MHz TX.....	57
Plot 63. Radiated Spurious Emissions, High Channel, 802.11g, 30 MHz – 1 GHz, 900 MHz TX	58
Plot 64. Radiated Spurious Emissions, High Channel, 802.11g, 1 GHz – 18 GHz, 900 MHz TX.....	58
Plot 65. Radiated Spurious Emissions, Low Channel, 802.11n, 30 MHz – 1 GHz, 900 MHz TX.....	59
Plot 66. Radiated Spurious Emissions, Low Channel, 802.11n, 1 GHz – 18 GHz, 900 MHz TX	59

Plot 67. Radiated Spurious Emissions, Mid Channel, 802.11n, 30 MHz – 1 GHz, 900 MHz TX	60
Plot 68. Radiated Spurious Emissions, Mid Channel, 802.11n, 1 GHz – 18 GHz, 900 MHz TX.....	60
Plot 69. Radiated Spurious Emissions, High Channel, 802.11n, 30 MHz – 1 GHz, 900 MHz TX.....	61
Plot 70. Radiated Spurious Emissions, High Channel, 802.11n, 1 GHz – 18 GHz, 900 MHz TX.....	61
Plot 71. Conducted Spurious Emissions, Low Channel, 802.11b, 30 MHz – 26 GHz.....	64
Plot 72. Conducted Spurious Emissions, Mid Channel, 802.11b, 30 MHz – 26 GHz.....	64
Plot 73. Conducted Spurious Emissions, High Channel, 802.11b, 30 MHz – 26 GHz	64
Plot 74. Conducted Spurious Emissions, Low Channel, 802.11g, 30 MHz – 26 GHz.....	65
Plot 75. Conducted Spurious Emissions, Mid Channel, 802.11g, 30 MHz – 26 GHz.....	65
Plot 76. Conducted Spurious Emissions, High Channel, 802.11g, 30 MHz – 26 GHz	65
Plot 77. Conducted Spurious Emissions, Low Channel, 802.11n, 30 MHz – 26 GHz.....	66
Plot 78. Conducted Spurious Emissions, Mid Channel, 802.11n, 30 MHz – 26 GHz.....	66
Plot 79. Conducted Spurious Emissions, High Channel, 802.11n, 30 MHz – 26 GHz	66
Plot 80. Peak Power Spectral Density, Low Channel, 802.11b, Peak Search	69
Plot 81. Peak Power Spectral Density, Low Channel, 802.11b.....	69
Plot 82. Peak Power Spectral Density, Mid Channel, 802.11b, Peak Search.....	70
Plot 83. Peak Power Spectral Density, Mid Channel, 802.11b	70
Plot 84. Peak Power Spectral Density, High Channel, 802.11b, Peak Search.....	71
Plot 85. Peak Power Spectral Density, High Channel, 802.11b	71
Plot 86. Peak Power Spectral Density, Low Channel, 802.11g, Peak Search	72
Plot 87. Peak Power Spectral Density, Low Channel, 802.11g.....	72
Plot 88. Peak Power Spectral Density, Mid Channel, 802.11g, Peak Search.....	73
Plot 89. Peak Power Spectral Density, Mid Channel, 802.11g	73
Plot 90. Peak Power Spectral Density, High Channel, 802.11g, Peak Search.....	74
Plot 91. Peak Power Spectral Density, High Channel, 802.11g	74
Plot 92. Peak Power Spectral Density, Low Channel, 802.11n, Peak Search	75
Plot 93. Peak Power Spectral Density, Low Channel, 802.11n.....	75
Plot 94. Peak Power Spectral Density, Mid Channel, 802.11n, Peak Search.....	76
Plot 95. Peak Power Spectral Density, Mid Channel, 802.11n	76
Plot 96. Peak Power Spectral Density, High Channel, 802.11n, Peak Search.....	77
Plot 97. Peak Power Spectral Density, High Channel, 802.11n	77

List of Figures

Figure 2. Block Diagram, Occupied Bandwidth Test Setup.....	23
Figure 3. Peak Power Output Test Setup.....	31
Figure 4. Block Diagram, Conducted Spurious Emissions Test Setup.....	63
Figure 5. Block Diagram, Peak Power Spectral Density Test Setup	67

List of Photographs

Photograph 1. Blacksumac, Inc. Piper.....	6
Photograph 2. Conducted Emissions, Test Setup	12
Photograph 3. Radiated Emissions, Test Setup	16
Photograph 4. Conducted Emissions, 15.207, Test Setup	22
Photograph 5. Radiated Spurious Emissions, Test Setup, 30 MHz – 1 GHz.....	62
Photograph 6. Radiated Spurious Emissions, Test Setup, Above 1 GHz.....	62

List of Terms and Abbreviations

AC	Alternating Current
ACF	Antenna Correction Factor
Cal	Calibration
<i>d</i>	Measurement Distance
dB	Decibels
dB μ A	Decibels above one microamp
dB μ V	Decibels above one microvolt
dB μ A/m	Decibels above one microamp per meter
dB μ V/m	Decibels above one microvolt per meter
DC	Direct Current
E	Electric Field
DSL	Digital Subscriber Line
ESD	Electrostatic Discharge
EUT	Equipment Under Test
<i>f</i>	Frequency
FCC	Federal Communications Commission
GRP	Ground Reference Plane
H	Magnetic Field
HCP	Horizontal Coupling Plane
Hz	Hertz
IEC	International Electrotechnical Commission
kHz	kilohertz
kPa	kilopascal
kV	kilovolt
LISN	Line Impedance Stabilization Network
MHz	Megahertz
μ H	microhenry
μ	microfarad
μ s	microseconds
NEBS	Network Equipment-Building System
PRF	Pulse Repetition Frequency
RF	Radio Frequency
RMS	Root-Mean-Square
TWT	Traveling Wave Tube
V/m	Volts per meter
VCP	Vertical Coupling Plane

I. Executive Summary

A. Purpose of Test

An EMC evaluation was performed to determine compliance of the Blacksumac, Inc. Piper, with the requirements of Part 15, §15.247. All references are to the most current version of Title 47 of the Code of Federal Regulations in effect. In accordance with §2.1033, the following data is presented in support of the Certification of the Piper. Blacksumac, Inc. should retain a copy of this document which should be kept on file for at least two years after the manufacturing of the Piper, has been **permanently** discontinued.

B. Executive Summary

The following tests were conducted on a sample of the equipment for the purpose of demonstrating compliance with Part 15, §15.247, in accordance with Blacksumac, Inc., purchase order number 9BLA2711R2. All tests were conducted using measurement procedure ANSI C63.4-2003.

FCC Reference 47 CFR Part 15.247:2005	IC Reference RSS-210 Issue 8: 2010; RSS-GEN Issue 3: 2010	Description	Compliance
47 CFR Part 15.107 (a)	ICES-003 Issue 5 August 2012	Conducted Emission Limits for a Class B Digital Device	Compliant
47 CFR Part 15.109 (a)	ICES-003 Issue 5 August 2012	Radiated Emission Limits for a Class B Digital Device	Compliant
Title 47 of the CFR, Part 15 §15.203	N/A	Antenna Requirement	Compliant
Title 47 of the CFR, Part 15 §15.207(a)	RSS-GEN (7.2.4)	Conducted Emission Limits	Compliant
Title 47 of the CFR, Part 15 §15.247(a)(2)	RSS-Gen(4.6)	6dB Occupied Bandwidth	Compliant
		99% Occupied Bandwidth	Compliant
Title 47 of the CFR, Part 15 §15.247(b)	RSS-210(A8.4)	Peak Power Output	Compliant
Title 47 of the CFR, Part 15 §15.247(d); §15.209; §15.205	RSS-210(A8.5)	Radiated Spurious Emissions Requirements	Compliant
Title 47 of the CFR, Part 15 §15.247(d)	RSS-210(A8.5)	RF Conducted Spurious Emissions Requirements	Compliant
Title 47 of the CFR, Part 15 §15.247(d)	RSS-210(A8.5)	RF Conducted Band Edge	Not Applicable
Title 47 of the CFR, Part 15; §15.247(e)	RSS-210(A8.2)	Peak Power Spectral Density	Compliant
Title 47 of the CFR, Part 15 §15.247(i)	RSS-Gen(5.6)	Maximum Permissible Exposure (MPE)	Compliant

Table 1. Executive Summary of EMC Part 15.247 Compliance Testing

II. Equipment Configuration

A. Overview

MET Laboratories, Inc. was contracted by Blacksumac, Inc. to perform testing on the Piper, under Blacksumac, Inc.'s purchase order number 9BLA2711R2.

This document describes the test setups, test methods, required test equipment, and the test limit criteria used to perform compliance testing of the Blacksumac, Inc., Piper.

The results obtained relate only to the item(s) tested.

Model(s) Tested:	Piper	
Model(s) Covered:	Piper	
EUT Specifications:	Primary Power: 120 VAC, 60 Hz	
	FCC ID: 2AA5P-P10A001 IC: 11477A-P10A001	
	Type of Modulations:	DSSS and OFDM
	Equipment Code:	DTS
	Peak RF Output Power:	-14.39dBm
	EUT Frequency Ranges:	2412 – 2462 MHz
Analysis:	The results obtained relate only to the item(s) tested.	
Environmental Test Conditions:	Temperature: 15-35° C	
	Relative Humidity: 30-60%	
	Barometric Pressure: 860-1060 mbar	
Evaluated by:	Benjamin Taylor	
Report Date(s):	December 13, 2013	

Table 2. EUT Summary Table

B. References

CFR 47, Part 15, Subpart C	Federal Communication Commission, Code of Federal Regulations, Title 47, Part 15: General Rules and Regulations, Allocation, Assignment, and Use of Radio Frequencies
CFR 47, Part 15, Subpart B	Electromagnetic Compatibility: Criteria for Radio Frequency Devices
RSS-210, Issue 8, Dec. 2010	Low-power Licence-exempt Radiocommunications Devices (All Frequency Bands): Category I Equipment
RSS-GEN, Issue 3, Dec. 2010	General Requirements and Information for the Certification of Radio Apparatus
ICES-003, Issue 5 August 2012	Information Technology Equipment (ITE) — Limits and methods of measurement
ANSI C63.4:2003	Methods and Measurements of Radio-Noise Emissions from Low-Voltage Electrical And Electronic Equipment in the Range of 9 kHz to 40 GHz
ISO/IEC 17025:2005	General Requirements for the Competence of Testing and Calibration Laboratories
ANSI C63.10-2009	American National Standard for Testing Unlicensed Wireless Devices

Table 3. References

C. Test Site

All testing was performed at MET Laboratories, Inc., 914 W. Patapsco Ave., Baltimore, MD 21230. All equipment used in making physical determinations is accurate and bears recent traceability to the National Institute of Standards and Technology.

Radiated Emissions measurements were performed in a 3 meter semi-anechoic chamber (equivalent to an Open Area Test Site). In accordance with §2.948(a)(3), a complete site description is contained at MET Laboratories.

D. Description of Test Sample

The Blacksumac, Inc. Piper, Equipment Under Test (EUT), is a consumer electronic device that monitors a user's home. It can sit on a table or be mounted to a wall. It connects to the user's home Wi-Fi network and can be controlled via an app on the user's smart phone. Piper also has a z-wave radio to control z-wave home automation devices, if the user chooses. Piper has a battery backup (3xAAA) for power outages.



Photograph 1. Blacksumac, Inc. Piper

E. Equipment Configuration

Ref. ID	Name / Description	Model Number	Part Number	Serial Number	Revision
1	Piper in Enclosure	71-00007	71-00007	BLSCT132800073	0.07
2	AC adaptor	WSU050-1500	--	1	--
3	Piper –no enclosure - with semi-rigid coax	71-00007	71-00007	BLSCT132800036	0.07

Table 4. Equipment Configuration

F. Support Equipment

Support equipment necessary for the operation and testing of the EUT is included in the following list.

Ref. ID	Name / Description	Manufacturer	Model Number
4	USB to Serial Cable	--	--
5	AC adaptor – extra for backup	Triad	WSU050-1500
6	Printed user documentation	Blacksumac	N/A
4	USB to Serial Cable (backup)	--	--

Table 5. Support Equipment

G. Mode of Operation

1. All radios off
2. Z-wave transmitting at 908.4MHz, Wi-Fi off
3. Z-wave transmitting at 908.4MHz + Wi-Fi transmitting
4. Wi-Fi transmitting

H. Method of Monitoring EUT Operation

1. If the LED on Piper is ON, the device is powered and working. An antenna and spectrum analyzer is used to confirm Piper is transmitting on the correct channels.
2. If the LED on Piper of OFF, the device is not powered and not working.

I. Modifications

a) Modifications to EUT

Added an L-C filter at the output of a D-class audio amp.
Routing speaker wire in proper wire routing channel in the enclosure.

b) Modifications to Test Standard

No modifications were made to the test standard.

J. Disposition of EUT

The test sample including all support equipment submitted to the Electro-Magnetic Compatibility Lab for testing was returned to Blacksumac, Inc. upon completion of testing.

III. Electromagnetic Compatibility Criteria for Unintentional Radiators

Electromagnetic Compatibility Criteria

§ 15.107 Conducted Emissions Limits

Test Requirement(s): **15.107 (a)** Except for Class A digital devices, for equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in Table 6. Compliance with this provision shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminals.

15.107 (b) For a Class A digital device that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in Table 6. Compliance with this provision shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminals. The lower limit applies at the band edges.

Frequency range (MHz)	Class A Conducted Limits (dB μ V)		*Class B Conducted Limits (dB μ V)	
	Quasi-Peak	Average	Quasi-Peak	Average
* 0.15- 0.45	79	66	66 - 56	56 - 46
0.45 - 0.5	79	66	56	46
0.5 - 30	73	60	60	50

Note 1 — The lower limit shall apply at the transition frequencies.
Note 2 — The limit decreases linearly with the logarithm if the frequency in the range 0.15 MHz to 0.5 MHz.

Table 6. Conducted Limits for Radio Frequency Devices calculated from FCC Part 15 Subsections 15.107(a) (b)

Test Procedures: The EUT was placed on a non-metallic table, 80 cm above the ground plane and 40 cm from a vertical ground plane. The method of testing, test conditions, and test procedures of ANSI C63.4 were used. The EUT was powered through a 50 Ω /50 μ H LISN. An EMI receiver, connected to the measurement port of the LISN, scanned the frequency range from 150 kHz to 30 MHz in order to find the peak conducted emissions. All peak emissions within 6 dB of the limit were re-measured using a quasi-peak and/or average detector as appropriate.

Test Results: The EUT was compliant with the Class B requirement(s) of this section. Measured emissions were below applicable limits.


Test Engineer(s): Surinder Singh

Test Date(s): 06/05/13

Conducted Emissions - Voltage, AC Power, Phase Line (120 VAC, 60 Hz)

Frequency (MHz)	Uncorrected Meter Reading (dBμV) QP	Cable Loss (dB)	Corrected Measurement (dBμV) QP	Limit (dBμV) QP	Margin (dB) QP	Uncorrected Meter Reading (dBμV) Avg.	Cable Loss (dB)	Corrected Measurement (dBμV) AVG	Limit (dBμV) AVG	Margin (dB) AVG
0.399	16.89	0	16.89	57.87	-40.98	4.82	0	4.82	47.87	-43.05
0.677	18.37	0	18.37	56	-37.63	4.41	0	4.41	46	-41.59
0.804	21.49	0	21.49	56	-34.51	7.11	0	7.11	46	-38.89
1.946	16.11	0	16.11	56	-39.89	3.29	0	3.29	46	-42.71
4.633	12.66	0	12.66	56	-43.34	2.74	0	2.74	46	-43.26
19.22	15.38	0	15.38	60	-44.62	2.47	0	2.47	50	-47.53

Table 7. Conducted Emissions - Voltage, AC Power, Phase Line (120 VAC, 60 Hz)




Plot 1. Conducted Emission, Phase Line Plot

Conducted Emissions - Voltage, AC Power, Neutral Line (120 VAC, 60 Hz)

Frequency (MHz)	Uncorrected Meter Reading (dBμV) QP	Cable Loss (dB)	Corrected Measurement (dBμV) QP	Limit (dBμV) QP	Margin (dB) QP	Uncorrected Meter Reading (dBμV) Avg.	Cable Loss (dB)	Corrected Measurement (dBμV) AVG	Limit (dBμV) AVG	Margin (dB) AVG
0.399	16.01	0	16.01	57.87	-41.86	3.6	0	3.6	47.87	-44.27
0.677	17.62	0	17.62	56	-38.38	4.013	0	4.013	46	-41.987
0.804	22.34	0	22.34	56	-33.66	6.407	0	6.407	46	-39.593
1.946	15.42	0	15.42	56	-40.58	3.152	0	3.152	46	-42.848
4.633	12.64	0	12.64	56	-43.36	2.222	0	2.222	46	-43.778
19.22	15.45	0	15.45	60	-44.55	2.987	0	2.987	50	-47.013

Table 8. Conducted Emissions - Voltage, AC Power, Neutral Line (120 VAC, 60 Hz)



Plot 2. Conducted Emission, Neutral Line Plot

Conducted Emission Limits Test Setup



Photograph 2. Conducted Emissions, Test Setup

Radiated Emission Limits

§ 15.109 Radiated Emissions Limits

Test Requirement(s): **15.109 (a)** Except for Class A digital devices, the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the Class B limits expressed in Table 9.

15.109 (b) The field strength of radiated emissions from a Class A digital device, as determined at a distance of 10 meters, shall not exceed the Class A limits expressed in Table 9.

Frequency (MHz)	Field Strength (dBµV/m)	
	§15.109 (b), Class A Limit (dBµV) @ 10m	§15.109 (a), Class B Limit (dBµV) @ 3m
30 - 88	39.00	40.00
88 - 216	43.50	43.50
216 - 960	46.40	46.00
Above 960	49.50	54.00

Table 9. Radiated Emissions Limits calculated from FCC Part 15, §15.109 (a) (b)

Test Procedures: The EUT was placed on a non-metallic table, 80 cm above the ground plane on the turntable inside a semi-anechoic chamber. The method of testing and test conditions of ANSI C63.4 were used. An antenna was located 3 m from the EUT on an adjustable mast. A pre-scan was first performed in order to find prominent radiated emissions. For final emissions measurements at each frequency of interest, the EUT was rotated and the antenna height was varied between 1 m and 4 m in order to maximize the emission. Measurements in both horizontal and vertical polarities were made and the data was recorded. Unless otherwise specified, measurements were made using a quasi-peak detector with a 120 kHz bandwidth.

Test Results: The EUT was compliant with the Class B requirement(s) of this section. Measured emissions were below applicable limits.


Test Engineer(s): Benjamin Taylor

Test Date(s): 10/02/13

Radiated Emissions Limits Test Results, Class B

Frequency (MHz)	EUT Azimuth (Degrees)	Antenna Polarity (H/V)	Antenna HEIGHT (m)	Uncorrected Amplitude (dBµV)	Antenna Correction Factor (dB) (+)	Cable Loss (dB) (+)	Distance Correction Factor (dB) (-)	Corrected Amplitude (dBµV/m)	Limit (dBµV/m)	Margin (dB)
46.855586	348	H	1.09	5.65	9.89	0.46	0.00	16.00	40.00	-24.00
46.855586	359	V	1.06	10.41	9.89	0.46	0.00	20.76	40.00	-19.24
131.30261	331	H	1.08	5.72	13.77	0.92	0.00	20.41	43.50	-23.09
131.30261	317	V	1.11	6.34	13.77	0.92	0.00	21.03	43.50	-22.47
259.95992	290	H	1.04	5.72	12.80	1.32	0.00	19.84	46.00	-26.16
259.95992	304	V	1.08	7.36	12.80	1.32	0.00	21.48	46.00	-24.52
335.76152	270	H	1.08	5.18	14.82	1.33	0.00	21.33	46.00	-24.67
335.76152	282	V	1.05	5.65	14.82	1.33	0.00	21.80	46.00	-24.20
479.95029	172	H	1.05	6.71	17.90	1.82	0.00	26.43	46.00	-19.57
479.95029	172	V	1.02	15.16	17.90	1.82	0.00	34.88	46.00	-11.12
917.32841	210	H	1.09	6.23	23.10	2.81	0.00	32.14	46.00	-13.86
917.32841	196	V	1.12	6.30	23.10	2.81	0.00	32.21	46.00	-13.79

Table 10. Radiated Emissions Limits, Test Results, 30 MHz – 1 GHz, FCC Limits




Plot 3. Radiated Emissions, 30 MHz - 1 GHz, FCC Limits

Radiated Emissions Limits Test Results, Class B


Frequency (MHz)	EUT Azimuth (Degrees)	Antenna Polarity (H/V)	Antenna HEIGHT (m)	Uncorrected Amplitude (dB μ V)	Antenna Correction Factor (dB) (+)	Cable Loss (dB) (+)	Distance Correction Factor (dB) (-)	Corrected Amplitude (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
46.855586	348	H	1.09	5.65	9.89	0.46	10.46	5.54	30.00	-24.46
46.855586	359	V	1.06	10.41	9.89	0.46	10.46	10.30	30.00	-19.70
131.30261	331	H	1.08	5.72	13.77	0.92	10.46	9.95	30.00	-20.05
131.30261	317	V	1.11	6.34	13.77	0.92	10.46	10.57	30.00	-19.43
259.95992	290	H	1.04	5.72	12.80	1.32	10.46	9.38	37.00	-27.62
259.95992	304	V	1.08	7.36	12.80	1.32	10.46	11.02	37.00	-25.98
335.76152	270	H	1.08	5.18	14.82	1.33	10.46	10.87	37.00	-26.13
335.76152	282	V	1.05	5.65	14.82	1.33	10.46	11.34	37.00	-25.66
479.95029	172	H	1.05	6.71	17.90	1.82	10.46	15.97	37.00	-21.03
479.95029	172	V	1.02	15.16	17.90	1.82	10.46	24.42	37.00	-12.58
917.32841	210	H	1.09	6.23	23.10	2.81	10.46	21.68	37.00	-15.32
917.32841	196	V	1.12	6.30	23.10	2.81	10.46	21.75	37.00	-15.25

Table 11. Radiated Emissions Limits, Test Results, ICES-003 Limits



Plot 4. Radiated Emissions, ICES-003 Limits

Radiated Emissions Limits Test Setup



Photograph 3. Radiated Emissions, Test Setup

IV. Electromagnetic Compatibility Criteria for Intentional Radiators

Electromagnetic Compatibility Criteria for Intentional Radiators

§ 15.203 Antenna Requirement

Test Requirement: § 15.203: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

The structure and application of the EUT were analyzed to determine compliance with Section 15.203 of the Rules. Section 15.203 states that the subject device must meet at least one of the following criteria:

- a.) Antenna must be permanently attached to the unit.
- b.) Antenna must use a unique type of connector to attach to the EUT.
- c.) Unit must be professionally installed. Installer shall be responsible for verifying that the correct antenna is employed with the unit.

Results: The EUT as tested is compliant the criteria of §15.203. EUT contains an integral antenna.

Test Engineer(s): Benjamin Taylor

Test Date(s): 08/29/13

Electromagnetic Compatibility Criteria for Intentional Radiators

§ 15.207(a) Conducted Emissions Limits

Test Requirement(s): § 15.207 (a): For an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30MHz, shall not exceed the limits in the following table, as measured using a 50 μ H/50 Σ line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

Frequency range (MHz)	§ 15.207(a), Conducted Limit (dB μ V)	
	Quasi-Peak	Average
* 0.15- 0.45	66 - 56	56 - 46
0.45 - 0.5	56	46
0.5 - 30	60	50

Table 12. Conducted Limits for Intentional Radiators from FCC Part 15 § 15.207(a)

Test Procedure: The EUT was placed on a non-metallic table 80cm above ground plane and 40cm from a vertical ground plane. The EUT was powered from a 50 Ω /50 μ H Line Impedance Stabilization Network (LISN). The EMC receiver scanned the frequency range from 150 kHz to 30 MHz. Conducted Emissions measurements were made in accordance with *ANSI C63.4-2003 "Methods and Measurements of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9kHz to 40 GHz"*. The measurements were performed over the frequency range of 0.15 MHz to 30 MHz using a 50 Ω /50 μ H LISN as the input transducer to an EMC/field intensity meter. For the purpose of this testing, the transmitter was turned on. Scans were performed with the transmitter on.

Test Results: The EUT was compliant with this requirement.


Test Engineer(s): Benjamin Taylor

Test Date(s): 09/09/13

15.207(a) Conducted Emissions Test Results

Frequency (MHz)	Uncorrected Meter Reading (dBμV) QP	Cable Loss (dB)	Corrected Measurement (dBμV) QP	Limit (dBμV) QP	Margin (dB) QP	Uncorrected Meter Reading (dBμV) Avg.	Cable Loss (dB)	Corrected Measurement (dBμV) AVG	Limit (dBμV) AVG	Margin (dB) AVG
0.2024	54.57	0	54.57	63.51	-8.94	39.55	0	39.55	53.51	-13.96
0.404	50.52	0	50.52	57.77	-7.25	33.91	0	33.91	47.77	-13.86
0.5985	46.9	0	46.9	56	-9.1	27.08	0	27.08	46	-18.92
1.534	45.91	0	45.91	56	-10.09	29.45	0	29.45	46	-16.55
2.7	45.45	0	45.45	56	-10.55	25.87	0	25.87	46	-20.13

Table 13. Conducted Emissions, 15.207(a), Phase Line, Test Results




Plot 5. Conducted Emissions, 15.207, Phase Line

15.207(a) Conducted Emissions Test Results

Frequency (MHz)	Uncorrected Meter Reading (dBμV) QP	Cable Loss (dB)	Corrected Measurement (dBμV) QP	Limit (dBμV) QP	Margin (dB) QP	Uncorrected Meter Reading (dBμV) Avg.	Cable Loss (dB)	Corrected Measurement (dBμV) AVG	Limit (dBμV) AVG	Margin (dB) AVG
0.1994	53.89	0	53.89	63.64	-9.75	40.78	0	40.78	53.64	-12.86
0.4015	50.85	0	50.85	57.82	-6.97	38.67	0	38.67	47.82	-9.15
0.7686	47.38	0	47.38	56	-8.62	28.42	0	28.42	46	-17.58
1.4577	47.89	0	47.89	56	-8.11	30.19	0	30.19	46	-15.81
2.09	46.64	0	46.64	56	-9.36	30.5	0	30.5	46	-15.5

Table 14. Conducted Emissions, 15.207(a), Neutral Line, Test Results



Plot 6. Conducted Emissions, 15.207, Neutral Line

15.207(a) Conducted Emissions Test Setup Photo



Photograph 4. Conducted Emissions, 15.207, Test Setup

Electromagnetic Compatibility Criteria for Intentional Radiators

§ 15.247(a)(2) 6 dB and 99% Bandwidth

Test Requirements: § 15.247(a)(2): Operation under the provisions of this section is limited to frequency hopping and digitally modulated intentional radiators that comply with the following provisions:

For systems using digital modulation techniques, the EUT may operate in the 902-928 MHz, 2400-2483.5 MHz and 5725-5850 MHz bands. The minimum 6dB bandwidth shall be at least 500 kHz.

Test Procedure: The transmitter was on and transmitting at the highest output power. The bandwidth of the fundamental frequency was measured with the spectrum analyzer using a RBW approximately 1% of the total emission bandwidth, VBW > RBW. The 6 dB Bandwidth was measured and recorded. The measurements were performed on the low, mid and high channels.

Test Results The EUT was compliant with § 15.247 (a)(2).

The 6 dB and 99% Bandwidth was determined from the plots on the following pages.

Test Engineer(s): Benjamin Taylor

Test Date(s): 09/09/13




Figure 1. Block Diagram, Occupied Bandwidth Test Setup

Occupied Bandwidth Test Results


Occupied Bandwidth			
	Carrier Channel	Frequency (MHz)	Measured 6 dB Bandwidth (MHz)
802.11b	Low	2412	8.973
	Mid	2437	9.209
	High	2462	9.960
802.11g	Low	2412	16.084
	Mid	2437	16.461
	High	2462	16.495
802.11n	Low	2412	16.459
	Mid	2437	16.382
	High	2462	16.336

Table 15. 6 dB Occupied Bandwidth, Test Results


Occupied Bandwidth			
	Carrier Channel	Frequency (MHz)	Measured 99% Bandwidth (MHz)
802.11b	Low	2412	14.4674
	Mid	2437	15.5968
	High	2462	15.2499
802.11g	Low	2412	16.3894
	Mid	2437	16.5331
	High	2462	16.5387
802.11n	Low	2412	16.4621
	Mid	2437	16.5389
	High	2462	16.4554

Table 16. 99% Occupied Bandwidth, Test Results


6 dB Occupied Bandwidth Test Results




Plot 7. 6 dB Occupied Bandwidth, Low Channel, 802.11b




Plot 8. 6 dB Occupied Bandwidth, Mid Channel, 802.11b




Plot 9. 6 dB Occupied Bandwidth, High Channel, 802.11b




Plot 10. 6 dB Occupied Bandwidth, Low Channel, 802.11g




Plot 11. 6 dB Occupied Bandwidth, Mid Channel, 802.11g




Plot 12. 6 dB Occupied Bandwidth, High Channel, 802.11g



Plot 13. 6 dB Occupied Bandwidth, Low Channel, 802.11n




Plot 14. 6 dB Occupied Bandwidth, Mid Channel, 802.11n




Plot 15. 6 dB Occupied Bandwidth, High Channel, 802.11n


99% Occupied Bandwidth Test Results




Plot 16. 99% Occupied Bandwidth, Low Channel, 802.11b




Plot 17. 99% Occupied Bandwidth, Mid Channel, 802.11b




Plot 18. 99% Occupied Bandwidth, High Channel, 802.11b




Plot 19. 99% Occupied Bandwidth, Low Channel, 802.11g




Plot 20. 99% Occupied Bandwidth, Mid Channel, 802.11g




Plot 21. 99% Occupied Bandwidth, High Channel, 802.11g



Plot 22. 99% Occupied Bandwidth, Low Channel, 802.11n



Plot 23. 99% Occupied Bandwidth, Mid Channel, 802.11n



Plot 24. 99% Occupied Bandwidth, High Channel, 802.11n

Electromagnetic Compatibility Criteria for Intentional Radiators

§ 15.247(b) Peak Power Output

Test Requirements: §15.247(b): The maximum peak output power of the intentional radiator shall not exceed the following:

Digital Transmission Systems (MHz)	Output Limit (Watts)
902-928	1.000
2400-2483.5	1.000
5725- 5850	1.000

Table 17. Output Power Requirements from §15.247(b)

§15.247(b)(4): The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Test Procedure: The transmitter was connected to a calibrated spectrum analyzer. The EUT was measured at the low, mid and high channels of each band at the maximum power level.

Test Results: The EUT was compliant with the Peak Power Output limits of §15.247(b).

Test Engineer(s): Benjamin Taylor

Test Date(s): 09/09/13





Figure 2. Peak Power Output Test Setup

Peak Power Output Test Results


Peak Conducted Output Power			
	Carrier Channel	Frequency (MHz)	Measured Peak Output Power dBm
802.11b	Low	2412	-14.65
	Mid	2437	-18.00
	High	2462	-14.39
802.11g	Low	2412	-18.46
	Mid	2437	-21.65
	High	2462	-17.80
802.11n	Low	2412	-18.73
	Mid	2437	-21.29
	High	2462	-17.51

Table 18. Peak Power Output, Test Results


Peak Power Output Test Results




Plot 25. Peak Power Output, Low Channel, 802.11b




Plot 26. Peak Power Output, Mid Channel, 802.11b




Plot 27. Peak Power Output, High Channel, 802.11b




Plot 28. Peak Power Output, Low Channel, 802.11g




Plot 29. Peak Power Output, Mid Channel, 802.11g




Plot 30. Peak Power Output, High Channel, 802.11g



Plot 31. Peak Power Output, Low Channel, 802.11n



Plot 32. Peak Power Output, Mid Channel, 802.11n



Plot 33. Peak Power Output, High Channel, 802.11n

Electromagnetic Compatibility Criteria for Intentional Radiators

§ 15.247(d) Radiated Spurious Emissions Requirements and Band Edge

Test Requirements: §15.247(d); §15.205: Emissions outside the frequency band.

§15.247(d): In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in § 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a).

§15.205(a): Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090–0.110-----	16.42–16.423	399.9–410	4.5–5.15
¹ 0.495–0.505-----	16.69475–16.69525	608–614	5.35–5.46
2.1735–2.1905-----	16.80425–16.80475	960–1240	7.25–7.75
4.125–4.128-----	25.5–25.67	1300–1427	8.025–8.5
4.17725–4.17775-----	37.5–38.25	1435–1626.5	9.0–9.2
4.20725–4.20775-----	73–74.6	1645.5–1646.5	9.3–9.5
6.215–6.218-----	74.8–75.2	1660–1710	10.6–12.7
6.26775–6.26825-----	108–121.94	1718.8–1722.2	13.25–13.4
6.31175–6.31225-----	123–138	2200–2300	14.47–14.5
8.291–8.294-----	149.9–150.05	2310–2390	15.35–16.2
8.362–8.366-----	156.52475–156.52525	2483.5–2500	17.7–21.4
8.37625–8.38675-----	156.7–156.9	2655–2900	22.01–23.12
8.41425–8.41475-----	162.0125–167.17	3260–3267	23.6–24.0
12.29–12.293-----	167.72–173.2	3332–3339	31.2–31.8
12.51975–12.52025-----	240–285	3345.8–3358.36.	43–36.5
12.57675–12.57725-----	322–335.4	3600–4400	(²)

Table 19. Restricted Bands of Operation

¹ Until February 1, 1999, this restricted band shall be 0.490 – 0.510 MHz.

² Above 38.6

Test Requirement(s): § 15.209 (a): Except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in Table 20.

Frequency (MHz)	§ 15.209(a), Radiated Emission Limits (dB μ V) @ 3m
30 - 88	40.00
88 - 216	43.50
216 - 960	46.00
Above 960	54.00

Table 20. Radiated Emissions Limits Calculated from FCC Part 15, § 15.209 (a)


Test Procedures: The transmitter was turned on. Measurements were performed of the low, mid and high Channels. The EUT was rotated orthogonally through all three axes. Plots shown are corrected for both antenna correction factor and distance and compared to a 3 m limit line. Only noise floor was measured above 18 GHz.

Test Results: The EUT was compliant with the Radiated Spurious Emission limits of § 15.247(d).


Test Engineer(s): Benjamin Taylor

Test Date(s): 09/25/13


Radiated Spurious Emissions Test Results




Plot 34. Radiated Spurious Emissions, Low Channel, 802.11b, 30 MHz – 1 GHz




Plot 35. Radiated Spurious Emissions, Low Channel, 802.11b, 1 GHz – 18 GHz, Peak under Average




Plot 36. Radiated Spurious Emissions, Low Channel, 802.11b, 1 GHz – 18 GHz, 7237 MHz, Average




Plot 37. Radiated Spurious Emissions, Mid Channel, 802.11b, 30 MHz – 1 GHz




Plot 38. Radiated Spurious Emissions, Mid Channel, 802.11b, 1 GHz – 18 GHz, Peak under Average




Plot 39. Radiated Spurious Emissions, High Channel, 802.11b, 30 MHz – 1 GHz




Plot 40. Radiated Spurious Emissions, High Channel, 802.11b, 1 GHz – 18 GHz, Peak under Average




Plot 41. Radiated Spurious Emissions, Low Channel, 802.11g, 30 MHz – 1 GHz




Plot 42. Radiated Spurious Emissions, Low Channel, 802.11g, 1 GHz – 18 GHz, Peak under Average




Plot 43. Radiated Spurious Emissions, Mid Channel, 802.11g, 30 MHz – 1 GHz




Plot 44. Radiated Spurious Emissions, Mid Channel, 802.11g, 1 GHz – 18 GHz, Peak under Average




Plot 45. Radiated Spurious Emissions, High Channel, 802.11g, 30 MHz – 1 GHz




Plot 46. Radiated Spurious Emissions, High Channel, 802.11g, 1 GHz – 18 GHz, Peak under Average




Plot 47. Radiated Spurious Emissions, Low Channel, 802.11n, 30 MHz – 1 GHz




Plot 48. Radiated Spurious Emissions, Low Channel, 802.11n, 1 GHz – 18 GHz, Peak under Average




Plot 49. Radiated Spurious Emissions, Mid Channel, 802.11n, 30 MHz – 1 GHz



Plot 50. Radiated Spurious Emissions, Mid Channel, 802.11n, 1 GHz – 18 GHz, Peak under Average




Plot 51. Radiated Spurious Emissions, High Channel, 802.11n, 30 MHz – 1 GHz




Plot 52. Radiated Spurious Emissions, High Channel, 802.11n, 1 GHz – 18 GHz, Peak under Average


Radiated Band Edge




Plot 53. Radiated Band Edge, Low Channel, 802.11b, Peak




Plot 54. Radiated Band Edge, Low Channel, 802.11b, Average




Plot 55. Radiated Band Edge, High Channel, 802.11b, Peak




Plot 56. Radiated Band Edge, High Channel, 802.11b, Average




Plot 57. Radiated Band Edge, Low Channel, 802.11g, Peak




Plot 58. Radiated Band Edge, Low Channel, 802.11g, Average




Plot 59. Radiated Band Edge, High Channel, 802.11g, Peak




Plot 60. Radiated Band Edge, High Channel, 802.11g, Average




Plot 61. Radiated Band Edge, Low Channel, 802.11n, Peak



Plot 62. Radiated Band Edge, Low Channel, 802.11n, Average




Plot 63. Radiated Band Edge, High Channel, 802.11n, Peak




Plot 64. Radiated Band Edge, High Channel, 802.11n, Average


Simultaneous Operation




Plot 65. Radiated Spurious Emissions, Low Channel, 802.11b, 30 MHz – 1 GHz, 900 MHz TX




Plot 66. Radiated Spurious Emissions, Low Channel, 802.11b, 1 GHz – 18 GHz, 900 MHz TX




Plot 67. Radiated Spurious Emissions, Mid Channel, 802.11b, 30 MHz – 1 GHz, 900 MHz TX




Plot 68. Radiated Spurious Emissions, Mid Channel, 802.11b, 1 GHz – 18 GHz, 900 MHz TX




Plot 69. Radiated Spurious Emissions, High Channel, 802.11b, 30 MHz – 1 GHz, 900 MHz TX




Plot 70. Radiated Spurious Emissions, High Channel, 802.11b, 1 GHz – 18 GHz, 900 MHz TX




Plot 71. Radiated Spurious Emissions, Low Channel, 802.11g, 30 MHz – 1 GHz, 900 MHz TX




Plot 72. Radiated Spurious Emissions, Low Channel, 802.11g, 1 GHz – 18 GHz, 900 MHz TX




Plot 73. Radiated Spurious Emissions, Mid Channel, 802.11g, 30 MHz – 1 GHz, 900 MHz TX




Plot 74. Radiated Spurious Emissions, Mid Channel, 802.11g, 1 GHz – 18 GHz, 900 MHz TX




Plot 75. Radiated Spurious Emissions, High Channel, 802.11g, 30 MHz – 1 GHz, 900 MHz TX




Plot 76. Radiated Spurious Emissions, High Channel, 802.11g, 1 GHz – 18 GHz, 900 MHz TX




Plot 77. Radiated Spurious Emissions, Low Channel, 802.11n, 30 MHz – 1 GHz, 900 MHz TX




Plot 78. Radiated Spurious Emissions, Low Channel, 802.11n, 1 GHz – 18 GHz, 900 MHz TX




Plot 79. Radiated Spurious Emissions, Mid Channel, 802.11n, 30 MHz – 1 GHz, 900 MHz TX



Plot 80. Radiated Spurious Emissions, Mid Channel, 802.11n, 1 GHz – 18 GHz, 900 MHz TX




Plot 81. Radiated Spurious Emissions, High Channel, 802.11n, 30 MHz – 1 GHz, 900 MHz TX




Plot 82. Radiated Spurious Emissions, High Channel, 802.11n, 1 GHz – 18 GHz, 900 MHz TX

Radiated Spurious Emissions Test Setup



Photograph 5. Radiated Spurious Emissions, Test Setup, 30 MHz – 1 GHz



Photograph 6. Radiated Spurious Emissions, Test Setup, Above 1 GHz

Electromagnetic Compatibility Criteria for Intentional Radiators

§ 15.247(d) RF Conducted Spurious Emissions Requirements and Band Edge

Test Requirement: **15.247(d)** In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.

Test Procedure: For intentional radiators with a digital device portion which operates below 10 GHz, the spectrum was investigated as per §15.33(a)(1) and §15.33(a)(4); i.e., the lowest RF signal generated or used in the device up to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.

Since the EUT had an integral antenna, conducted measurements could not be performed. Measurements needed to be taken radiated. An antenna was located 3 m away from the EUT and plots were taken. The EUT was rotated through all three orthogonal axes. The plots were corrected for both antenna correction factor and cable loss.

See following pages for detailed test results with RF Conducted Spurious Emissions.

Test Results: The EUT was compliant with the Conducted Spurious Emission limits of §15.247(d).

Test Engineer(s): Benjamin Taylor

Test Date(s): 09/09/13






Figure 3. Block Diagram, Conducted Spurious Emissions Test Setup


Conducted Spurious Emissions Test Results




Plot 83. Conducted Spurious Emissions, Low Channel, 802.11b, 30 MHz – 26 GHz




Plot 84. Conducted Spurious Emissions, Mid Channel, 802.11b, 30 MHz – 26 GHz




Plot 85. Conducted Spurious Emissions, High Channel, 802.11b, 30 MHz – 26 GHz




Plot 86. Conducted Spurious Emissions, Low Channel, 802.11g, 30 MHz – 26 GHz




Plot 87. Conducted Spurious Emissions, Mid Channel, 802.11g, 30 MHz – 26 GHz




Plot 88. Conducted Spurious Emissions, High Channel, 802.11g, 30 MHz – 26 GHz



Plot 89. Conducted Spurious Emissions, Low Channel, 802.11n, 30 MHz – 26 GHz



Plot 90. Conducted Spurious Emissions, Mid Channel, 802.11n, 30 MHz – 26 GHz



Plot 91. Conducted Spurious Emissions, High Channel, 802.11n, 30 MHz – 26 GHz

Electromagnetic Compatibility Criteria for Intentional Radiators

§ 15.247(e) Peak Power Spectral Density

Test Requirements: §15.247(e): For digitally modulated systems, the peak power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3 kHz band during any time interval of continuous transmission.

Test Procedure: The transmitter was connected directly to a Spectrum Analyzer through an attenuator. The transmitter was set to operate at maximum power. The RBW was set to 3 kHz and a VBW set to 9 kHz or greater. Sweep time was manually set to 500seconds as per the guidance. A peak detector was used. Measurements were carried out at the low, mid and high channels.

Test Results: The EUT was compliant with the peak power spectral density limits of § 15.247 (e).
The peak power spectral density was determined from plots on the following page(s).

Test Engineer: Benjamin Taylor

Test Date: 09/09/13





Figure 4. Block Diagram, Peak Power Spectral Density Test Setup

Peak Power Spectral Density Test Results


Peak Power Spectral Density					
	Carrier Channel	Frequency (MHz)	Measured PPSD (dBm)	Limit (dBm)	Margin (dB)
802.11b	Low	2412	-41.23	8	-49.23
	Mid	2437	-45.10	8	-53.10
	High	2462	-41.23	8	-49.23
802.11g	Low	2412	-48.52	8	-56.52
	Mid	2437	-51.68	8	-59.68
	High	2462	-48.81	8	-56.81
802.11n	Low	2412	-48.36	8	-56.36
	Mid	2437	-51.03	8	-59.03
	High	2462	-47.24	8	-55.24

Table 21. Peak Power Spectral Density, Test Results


Peak Power Spectral Density




Plot 92. Peak Power Spectral Density, Low Channel, 802.11b, Peak Search




Plot 93. Peak Power Spectral Density, Low Channel, 802.11b




Plot 94. Peak Power Spectral Density, Mid Channel, 802.11b, Peak Search




Plot 95. Peak Power Spectral Density, Mid Channel, 802.11b




Plot 96. Peak Power Spectral Density, High Channel, 802.11b, Peak Search




Plot 97. Peak Power Spectral Density, High Channel, 802.11b




Plot 98. Peak Power Spectral Density, Low Channel, 802.11g, Peak Search




Plot 99. Peak Power Spectral Density, Low Channel, 802.11g




Plot 100. Peak Power Spectral Density, Mid Channel, 802.11g, Peak Search




Plot 101. Peak Power Spectral Density, Mid Channel, 802.11g




Plot 102. Peak Power Spectral Density, High Channel, 802.11g, Peak Search




Plot 103. Peak Power Spectral Density, High Channel, 802.11g




Plot 104. Peak Power Spectral Density, Low Channel, 802.11n, Peak Search




Plot 105. Peak Power Spectral Density, Low Channel, 802.11n




Plot 106. Peak Power Spectral Density, Mid Channel, 802.11n, Peak Search



Plot 107. Peak Power Spectral Density, Mid Channel, 802.11n



Plot 108. Peak Power Spectral Density, High Channel, 802.11n, Peak Search



Plot 109. Peak Power Spectral Density, High Channel, 802.11n

Electromagnetic Compatibility Criteria for Intentional Radiators

§ 15.247(i) Maximum Permissible Exposure

RF Exposure Requirements: §1.1307(b)(1) and §1.1307(b)(2): Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines.

RF Radiation Exposure Limit: §1.1310: As specified in this section, the Maximum Permissible Exposure (MPE) Limit shall be used to evaluate the environmental impact of human exposure to radiofrequency (RF) radiation as specified in Sec. 1.1307(b), except in the case of portable devices which shall be evaluated according to the provisions of Sec. 2.1093 of this chapter.

The co-located, 900MHz radio is filed under 15.249, with low enough power to be exempt from MPE; therefore this MPE evaluation addresses only the 2.4GHz, 15.247 radio.

MPE Limit Calculation: EUT's operating frequencies @ 2400-2483.5 MHz; highest conducted power = *-14.39dBm* (peak) therefore, **Limit for Uncontrolled exposure: 1 mW/cm² or 10 W/m²**

EUT maximum antenna gain = *0dBi*.

Equation from page 18 of OET 65, Edition 97-01

$$S = PG / 4\pi R^2 \quad \text{or} \quad R = \sqrt{PG / 4\pi S}$$

where, S = Power Density (1 mW/cm²)
P = Power Input to antenna (41.4mW)
G = Antenna Gain (63.1 numeric)

$$R = (0.036 * 1.26 / 4 * 3.14 * 1.0)^{1/2} = (0.0454 / 12.56)^{1/2} = 0.06\text{cm}$$

IV. Test Equipment

Test Equipment

Calibrated test equipment utilized during testing was maintained in a current state of calibration per the requirements of ISO/IEC 17025:2005.

MET Asset #	Equipment	Manufacturer	Model	Last Cal Date	Cal Due Date
1T4771	PSA SPECTRUM ANALYZER	AGILENT TECHNOLOGIES	E4446A	02/15/2013	08/15/2014
1T4409	EMI RECEIVER	ROHDE & SCHWARZ	ESIB7	07/16/2012	07/16/2014
1T4751	ANTENNA - BILOG	SUNOL SCIENCES	JB6	01/08/2013	07/08/2014
1T4483	ANTENNA; HORN	ETS-LINDGREN	3117	08/06/2012	02/06/2014
1T4745	ANTENNA, HORN	ETS-LINDGREN	3116	10/19/2012	10/19/2013
1T4300A	SEMI-ANECHOIC CHAMBER # 1 (FCC)	EMC TEST SYSTEMS	NONE	07/24/2012	07/24/2015
1T4442	PRE-AMPLIFIER, MICROWAVE	MITEQ	AFS42-01001800-30-10P	SEE NOTE	
1T4742	PRE-AMPLIFIER, HIGH-FREQUENCY	MITEQ	AFS42-01001800-30-10P-42	SEE NOTE	
1T4149	HIGH-FREQUENCY ANECHOIC CHAMBER	RAY-PROOF	81	NOT REQUIRED	

Table 22. Test Equipment List

Note: Functionally tested equipment is verified using calibrated instrumentation at the time of testing.

V. Certification & User's Manual Information

Certification & User's Manual Information

A. Certification Information

The following is extracted from Title 47 of the Code of Federal Regulations, Part 2, Subpart I — Marketing of Radio frequency devices:

§ 2.801 Radio-frequency device defined.

As used in this part, a radio-frequency device is any device which in its operation is capable of Emitting radio-frequency energy by radiation, conduction, or other means. Radio- frequency devices include, but are not limited to:

- (a) The various types of radio communication transmitting devices described throughout this chapter.
- (b) *The incidental, unintentional and intentional radiators defined in Part 15 of this chapter.*
- (c) The industrial, scientific, and medical equipment described in Part 18 of this chapter.
- (d) Any part or component thereof which in use emits radio-frequency energy by radiation, conduction, or other means.

§ 2.803 Marketing of radio frequency devices prior to equipment authorization.

- (a) Except as provided elsewhere in this chapter, no person shall sell or lease, or offer for sale or lease (including advertising for sale or lease), or import, ship or distribute for the purpose of selling or leasing or offering for sale or lease, any radio frequency device unless:
 - (1) In the case of a device subject to certification, such device has been authorized by the Commission in accordance with the rules in this chapter and is properly identified and labeled as required by §2.925 and other relevant sections in this chapter; or
 - (2) In the case of a device that is not required to have a grant of equipment authorization issued by the Commission, but which must comply with the specified technical standards prior to use, such device also complies with all applicable administrative (including verification of the equipment or authorization under a Declaration of Conformity, where required), technical, labeling and identification requirements specified in this chapter.
- (d) Notwithstanding the provisions of paragraph (a) of this section, the offer for sale solely to business, commercial, industrial, scientific or medical users (but not an offer for sale to other parties or to end users located in a residential environment) of a radio frequency device that is in the conceptual, developmental, design or pre-production stage is permitted prior to equipment authorization or, for devices not subject to the equipment authorization requirements, prior to a determination of compliance with the applicable technical requirements *provided* that the prospective buyer is advised in writing at the time of the offer for sale that the equipment is subject to the FCC rules and that the equipment will comply with the appropriate rules before delivery to the buyer or to centers of distribution.

- (e)(1) Notwithstanding the provisions of paragraph (a) of this section, prior to equipment authorization or determination of compliance with the applicable technical requirements any radio frequency device may be operated, but not marketed, for the following purposes and under the following conditions:
- (i) *Compliance testing*;
 - (ii) Demonstrations at a trade show provided the notice contained in paragraph (c) of this section is displayed in a conspicuous location on, or immediately adjacent to, the device;
 - (iii) Demonstrations at an exhibition conducted at a business, commercial, industrial, scientific or medical location, but excluding locations in a residential environment, provided the notice contained in paragraphs (c) or (d) of this section, as appropriate, is displayed in a conspicuous location on, or immediately adjacent to, the device;
 - (iv) Evaluation of product performance and determination of customer acceptability, provided such operation takes place at the manufacturer's facilities during developmental, design or pre-production states; or
 - (v) Evaluation of product performance and determination of customer acceptability where customer acceptability of a radio frequency device cannot be determined at the manufacturer's facilities because of size or unique capability of the device, provided the device is operated at a business, commercial, industrial, scientific or medical user's site, but not at a residential site, during the development, design or pre-production stages.
- (e)(2) For the purpose of paragraphs (e)(1)(iv) and (e)(1)(v) of this section, the term *manufacturer's facilities* includes the facilities of the party responsible for compliance with the regulations and the manufacturer's premises, as well as the facilities of other entities working under the authorization of the responsible party in connection with the development and manufacture, but not the marketing, of the equipment.
- (f) For radio frequency devices subject to verification and sold solely to business, commercial, industrial, scientific and medical users (excluding products sold to other parties or for operation in a residential environment), parties responsible for verification of the devices shall have the option of ensuring compliance with the applicable technical specifications of this chapter at each end user's location after installation, provided that the purchase or lease agreement includes a proviso that such a determination of compliance be made and is the responsibility of the party responsible for verification of the equipment.

Certification & User's Manual Information

The following is extracted from Title 47 of the Code of Federal Regulations, Part 2, Subpart J — Equipment Authorization Procedures:

§ 2.901 Basis and Purpose

- (a) In order to carry out its responsibilities under the Communications Act and the various treaties and international regulations, and in order to promote efficient use of the radio spectrum, the Commission has developed technical standards for radio frequency equipment and parts or components thereof. The technical standards applicable to individual types of equipment are found in that part of the rules governing the service wherein the equipment is to be operated.¹ *In addition to the technical standards provided, the rules governing the service may require that such equipment be verified by the manufacturer or importer, be authorized under a Declaration of Conformity, or receive an equipment authorization from the Commission by one of the following procedures: certification or registration.*
- (b) The following sections describe the verification procedure, the procedure for a Declaration of Conformity, and the procedures to be followed in obtaining certification from the Commission and the conditions attendant to such a grant.

§ 2.907 Certification.

- (a) Certification is an equipment authorization issued by the Commission, based on representation and test data submitted by the applicant.
- (b) Certification attaches to all units subsequently marketed by the grantee which are identical (see Section 2.908) to the sample tested except for permissive changes or other variations authorized by the Commission pursuant to Section 2.1043.

¹ In this case, the equipment is subject to the rules of Part 15. More specifically, the equipment falls under Subpart B (of Part 15), which deals with unintentional radiators.

Certification & User's Manual Information

§ 2.948 Description of measurement facilities.

- (a) Each party making measurements of equipment that is subject to an equipment authorization under Part 15 or Part 18 of this chapter, regardless of whether the measurements are filed with the Commission or kept on file by the party responsible for compliance of equipment marketed within the U.S. or its possessions, shall compile a description of the measurement facilities employed.
- (1) If the measured equipment is subject to the verification procedure, the description of the measurement facilities shall be retained by the party responsible for verification of the equipment.
- (i) *If the equipment is verified through measurements performed by an independent laboratory, it is acceptable for the party responsible for verification of the equipment to rely upon the description of the measurement facilities retained by or placed on file with the Commission by that laboratory. In this situation, the party responsible for the verification of the equipment is not required to retain a duplicate copy of the description of the measurement facilities.*
- (ii) If the equipment is verified based on measurements performed at the installation site of the equipment, no specific site calibration data is required. It is acceptable to retain the description of the measurement facilities at the site at which the measurements were performed.
- (2) If the equipment is to be authorized by the Commission under the certification procedure, the description of the measurement facilities shall be filed with the Commission's Laboratory in Columbia, Maryland. The data describing the measurement facilities need only be filed once but must be updated as changes are made to the measurement facilities or as otherwise described in this section. At least every three years, the organization responsible for filing the data with the Commission shall certify that the data on file is current.

Certification & User's Manual Information

1. Label and User's Manual Information

The following is extracted from Title 47 of the Code of Federal Regulations, Part 15, Subpart A — General:

§ 15.19 Labeling requirements.

(a) *In addition to the requirements in Part 2 of this chapter, a device subject to certification or verification shall be labeled as follows:*

- (1) Receivers associated with the operation of a licensed radio service, e.g., FM broadcast under Part 73 of this chapter, land mobile operation under Part 90, etc., shall bear the following statement in a conspicuous location on the device:

This device complies with Part 15 of the FCC Rules. Operation is subject to the condition that this device does not cause harmful interference.

- (2) A stand-alone cable input selector switch, shall bear the following statement in a conspicuous location on the device:

This device is verified to comply with Part 15 of the FCC Rules for use with cable television service.

- (3) All other devices shall bear the following statement in a conspicuous location on the device:

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

- (4) Where a device is constructed in two or more sections connected by wires and marketed together, the statement specified under paragraph (a) of this section is required to be affixed only to the main control unit.

- (5) When the device is so small or for such use that it is not practicable to place the statement specified under paragraph (a) of this section on it, the information required by this paragraph shall be placed in a prominent location in the instruction manual or pamphlet supplied to the user or, alternatively, shall be placed on the container in which the device is marketed. However, the FCC identifier or the unique identifier, as appropriate, must be displayed on the device.

§ 15.21 Information to user.

The user's manual or instruction manual for an intentional or unintentional radiator shall caution the user that changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

Verification & User's Manual Information

The following is extracted from Title 47 of the Code of Federal Regulations, Part 15, Subpart B — Unintentional Radiators:

§ 15.105 Information to the user.

- (a) For a Class A digital device or peripheral, the instructions furnished the user shall include the following or similar statement, placed in a prominent location in the text of the manual:

Note: This equipment has been tested and found to comply with the limits for a Class A digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference when the equipment is operated in a commercial environment. This equipment generates, uses, and can radiate radio frequency energy and, if not installed and used in accordance with the instruction manual, may cause harmful interference to radio communications. Operation of this equipment in a residential area is likely to cause harmful interference in which case the user will be required to correct the interference at own expense.

- (b) For a Class B digital device or peripheral, the instructions furnished the user shall include the following or similar statement, placed in a prominent location in the text of the manual:

Note: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference when the equipment is operated in a residential environment. This equipment generates, uses, and can radiate radio frequency energy and, if not installed and used in accordance with the instruction manual, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

ICES-003 Procedural & Labeling Requirements

From the Industry Canada Electromagnetic Compatibility Advisory Bulletin entitled, "Implementation and Interpretation of the Interference-Causing Equipment Standard for Digital Apparatus, ICES-003" (EMCAB-3, Issue 2, July 1995):

"At present, CISPR 22: 2002 and ICES technical requirements are essentially equivalent. Therefore, if you have CISPR 22: 2002 approval by meeting CISPR Publication 22, the only additional requirements are: to attach a note to the report of the test results for compliance, indicating that these results are deemed satisfactory evidence of compliance with ICES-003 of the Canadian Interference-Causing Equipment Regulations; to maintain these records on file for the requisite five year period; and to provide the device with a notice of compliance in accordance with ICES-003."

Procedural Requirements:

According to Industry Canada's Interference Causing Equipment Standard for Digital Apparatus ICES-003 Issue 5 August 2012:

- Section 6.1: A record of the measurements and results, showing the date that the measurements were completed, shall be retained by the manufacturer or importer for a period of at least five years from the date shown in the record and made available for examination on the request of the Minister.
- Section 6.2: A written notice indicating compliance must accompany each unit of digital apparatus to the end user. The notice shall be in the form of a label that is affixed to the apparatus. Where because of insufficient space or other constraints it is not feasible to affix a label to the apparatus, the notice may be in the form of a statement in the users' manual.

Labeling Requirements:

The suggested text for the notice, in English and in French, is provided below, from the Annex of ICES-003:

This Class [²] digital apparatus complies with Canadian ICES-003.

Cet appareil numérique de la classe [¹] est conforme à la norme NMB-003 du Canada.

² Insert either A or B but not both as appropriate for the equipment requirements.

End of Report