

Test Mode	UNII-2A
-----------	---------

Voltage vs. Frequency Stability

Voltage (V)	Measurement Frequency (MHz)
Center Frequency	5260.0000
13.8	5259.9550
12	5259.9550
10.2	5259.9600
Maximum Deviation (MHz)	0.0450
Maximum Deviation (ppm)	8.5528

Temperature vs. Frequency Stability

Temperature (°C)	Measurement Frequency (MHz)
Center Frequency	5260.0000
0	5259.9599
10	5259.9550
20	5259.9600
30	5259.9550
40	5259.9550
45	5259.9600
Maximum Deviation (MHz)	0.0450
Maximum Deviation (ppm)	8.5551

Test Mode	UNII-2C
-----------	---------

Voltage vs. Frequency Stability

Voltage (V)	Measurement Frequency (MHz)
Center Frequency	5500.0000
13.8	5499.9600
12	5499.9600
10.2	5499.9600
Maximum Deviation (MHz)	0.0400
Maximum Deviation (ppm)	7.2773

Temperature vs. Frequency Stability

Temperature (°C)	Measurement Frequency (MHz)
Center Frequency	5500.0000
0	5499.9550
10	5499.9751
20	5499.9550
30	5499.9399
40	5499.9400
45	5499.9399
Maximum Deviation (MHz)	0.0601
Maximum Deviation (ppm)	10.9295

Test Mode	UNII-3
-----------	--------

Voltage vs. Frequency Stability

Voltage (V)	Measurement Frequency (MHz)
Center Frequency	5745.0000
13.8	5744.9600
12	5744.9399
10.2	5744.9399
Maximum Deviation (MHz)	0.0601
Maximum Deviation (ppm)	10.4656

Temperature vs. Frequency Stability

Temperature (°C)	Measurement Frequency (MHz)
Center Frequency	5745.0000
0	5744.9350
10	5744.9399
20	5744.9350
30	5744.9550
40	5744.9200
45	5744.9350
Maximum Deviation (MHz)	0.0800
Maximum Deviation (ppm)	13.9295

End of Test Report