


## SAR Exclusion Evaluation Report

Applicant : KRONOZ  
Product Type : Smart Watch  
Trade Name : MYKRONOZ  
Model Number : ZeRound<sup>2</sup>HR, ZeRound<sup>2</sup>  
Date of Received : May 12, 2017  
Test Period : May 23, 2017  
Date of Issued : Jul. 05, 2017

### Issue by

Approved By :   
(Bill Hu)

Tested By :   
(Mark Duan)

A Test Lab Techno Corp.  
No. 140-1, Changan Street, Bade District,  
Taoyuan City 33465, Taiwan (R.O.C)  
Tel : +886-3-2710188 / Fax : +886-3-2710190



Taiwan Accreditation Foundation accreditation number: 1330

Test Firm MRA designation number: TW0010

**Note:** This report shall not be reproduced except in full, without the written approval of A Test Lab Techno Corp. This document may be altered or revised by A Test Lab Techno Corp. personnel only, and shall be noted in the revision section of the document. The client should not use it to claim product endorsement by TAF, or any government agencies. The test results in the report only apply to the tested sample.



### Revision History

Rev.	Issue Date	Revisions	Revised By
00	Jul. 05, 2017	Initial Issue	Snow Wang



# Contents

<b>1.</b>	<b>Description of Equipment under Test (EUT)</b> .....	<b>4</b>
<b>2.</b>	<b>Reference Testing Standards</b> .....	<b>4</b>
<b>3.</b>	<b>SAR Test Exclusion</b> .....	<b>5</b>
3.1	Conducted Power .....	6
3.2	Antenna Location.....	7
3.3	Evaluation Results .....	7



## 1. Description of Equipment under Test (EUT)

Applicant	KRONOZ ROUTE DE VALAVRAN 96, GENTHOD, 1294, Switzerland		
Manufacturer	KRONOZ ROUTE DE VALAVRAN 96, GENTHOD, 1294, Switzerland		
Product Type	Smart Watch		
Trade Name	MYKRONOZ		
Model Number	ZeRound <sup>2</sup> HR, ZeRound <sup>2</sup>		
Models Different Description	ZeRound <sup>2</sup> HR has the heart rate sensor.		
FCC ID	2AA7D-ZERD2		
Operate Freq. Band	Frequency Range (MHz)	Modulation Type	Number of Channels
Bluetooth BR	2402 ~ 2480	GFSK	79
Bluetooth EDR	2402 ~ 2480	$\pi/4$ -DQPSK	79
		8DPSK	79
Bluetooth LE	2402 ~ 2480	GFSK	40
Antenna information	Type		Max. Gain (dBi)
	FPC Antenna		-1.5

The above equipment was tested by A Test Lab Techno Corp. For compliance with the requirements set forth in 47 CFR § 2.1093. The results of testing in this report apply only to the product/system, which was tested. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

## 2. Reference Testing Standards

Standard	Description	Version
ANSI/IEEE C95.1	American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 300 KHz to 100 GHz, New York.	1992
IEEE 1528	IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head From Wireless Communications Devices: Measurement Techniques.	2013
FCC 47 CFR Part 2.1093	Radiofrequency radiation exposure evaluation: portable devices.	---
FCC KDB 865664 D01	SAR measurement 100 MHz to 6 GHz - describes SAR measurement procedures for devices operating between 100 MHz to 6 GHz	v01r04
FCC KDB 865664 D02	RF Exposure Reporting - provides general reporting requirements as well as certain specific information required to support MPE and SAR compliance.	v01r02
FCC KDB 447498 D01	General RF Exposure Guidance - provides guidance pertaining to RF exposure requirements for mobile and portable device equipment authorizations.	v06



### 3. SAR Test Exclusion

As RF exposure evaluation of portable device, SAR test is not required when the evaluation results. According to KDB 447498 4.3.1, unless excluded by specific FCC test procedures, portable devices shall include SAR data for equipment approval. SAR test necessity will be based on the exclusion result.

The test exclusion refers KDB 447498 as below:

**≤50mm:**

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR

**>50mm and <200mm:**

- a)  $[\text{Power allowed at numeric threshold for 50 mm in step 1}) + (\text{test separation distance} - 50 \text{ mm}) \cdot (f(\text{MHz})/150)]$  mW, at 100 MHz to 1500 MHz
- b)  $[\text{Power allowed at numeric threshold for 50 mm in step 1}) + (\text{test separation distance} - 50 \text{ mm}) \cdot 10]$  mW at > 1500 MHz and  $\leq 6$  GHz



### 3.1 Conducted Power

The conducted power turn-up tolerance, please reference manufacturer specification.

Operate Band	Modulation Type	Data Rate (Mbps)	Frequency (MHz)	Packet Type	Average Power (dBm)
Bluetooth BR	GFSK	1	2402	DH1	-1.26
				DH3	2.19
				DH5	2.96
			2441	DH1	-1.06
				DH3	2.39
				DH5	3.19
			2480	DH1	-0.21
				DH3	3.24
				DH5	3.98
Bluetooth EDR	$\pi/4$ -DQPSK	2	2402	2DH1	-4.17
				2DH3	-1.26
				2DH5	-0.57
			2441	2DH1	-3.69
				2DH3	-0.77
				2DH5	-0.09
			2480	2DH1	-2.81
				2DH3	0.12
				2DH5	0.79
	8DPSK	3	2402	3DH1	-4.15
				3DH3	-1.26
				3DH5	-0.56
			2441	3DH1	-3.66
				3DH3	-0.77
				3DH5	-0.02
2480	3DH1	-2.80			
	3DH3	0.14			
	3DH5	0.80			

Operate Band	Modulation Type	Data Rate (Mbps)	Frequency (MHz)	Average Power (dBm)
Bluetooth LE	GFSK	1	2402	1.52
			2440	1.99
			2480	2.85

### 3.2 Antenna Location

Transmitter and antenna implementation	
Operate Band	Bluetooth Antenna
Bluetooth	V

Ant. Used	Antenna to user distance (mm)					
	Side 1	Side 2	Side 3	Side 4	Side 5	Side 6
Bluetooth Antenna	5	5	5	5	5	5

Note : We use a minimum distance of 5mm for Bluetooth function.

### 3.3 Evaluation Results

The evaluation of SAR test reduction according to KDB447498

SAR test is not required when the results showed "EXEMPT".

Ant. Used	Band	Channel	Frequency	Tune-Power		Calculated value and evaluated result					
			(GHz)	(dBm)	(mW)	Side 1	Side 2	Side 3	Side 4	Side 5	Side 6
Bluetooth Antenna	Bluetooth BR/EDR	78	2.48	4	3	0.9	0.9	0.9	0.9	0.9	0.9
						EXEMPT	EXEMPT	EXEMPT	EXEMPT	EXEMPT	EXEMPT
Bluetooth Antenna	Bluetooth LE	39	2.48	3	2	0.6	0.6	0.6	0.6	0.6	0.6
						EXEMPT	EXEMPT	EXEMPT	EXEMPT	EXEMPT	EXEMPT

- Note:
1. Calculated Value include string "mW",that is mean through compare output power with threshold, if the output power more than threshold value the SAR test should be perform. Otherwise,the SAR test could be exempt. (> 50mm)
  - 2.Calculated Value only inculde number format, that is mean through compare output power with threshold, if the Calculated value more than 3, the SAR test should be perform. Otherwise, the SAR test could be exempt. (<50mm)
  - 3.When an antenna qualifies for the standalone SAR test exclusion of KDB 447498 section 4.3.1 and also transmits simultaneously with other antennas, the standalone SAR value must be estimated according to KDB 447498 section "4.3.2. Simultaneous transmission SAR test exclusion considerations b) "
  - 4.We used highest frequency and power,that result should be evaluated the worst case.
  - 5.Power and distance are rounded to the nearest mW and mm before calculation.
  - 6.The result is rounded to one decimal place for comparison.
  - 7.We use a minimum distance of 5mm for bluetooth function.