







ISO/IEC17025Accredited Lab.

Report No: FCC 1310021 File reference No: 2013-10-15

Applicant: Shenzhen BETRUE Technology Co., Ltd.

Product: Bluetooth Waterproof Speaker

Model No: BTS05

Trademark: N/A

Test Standards: FCC Part 15 Subpart C, Paragraph 15.247

It is herewith confirmed and found to comply with the Test result:

requirements set up by ANSI C63.4&FCC Part 15 Subpart C, Paragraph 15.247 regulations for the evaluation

electromagnetic compatibility

Approved By

Jack Chung

Jack Chung Manager

Dated: October 15, 2013

Results appearing herein relate only to the sample tested

The technical reports is issued errors and omissions exempt and is subject to withdrawal at

SHENZHEN TIMEWAY TECHNOLOGY CONSULTING CO LTD

5/F,Block 4, Anhua Industrial Zone.,No.8 TaiRan Rd.CheGongMiao,FuTian District, Shenzhen, CHINA.

> Tel (755) 83448688 Fax (755) 83442996

Report No: 1310021 Page 2 of 79

Date: 2013-10-15



Special Statement:

The testing quality ability of our laboratory meet with "Quality Law of People's Republic of China" Clause 19.

The testing quality system of our laboratory meets with ISO/IEC-17025 requirements, which is approved by CNAS. This approval result is accepted by MRA of APLAC.

Our test facility is recognized, certified, or accredited by the following organizations:

CNAS-LAB Code: L2292

The EMC Laboratory has been assessed and in compliance with CNAS-CL01 accreditation criteria for testing Laboratories (identical to ISO/IEC 17025:1999 General Requirements) for the Competence of testing Laboratories.

FCC-Registration No.: 899988

The EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications commission. The acceptance letter from the FCC is maintained in our files. Registration No.:899988.

IC- Registration No.: IC5205A-02

The EMC Laboratory has been registered and fully described in a report filed with the (IC) Industry Canada. The acceptance letter from the IC is maintained in our files. Registration No.: IC 5205A-02.

Page 3 of 79

Report No: 1310021 Date: 2013-10-15



Test Report Conclusion Content

1.0	General Details	4
1.1	Test Lab Details	4
1.2	Applicant Details	4
1.3	Description of EUT	4
1.4	Submitted Sample	4
1.5	Test Duration.	4
1.6	Test Uncertainty.	5
1.7	Test By	5
2.0	List of Measurement Equipment.	6
3.0	Technical Details	7
3.1	Summary of Test Results	7
3.2	Test Standards	7
4.0	EUT Modification.	7
5.0	Power Line Conducted Emission Test.	8
5.1	Schematics of the Test.	8
5.2	Test Method and Test Procedure.	8
5.3	Configuration of the EUT	8
5.4	EUT Operating Condition.	9
5.5	Conducted Emission Limit.	9
5.6	Test Result.	9
6.0	Radiated Emission test	12
6.1	Test Method and Test Procedure.	12
6.2	Configuration of the EUT	12
6.3	EUT Operation Condition.	12
6.4	Radiated Emission Limit.	13
7.0	20dB Bandwidth Measurement	22
8.0	Maximum Peak Output Power.	34
9.0	Carrier Frequency Separation.	37
10.0	Number of Hopping Channel.	41
11.0	Time of Occupancy (Dwell Time)	45
12.0	Out of Band Measurement.	57
13.0	Antenna Requirement.	71
14.0	RF Exposure	72
15.0	FCC Label.	73
16.0	Photo of Test Setup and EUT View	74

Date: 2013-10-15



1.0 General Details

1.1 Test Lab Details

Name: SHENZHEN TIMEWAY TECHNOLOGY CONSULTING CO LTD

Address: 5/F,Block 4, Anhua Industrial Zone.,No.8 TaiRan Rd.CheGongMiao,FuTian District,

Shenzhen, CHINA.

Telephone: (755) 83448688 Fax: (755) 83442996

Site on File with the Federal Communications Commission – United Sates

Registration Number: 899988

For 3m & 10 m OATS

Site Listed with Industry Canada of Ottawa, Canada

Registration Number: IC: 5205A-02

For 3m & 10 m OATS

1.2 Applicant Details

Applicant: Shenzhen BETRUE Technology Co., Ltd.

Address: 4F, 1C Building, Hongpai Technology Park, TianFu Road, Qiaotou, FuYong Street, Baoan

District, Shenzhen City, Guangdong Province, P.R China

Telephone: 0755-61504566 Fax: 0755-61504570

1.3 Description of EUT

Product: Bluetooth Waterproof Speaker

Manufacturer: Shenzhen BETRUE Technology Co., Ltd.

Address: 4F, 1C Building, Hongpai Technology Park, TianFu Road, Qiaotou, FuYong

Street, Baoan District, Shenzhen City, Guangdong Province, P.R China

Brand Name: N/A
Model Number: BTS05
Additional Model Name N/A
Additional Trade Name N/A

Type of Modulation GFSK, Л/4QPSK, 8DPSK

Frequency range 2402-2480MHz

Number of Channel 79

Frequency Selection By software

Antenna type PCB Printed Antenna used, the antenna gain is 0dBi Rating Input Voltage: DC3.7V powered by Lion-Battery

1.4 Submitted Sample: 1 Sample

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co .,Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Report No: 1310021 Page 5 of 79

Date: 2013-10-15



1.5 Test Duration:

2013-10-10 to 2013-10-15

1.6 Test Uncertainty

Conducted Emissions Uncertainty = 3.6dB Radiated Emissions Uncertainty = 4.7dB

1.7 Test Engineer

Terry Tang

The sample tested by

Print Name: Terry Tang

Page 6 of 79

Report No: 1310021 Date: 2013-10-15



2.0	Test Equipments						
Instrument Type	Manufacturer	Model	Serial No.	Date of Cal.	Due Date		
ESPI Test Receiver	ROHDE&SCHWARZ	ESPI 3	100379	2013-08-23	2014-08-22		
TWO Line-V-NETW	ROHDE&SCHWARZ	EZH3-Z5	100294	2013-08-23	2014-08-22		
TWO Line-V-NETW	ROHDE&SCHWARZ	EZH3-Z5	100253	2013-08-23	2014-08-22		
Ultra Broadband ANT	ROHDE&SCHWARZ	HL562	100157	2013-08-25	2014-08-24		
ESDV Test Receiver	ROHDE&SCHWARZ	ESDV	100008	2013-08-23	2014-08-22		
Impuls-Begrenzer	ROHDE&SCHWARZ	ESH3-Z2	100281	2013-08-24	2014-08-23		
System Controller	CT	SC100	-				
Printer	EPSON	РНОТО ЕХЗ	CFNH234850				
Computer	IBM	8434	1S8434KCE99BLXL O*	-	-		
Loop Antenna	EMCO	6502	00042960	2013-08-23	2014-08-22		
ESPI Test Receiver	ROHDE&SCHWARZ	ESI26	838786/013	2013-08-23	2014-08-22		
3m OATS			N/A	2013-08-22	2014-08-21		
Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170265	2013-08-24	2014-08-23		
Horn Antenna	SCHWARZBECK	BBHA 9120D	9120D-631	2013-08-24	2014-08-23		
Power meter	Anritsu	ML2487A	6K00003613	2013-08-24	2014-08-23		
Power sensor	Anritsu	MA2491A	32263	2013-08-24	2014-08-23		
Bilog Antenna	Schwarebeck	VULB9163	9163/340	2013-08-21	2014-08-20		
LISN	AFJ	LS16C	10010947251	2013-08-21	2014-08-20		
LISN (Three Phase)	Schwarebeck	NSLK 8126	8126453	2013-08-23	2014-08-22		
9*6*6 Anechoic			N/A	2013-08-22	2014-08-21		
EMI Test Receiver	RS	ESCS30	100139	2013-08-23	2014-08-22		
LISN	AFJ	LS16C	10010947251	2013-08-23	2014-08-22		
LISN (Three Phase)	Schwarebeck	NSLK 8126	8126453	2013-08-23	2014-08-22		

Report No: 1310021 Page 7 of 79

Date: 2013-10-15



3.0 Technical Details

3.1 Summary of test results

The EUT has been tested according to the following specifications:

Requirement	CFR 47 Section	Result	Notes
Antenna Requirement	15.203, 15.247(b)(4)	PASS	Complies
Maximum Peak Out Power	15.247 (b)(1), (4)	PASS	Complies
Carrier Frequency Separation	15.247(a)(1)	PASS	Complies
20dB Channel Bandwidth	15.247 (a)(1)	PASS	Complies
Number of Hopping Channels	15.247(a)(iii), 15.247(b)(1)	PASS	Complies
Time of Occupancy (Dwell Time)	15.247(a)(iii)	PASS	Complies
Spurious Emission, Band Edge, and	15.247(d),15.205(a),	PASS	Complies
Restricted bands	15.209 (a),15.109		
Conducted Emissions	15.207(a), 15.107	PASS	Complies
RF Exposure	15.247(i), 1.1307(b)(1)	PASS	Complies

3.2 Test Standards

FCC Part 15 Subpart & Subpart C, Paragraph 15.247

4.0 EUT Modification

No modification by Shenzhen Timeway Technology Consulting Co., Ltd


Report No: 1310021 Page 8 of 79

Date: 2013-10-15



5. Power Line Conducted Emission Test

5.1 Schematics of the test




EUT: Equipment Under Test

5.2 Test Method and test Procedure

The EUT was tested according to ANSI C63.4-2003. The Frequency spectrum From 0.15MHz to 30MHz was investigated. The LISN used was 50ohm/50uH as specified by section 5.1 of ANSI C63.4-2003.

Test Voltage: 120V~60Hz Block diagram of Test setup



5.3 Configuration of The EUT

The EUT was configured according to ANSI C63.4-2003. All interface ports were connected to the appropriate peripherals. All peripherals and cables are listed below.

79 channels are provided to the EUT

Page 9 of 79

Report No: 1310021 Date: 2013-10-15



A. EUT

Device	Manufacturer	Model	FCC ID
Bluetooth Waterproof	Shenzhen BETRUE Technology	BTS05	2AA7L-BTS05
Speaker	Co., Ltd.	D1303	

B. Internal Device

Device	Manufacturer	Model	FCC ID/DOC
N/A			

C. Peripherals

Device	Manufacturer	Model	FCC ID/DOC	Cable

5.4 EUT Operating Condition

Operating condition is according to ANSI C63.4 -2003.

- A Setup the EUT and simulators as shown on follow
- B Enable AF signal and confirm EUT active to normal condition

5.5 Power line conducted Emission Limit according to Paragraph 15.107, 15.207

Frequency	Class A Lim	its (dB µ V)	Class B Limits (dB µ V)		
(MHz)	Quasi-peak Level	Average Level	Quasi-peak Level	Average Level	
$0.15 \sim 0.50$	79.0	66.0	66.0~56.0*	56.0~46.0*	
$0.50 \sim 5.00$	73.0	60.0	56.0	46.0	
$5.00 \sim 30.00$	73.0	60.0	60.0	50.0	

Notes:

- 1. *Decreasing linearly with logarithm of frequency.
- 2. The tighter limit shall apply at the transition frequencies

5.6 Test Results

The frequency spectrum from 0.15MHz to 30MHz was investigated. All reading are quasi-peak values with a resolution bandwidth of 9kHz.

Report No: 1310021 Page 10 of 79

Date: 2013-10-15



A: Conducted Emission on Live Terminal (150kHz to 30MHz)

EUT Operating Environment


Temperature: 26°C Humidity: 65%RH Atmospheric Pressure: 101 KPa

EUT set Condition: Charging and Keep Transmitting

Equipment Level: Class B

Results: PASS

Please refer to following diagram for individual



Frequency	Line	Reading(dBμV)	Limit(dBμV)
(MHz)	Line	Quasi-peak	Average	Quasi-peak	Average
0.153	Live	57.30	33.80	65.81	55.81
0.179	Live	54.43	37.63	64.50	54.50
2.621	Live	40.25	29.05	56.00	46.00

Report No: 1310021 Page 11 of 79

Date: 2013-10-15



B: Conducted Emission on Neutral Terminal (150kHz to 30MHz)

EUT Operating Environment


Temperature: 26°C Humidity: 65%RH Atmospheric Pressure: 101 KPa

EUT set Condition: Charging and Keep Transmitting

Equipment Level: Class B

Results: Pass

Please refer to following diagram for individual



Frequency	Line	Reading(dBμV)	Limit(dBμV)
(MHz)	Line	Quasi-peak	Average	Quasi-peak	Average
0.150	Neutral	58.30	41.20	65.96	55.96
0.182	Neutral	53.93	41.23	64.38	54.38
2.526	Neutral	41.51	26.11	56.00	46.00

Report No: 1310021 Page 12 of 79

Date: 2013-10-15



6 Radiated Emission Test

- 6.1 Test Method and test Procedure:
- (1) The EUT was tested according to ANSI C63.4 –2003. The radiated test was performed at Timeway Laboratory. This site is on file with the FCC laboratory division, Registration No.899988
- (2) The EUT, peripherals were put on the turntable which table size is 1m x 1.5 m, table high 0.8 m. All set up is according to ANSI C63.4-2003.
- (3) The frequency spectrum from 30 MHz to 1 GHz was investigated. All readings from 30 MHz to 1 GHz are quasi-peak values with a resolution bandwidth of 120 kHz. For measurement above 1GHz, peak values with RBW=VBW=1MHz and PK detector. AV value with RBW=1MHz, VBW=10Hz and PK detector. Measurements were made at 3 meters.
- (4) The antenna high is varied from 1 m to 4 m high to find the maximum emission for each frequency.
- (5) Maximizing procedure was performed on the six (6) highest emissions to ensure EUT compliance is with all installation combinations. All data was recorded in the peak detection mode. Quasi-peak readings was performed only when an emission was found to be marginal (within -4 dB of specification limit), and are distinguished with a "QP" in the data table.
- (6) The antenna polarization : Vertical polarization and Horizontal polarization.

Block diagram of Test setup Distance = 3m Computer Pre -Amplifier EUT Turn-table Receiver

- 6.2 Configuration of The EUT
 Same as section 5.3 of this report
- 6.3 EUT Operating Condition
 Same as section 5.4 of this report.

Report No: 1310021 Page 13 of 79

TIMEWAY Statistics Lags

6.4 Radiated Emission Limit

Date: 2013-10-15

All emission from a digital device, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strength specified below:

Frequencies in restricted band are complied to limit on Paragraph 15.109. 15.209

Frequency Range (MHz)	Distance (m)	Field strength (dB µ V/m)
30-88	3	40.0
88-216	3	43.5
216-960	3	46.0
Above 960	3	54.0

Note:

- 1. RF Voltage $(dBuV) = 20 \log RF \text{ Voltage } (uV)$
- 2. In the Above Table, the higher limit applies at the band edges.
- 3. Distance refers to the distance in meters between the measuring instrument antenna and the EUT
- 4. This is a handhold device. The radiated emissions should be tested under 3-axes position (Lying, Side, and Stand), After pre-test. It was found that the worse radiated emission was get at the lying position.
- 5. After pre-scanning, **GFSK** was the worse case. The test data of this mode was recorded.

Report No: 1310021 Page 14 of 79

Date: 2013-10-15



Test result

General Radiated Emission Data and Harmonics Radiated Emission Data

Radiated Emission In Horizontal/ In Vertical (30MHz----1000MHz)

EUT set Condition: Keep Transmitting

Results: Pass


Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB \u03b4 V/m)
132.000	34.22	Н	43.50
198.000	36.81	Н	43.50
165.000	31.50	V	43.50
198.000	33.32	V	43.50

Report No: 1310021 Page 15 of 79

Date: 2013-10-15



Test Figure:



Date: 11.0CT.2013 17:36:22


Report No: 1310021 Page 16 of 79

Date: 2013-10-15



Test Figure:

V



Date: 11.OCT.2013 17:29:49

Report No: 1310021 Page 17 of 79

Date: 2013-10-15



Operation Mode: Transmitting under Low Channel (2402MHz)

	0		
Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB \(\mu \)V/m)
2402	88.98 (PK)	Н	Fundamental Frequency
2402	89.58 (PK)	V	Fundamental Frequency
4804	48.31 (PK)	Н	74(Peak)/ 54(AV)
4804	47.73 (PK)	V	74(Peak)/ 54(AV)
7206		H/V	74(Peak)/ 54(AV)
9608		H/V	74(Peak)/ 54(AV)
12010		H/V	74(Peak)/ 54(AV)
14412		H/V	74(Peak)/ 54(AV)
16814		H/V	74(Peak)/ 54(AV)
19216		H/V	74(Peak)/ 54(AV)
21618		H/V	74(Peak)/ 54(AV)
24020		H/V	74(Peak)/ 54(AV)

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

2. Remark "---" means that the emissions level is too low to be measured

Operation Mode: Transmitting g under Middle Channel (2441MHz)

	0.0	`	<i>'</i>
Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB \mu V/m)
2441	90.78 (PK)	Н	Evendom antal Engavanov
2441	90.52 (PK)	V	Fundamental Frequency
4882	48.23 (PK)	Н	74(Peak)/ 54(AV)
4882	48.54 (PK)	V	74(Peak)/ 54(AV)
7323		H/V	74(Peak)/ 54(AV)
9764		H/V	74(Peak)/ 54(AV)
12205		H/V	74(Peak)/ 54(AV)
14646		H/V	74(Peak)/ 54(AV)
17087		H/V	74(Peak)/ 54(AV)
19528		H/V	74(Peak)/ 54(AV)
21969		H/V	74(Peak)/ 54(AV)
24410		H/V	74(Peak)/ 54(AV)

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

2. Remark "---" means that the emissions level is too low to be measured

Report No: 1310021 Page 18 of 79

Date: 2013-10-15



Operation Mode: Transmitting under High Channel (2480MHz)

Frequency (MHz)	Level@3m (dB \u03bc V/m)	Antenna Polarity	Limit@3m (dB \(\mu \)V/m)
2480	88.56 (PK)	Н	Fundamental Frequency
2480	88.57 (PK)	V	Fundamental Frequency
4960	47.39 (PK)	Н	74(Peak)/ 54(AV)
4960	47.19 (PK)	V	74(Peak)/ 54(AV)
7440		H/V	74(Peak)/ 54(AV)
9920		H/V	74(Peak)/ 54(AV)
12400		H/V	74(Peak)/ 54(AV)
14880		H/V	74(Peak)/ 54(AV)
17360		H/V	74(Peak)/ 54(AV)
19840		H/V	74(Peak)/ 54(AV)
22320		H/V	74(Peak)/ 54(AV)
24800		H/V	74(Peak)/ 54(AV)

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit


^{2.} Remark "---" means that the emissions level is too low to be measured

Report No: 1310021 Date: 2013-10-15




Please refer to the following test plots for details:

Low Channel: Horizontal



Low Channel: Vertical



The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.


In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co .,Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Page 20 of 79


Report No: 1310021 Date: 2013-10-15



Middle Channel: Horizontal



Middle Channel: Vertical




The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.


Report No: 1310021 Date: 2013-10-15



High Channel: Horizontal



High Channel: Vertical



Note: for the radiated emissions above 18G, it is the floor noise.

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co .,Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Report No: 1310021 Page 22 of 79

Date: 2013-10-15



7.0 20dB Bandwidth Measurement

7.1 Regulation

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§ 15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.

7.2 Limits of 20dB Bandwidth Measurement

N/A

7.3 Test Procedure.

- 1. Check the calibration of the measuring instrument (spectrum analyzer) using either an internal calibrator or a known signal from an external generator.
- 2. Set the spectrum analyzer as follows: Span =5MHz, VBW =30kHz, RBW=100kHz, Sweep = auto Detector function = peak ,Trace = max hold
- 3. Measure the highest amplitude appearing on spectral display and record the level to calculate results. 6. Repeat above procedures until all frequencies measured were complete.

7.4 Test Result

Type of Modulation: GFSK

EUT	Bluetooth Waterproof Speaker		Model	BTS05	
Mode	de Keep Transmitting		e Keep Transmitting Input Voltage		DC3.7V
Temperat	ature 24 deg. C,		Humidity	56% RH	
Channel	Channel Frequency (MHz)	20 dB Bandwidth (kHz)	Maximum Limit (kHz)	Pass/ Fail	
Low	2402 858		858		
Middle	2441 840			Pass	
High	2480 840			Pass	


Report No: 1310021 Page 23 of 79

Date: 2013-10-15



Test Figure:

1. Condition: Low Channel




Date: 10.OCT.2013 18:09:41

Report No: 1310021 Page 24 of 79

Date: 2013-10-15



2. Condition: Middle Channel




Date: 10.OCT.2013 18:10:35

Report No: 1310021 Page 25 of 79

Date: 2013-10-15



3. High Channel



Date: 10.OCT.2013 18:11:09

Report No: 1310021 Page 26 of 79

Date: 2013-10-15



Test Result

Type of Modulation: JI/4QPSK

EUT	Bluetooth Waterproof Speaker		Model	BTS05
Mode	Keep Transmitting		Input Voltage	DC3.7V
Temperat	rature 24 deg. C,		Humidity	56% RH
Channel	Channel Frequency (MHz)	20 dB Bandwidth (kHz)	Maximum Limit (kHz)	Pass/ Fail
Low	2402	1218		Pass
Middle	2441	2441 1218		Pass
High	2480 1212			Pass


Report No: 1310021 Page 27 of 79

Date: 2013-10-15



Test Figure:

1. Condition: Low Channel




Date: 11.OCT.2013 10:44:57

Report No: 1310021 Page 28 of 79

Date: 2013-10-15



2. Condition: Middle Channel




Date: 11.OCT.2013 10:44:17

Report No: 1310021 Page 29 of 79

Date: 2013-10-15



3. High Channel



Date: 11.OCT.2013 10:43:19

Report No: 1310021 Page 30 of 79

Date: 2013-10-15



Test Result

Type of Modulation: 8DPSK

EUT	Bluetoo	Bluetooth Waterproof Speaker		Bluetooth Waterproof Speaker Model		BTS05
Mode	Keep Transmitting		Keep Transmitting Input Volta		Input Voltage	DC3.7V
Temperat	ature 24 deg. C,		Humidity	56% RH		
Channel	Channel Frequency (MHz) 20 dB Ban (kHz)		Maximum Limit (kHz)	Pass/ Fail		
Low	2402	1224		Pass		
Middle	2441 1224			Pass		
High	1 2480 1218			Pass		


Report No: 1310021 Page 31 of 79

Date: 2013-10-15



Test Figure:

1. Condition: Low Channel




Date: 10.OCT.2013 18:55:25

Report No: 1310021 Page 32 of 79

Date: 2013-10-15



2. Condition: Middle Channel




Date: 10.OCT.2013 18:56:17

Report No: 1310021 Page 33 of 79

Date: 2013-10-15



3. High Channel



Date: 10.OCT.2013 18:57:02

Report No: 1310021 Page 34 of 79

Date: 2013-10-15



8. Maximum Peak Output Power

8.1 Regulation

According to §15.247(b)(1), for frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5MHz band:0.125 watts. According to §15.247(b)(4), the conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

8.2 Limits of Maximum Peak Output Power

The Maximum Peak Output Power Measurement is 30dBm.

8.3 Test Procedure

- 1. Check the calibration of the measuring instrument (spectrum analyzer) using either an internal calibrator or a known signal from an external generator.
- 2. Set the spectrum analyzer as follows: Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel; RBW > the 20 dB bandwidth of the emission being measured; VBW = RBW=3MHz; Sweep = auto; Detector function = peak; Trace = max hold
- 3. Measure the highest amplitude appearing on spectral display and record the level to calculate results.
- 4. Repeat above procedures until all frequencies measured were complete.

Page 35 of 79

Report No: 1310021 Date: 2013-10-15



8.4Test Results

Type of Modulation: GFSK

EUT	Bluetoot	h Waterproof Speaker	Model		BTS05
Mode Ke		eep Transmitting		ıt Voltage	DC3.7V
Temperatur	re	24 deg. C,	Humidity		56% RH
Channel	Channel Frequency (MHz) Peak Power Output (dBm))	Peak Power Limit (dBm)	Pass/ Fail
Low	2402	-1.17		30	Pass
Middle	2441	-0.38		30	Pass
High 2480 -0.19			30	Pass	

Note: 1. the result basic equation calculation as follow:

Peak Power Output = Peak Power Reading + Cable loss + Attenuator

2. Worse case was recorded

Type of Modulation: J\(J\)/4OPSK

-5F* *						
EUT	Bluetoot	h Waterproof Speaker	Model		BTS05	
Mode Ke		eep Transmitting		t Voltage	DC3.7V	
Temperatur	re	24 deg. C, Humidity		56% RH		
Channel	Channel Frequency (MHz)	Peak Power Output (dBm)	Peak Power Limit (dBm)	Pass/ Fail	
Low	2402	-1.87		30	Pass	
Middle	2441	-1.05		30	Pass	
High	figh 2480 -0.83			30	Pass	

Note: 1. the result basic equation calculation as follow:

Peak Power Output = Peak Power Reading + Cable loss + Attenuator

2. Worse case was recorded

Report No: 1310021 Page 36 of 79

Date: 2013-10-15



Type of Modulation: 8DPSK

EUT	Bluetoot	Bluetooth Waterproof Speaker		Model	BTS05
Mode Ke		eep Transmitting Inp		t Voltage	DC3.7V
Temperatur	re	24 deg. C, Humidity		umidity	56% RH
Channel	Channel Frequency (MHz)	Peak Power Output (dBm)	Peak Power Limit (dBm)	Pass/ Fail
Low	2402	-2.24		30	Pass
Middle	2441	-1.41		30	Pass
High	2480	-1.14		30	Pass

Note: 1. the result basic equation calculation as follow:

Peak Power Output = Peak Power Reading + Cable loss + Attenuator

2. Worse case was recorded

Report No: 1310021 Page 37 of 79

Date: 2013-10-15



9. Carrier Frequency Separation

9.1 Regulation

According to §15.247(a)(1), frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

9.2 Limits of Carrier Frequency Separation

The Maximum Power Spectral Density Measurement is 25kHz or two-thirds of the 20dB bandwidth of the hopping Channel which is great.

9.3 Test Procedure

- 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- 2. Set the spectrum analyzer as follows: Span = wide enough to capture the peaks of two adjacent channels: Resolution (or IF) Bandwidth (RBW) \geq 1% of the span; Video (or Average) Bandwidth (VBW) \geq RBW; Sweep = auto; Detector function = peak; Trace = max hold
- 3. Measure the separation between the peaks of the adjacent channels using the marker-delta function.
- 4. Repeat above procedures until all frequencies measured were complete.

Page 38 of 79

Report No: 1310021 Date: 2013-10-15




9.4Test Result

Type of Modulation: GFSK

EUT	Bluetooth Waterproo	Model		BTS05		
Mode	Hopping On		Input Voltage		DC3.7V	
Temperature	24 deg. C,		Humidity	56% RH		
Carrier Frequency Separation		Limit		Pass/ Fail		
1000kHz		≥ 25 kHz or 2	≥ 25 kHz or 2/3 of 20 dB bandwidth		Pass	

Test Plots



Date: 10.OCT.2013 18:28:04

Page 39 of 79


Report No: 1310021 Date: 2013-10-15



Type of Modulation: JI/4QPSK

EUT	Bluetooth Waterproo	of Speaker	Model		BTS05	
Mode	Hopping On		Input Voltage		DC3.7V	
Temperature	24 deg. C,		Humidity		56% RH	
Carrier Frequency Separation		Limit		Pass/ Fail		
1000kHz		≥ 25 kHz or 2	2/3 of 20 dB bandy	width	Pass	

Test Plots



Date: 11.OCT.2013 11:45:43

Page 40 of 79


Report No: 1310021 Date: 2013-10-15



Type of Modulation: 8DPSK

EUT	Bluetooth Waterproo	Model		BTS05		
Mode	Hopping On		Input Voltage		DC3.7V	
Temperature	24 deg. C,		Humidity	56% RH		
Carrier Frequency Separation			Limit		Pass/ Fail	
1000kHz		≥ 25 kHz or 2	2/3 of 20 dB bands	width	Pass	

Test Plots



Date: 10.OCT.2013 18:33:11

Report No: 1310021 Page 41 of 79

Date: 2013-10-15



10. Number of Hopping Channels

10.1 Regulation

According to §15.247(a)(1)(iii), frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used. According to §15.247(b)(1), for frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.

10.2 Limits of Number of Hopping Channels

The frequency hopping systems in the 2400-2483.5MHz band shall use at least 15 channels.

10.3 Test Procedure

- 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- 2. Set the spectrum analyzer as follows: Span = the frequency band of operation; RBW=100 kHz, VBW= 100 kHz;

Sweep = auto; Detector function = peak; Trace = max hold

3. Record the number of hopping channels.

Report No: 1310021 Page 42 of 79

Date: 2013-10-15




10.4Test Result

Type of Modulation: GFSK

EUT	Bluetooth Waterproof Speaker		Model			BTS05
Mode		Hopping On		Input Voltage		DC3.7V
Temperature		24 deg. C,		Humidity		56% RH
Operating Frequ	Operating Frequency Number of hopping channels Limi		t	Pass/ Fail		
2402-2480MHz 79		79		≥ 15		Pass

Test Plot



Date: 10.OCT.2013 18:23:26

Report No: 1310021 Page 43 of 79


Date: 2013-10-15



Type of Modulation: JI/4QPSK

EUT	Bluetooth Waterproof Speaker		M	Model		BTS05
Mode		Hopping On Input Voltage DC3.7		DC3.7V		
Temperature		24 deg. C,	Hur	umidity 56% RH		56% RH
Operating Frequ	iency	Number of hopping cha	nnels	Limit		Pass/ Fail
2402-2480M	Hz	79		≥ 15 Pa		Pass

Test Plot



Date: 11.OCT.2013 11:34:22

Report No: 1310021 Page 44 of 79


Date: 2013-10-15



Type of Modulation: 8DPSK

EUT	Blueto	ooth Waterproof Speaker	er Model BTS05			BTS05	
Mode	Hopping On		Input Voltage		ut Voltage DC3.7V		
Temperature		24 deg. C,	Humidity		idity 56% RH		
Operating Frequ	iency	Number of hopping cha	nnels	Limit I		Pass/ Fail	
2402-2480M	Hz	79	•	≥ 15 Pass		Pass	

Test Plot



Date: 10.OCT.2013 18:36:25

Report No: 1310021 Page 45 of 79

Date: 2013-10-15



11. Time of Occupancy (Dwell Time)

11.1 Regulation

According to §15.247(a)(1)(iii), frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

11.2 Limits of Carrier Frequency Separation

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed

11.3 Test Procedure

- 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- 2. Set the spectrum analyzer as follows: Span = zero span, centered on a hopping channel; RBW = 1 MHz; VBW
- ≥ RBW; Sweep = as necessary to capture the entire dwell time per hopping channel; Detector function = peak; Trace = max hold
- 3. Measure the dwell time using the marker-delta function.
- 4. Repeat above procedures until all frequencies measured were complete.
- 5. Repeat this test for different modes of operation (e.g., data rate, modulation format, etc.), if applicable.

Report No: 1310021 Page 46 of 79

Date: 2013-10-15



11.4 Test Result

Type of Modulation: GFSK

EUT	Bluetooth Wate	rproof Speaker	Model]	BTS05
Mode	Keep Transmitting Input Voltage		Input Voltage	DC3.7V	
Temperatur	re 24 de	g. C,	Humidity	56% RH	
Channel	Reading	Норі	ng Rate	Actual	Limit
Low	2.98	266.6	67 hop/s	0.318	0.4s
Middle	2.96	266.6	67 hop/s	0.316	0.4s
High	2.98	266.6	67 hop/s	0.318	0.4s

Actual = Reading \times (Hopping rate / Number of channels) \times Test period, Test period = 0.4 [seconds / channel] \times 79 [channel] = 31.6 [seconds] NOTE: The EUT makes worst case 1600 hops per second or 1 time slot has a length of 625 μ s with 79 channels. A DH5 Packet needs 5 time slot for transmitting and 1 time slot for receiving. Then the EUT makes worst case 266.667 hops per second with 79 channels.

Note: DH5 was the worse case


Report No: 1310021 Page 47 of 79

Date: 2013-10-15



Test Plots:

Low Channel:




Date: 10.OCT.2013 18:14:55

Report No: 1310021 Page 48 of 79

Date: 2013-10-15



Middle Channel:




Date: 10.OCT.2013 18:15:41

Report No: 1310021 Page 49 of 79

Date: 2013-10-15



High Channel



Date: 10.OCT.2013 18:16:26

Report No: 1310021 Page 50 of 79

Date: 2013-10-15



Test Result

Type of Modulation: $\pi/4QPSK$

EUT	Bluetooth Water	rproof Speaker	Model	-	BTS05
Mode	Keep Tran	Input Voltage		Ι	DC3.7V
Temperatur	re 24 de	g. C,	Humidity	5	66% RH
Channel	Reading	Норі	ng Rate	Actual	Limit
Low	2.96	266.6	67 hop/s	0.316	0.4s
Middle	2.98	266.6	67 hop/s	0.318	0.4s
High	2.98	266.6	67 hop/s	0.318	0.4s

Actual = Reading \times (Hopping rate / Number of channels) \times Test period ,Test period = 0.4 [seconds / channel] \times 79 [channel] = 31.6 [seconds] NOTE: The EUT makes worst case 1600 hops per second or 1 time slot has a length of 625 μ s with 79 channels. A DH5 Packet needs 5 time slot for transmitting and 1 time slot for receiving. Then the EUT makes worst case 266.667 hops per second with 79 channels.

Note: DH5 was the worse case


Report No: 1310021 Page 51 of 79

Date: 2013-10-15



Test Plots:

Low Channel:




Date: 11.OCT.2013 10:37:35

Report No: 1310021 Page 52 of 79

Date: 2013-10-15



Middle Channel:




Date: 11.OCT.2013 10:36:46

Report No: 1310021 Page 53 of 79

Date: 2013-10-15



High Channel



Date: 11.0CT.2013 10:38:13

Report No: 1310021 Page 54 of 79

Date: 2013-10-15



Type of Modulation: 8DPSK

EUT	Bluetooth Water	Bluetooth Waterproof Speaker		del	BTS05	
Mode	Keep Tra	nsmitting	Input Voltage		DC3.7V	
Temperatur	re 24 de	eg. C,	Humidity		dity 56% RH	
Channel	Reading	Hoping Ra	ate		Actual	Limit
Low	2.98	266.667 hc	pp/s		0.318	0.4s
Middle	2.98	266.667 hop/s			0.318	0.4s
High	2.96	266.667 hc	pp/s		0.316	0.4s

Actual = Reading \times (Hopping rate / Number of channels) \times Test period, Test period = 0.4 [seconds / channel] \times 79 [channel] = 31.6 [seconds] NOTE: The EUT makes worst case 1600 hops per second or 1 time slot has a length of 625 μ s with 79 channels. A DH5 Packet needs 5 time slot for transmitting and 1 time slot for receiving. Then the EUT makes worst case 266.667 hops per second with 79 channels.

Note: DH5 was the worse case


Report No: 1310021 Page 55 of 79

Date: 2013-10-15



Test Plots:

Low Channel:




Date: 10.OCT.2013 18:58:59

Report No: 1310021 Page 56 of 79

Date: 2013-10-15



Middle Channel:




Date: 10.OCT.2013 18:59:40

Report No: 1310021 Page 57 of 79

Date: 2013-10-15



High Channel



Date: 10.OCT.2013 19:00:14


Report No: 1310021 Page 58 of 79

Date: 2013-10-15



12 Out of Band Measurement

12.1 Test Setup



The restricted band requirement based on radiated emission test; please see the clause 6 for the test setup

12.2 Limits of Out of Band Emissions Measurement

- 1. Below –20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).
- 2. Fall in the restricted bands listed in section 15.205. The maximum permitted average field strength is listed in section 15.209.

12.3 Test Procedure

For signals in the restricted bands above and below the 2.4-2.483GHz allocated band a measurement was made of Radiated emission test. Peak values with RBW=VBW=1MHz and PK detector.

For bandage test, the spectrum set as follows: RBW=VBW=100 kHz. A conducted measurement used

Note: 1. For band-edge measurement, the frequency from 30MHz-25GHz was tested. And It met the FCC rule.

2. This is a handhold device. The radiated emissions should be tested under 3-axes position (Lying, Side, and Stand), After pre-test. It was found that the worse radiated emission was get at the lying position.

Page 59 of 79

Report No: 1310021 Date: 2013-10-15




Type of Modulation: GFSK

12.4 Out of Band Test Result

Product:	Bluetoot	h Waterproof Speaker	Test Mode:	Low Channel
Mode	Kee	ping Transmitting	Input Voltage	DC3.7V
Temperature	24 deg. C		Humidity	56% RH
Test Result:		Pass	Detector	PK
The Max. FS in	PK (dBµV/m)	38.2		$74(dB\mu V/m)$
Restrict Band	$AV(dB\mu V/m)$	BμV/m)		54(dBμV/m)
2390MHz				

Test Figure:



Date: 10.OCT.2013 18:17:29

Page 60 of 79

Report No: 1310021 Date: 2013-10-15




Type of Modulation: GFSK

12.4 Out of Band Test Result

Product:	Bluetoot	h Waterproof Speaker	Test Mode:	High Channel
Mode	Keej	ping Transmitting	Input Voltage	DC3.7V
Temperature		24 deg. C,		56% RH
Test Result:		Pass	Detector	PK
The Max. FS in	PK (dBμV/m)	41.9		$74(dB\mu V/m)$
Restrict Band	$AV(dB\mu V/m)$		Limit	$54(dB\mu V/m)$
2483.5MHz				

Test Figure:



Date: 10.OCT.2013 18:21:13

Report No: 1310021 Page 61 of 79

Date: 2013-10-15




Type of Modulation: GFSK

12.4 Out of Band Test Result

Product:	Bluetoot	h Waterproof Speaker	Test Mode:	Hopping mode
Mode		Hopping On	Input Voltage	DC3.7V
Temperature		24 deg. C,	Humidity	56% RH
Test Result:		Pass	Detector	PK
The Max. FS in	PK (dBμV/m)	37.2		$74(dB\mu V/m)$
Restrict Band	AV(dBμV/m)	AV(dBμV/m)		$54(dB\mu V/m)$
2390MHz				

Test Figure:



Date: 10.OCT.2013 18:19:24

Report No: 1310021 Date: 2013-10-15




Type of Modulation: GFSK

12.4 Out of Band Test Result

Product:	Bluetooth Waterproof Speaker		Test Mode:	Hopping mode
Mode	Hopping On		Input Voltage	DC3.7V
Temperature	24 deg. C,		Humidity	56% RH
Test Result:	Pass		Detector	PK
The Max. FS in	PK (dBμV/m)	39.6		$74(dB\mu V/m)$
Restrict Band	AV(dBμV/m)		Limit	$54(dB\mu V/m)$
2483.5MHz				

Test Figure:



Date: 10.OCT.2013 18:20:40

Page 63 of 79

Report No: 1310021 Date: 2013-10-15




Type of Modulation: JI/4QPSK

12.4 Out of Band Test Result

Product:	Bluetooth Waterproof Speaker		Test Mode:	Low Channel
Mode	Keeping Transmitting		Input Voltage	DC3.7V
Temperature	24 deg. C		Humidity	56% RH
Test Result:	Pass		Detector	PK
The Max. FS in	PK (dBμV/m) 37.5			74(dBμV/m)
Restrict Band	AV(dBμV/m)		Limit	54(dBμV/m)
2390MHz				

Test Figure:



Date: 11.OCT.2013 10:45:56

Page 64 of 79

Report No: 1310021 Date: 2013-10-15




Type of Modulation: JI/4QPSK

12.4 Out of Band Test Result

Product:	Bluetooth Waterproof Speaker		Test Mode:	High Channel
Mode	Keeping Transmitting		Input Voltage	DC3.7V
Temperature	24 deg. C,		Humidity	56% RH
Test Result:	Pass		Detector	PK
The Max. FS in	PK (dBμV/m) 41.2			$74(dB\mu V/m)$
Restrict Band	AV(dBμV/m)		Limit	$54(dB\mu V/m)$
2483.5MHz				

Test Figure:



Date: 11.0CT.2013 10:56:36

Page 65 of 79

Report No: 1310021 Date: 2013-10-15




Type of Modulation: $\pi/4$ QPSK

12.4 Out of Band Test Result

Product:	Bluetoot	h Waterproof Speaker	Test Mode:	Hopping mode
Mode	Hopping On		Input Voltage	DC3.7V
Temperature	24 deg. C,		Humidity	56% RH
Test Result:	Pass		Detector	PK
The Max. FS in	PK (dBμV/m) 37.2			$74(dB\mu V/m)$
Restrict Band	AV(dBμV/m)		Limit	54(dBµV/m)
2390MHz				

Test Figure:



Date: 11.0CT.2013 10:51:27

Report No: 1310021 Date: 2013-10-15




Type of Modulation: $\pi/4$ QPSK

12.4 Out of Band Test Result

Product:	Bluetoot	h Waterproof Speaker	Test Mode:	Hopping mode
Mode	Hopping On		Input Voltage	DC3.7V
Temperature	24 deg. C,		Humidity	56% RH
Test Result:	Pass		Detector	PK
The Max. FS in	PK (dBμV/m) 40.8			$74(dB\mu V/m)$
Restrict Band	AV(dBμV/m)		Limit	54(dBμV/m)
2483.5MHz				

Test Figure:



Date: 11.OCT.2013 10:55:28

Page 67 of 79

Report No: 1310021 Date: 2013-10-15




Type of Modulation: 8DPSK

12.4 Out of Band Test Result

Product:	Bluetooth Waterproof Speaker		Test Mode:	Low Channel
Mode	Keeping Transmitting		Input Voltage	DC3.7V
Temperature	24 deg. C		Humidity	56% RH
Test Result:	Pass		Detector	PK
The Max. FS in	PK (dBμV/m) 38.3			$74(dB\mu V/m)$
Restrict Band	AV(dBμV/m)		Limit	54(dBµV/m)
2390MHz				

Test Figure:



Date: 10.OCT.2013 18:45:15

Page 68 of 79

Report No: 1310021 Date: 2013-10-15




Type of Modulation: 8DPSK

12.4 Out of Band Test Result

Product:	Bluetooth Waterproof Speaker		Test Mode:	High Channel
Mode	Keeping Transmitting		Input Voltage	DC3.7V
Temperature	24 deg. C,		Humidity	56% RH
Test Result:	Pass		Detector	PK
The Max. FS in	PK (dBμV/m) 40.5			$74(dB\mu V/m)$
Restrict Band	AV(dBμV/m)		Limit	54(dBμV/m)
2483.5MHz				

Test Figure:



Date: 10.OCT.2013 18:44:41

Report No: 1310021 Page 69 of 79

Date: 2013-10-15




Type of Modulation: 8DPSK

Out of Band Test Result 12.4

Product:	Bluetoot	h Waterproof Speaker	Test Mode:	Hopping mode
Mode	Hopping On		Input Voltage	DC3.7V
Temperature	24 deg. C,		Humidity	56% RH
Test Result:	Pass		Detector	PK
The Max. FS in	PK (dBμV/m) 37.4			$74(dB\mu V/m)$
Restrict Band	AV(dBμV/m)		Limit	$54(dB\mu V/m)$
2390MHz				

Test Figure:





Date: 10.OCT.2013 18:47:35

Page 70 of 79

Report No: 1310021 Date: 2013-10-15




Type of Modulation: 8DPSK

12.4 Out of Band Test Result

Product:	Bluetooth Waterproof Speaker		Test Mode:	Hopping mode
Mode	Hopping On		Input Voltage	DC3.7V
Temperature	24 deg. C,		Humidity	56% RH
Test Result:	Pass		Detector	PK
The Max. FS in	PK (dBμV/m) 41.0			$74(dB\mu V/m)$
Restrict Band	AV(dBμV/m)		Limit	54(dBμV/m)
2483.5MHz				

Test Figure:



Date: 10.OCT.2013 18:44:24

Report No: 1310021 Page 71 of 79

Date: 2013-10-15



13.0 Antenna Requirement

13.1 Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (b), if transmitter antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the mount in dB that the directional gain of the antenna exceeds 6 dBi.

13.2 Antenna Connected constructions

PCB Printed Antenna used. The maximum Gain of this antenna is 0dBi

Report No: 1310021 Page 72 of 79

Date: 2013-10-15




15.0 FCC ID Label

FCC ID: 2AA7L-BTS05

This device complies with part 15 of the FCC rules. Operation is subject to the following two conditions (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

The label must not be a stick-on paper label. The label on these products must be permanently affixed to the product and readily visible at the time of purchase and must last the expected lifetime of the equipment not be readily detachable.

Mark Location:



Report No: 1310021 Page 73 of 79

Date: 2013-10-15



16.0 Photo of testing

Conducted Emission Test Setup:




Report No: 1310021 Date: 2013-10-15



Radiated Emission Test Setup:





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it. or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co.,Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Page 75 of 79

Report No: 1310021 Date: 2013-10-15



Photo for the EUT





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co., Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co .,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co., Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co .,Ltd reserves the rights to withdraw it and to

adopt any other remedies which may be appropriate.


Page 76 of 79

Report No: 1310021 Date: 2013-10-15



Photo for the EUT





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co., Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co .,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co., Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co .,Ltd reserves the rights to withdraw it and to

adopt any other remedies which may be appropriate.

Page 77 of 79

Report No: 1310021 Date: 2013-10-15



Photo for the EUT





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier of others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co.,Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.


Page 78 of 79

Report No: 1310021 Date: 2013-10-15



Photo for the EUT





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it. or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.


of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co.,Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Report No: 1310021 Date: 2013-10-15



Photo for the EUT





End of the report

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it. or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier of others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co.,Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.