

PMX-5CAN

FREQUENCY RANGE: FM 87.5 - 107.9 MHz **SPEAKER IMPEDANCE:** 2 - 8 OHMS
 AM 526.5 - 1606.5 KHz
 WB 162.4 - 162.55 KHz

OPTIONAL PMX-CAR CAN BUS

RED (ZONE 2 LINE OUT FRONT) / WHITE (ZONE 2 LINE OUT LEFT)

RED (AUX IN FRONT) / WHITE (AUX IN LEFT) / SHIELD (OPTIONAL)

FMIC

ANTENNA

SUB-W OUT (RED / WHITE)


REAR LINE OUT (RED / WHITE)

FRONT LINE OUT (RED / WHITE)

USB

15A FUSE


REMOTE CABLE



SECTION A **SECTION B**



Pin #	WIRE COLOR	WIRE DESCRIPTION	AWG
1	GREEN	SPEAKER REAR LEFT (-)	20
2	GREEN/BLACK	SPEAKER REAR LEFT (+)	20
3	ORANGE/WHITE	ILLUMINATION INPUT	20
4	WHITE	SPEAKER FRONT LEFT (-)	20
5	WHITE/BLACK	SPEAKER FRONT LEFT (+)	20
6	RED	+12V ACC (IGN SWITCH)	16
7	GREY	SPEAKER FRONT RIGHT (-)	20
8	GREY/BLACK	SPEAKER FRONT RIGHT (+)	20
9	BLUE/WHITE	REMOTE (-)	20
10	PURPLE	SPEAKER REAR RIGHT (-)	20
11	PURPLE/BLACK	SPEAKER REAR RIGHT (+)	20
12	BLACK	GROUND (-)	16

12V GROUND



S/N: 416040001-73

FCC ID: 2AAT8-PMX-5CAN
 IC: 27141-PMX5CAN
 Rockford Corporation 600 South Rockford
 Drive Tempe Arizona United States

MADE IN CHINA

THIS DEVICE COMPLIES WITH PART 15 OF THE FCC RULES AND REGULATIONS. OPERATION IS SUBJECT TO THE FOLLOWING TWO CONDITIONS:

1) THE DEVICE MAY NOT CAUSE HARMFUL INTERFERENCE, AND

2) THE DEVICE MUST ACCEPT ANY INTERFERENCE RECEIVED, INCLUDING INTERFERENCE THAT MAY CAUSE UNDESIRABLE OPERATION