

moshi

SnapTo car mount with Wireless Charging

User Manual

Model: 99MO122002

- Package Contents

- 1 x SnapTo Car Mount with Wireless Charging
- 1 x USB-C to USB-A Cable
- 2 x SnapTo Tabs

- Install the SnapTo tabs

- Remove the plastic placeholder tabs from your Moshi case.
- Peel the adhesive liner from the SnapTo metal tab.
- Place the tab into your case and press firmly for 30 seconds.
- Repeat for the 2nd tab.

- How to install the SnapTo Car Mount

- Vent installation
 - i. Remove the SnapTo Car Mount with Wireless Charging from its dashboard adapter.
 - ii. Connect the included cable into the USB-C port on the bottom of the wireless charger, then plug the other end into the USB-A port located in your car.
 - * Note 1: For older vehicles, consider using a high-output USB-A car charger (10 W recommended for fast-charging, not included) for better performance.
 - * Note 2: A QuickCharge™ 9V charger is required to enable the fast-charging protocols of Apple (7.5 W) and Samsung (9 W).
 - iii. Clip the mount to your preferred vent. Note: the mount can easily be moved from vehicle to vehicle.
- Dashboard installation. The supplied dashboard adapter allows you to install the SnapTo Car Mount on a flat surface*.
 - i. Select a flat mounting location that keeps your phone easily viewable and safe. Make sure the mounting surface is clean and dry.
 - ii. Peel off the adhesive liner from the bottom of the dashboard adapter.
 - iii. Firmly press the adapter onto the clean and dry mounting surface for 30 seconds.
 - iv. Wait 24 hours for the adhesive to fully set.

- v. After 24 hours has passed, insert the mount into the dashboard adapter and adjust to your preferred viewing angle.

* Note: The dashboard adapter's automotive-grade adhesive can only be used once and is semi-permanent. Carefully select your mounting location. If you need to remove the adapter, visit 3M's website for instructions:

<http://bit.ly/2G6lacj>.

- Charging automatically begins when you connect your phone to the charger.
 - LED behavior:
 - i. Off: Not charging
 - ii. Breathing light: Charging
 - iii. Steady on: Fully charged
 - iv. Flashing: Foreign Object Detection error
 - Foreign Object Detection Troubleshooting:
 - i. Remove any metal objects like coins or keys between your device and SnapTo Car Mount with Wireless Charging.
 - ii. Unplug the power adapter for SnapTo Car Mount with Wireless Charging then plug it in again.
 - iii. If the problem still exists, please contact support@moshi.com.

- Wireless Charging Performance
 - Note: DO NOT DIRECT WARM OR HOT AIR ONTO THE WIRELESS CHARGER WHILE IT IS ATTACHED TO THE VENT. This could decrease charging efficiency or damage the car mount and attached device. When running the vehicle's heater, completely close the vent the mount is attached to, or direct the warm air out of the vehicle's lower vents, entirely away from the upper vents.

FCC Interference Statement

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no

guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

FCC Caution: To assure continued compliance, any changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate this equipment. (Example – use only shielded interface cables when connecting to computer or peripheral devices).

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

FCC Radiation Exposure Statement

This equipment complies with FCC radiation exposure limits set forth for an uncontrolled environment.

This equipment should be installed and operated with a minimum distance of 20 centimeters between the radiator and your body.

This transmitter must not be co-located or operating in conjunction with any other antenna or transmitter.

IC

This device complies with Industry Canada licence-exempt RSS standard(s). Operation is subject to the following two conditions: (1) this device may not cause interference, and (2) this device must accept any interference, including interference that may cause undesired operation of the device.