

Maximum Permissible Exposure

FCC ID : 2AA7Y-MOSHIQI006
Equipment : Lounge Q Wireless Charging Stand
Brand Name : moshi
Model Name : 99MO022218
Applicant : Aevoe Inc.
3F, No. 42, Sec. 2, Zhongshan N. Rd., Zhongshan
Dist., Taipei City 104, Taiwan
Manufacturer : Powergene Technology Co., Ltd. Taiwan Branch
1F-5, No.1, Wuquan 1st Rd., Xinzhuang Dist.,
New Taipei City, Taiwan
Standard : 47 CFR Part 2.1091

The product was received on Apr. 01, 2020, and testing was started from Apr. 13, 2020 and completed on Apr. 13, 2020. We, SPORTON INTERNATIONAL INC. Hsinhua Laboratory, would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.10-2013 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. Hsinhua Laboratory, the test report shall not be reproduced except in full.



Approved by: Allen Lin

SPORTON INTERNATIONAL INC. Hsinhua Laboratory

No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333411, Taiwan (R.O.C.)



Table of Contents

HISTORY OF THIS TEST REPORT3

1 HUMAN EXPOSURE ASSESSMENT5

1.1 Maximum Permissible Exposure5

1.2 Testing Applied Standards5

1.3 Testing Location Information6

1.4 Support Equipment.....6

1.5 The Worst Condition.....7

1.6 Test Method.....7

1.7 Test Setup8

1.8 Result of Maximum Permissible Exposure.....9

2 TEST EQUIPMENT AND CALIBRATION DATA10

Appendix A. Test Photos A1

Photographs of EUT V01



Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
1.5	-	Maximum Permissible Exposure	PASS	-

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

None.

Reviewed by: Sam Tasi

Report Producer: Ann Hou

1 Human Exposure Assessment

1.1 Maximum Permissible Exposure

1.1.1 Limit of Maximum Permissible Exposure

Limits for Occupational / Controlled Exposure				
Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f ²)*	6
30-300	61.4	0.163	1.0	6
300-1500	-	-	F/300	6
1500-100,000	-	-	5	6
Limits for General Population / Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f ²)*	30
30-300	27.5	0.073	0.2	30
300-1500	-	-	F/1500	30
1500-100,000	-	-	1.0	30
Note 1: f = frequency in MHz ; *Plane-wave equivalent power density				
Note 2: For the applicable limit, see FCC 1.1310.				

1.2 Testing Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR Part 2.1091

The following reference test guidance is not within the scope of accreditation of TAF:

- ♦ ANSI C63.10-2013



1.3 Testing Location Information

Test Lab. : Sporton International Inc. Hsinhua Laboratory				
<input checked="" type="checkbox"/> Hsinhua (TAF: 3785)	ADD: No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333411, Taiwan (R.O.C.)			
	TEL: 886-3-327-3456		FAX: 886-3-327-0973	
Test site Designation No. TW3785 with FCC.				
Test Condition	Test Site No.	Test Engineer	Test Environment	Test Date
RF Conducted	TH01-HY	Barry	24.2~25.3°C / 55~61%	13/Apr/2020
<input type="checkbox"/> Wen 33rd. St. (TAF: 3785)	ADD: No.14-1, Ln. 19, Wen 33rd St., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.)			
	TEL: 886-3-318-0787		FAX: 886-3-318-0287	
Test site Designation No. TW0008 with FCC.				

1.4 Support Equipment

Support Equipment				
No.	Equipment	Brand Name	Model Name	FCC ID
1	Mobile Phone	APPLE	A1905	DoC
2	AC adapter	Moshi	-	-

Note: Support equipment No. 2 were provided by customer.




1.5 The Worst Condition

Ancillary Equipment	Charging Condition	Worst Charging Condition
Mobile Phone	Charging Mode	Low power<25%

1.6 Test Method

Test Method	
<input checked="" type="checkbox"/>	Performed aggregate both leakage H-field at surrounding the device from all simultaneous transmitting coils.
<input checked="" type="checkbox"/>	During testing, the EUT was placed on a non-conductive table top and the ancillary equipment (e.g., mobile phone) was placed on the EUT for charging. Maximum E-field and H-field measurements were tested 15cm and 20cm from each side of the EUT. Along the side of the EUT to center of E-field probe and H-field probe were positioned at the location to search maximum field strength.
<input checked="" type="checkbox"/>	E-field transfer to H-field
-	$E\text{-field} = Z_0 \times H\text{-field}$ $H\text{-field} = E\text{-field} \div Z_0$ Where $Z_0 = \text{Free Space Impedance} = 377\Omega$

1.7 Test Setup



Note1 : find worst position for each axis.

Note2 : This shall be measured as the distance from the edge of the device to the center of the measurement probe.

1.8 Result of Maximum Permissible Exposure

Maximum Permissible Exposure				
Charging Condition	Separation	Probe from EUT Side	E-field (V/m)	H-field (A/m)
Low power<25%	15cm	Left	0.69	0.002
Low power<25%	15cm	Right	0.83	0.002
Low power<25%	15cm	Top	0.66	0.002
Low power<25%	15cm	Bottom	0.61	0.002
Low power<25%	20cm	Y-axis above EUT	0.96	0.003
Limit			614	1.63
Margin Limit (%)			0.16%	0.16%



2 Test Equipment and Calibration Data

Instrument for Conducted Test

Instrument	Manufacturer	Model No.	Serial No.	Spec.	Calibration Date	Calibration Due Date
B-Field Probe	Narda Safety Test Solutions GmbH	B-Field Probe 100 cm ²	M-0652	50Hz~400kHz	20/Jul/2018	19/Jul/2020
Exposure Level Tester	Narda Safety Test Solutions GmbH	ELT-400	N-0210	100kHz~3MHz	20/Jul/2018	19/Jul/2020
Probe EF	Narda Safety Test Solutions GmbH	0391 E-Field	D-0667	0.1MHz ~ 3GHz	20/Jul/2018	19/Jul/2020
Broadband Field Meter	Narda Safety Test Solutions GmbH	NBM-550	E-0847	0.1MHz ~ 3GHz	20/Jul/2018	19/Jul/2020