

FCC Radio Test Report

FCC ID: 2AA7Y-SPATIA

This report concerns (check one): Original Grant Class II Change

Project No. : 1407010
Equipment : WIRELESS SPEAKER SYSTEM
Model Name : Spatia
Applicant : Aevoe Inc.
Address : 14F.-1, No. 456, Section 4, Xinyi Road, Xinyi District, Taipei City, TAIWAN.


Date of Receipt : Jul. 09, 2014
Date of Test : Jul. 09, 2014 ~ Oct.15, 2014
Issued Date : Oct.16, 2014
Tested by : BTL Inc.

Testing Engineer :




(Josh Lin)

Technical Manager :



(Jeff Yang)

Authorized Signatory :



(Andy Chiu)

B T L I N C .

B1, No. 37, Lane 365, YangGuang St.
NeiHu District, Taipei City 114, Taipei, Taiwan.
TEL: +886-2-2657-3299 FAX: +886-2-2657-3331

Declaration

BTL represents to the client that testing is done in accordance with standard procedures as applicable and that test instruments used has been calibrated with the standards traceable to National Measurement Laboratory (**NML**) of **R.O.C**, or National Institute of Standards and Technology (**NIST**) of **U.S.A**.

BTL's reports apply only to the specific samples tested under conditions. It is manufacture's responsibility to ensure that additional production units of this model are manufactured with the identical electrical and mechanical components. **BTL** shall have no liability for any declarations, inferences or generalizations drawn by the client or others from **BTL** issued reports.

BTL's reports must not be used by the client to claim product endorsement by the authorities or any agency of the Government.

This report is the confidential property of the client. As a mutual protection to the clients, the public and **BTL-self**, extracts from the test report shall not be reproduced except in full with **BTL's** authorized written approval.

BTL's laboratory quality assurance procedures are in compliance with the **ISO Guide 17025** requirements, and accredited by the conformity assessment authorities listed in this test report.

Limitation

For the use of the authority's logo is limited unless the Test Standard(s)/Scope(s)/Item(s) mentioned in this test report is (are) included in the conformity assessment authorities acceptance respective.

Table of Contents	Page
1 . CERTIFICATION	6
2 . SUMMARY OF TEST RESULTS	7
2.1 TEST FACILITY	8
2.2 MEASUREMENT UNCERTAINTY	8
3 . GENERAL INFORMATION	9
3.1 GENERAL DESCRIPTION OF EUT	9
3.2 DESCRIPTION OF TEST MODES	11
3.3 TABLE OF PARAMETERS OF TEXT SOFTWARE SETTING	12
3.4 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	13
3.5 DESCRIPTION OF SUPPORT UNITS	14
4 . EMC EMISSION TEST	15
4.1 CONDUCTED EMISSION MEASUREMENT	15
4.1.1 POWER LINE CONDUCTED EMISSION LIMITS	15
4.1.2 TEST PROCEDURE	15
4.1.3 DEVIATION FROM TEST STANDARD	15
4.1.4 TEST SETUP	16
4.1.5 EUT OPERATING CONDITIONS	16
4.1.6 EUT TEST CONDITIONS	16
4.1.7 TEST RESULTS	16
4.2 RADIATED EMISSION MEASUREMENT	17
4.2.1 RADIATED EMISSION LIMITS	17
4.2.2 TEST PROCEDURE	18
4.2.3 DEVIATION FROM TEST STANDARD	18
4.2.4 TEST SETUP	18
4.2.5 EUT OPERATING CONDITIONS	19
4.2.6 EUT TEST CONDITIONS	19
4.2.7 TEST RESULTS (9KHZ TO 30MHZ)	20
4.2.8 TEST RESULTS (BETWEEN 30MHZ TO 1000 MHZ)	20
4.2.9 TEST RESULTS (ABOVE 1000 MHZ)	20
5 . BANDWIDTH TEST	21
5.1 APPLIED PROCEDURES	21
5.1.1 TEST PROCEDURE	21
5.1.2 DEVIATION FROM STANDARD	21
5.1.3 TEST SETUP	21
5.1.4 EUT OPERATION CONDITIONS	21
5.1.5 EUT TEST CONDITIONS	21
5.1.6 TEST RESULTS	21

Table of Contents	Page
6 . MAXIMUM OUTPUT POWER TEST	22
6.1 APPLIED PROCEDURES / LIMIT	22
6.1.1 TEST PROCEDURE	22
6.1.2 DEVIATION FROM STANDARD	22
6.1.3 TEST SETUP	22
6.1.4 EUT OPERATION CONDITIONS	22
6.1.5 EUT TEST CONDITIONS	22
6.1.6 TEST RESULTS	22
7 . ANTENNA CONDUCTED SPURIOUS EMISSION	23
7.1 APPLIED PROCEDURES / LIMIT	23
7.1.1 TEST PROCEDURE	23
7.1.2 DEVIATION FROM STANDARD	23
7.1.3 TEST SETUP	23
7.1.4 EUT OPERATION CONDITIONS	23
7.1.5 EUT TEST CONDITIONS	23
7.1.6 TEST RESULTS	23
8 . POWER SPECTRAL DENSITY TEST	24
8.1 APPLIED PROCEDURES / LIMIT	24
8.1.1 TEST PROCEDURE	24
8.1.2 DEVIATION FROM STANDARD	24
8.1.3 TEST SETUP	24
8.1.4 EUT OPERATION CONDITIONS	24
8.1.5 EUT TEST CONDITIONS	24
8.1.6 TEST RESULTS	24
9 . MEASUREMENT INSTRUMENTS LIST	25
10 . EUT TEST PHOTO	27
ATTACHMENT A - CONDUCTED EMISSION	31
ATTACHMENT B - RADIATED EMISSION (9KHZ-30MHZ)	34
ATTACHMENT C - RADIATED EMISSION (30MHZ TO 1000MHZ)	36
ATTACHMENT D - RADIATED EMISSION (ABOVE 1000MHZ)	39
ATTACHMENT E - BANDWIDTH	64
ATTACHMENT F - MAXIMUM OUTPUT POWER	69
ATTACHMENT G - ANTENNA CONDUCTED SPURIOUS EMISSION	71
ATTACHMENT H - POWER SPECTRAL DENSITY	80

REPORT ISSUED HISTORY

Issued No.	Description	Issued Date
BTL-FCCP-1-1407010	Original Issue.	Oct. 16, 2014

1. CERTIFICATION

Equipment : WIRELESS SPEAKER SYSTEM
Brand Name : moshi
Model Name : Spatia
Applicant : Aevoe Inc.
Manufacturer : CHIYU ELECTRONICS (SHEN ZHEN) CO.,LTD
Address : No. 101, Chi-Yu Road, Chi-Yu Industrial Zone, Fu-Yong Town, Bao-An District, ShenZhen, China.
Factory : CHIYU ELECTRONICS (SHEN ZHEN) CO.,LTD
Address : No. 101, Chi-Yu Road, Chi-Yu Industrial Zone, Fu-Yong Town, Bao-An District, ShenZhen, China.
Date of Test : Jul. 09, 2014 ~ Oct.15, 2014
Test Sample : ENGINEERING SAMPLE
Standard(s) : FCC Part15, Subpart C: 2013 (15.247) / ANSI C63.4-2009

The above equipment has been tested and found compliance with the requirement of the relative standards by BTL Inc.

The test data, data evaluation, and equipment configuration contained in our test report (Ref No. BTL-FCCP-1-1407010) were obtained utilizing the test procedures, test instruments, test sites that has been accredited by the Authority of TAF according to the ISO-17025 quality assessment standard and technical standard(s).

2. SUMMARY OF TEST RESULTS

Test procedures according to the technical standard(s):

Applied Standard(s): FCC Part15 (15.247) , Subpart C: 2013			
Section	Test Item	Judgment	Remark
15.207	Conducted Emission	PASS	
15.247(d)	Antenna conducted Spurious Emission	PASS	
15.247(a)(2)	6dB Bandwidth	PASS	
15.247(b)(3)	Peak Output Power	PASS	
15.247(e)	Power Spectral Density	PASS	
15.203	Antenna Requirement	PASS	
15.209/15.205	Transmitter Radiated Emissions	PASS	

NOTE:

- (1) "N/A" denotes test is not applicable in this test report.
- (2) The test follows FCC KDB Publication No. 558074 D01 DTS Meas Guidance v03r02 (Measurement Guidelines of DTS)

2.1 TEST FACILITY

The test facilities used to collect the test data in this report:

Conducted emission Test:

C02: 1F., No. 61, Ln. 77, Sing-ai Rd., Neihu Dist., Taipei City 114, Taiwan (R.O.C.)

Radiated emission Test (Below 1 GHz):

CB08: 1F., No. 61, Ln. 77, Sing-ai Rd., Neihu Dist., Taipei City 114, Taiwan (R.O.C.)

Radiated emission Test (Above 1 GHz):

CB08: 1F., No. 61, Ln. 77, Sing-ai Rd., Neihu Dist., Taipei City 114, Taiwan (R.O.C.)

2.2 MEASUREMENT UNCERTAINTY

The measurement uncertainty is not specified by FCC/Industry Canada rules and for reference only.

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95%.

The measurement instrumentation uncertainty considerations contained in CISPR 16-4-2.

A. Conducted emission test:

Test Site	Measurement Frequency Range	U, (dB)	NOTE
C02	150 kHz ~ 30 MHz	2.59	

B. Radiated emission test:

Test Site	Item	Measurement Frequency Range	Uncertainty	NOTE	
CB08	Radiated emission at 3m	Horizontal Polarization	30 - 200MHz	3.35 dB	
			200 - 1000MHz	3.11 dB	
			1 - 18GHz	3.97 dB	
			18 - 40GHz	4.01 dB	
		Vertical Polarization	30 - 200MHz	3.22 dB	
			200 - 1000MHz	3.24 dB	
			1 - 18GHz	4.05 dB	
			18 - 40GHz	4.04 dB	

Our calculated Measurement Instrumentation Uncertainty is shown in the tables above. These are our U_{lab} values in CISPR 16-4-2 terminology.

Since Table 1 of CISPR 16-4-2 has values of measurement instrumentation uncertainty, called U_{CISPR} , as follows:

Conducted Disturbance (mains port) – 150 kHz – 30 MHz: 3.6 dB

Radiated Disturbance (electric field strength on an open area test site or alternative test site) – 30 MHz – 1000 MHz: 5.2 dB

It can be seen that our U_{lab} values are smaller than U_{CISPR} .

If U_{lab} is less than or equal to U_{CISPR} , then:

- compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.

If U_{lab} is greater than U_{CISPR} , then:

- compliance is deemed to occur if no measured disturbance level, increased by $(U_{lab} - U_{CISPR})$, exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level, increased by $(U_{lab} - U_{CISPR})$, exceeds the disturbance limit.

3. GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

Equipment	WIRELESS SPEAKER SYSTEM	
Brand Name	moshi	
Model Name	Spatia	
Model Difference	N/A	
Product Description	Operation Frequency	2412~2462 MHz
	Modulation Technology	802.11b:DSSS 802.11g:OFDM
	Bit Rate of Transmitter	802.11b: 11/5.5/2/1 Mbps 802.11g: 54/48/36/24/18/12/9/6 Mbps
	Output Power (Max.)	802.11b: -5.49dBm (0.0003W) 802.11g: 3.44dBm (0.0022W)
Power Source	#1 DC Voltage supplied from External Power Supply. #2 Supplied from USB port	
Power Rating	#1 External Power Supply: Brand/Model:GPE,GPE060D-240250D I/P: AC 100-240V~50/60Hz 1.5A O/P: DC 24V 2500mA 60W #2 DC 5V	



Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

2. Channel List:

CH01 – CH11 for 802.11b, 802.11g							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
01	2412	04	2427	07	2442	10	2457
02	2417	05	2432	08	2447	11	2462
03	2422	06	2437	09	2452		

3. Table for Filed Antenna

Ant	Brand	Model Name	Antenna Type	Connector	Gain (dBi)	Note
1		C147-510857-A (SSR-20163)	PCB	MHF	3.07	TX
2		C147-510857-A (SSR-20163)	PCB	MHF	3.07	RX

3.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generated from EUT, the test system was pre-scanning tested based on the consideration of following EUT operation mode or test configuration mode which possibly have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	TX B MODE CHANNEL 01/06/11
Mode 2	TX G MODE CHANNEL 01/06/11
Mode 3	TX MODE

The EUT system operated these modes were found to be the worst case during the pre-scanning test as following:

For Conducted Test	
Final Test Mode	Description
Mode 3	TX MODE

For Radiated Test	
Final Test Mode	Description
Mode 1	TX B MODE CHANNEL 01/06/11
Mode 2	TX G MODE CHANNEL 01/06/11

Note:


- (1) The measurements are performed at the high, middle, low available channels.
- (2) 802.11b mode: DBPSK (1Mbps)
802.11g mode: OFDM (6Mbps)
For radiated emission tests, the highest output powers were set for final test.
- (3) For radiated below 1G test, the 802.11b is found to be the worst case and recorded.

3.3 TABLE OF PARAMETERS OF TEXT SOFTWARE SETTING

During testing, channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters of WLAN

Test software version	DOS		
Frequency (MHz)	2412	2437	2462
802.11b	12	12	12
802.11g	11	11	11

3.4 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED



C-1 DATA Cable
C-2 RS232 Cable

3.5 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	FCC ID/IC	Series No.	Note
E-1	Notebook PC	DELL	PP18L	DOC	PF329 A01	
E-2	Fixture	N/A	N/A	N/A	N/A	

Item	Shielded Type	Ferrite Core	Length	Note
C-1	NO	NO	0.3m	
C-2	YES	NO	1.5m	

4. EMC EMISSION TEST

4.1 CONDUCTED EMISSION MEASUREMENT

4.1.1 POWER LINE CONDUCTED EMISSION Limits (Frequency Range 150KHz-30MHz)

Frequency of Emission (MHz)	Conducted Limit (dB μ V)	
	Quasi-peak	Average
0.15 -0.5	66 to 56*	56 to 46*
0.50 -5.0	56	46
5.0 -30.0	60	50

Note:

(1) The limit of " * " decreases with the logarithm of the frequency

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 KHz


4.1.2 TEST PROCEDURE

- a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

4.1.3 DEVIATION FROM TEST STANDARD

No deviation

4.1.4 TEST SETUP



- Note:**
1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

4.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

4.1.6 EUT TEST CONDITIONS

Temperature: 24°C Relative Humidity: 59% Test Voltage: AC 120V/60Hz

4.1.7 TEST RESULTS

Please refer to the Attachment A.

4.2 RADIATED EMISSION MEASUREMENT

4.2.1 RADIATED EMISSION LIMITS

20dB in any 100 KHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

LIMITS OF RADIATED EMISSION MEASUREMENT (9KHz-1000MHz)

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
960~1000	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

Frequency (MHz)	(dBuV/m) (at 3 meters)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RBW / VBW (Emission in restricted band)	1MHz / 1MHz for Peak, 1 MHz / 10Hz for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9KHz~90KHz for PK/AVG detector
Start ~ Stop Frequency	90KHz~110KHz for QP detector
Start ~ Stop Frequency	110KHz~490KHz for PK/AVG detector
Start ~ Stop Frequency	490KHz~30MHz for QP detector
Start ~ Stop Frequency	30MHz~1000MHz for QP detector

4.2.2 TEST PROCEDURE


- The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.(below 1GHz)
- The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.(above 1GHz)
- The height of the equipment or of the substitution antenna shall be 0.8 m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

4.2.3 DEVIATION FROM TEST STANDARD


No deviation

4.2.4 TEST SETUP


(A) Radiated Emission Test Set-Up Frequency Below 1 GHz



(B) Radiated Emission Test Set-Up Frequency Above 1 GHz



(C) For radiated emissions below 30MHz



4.2.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 4.1.5 Unless otherwise a special operating condition is specified in the follows during the testing.

4.2.6 EUT TEST CONDITIONS

Temperature: 22°C Relative Humidity: 60% Test Voltage: AC 120V/60Hz

4.2.7 TEST RESULTS (9KHZ TO 30MHZ)

Please refer to the Attachment B

Remark:

- (1) The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.
- (2) Distance extrapolation factor = $40 \log(\text{specific distance} / \text{test distance})$ (dB).
- (3) Limit line = specific limits (dBuV) + distance extrapolation factor.

4.2.8 TEST RESULTS (BETWEEN 30MHZ TO 1000 MHZ)

Please refer to the Attachment C.

4.2.9 TEST RESULTS (ABOVE 1000 MHZ)

Please refer to the Attachment D.

5. BANDWIDTH TEST

5.1 Applied procedures

FCC Part15 (15.247) , Subpart C			
Section	Test Item	Frequency Range (MHz)	Result
15.247(a)(2)	Bandwidth	2400-2483.5	PASS

5.1.1 TEST PROCEDURE

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- b. Spectrum Setting: RBW= 100KHz, VBW=300KHz, Sweep time = 2.5 ms.

5.1.2 DEVIATION FROM STANDARD

No deviation.

5.1.3 TEST SETUP



5.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 4.1.5 Unless otherwise a special operating condition is specified in the follows during the testing.

5.1.5 EUT TEST CONDITIONS

Temperature: 22°C Relative Humidity: 60% Test Voltage: AC 120V/60Hz

5.1.6 TEST RESULTS

Please refer to the Attachment E.

6. MAXIMUM OUTPUT POWER TEST

6.1 Applied procedures / limit

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(b)(3)	Maximum Output Power	1 Watt or 30dBm	2400-2483.5	PASS

6.1.1 TEST PROCEDURE

- a. The EUT was directly connected to the power meter and antenna output port as show in the block diagram below,
- b. The maximum peak conducted output power was performed in accordance with method 9.1.3 of FCC KDB 558074 D01 DTS Meas Guidance v03r02.

6.1.2 DEVIATION FROM STANDARD

No deviation.

6.1.3 TEST SETUP



6.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 4.1.5 Unless otherwise a special operating condition is specified in the follows during the testing. Transmit output power was measured while the host equipment supply voltage was varied from 85 % to 115 % of the nominal rated supply voltage. No change in transmit output power was observed.

6.1.5 EUT TEST CONDITIONS

Temperature: 22°C Relative Humidity: 60% Test Voltage: AC 120V/60Hz

6.1.6 TEST RESULTS

Please refer to the Attachment F.

7. ANTENNA CONDUCTED SPURIOUS EMISSION

7.1 Applied procedures / limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.


7.1.1 TEST PROCEDURE

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- b. Spectrum Setting: RBW= 100KHz, VBW=300KHz, Sweep time = Auto.

7.1.2 DEVIATION FROM STANDARD

No deviation.

7.1.3 TEST SETUP



7.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 4.1.5 Unless otherwise a special operating condition is specified in the follows during the testing.

7.1.5 EUT TEST CONDITIONS

Temperature: 22°C Relative Humidity: 60% Test Voltage: AC 120V/60Hz

7.1.6 TEST RESULTS

Please refer to the Attachment G.

8. POWER SPECTRAL DENSITY TEST

8.1 Applied procedures / limit

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(e)	Power Spectral Density	8 dBm (in any 3KHz)	2400-2483.5	PASS


8.1.1 TEST PROCEDURE

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- b. Spectrum Setting: RBW=3KHz, VBW=10KHz, Sweep time = Auto.

8.1.2 DEVIATION FROM STANDARD

No deviation.

8.1.3 TEST SETUP



8.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 4.1.5 Unless otherwise a special operating condition is specified in the follows during the testing.

8.1.5 EUT TEST CONDITIONS

Temperature: 22°C Relative Humidity: 60% Test Voltage: AC 120V/60Hz

8.1.6 TEST RESULTS

Please refer to the Attachment H.

9. MEASUREMENT INSTRUMENTS LIST

Conducted Emission Measurement					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	LISN	R&s	ENV216	100087	Nov. 23, 2014
2	Test Cable	TIMES	CFD300-NL	C01	Jun. 15, 2015
3	EMI Test Receiver	R&S	ESCI	100082	Apr. 13, 2015
4	Measurement Software	EZ	EZ_EMG (Version NB-02A)	N/A	N/A

Radiated Emission Measurement					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP-30	100854	Sep. 07, 2015
2	Horn Antenna	Schwarzbeck	BBHA 9120	D-325	Apr. 14, 2015
3	Microwave Pre_amplifier	Agilent	8449B	3008A01714	Apr. 15, 2015
4	Microflex Cable	Harbour industries	27478LL142	1m	May. 12, 2015
5	Microflex Cable	EMC	S104-SMA	8m	May. 14, 2015
6	Microflex Cable	Harbour industries	27478LL142	3m	May. 12, 2015
7	Test Cable	LMR	LMR-400	12m	May. 13, 2015
8	Test Cable	LMR	LMR-400	3m	May. 13, 2015
9	Pre-Amplifier	Anritsu	MH648A	M92649	Jun. 17, 2015
10	Log-Bicon Antenna	Schwarzbeck	VULB9168-35 2	9168-352	Sep. 03, 2015

6dB Bandwidth Measurement					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP-30	100854	Sep. 07, 2015

Peak Output Power Measurement					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP-30	100854	Sep. 07, 2015


Antenna Conducted Spurious Emission Measurement					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP-30	100854	Sep. 07, 2015

Power Spectral Density Measurement					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP-30	100854	Sep. 07, 2015

Remark: "N/A" denotes no model name, serial no. or calibration specified.
 All calibration period of equipment list is one year.


10. EUT TEST PHOTO



Conducted Measurement Photos



Radiated Measurement Photos



9K-30MHz



Radiated Measurement Photos**30MHz-1G**

Radiated Measurement Photos

Above 1G



ATTACHMENT A - CONDUCTED EMISSION

Test Mode : TX MODE

Line



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1	*	0.1500	43.72	9.65	53.37	66.00	-12.63	peak	
2		0.1948	40.83	9.65	50.48	63.83	-13.35	peak	
3		0.2473	39.02	9.70	48.72	61.85	-13.13	peak	
4		0.3047	36.76	9.77	46.53	60.11	-13.58	peak	
5		0.4867	33.06	9.98	43.04	56.22	-13.18	peak	
6		4.0640	26.60	9.88	36.48	56.00	-19.52	peak	

Test Mode : TX MODE

Neutral



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.1521	43.31	9.64	52.95	65.88	-12.93	peak	
2		0.1884	41.66	9.64	51.30	64.11	-12.81	peak	
3		0.2431	39.36	9.64	49.00	61.99	-12.99	peak	
4	*	0.3320	37.12	9.65	46.77	59.40	-12.63	peak	
5		0.4790	33.54	9.67	43.21	56.36	-13.15	peak	
6		0.6260	28.78	9.67	38.45	56.00	-17.55	peak	

ATTACHMENT B - RADIATED EMISSION (9KHZ-30MHZ)

Test Mode:	TX Mode
------------	---------

Frequency (MHz)	Ant 0°/90°	Read level dBuV/m	Factor (dB)	Measured(FS) (dBuV/m)	Limit(QP) (dBuV/m)	Margin (dB)	Note
0.3840	0°	39.55	10.80	50.35	95.92	-45.57	PK
0.3840	0°	24.33	10.80	35.13	115.92	-80.79	AVG
9.3060	0°	14.55	10.92	25.47	69.54	-44.07	QP
13.8790	0°	11.76	10.69	22.45	69.54	-47.09	QP
15.0040	0°	11.92	10.60	22.52	69.54	-47.02	QP
27.9006	0°	15.09	8.70	23.79	69.54	-45.75	QP
28.6504	0°	18.63	8.56	27.19	69.54	-42.35	QP

Frequency (MHz)	Ant 0°/90°	Read level dBuV/m	Factor (dB)	Measured(FS) (dBuV/m)	Limit(QP) (dBuV/m)	Margin (dB)	Note
0.7588	90°	31.94	11.01	42.95	70.00	-27.05	QP
9.3062	90°	15.60	10.92	26.52	69.54	-43.02	QP
12.7552	90°	11.87	10.78	22.65	69.54	-46.89	QP
15.0795	90°	11.46	10.59	22.05	69.54	-47.49	QP
27.5257	90°	14.96	8.77	23.73	69.54	-45.81	QP
28.6504	90°	18.61	8.56	27.17	69.54	-42.37	QP


Remark:

- (1) The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.
- (2) Distance extrapolation factor = $40 \log(\text{specific distance} / \text{test distance})$ (dB);
- (3) Limit line = specific limits (dBuV) + distance extrapolation factor.

ATTACHMENT C - RADIATED EMISSION (30MHZ TO 1000MHZ)

Test Mode: TX B MODE CHANNEL 06


Vertical



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		117.3000	53.42	-16.52	36.90	43.50	-6.60	peak	
2		146.4000	50.30	-14.18	36.12	43.50	-7.38	peak	
3	*	179.3800	52.35	-15.36	36.99	43.50	-6.51	peak	
4		336.5200	50.53	-12.54	37.99	46.00	-8.01	peak	
5		518.8800	46.71	-8.81	37.90	46.00	-8.10	peak	
6		567.3800	44.81	-7.79	37.02	46.00	-8.98	peak	

Test Mode: TX B MODE CHANNEL 06

Horizontal




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	*	146.4000	52.00	-14.18	37.82	43.50	-5.68	peak	
2		239.5200	53.86	-15.28	38.58	46.00	-7.42	peak	
3		299.6600	50.79	-13.50	37.29	46.00	-8.71	peak	
4		383.0800	50.94	-11.52	39.42	46.00	-6.58	peak	
5		701.2400	41.55	-5.42	36.13	46.00	-9.87	peak	
6		1000.0000	45.12	-1.28	43.84	54.00	-10.16	peak	

ATTACHMENT D - RADIATED EMISSION (ABOVE 1000MHZ)

Orthogonal Axis :	X
Test Mode :	TX B MODE 2412MHz


Vertical



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		2390.000	22.30	31.02	53.32	74.00	-20.68	peak	
2		2390.000	10.76	31.02	41.78	54.00	-12.22	AVG	
3	X	2413.000	62.05	31.13	93.18	74.00	19.18	peak	no limit
4	*	2413.000	57.15	31.13	88.28	54.00	34.28	AVG	no limit

Orthogonal Axis :	X
Test Mode :	TX B MODE 2412MHz


Vertical



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		4824.400	41.23	7.39	48.62	74.00	-25.38	peak	
2		4824.400	29.91	7.39	37.30	54.00	-16.70	AVG	
3		7236.040	41.22	14.87	56.09	74.00	-17.91	peak	
4	*	7236.040	29.86	14.87	44.73	54.00	-9.27	AVG	

Orthogonal Axis :	X
Test Mode :	TX B MODE 2412MHz


Horizontal



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1		2384.800	22.60	31.00	53.60	74.00	-20.40	peak	
2		2384.800	11.87	31.00	42.87	54.00	-11.13	AVG	
3	X	2411.200	69.70	31.12	100.82	74.00	26.82	peak	no limit
4	*	2411.200	65.15	31.12	96.27	54.00	42.27	AVG	no limit

Orthogonal Axis :	X
Test Mode :	TX B MODE 2412MHz


Horizontal



No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	4824.410	41.34	7.39	48.73	74.00	-25.27	peak	
2	4824.410	29.34	7.39	36.73	54.00	-17.27	AVG	
3	7236.040	41.20	14.87	56.07	74.00	-17.93	peak	
4 *	7236.040	29.61	14.87	44.48	54.00	-9.52	AVG	

Orthogonal Axis :	X
Test Mode :	TX B MODE 2437MHz


Vertical



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1	X	2439.600	60.20	31.25	91.45	74.00	17.45	peak	no limit
2	*	2439.600	55.42	31.25	86.67	54.00	32.67	AVG	no limit

Orthogonal Axis :	X
Test Mode :	TX B MODE 2437MHz


Vertical



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		4874.200	41.37	7.47	48.84	74.00	-25.16	peak	
2		4874.200	29.70	7.47	37.17	54.00	-16.83	AVG	
3		7311.200	41.75	15.18	56.93	74.00	-17.07	peak	
4	*	7311.200	29.86	15.18	45.04	54.00	-8.96	AVG	

Orthogonal Axis :	X
Test Mode :	TX B MODE 2437MHz


Horizontal



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	X	2439.600	70.80	31.25	102.05	74.00	28.05	peak	no limit
2	*	2439.600	63.26	31.25	94.51	54.00	40.51	AVG	no limit

Orthogonal Axis :	X
Test Mode :	TX B MODE 2437MHz


Horizontal



No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	4874.520	41.34	7.47	48.81	74.00	-25.19	peak	
2	4874.520	29.26	7.47	36.73	54.00	-17.27	AVG	
3	7311.240	41.40	15.18	56.58	74.00	-17.42	peak	
4 *	7311.240	29.89	15.18	45.07	54.00	-8.93	AVG	

Orthogonal Axis :	X
Test Mode :	TX B MODE 2462MHz


Vertical



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1	X	2461.200	64.90	31.36	96.26	74.00	22.26	peak	no limit
2	*	2461.200	60.50	31.36	91.86	54.00	37.86	AVG	no limit
3		2483.500	25.71	31.46	57.17	74.00	-16.83	peak	
4		2483.500	11.21	31.46	42.67	54.00	-11.33	AVG	

Orthogonal Axis :	X
Test Mode :	TX B MODE 2462MHz


Vertical



No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	4924.500	41.24	7.53	48.77	74.00	-25.23	peak	
2	4924.500	30.39	7.53	37.92	54.00	-16.08	AVG	
3	7386.280	40.21	15.50	55.71	74.00	-18.29	peak	
4 *	7386.280	28.55	15.50	44.05	54.00	-9.95	AVG	

Orthogonal Axis :	X
Test Mode :	TX B MODE 2462MHz


Horizontal



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1	X	2461.200	69.44	31.36	100.80	74.00	26.80	peak	no limit
2	*	2461.200	63.37	31.36	94.73	54.00	40.73	AVG	no limit
3		2483.500	25.71	31.46	57.17	74.00	-16.83	peak	
4		2483.500	11.49	31.46	42.95	54.00	-11.05	AVG	

Orthogonal Axis :	X
Test Mode :	TX B MODE 2462MHz


Horizontal



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		4924.060	41.61	7.53	49.14	74.00	-24.86	peak	
2		4924.060	29.82	7.53	37.35	54.00	-16.65	AVG	
3		7386.040	39.80	15.50	55.30	74.00	-18.70	peak	
4	*	7386.040	28.12	15.50	43.62	54.00	-10.38	AVG	

Orthogonal Axis :	X
Test Mode :	TX G MODE 2412MHz


Vertical



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		2390.000	26.50	31.02	57.52	74.00	-16.48	peak	
2		2390.000	13.03	31.02	44.05	54.00	-9.95	AVG	
3	X	2407.000	68.30	31.10	99.40	74.00	25.40	peak	no limit
4	*	2407.000	54.44	31.10	85.54	54.00	31.54	AVG	no limit

Orthogonal Axis :	X
Test Mode :	TX G MODE 2412MHz


Vertical



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		4824.280	40.74	7.39	48.13	74.00	-25.87	peak	
2		4824.280	29.49	7.39	36.88	54.00	-17.12	AVG	
3		7236.440	41.51	14.87	56.38	74.00	-17.62	peak	
4	*	7236.440	29.51	14.87	44.38	54.00	-9.62	AVG	

Orthogonal Axis :	X
Test Mode :	TX G MODE 2412MHz


Horizontal



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		2390.000	33.60	31.02	64.62	74.00	-9.38	peak	
2		2390.000	17.45	31.02	48.47	54.00	-5.53	AVG	
3	X	2407.200	75.50	31.10	106.60	74.00	32.60	peak	no limit
4	*	2407.200	61.04	31.10	92.14	54.00	38.14	AVG	no limit


Orthogonal Axis :	X
Test Mode :	TX G MODE 2412MHz

Horizontal



No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measurement dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	4824.200	41.19	7.39	48.58	74.00	-25.42	peak	
2	4824.200	29.00	7.39	36.39	54.00	-17.61	AVG	
3	7236.280	41.10	14.87	55.97	74.00	-18.03	peak	
4 *	7236.280	29.44	14.87	44.31	54.00	-9.69	AVG	


Orthogonal Axis :	X
Test Mode :	TX G MODE 2437MHz



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	X	2434.200	69.20	31.23	100.43	74.00	26.43	peak	no limit
2	*	2434.200	55.90	31.23	87.13	54.00	33.13	AVG	no limit


Orthogonal Axis :	X
Test Mode :	TX G MODE 2437MHz

Vertical



No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	4874.160	41.38	7.47	48.85	74.00	-25.15	peak	
2	4874.160	29.56	7.47	37.03	54.00	-16.97	AVG	
3	7310.880	41.54	15.18	56.72	74.00	-17.28	peak	
4 *	7310.880	29.38	15.18	44.56	54.00	-9.44	AVG	


Orthogonal Axis :	X
Test Mode :	TX G MODE 2437MHz



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	X	2433.600	75.20	31.22	106.42	74.00	32.42	peak	no limit
2	*	2433.600	61.65	31.22	92.87	54.00	38.87	AVG	no limit

Orthogonal Axis :	X
Test Mode :	TX G MODE 2437MHz


Horizontal



No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	4874.120	41.45	7.47	48.92	74.00	-25.08	peak	
2	4874.120	29.46	7.47	36.93	54.00	-17.07	AVG	
3	7311.120	41.42	15.18	56.60	74.00	-17.40	peak	
4 *	7311.120	29.34	15.18	44.52	54.00	-9.48	AVG	

Orthogonal Axis :	X
Test Mode :	TX G MODE 2462MHz


Vertical



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	X	2455.800	69.50	31.33	100.83	74.00	26.83	peak	no limit
2	*	2455.800	55.45	31.33	86.78	54.00	32.78	AVG	no limit
3		2483.500	31.30	31.46	62.76	74.00	-11.24	peak	
4		2483.500	15.13	31.46	46.59	54.00	-7.41	AVG	


Orthogonal Axis :	X
Test Mode :	TX G MODE 2462MHz

Vertical



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		4923.860	42.41	7.53	49.94	74.00	-24.06	peak	
2		4924.900	30.23	7.53	37.76	54.00	-16.24	AVG	
3		7386.160	39.82	15.50	55.32	74.00	-18.68	peak	
4	*	7386.160	27.99	15.50	43.49	54.00	-10.51	AVG	


Orthogonal Axis :	X
Test Mode :	TX G MODE 2462MHz



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	X	2455.600	74.20	31.33	105.53	74.00	31.53	peak	no limit
2	*	2455.600	60.38	31.33	91.71	54.00	37.71	AVG	no limit
3		2483.500	35.50	31.46	66.96	74.00	-7.04	peak	
4		2483.500	19.88	31.46	51.34	54.00	-2.66	AVG	

Orthogonal Axis :	X
Test Mode :	TX G MODE 2462MHz

Horizontal




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		4924.500	42.15	7.53	49.68	74.00	-24.32	peak	
2		4924.500	29.68	7.53	37.21	54.00	-16.79	AVG	
3		7386.340	39.79	15.50	55.29	74.00	-18.71	peak	
4	*	7386.340	28.02	15.50	43.52	54.00	-10.48	AVG	

ATTACHMENT E - BANDWIDTH

Test Mode : TX B Mode_CH01/06/11


Frequency (MHz)	6dB Bandwidth (MHz)	99% Occupied BW (MHz)	Min. Limit (kHz)	Test Result
2412	12.06	16.12	500	Complies
2437	12.06	16.16	500	Complies
2462	12.10	16.08	500	Complies

TX CH01




Date: 1.AUG.2014 15:07:26

TX CH06



Date: 1.AUG.2014 15:10:18

TX CH11




Date: 1.AUG.2014 15:12:19

Test Mode: TX G Mode_CH01/06/11


Frequency (MHz)	6dB Bandwidth (MHz)	99% Occupied BW (MHz)	Min. Limit (kHz)	Test Result
2412	16.29	16.48	500	Complies
2437	16.37	16.48	500	Complies
2462	16.37	16.48	500	Complies

TX CH01




Date: 1.AUG.2014 15:15:51

TX CH06



Date: 1.AUG.2014 15:22:59

TX CH11



Date: 1.AUG.2014 15:25:25

ATTACHMENT F - MAXIMUM OUTPUT POWER

Test Mode: TX B Mode

Frequency (MHz)	Conducted Power (dBm)	Conducted Power (W)	Max. Limit (dBm)	Max. Limit (W)	Result
2412	-5.79	0.0003	30.00	1.00	Complies
2437	-5.49	0.0003	30.00	1.00	Complies
2462	-5.62	0.0003	30.00	1.00	Complies


Test Mode: TX G Mode

Frequency (MHz)	Conducted Power (dBm)	Conducted Power (W)	Max. Limit (dBm)	Max. Limit (W)	Result
2412	3.44	0.0022	30.00	1.00	Complies
2437	3.22	0.0021	30.00	1.00	Complies
2462	3.03	0.0020	30.00	1.00	Complies

**ATTACHMENT G - ANTENNA CONDUCTED SPURIOUS
EMISSION**


Test Mode :	TX B Mode
--------------------	------------------

TX B mode CH01




Date: 1.AUG.2014 15:09:10

TX B mode CH11




Date: 1.AUG.2014 15:14:13

TX B mode CH01 (10 Harmonic of the frequency)




Date: 1.AUG.2014 15:08:52

TX B mode CH06 (10 Harmonic of the frequency)



Date: 1.AUG.2014 15:11:14


TX B mode CH11 (10 Harmonic of the frequency)



Date: 1.AUG.2014 15:13:56


Test Mode :	TX G Mode
--------------------	------------------

TX G mode CH01




Date: 1.AUG.2014 15:21:54

TX G mode CH11




Date: 1.AUG.2014 15:28:18

TX G mode CH01 (10 Harmonic of the frequency)




Date: 1.AUG.2014 15:21:29

TX G mode CH06 (10 Harmonic of the frequency)



Date: 1.AUG.2014 15:24:11

TX G mode CH11 (10 Harmonic of the frequency)




Date: 1.AUG.2014 15:27:57

ATTACHMENT H - POWER SPECTRAL DENSITY

Test Mode :TX B Mode_CH01/06/11


Frequency (MHz)	Power Density (dBm/3kHz)	Power Density (mW/3kHz)	Max. Limit (dBm/3kHz)	Result
2412	-13.86	0.04	8.00	Complies
2437	-14.46	0.04	8.00	Complies
2462	-13.94	0.04	8.00	Complies

TX CH01




Date: 1.AUG.2014 15:09:29

TX CH06



Date: 1.AUG.2014 15:11:35

TX CH11




Date: 1.AUG.2014 15:14:40

Test Mode :TX G Mode_CH01/06/11


Frequency (MHz)	Power Density (dBm/3kHz)	Power Density (mW/3kHz)	Max. Limit (dBm/3kHz)	Result
2412	-12.23	0.06	8.00	Complies
2437	-11.97	0.06	8.00	Complies
2462	-12.26	0.06	8.00	Complies

TX CH01




Date: 1.AUG.2014 15:22:19

TX CH06



Date: 1.AUG.2014 15:24:37

TX CH11



Date: 1.AUG.2014 15:28:38