

RF TEST REPORT



Report No.: FCC_IC_RF_SL18071101-RII-001_Zigbee
Supersede Report No.:

Applicant	:	Rigado Inc.
Product Name	:	BMD-345 Bluetooth 5 BLE + 802.15.4 module
Model No.	:	BMD-345
Test Standard	:	47 CFR 15.247 RSS 247 Iss 2: Feb 2017
Test Method	:	ANSI C63.10: 2013 RSS Gen Iss 5: Apr 2018 558074 D01 DTS Meas Guidance v04
FCC ID	:	2AA9B11
IC	:	12208A-11
Dates of test	:	08/02/2018 -08/16/2018
Issue Date	:	08/23/2018
Test Result	:	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail
Equipment complied with the specification	[X]	
Equipment did not comply with the specification	[]	

This Test Report is Issued Under the Authority of:

Rachana Khanduri	Chen Ge
Test Engineer	Engineer Reviewer

Issued By:
SIEMIC Laboratories
775 Montague Expressway, Milpitas, 95035 CA



775 Montague Expressway, Milpitas, CA 95035, USA • Phone: (+1) 408 526 1188 • Facsimile: (+1) 408 526 1088

Visit us at: www.siemic.com; Follow us at:

Laboratory Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.



In addition to testing and certification, SIEMIC provides initial design reviews and compliance management throughout a project. Our extensive experience with China, Asia Pacific, North America, European, and International compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the global markets.

Accreditations for Conformity Assessment

Country/Region	Accreditation Body	Scope
USA	FCC, A2LA	EMC, RF/Wireless, Telecom
Canada	IC, A2LA, NIST	EMC, RF/Wireless, Telecom
Taiwan	BSMI, NCC, NIST	EMC, RF, Telecom, Safety
Hong Kong	OFTA, NIST	RF/Wireless, Telecom
Australia	NATA, NIST	EMC, RF, Telecom, Safety
Korea	KCC/RRA, NIST	EMI, EMS, RF, Telecom, Safety
Japan	VCCI, JATE, TELEC, RFT	EMI, RF/Wireless, Telecom
Mexico	NOM, COFETEL, Caniety	Safety, EMC, RF/Wireless, Telecom
Europe	A2LA, NIST	EMC, RF, Telecom, Safety
Israel	MOC, NIST	EMC, RF, Telecom, Safety

Accreditations for Product Certifications

Country	Accreditation Body	Scope
USA	FCC TCB, NIST	EMC, RF, Telecom
Canada	IC FCB, NIST	EMC, RF, Telecom
Singapore	iDA, NIST	EMC, RF, Telecom
EU	NB	EMC & RED
Japan	MIC (RCB 208)	RF, Telecom
Hong Kong	OFTA (US002)	RF, Telecom

CONTENTS

1	REPORT REVISION HISTORY	4
2	EXECUTIVE SUMMARY.....	5
3	CUSTOMER INFORMATION	5
4	TEST SITE INFORMATION	5
5	MODIFICATION.....	5
6	EUT INFORMATION	6
6.1	EUT Description	6
6.2	Radio Description	6
7	SUPPORTING EQUIPMENT/SOFTWARE AND CABLING DESCRIPTION.....	7
7.1	Supporting Equipment	7
7.2	Cabling Description	7
7.3	Test Software Description	7
8	TEST SUMMARY.....	8
9	MEASUREMENT UNCERTAINTY	9
9.1	Radiated Emissions (100kHz to 30MHz).....	9
9.2	Radiated Emissions (30MHz to 1GHz).....	9
9.3	Radiated Emissions (1GHz to 40GHz).....	10
9.4	RF conducted measurement.....	10
10	MEASUREMENTS, EXAMINATION AND DERIVED RESULTS.....	11
10.1	Antenna Requirement.....	11
10.2	Conducted Emissions.....	12
10.3	6dB & 99% Bandwidth.....	15
10.4	Output Power	19
10.5	Band Edge	23
10.6	Peak Spectral Density	25
10.7	Radiated Spurious Emissions below 1GHz	29
10.8	Radiated Spurious Emissions between 1GHz – 25GHz	31
ANNEX A.	TEST INSTRUMENT	34
ANNEX B.	SIEMIC ACCREDITATION	35

1 Report Revision History

Report No.	Report Version	Description	Issue Date
FCC_IC_RF_SL18071101-RII-001_Zigbee	None	Original	08/23/2018

2 Executive Summary

The purpose of this test program was to demonstrate compliance of following product

Company: Rigado Inc
Product: BMD-345 Bluetooth 5 BLE + 802.15.4 module
Model: BMD-345

against the current Stipulated Standards. The specified model product stated above has demonstrated compliance with the Stipulated Standard listed on 1st page.

3 Customer information

Applicant Name	:	Rigado Inc
Applicant Address	:	3950 Fairview Industrial Dr SE, STE 100, Salem OR 97302 USA
Manufacturer Name	:	Rigado Inc
Manufacturer Address	:	3950 Fairview Industrial Dr SE, STE 100, Salem OR 97302 USA

4 Test site information

Lab performing tests	SIEMIC Laboratories
Lab Address	775 Montague Expressway, Milpitas, CA 95035
FCC Test Site No.	881796
IC Test Site No.	4842D-2
VCCI Test Site No.	A0133

5 Modification

Index	Item	Description	Note
-	-	-	-

6 EUT Information

6.1 EUT Description

Product Name	BMD-345 Bluetooth 5 BLE + 802.15.4 module
Model No.	BMD-345
Trade Name	Rigado Inc
Serial No.	32D093
Host Model No.	N/A
Input Power	5VDC (USB)
Power Adapter Manu/Model	N/A
Power Adapter SN	N/A
Hardware Version	vA
Software Version	N/A
Date of EUT received	07/31/2018
Equipment Class/ Category	DTS
Port/Connectors	USB

6.2 Radio Description

802.15.4:

Radio Type	802.15.4
Operating Frequency	2402MHz-2480MHz
Modulation	O-QPSK
Channel Spacing	5 MHz
Antenna Type	PCB Trace Antenna- 1/4 wave length dipole
Antenna Gain	0.5 dBi
Antenna Connector Type	N/A

7 Supporting Equipment/Software and cabling Description

7.1 Supporting Equipment

Item	Supporting Equipment Description	Model	Serial Number	Manufacturer	Note
1	Laptop	Latitude E5410	N/A	Dell	-

7.2 Cabling Description

Name	Connection Start		Connection Stop		Length / shielding Info		Note
	From	I/O Port	To	I/O Port	Length (m)	Shielding	
USB	EUT	USB	Laptop	USB	2	Unshielded	-

7.3 Test Software Description

Test Item	Software	Description
RF Testing	-	Set the EUT to transmit continuously in different test modes and channels

8 Test Summary

Test Item	Test standard		Test Method/Procedure		Pass / Fail
Antenna Requirement	FCC	15.203	FCC	ANSI C63.10 – 2013 558074 D01 DTS Meas. Guidance v04	<input checked="" type="checkbox"/> Pass
	IC	-	IC		<input type="checkbox"/> N/A
Restricted Band of Operation	FCC	15.205	FCC	ANSI C63.10:2013 558074 D01 DTS Meas Guidance v04	<input checked="" type="checkbox"/> Pass
	IC	RSS Gen 8.10	IC		<input type="checkbox"/> N/A
AC Conducted Emissions	FCC	15.207(a)	FCC	ANSI C63.10:2013 RSS Gen Issue 5: 2018	<input checked="" type="checkbox"/> Pass
	IC	RSS Gen 8.8	IC		<input type="checkbox"/> N/A

DTS Band Requirement

Test Item	Test standard		Test Method/Procedure		Pass / Fail
99% Occupied Bandwidth	-	-	-	-	<input checked="" type="checkbox"/> Pass
	IC	RSS Gen 6.6	IC	RSS Gen Issue 5: 2018	<input type="checkbox"/> N/A
6dB Bandwidth	FCC	15.247(a)(2)	FCC	558074 D01 DTS Meas Guidance v04	<input checked="" type="checkbox"/> Pass
	IC	RSS247 (5.2.1)	IC		<input type="checkbox"/> N/A
Band Edge and Radiated Spurious Emissions	FCC	15.247(d)	FCC	ANSI C63.10:2013 558074 D01 DTS Meas Guidance v04	<input checked="" type="checkbox"/> Pass
	IC	RSS247 (5.5)	IC		<input type="checkbox"/> N/A
Output Power	FCC	15.247(b)	FCC	558074 D01 DTS Meas Guidance v04	<input checked="" type="checkbox"/> Pass
	IC	RSS247 (5.4.4)	IC		<input type="checkbox"/> N/A
Receiver Spurious Emissions	IC	RSS Gen (4.8)	IC	RSS Gen Issue 5: 2018	<input type="checkbox"/> Pass <input checked="" type="checkbox"/> N/A
Antenna Gain > 6 dBi	FCC	15.247(e)	FCC	-	<input type="checkbox"/> Pass
	IC	-	IC	-	<input checked="" type="checkbox"/> N/A
Power Spectral Density	FCC	15.247(e)	FCC	558074 D01 DTS Meas Guidance v04	<input checked="" type="checkbox"/> Pass
	IC	RSS247 (5.2.2)	IC		<input type="checkbox"/> N/A
RF Exposure requirement	FCC	15.247(l)	FCC	-	<input type="checkbox"/> Pass
	IC	RSS Gen(5.5)	IC	RSS Gen Issue 5: 2018	<input checked="" type="checkbox"/> N/A
Remark	1. All measurement uncertainties do not take into consideration for all presented test results.				

9 Measurement Uncertainty

9.1 Radiated Emissions (100kHz to 30MHz)

The test is to measure the radiated emissions of the EUT.

Some error sources that can contribute to the total uncertainty:

- Uncertainty of the receiver
- Uncertainty of the antenna
- Uncertainty of cables
- Uncertainty due to the mismatches

Source of Uncertainty	Value (dB)	Probability Distribution	Division	Sensitivity Coefficient	Expanded Uncertainty
Receiver Reading	0.10	Rectangular	1.732	1	0.069284
Cable Insertion Loss	0.21	Normal	2	1	0.105
Antenna Factor	0.65	Normal	2	1	0.325
Receiver CW accuracy	0.45	Rectangular	1.732	1	0.2598152
Mismatch	0.25	U-Shape	1.414	1	0.1768033
Combined Standard Uncertainty					0.935
Expanded Uncertainty (K=2)					1.87

The total derived measurement uncertainty is +/- 1.87 dB.

9.2 Radiated Emissions (30MHz to 1GHz)

The test is to measure the radiated emissions of the EUT.

Some error sources that can contribute to the total uncertainty:

- Uncertainty of the receiver
- Uncertainty of the antenna
- Uncertainty of cables
- Uncertainty due to the mismatches
- NSA Calibration
- Etc., details see the below table

Source of Uncertainty	Value (dB)	Probability Distribution	Division	Sensitivity Coefficient	Expanded Uncertainty
Receiver Reading	0.12	Rectangular	1.732	1	0.069284
Cable Insertion Loss	0.21	Normal	2	1	0.105
Filter Insertion Loss	0.25	Normal	2	1	0.125
Antenna Factor	0.65	Normal	2	1	0.325
Receiver CW accuracy	0.5	Rectangular	1.732	1	0.2886836
Pulse Amplitude Response	1.5	Rectangular	1.732	1	0.86605081
PRF Response	1.5	Rectangular	1.732	1	0.86605081
Mismatch Filter - Receiver	0.25	U-Shape	1.414	1	0.1768033
NSA Calibration	4.0	U-Shape	1.414	1	2.8288543
Combined Standard Uncertainty					3.0059131
Expanded Uncertainty (K=2)					6.0118262

The total derived measurement uncertainty is +/- 6.00 dB.

9.3 Radiated Emissions (1GHz to 40GHz)

The test is to measure the radiated emissions of the EUT.

Some error sources that can contribute to the total uncertainty:

- Uncertainty of the receiver
- Uncertainty of the antenna
- Uncertainty of cables
- Uncertainty due to the mismatches
- VSWR Calibration
- Etc., details see the below table

Source of Uncertainty	Value (dB)	Probability Distribution	Division	Sensitivity Coefficient	Expanded Uncertainty
Receiver Reading	0.12	Rectangular	1.732	1	0.0692840
Cable Insertion Loss	0.21	Normal	2	1	0.1050000
Filter Insertion Loss	0.25	Normal	2	1	0.1250000
Antenna Factor	0.65	Normal	2	1	0.3250000
Receiver CW accuracy	0.5	Rectangular	1.732	1	0.2886836
Pulse Amplitude Response	1.5	Rectangular	1.732	1	0.8660508
PRF Response	1.5	Rectangular	1.732	1	0.8660508
Mismatch Filter - Receiver	0.25	U-Shape	1.414	1	0.1768033
VSWR Calibration	2.0	U-Shape	1.414	1	1.4144272
Combined Standard Uncertainty					4.2363
Expanded Uncertainty (K=2)					8.4726

The total derived measurement uncertainty is +/- 8.47 dB.

9.4 RF conducted measurement

The test is to measure the RF output power from the EUT.

Some error sources that can contribute to the total uncertainty:

- Uncertainty of the Reference Level Uncertainty
- Uncertainty of variable attenuators
- Uncertainty of cables
- Uncertainty due to the mismatches

Source of Uncertainty	Value (dB)	Probability Distribution	Division	Sensitivity Coefficient	Expanded Uncertainty
Reference Level	0.12	Rectangular	1.732	1	0.069284
Cable Insertion Loss	0.21	Normal	2	1	0.105
Attenuator	0.25	Normal	2	1	0.125
Mismatch	0.25	U-Shape	1.414	1	0.1768033
Combined Standard Uncertainty					0.476087
Expanded Uncertainty (K=2)					0.952174

The total derived measurement uncertainty is +/- 0.95 dB.

10 Measurements, Examination and Derived Results


10.1 Antenna Requirement

Spec	Requirement	Applicable
§15.203	<p>An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.</p> <p>Antenna requirement must meet at least one of the following:</p> <ul style="list-style-type: none"> a) Antenna must be permanently attached to the device. b) The antenna must use a unique type of connector to attach to the device. c) Device must be professionally installed. The installer shall be responsible for ensuring that the correct antenna is employed by the device. 	<input checked="" type="checkbox"/>
Remark	The EUT uses a PCB Trace Antenna (Integrated) which meet the requirement.	
Result	<input checked="" type="checkbox"/> PASS <input type="checkbox"/> FAIL	

10.2 Conducted Emissions

Conducted Emission Limit

Frequency ranges (MHz)	Limit (dBuV)	
	OP	Average
0.15 ~ 0.5	66 ~ 56	56 ~ 46
0.5 ~ 5	56	46
5 ~ 30	60	50

Spec	Item	Requirement	Applicable
FCC 15.207 RSS247(A8.1)	a)	For Low-power radio-frequency devices that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN). The lower limit applies at the boundary between the frequency ranges.	<input checked="" type="checkbox"/>
Test Setup		 <p>Note:</p> <ol style="list-style-type: none"> 1. Support units were connected to second LISN. 2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes 	
Procedure			<ul style="list-style-type: none"> - The EUT and supporting equipment were set up in accordance with the requirements of the standard on top of a 1.5m x 1m x 0.8m high, non-metallic table, as shown in Annex B. - The power supply for the EUT was fed through a 50Ω/50μH EUT LISN, connected to filtered mains. - The RF OUT of the EUT LISN was connected to the EMI test receiver via a low-loss coaxial cable. - All other supporting equipment was powered separately from another main supply.
Remark	EUT was tested at 120VAC, 60Hz		
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail		


Test Data Yes N/A

Test Plot Yes (See below) N/A

Test was done by Rachana Khanduri at Conducted Emission test site.

Conducted Emission Test Results

Test specification:	Conducted Emissions		
Environmental Conditions:	Temp(°C):	21	Result:
	Humidity (%):	42	
	Atmospheric(mbar):	1021	
	Mains Power:	120Vac, 60Hz	
Tested by:	Rachana Khanduri		
Test Date:	08/15/2018		
Remarks	Conducted @ Live		




Live Plot at 120VAC, 60Hz

Frequency (MHz)	Raw (dBuV)	Cable Loss (dB)	Factors (dB)	Level (dBuV)	Measurement Type	Line / Neutral	Limit (dBuV)	Margin (dB)	Pass /Fail
0.190	40.43	9.32	0.04	49.79	Quasi Peak	Live	64.04	-14.25	Pass
0.163	38.54	9.33	0.05	47.92	Quasi Peak	Live	65.31	-17.39	Pass
0.254	30.46	9.32	0.04	39.82	Quasi Peak	Live	61.63	-21.82	Pass
0.334	24.72	9.33	0.04	34.09	Quasi Peak	Live	59.35	-25.26	Pass
0.386	25.78	9.33	0.04	35.14	Quasi Peak	Live	58.15	-23.01	Pass
0.202	39.04	9.32	0.04	48.40	Quasi Peak	Live	63.52	-15.12	Pass
0.190	22.71	9.32	0.04	32.08	Average	Live	54.04	-21.96	Pass
0.163	22.90	9.33	0.05	32.27	Average	Live	55.31	-23.03	Pass
0.254	13.99	9.32	0.04	23.35	Average	Live	51.63	-28.28	Pass
0.334	10.71	9.33	0.04	20.07	Average	Live	49.35	-29.28	Pass
0.386	12.59	9.33	0.04	21.96	Average	Live	48.15	-26.19	Pass
0.202	23.03	9.32	0.04	32.39	Average	Live	53.52	-21.13	Pass

Conducted Emission Test Results

Test specification:		Conducted Emissions	
Environmental Conditions:	Temp(°C):	21	Result: <input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail
	Humidity (%):	42	
	Atmospheric(mbar):	1021	
	Mains Power:	120Vac, 60Hz	
Tested by:	Rachana Khanduri		
Test Date:	08/15/2018		
Remarks	Conducted @ Neutral		




Neutral Plot at 120Vac, 60Hz

Frequency (MHz)	Raw (dBuV)	Cable Loss (dB)	Factors (dB)	Level (dBuV)	Measurement Type	Line / Neutral	Limit (dBuV)	Margin (dB)	Pass /Fail
0.189	41.95	9.32	0.04	51.32	Quasi Peak	Neutral	64.06	-12.74	Pass
0.260	31.86	9.32	0.04	41.22	Quasi Peak	Neutral	61.42	-20.20	Pass
0.150	39.08	9.33	0.05	48.46	Quasi Peak	Neutral	66.00	-17.54	Pass
0.319	28.54	9.32	0.04	37.90	Quasi Peak	Neutral	59.73	-21.83	Pass
0.385	24.82	9.33	0.04	34.18	Quasi Peak	Neutral	58.16	-23.98	Pass
0.514	17.19	9.33	0.04	26.57	Quasi Peak	Neutral	56.00	-29.43	Pass
0.189	22.99	9.32	0.04	32.36	Average	Neutral	54.06	-21.71	Pass
0.260	16.74	9.32	0.04	26.10	Average	Neutral	51.42	-25.32	Pass
0.150	18.87	9.33	0.05	28.25	Average	Neutral	56.00	-27.75	Pass
0.319	12.83	9.32	0.04	22.20	Average	Neutral	49.73	-27.54	Pass
0.385	12.00	9.33	0.04	21.37	Average	Neutral	48.16	-26.79	Pass
0.514	6.60	9.33	0.04	15.97	Average	Neutral	46.00	-30.03	Pass

Note: The results above show only the worst case.

10.3 6dB & 99% Bandwidth

Requirement(s):

Spec	Requirement	Applicable				
§ 15.247 RSS247 (5.2.1)	6dB BW \geq 500KHz;	<input checked="" type="checkbox"/>				
RSS Gen 4.6.1	The transmitter shall be operated at its maximum carrier power measured under normal test conditions. The span of the analyzer shall be set to capture all products of the modulation process, including the emission skirts. The resolution bandwidth shall be set to as close to 1% of the selected span as is possible without being below 1%. The video bandwidth shall be set to 3 times the resolution bandwidth. Video averaging is not permitted. Where practical, a sampling detector shall be used given that a peak or peak hold may produce a wider bandwidth than actual. The trace data points are recovered and directly summed in linear terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached and that frequency recorded. The process is repeated for the highest frequency data points. This frequency is recorded. The span between the two recorded frequencies is the occupied bandwidth	<input checked="" type="checkbox"/>				
Test Setup	 <p>Spectrum Analyzer</p>					
Test Procedure	<p>558074 D01 DTS Meas Guidance v04, 8.1 DTS bandwidth</p> <p><u>6dB Emission bandwidth measurement procedure</u></p> <ul style="list-style-type: none"> - Set RBW = 100 kHz. - Set the video bandwidth (VBW) \geq 3 x RBW. - Detector = Peak. - Trace mode = max hold. - Sweep = auto couple. - Allow the trace to stabilize. - Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission. 					
Test Date	08/15/2018	<table border="1"> <tr> <td>Environmental condition</td> <td>Temperature Relative Humidity Atmospheric Pressure</td> </tr> <tr> <td></td> <td>23°C 42% 1021mbar</td> </tr> </table>	Environmental condition	Temperature Relative Humidity Atmospheric Pressure		23°C 42% 1021mbar
Environmental condition	Temperature Relative Humidity Atmospheric Pressure					
	23°C 42% 1021mbar					
Remark	N/A					
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail					

Test Data Yes N/A

Test Plot Yes N/A

Test was done by Rachana Khanduri at RF test site.


Zigbee:

Channel	Channel Frequency (MHz)	OBW	
		99% (MHz)	6dB(MHz)
Low	2402	2.22	1.04
Mid	2440	2.20	1.08
High	2480	2.23	1.28

6dB & 99% Bandwidth Test Plots

Zigbee:






802.15.4-2480MHz

10.4 Output Power

Requirement(s):

Spec	Item	Requirement	Applicable
§ 15.247 RSS247 (5.4.4)	a)	FHSS in 2400-2483.5MHz with \geq 75 channels: \leq 1 Watt	<input type="checkbox"/>
	b)	FHSS in 5725-5850MHz: \leq 1 Watt	<input type="checkbox"/>
	c)	For all other FHSS in the 2400-2483.5MHz band: \leq 0.125 Watt.	<input type="checkbox"/>
	d)	FHSS in 902-928MHz with \geq 50 channels: \leq 1 Watt	<input type="checkbox"/>
	e)	FHSS in 902-928MHz with \geq 25 & $<$ 50 channels: \leq 0.25 Watt	<input type="checkbox"/>
	f)	DSSS in 902-928MHz, 2400-2483.5MHz, 5725-5850MHz: \leq 1 Watt	<input checked="" type="checkbox"/>
Test Setup	 <p>Spectrum Analyzer → EUT</p>		
Test Procedure	<p>558074 D01 DTS Meas Guidance v04, 9.1.1</p> <p><u>Measurement using a Spectrum Analyzer (SA)</u> This procedure shall be used when the measurement instrument has available a resolution bandwidth that is greater than the DTS bandwidth.</p> <ol style="list-style-type: none"> Set the RBW \geq DTS bandwidth. Set VBW \geq 3 <input type="checkbox"/> RBW. Set span \geq 3 <input type="checkbox"/> RBW Sweep time = auto couple. Detector = peak. Trace mode = max hold. Allow trace to fully stabilize Use peak marker function to determine the peak amplitude level. 		
Test Date	08/15/2018	Environmental condition	Temperature 23°C Relative Humidity 44% Atmospheric Pressure 1021mbar
Remark	NONE		
Result	<input checked="" type="checkbox"/> Pass	<input type="checkbox"/> Fail	

Test Data Yes N/A

Test Plot Yes (See below) N/A

Test was done by Rachana Khanduri at RF test site.

Output Power measurement results :


802.15.4 :

Type	Freq (MHz)	Test mode	CH	Conducted Power (dBm)	Limit (dBm)	Result
Output power	2402	Zigbee	Low	12.50	≤30	Pass
	2440	Zigbee	Mid	11.82	≤30	Pass
	2480	Zigbee	High	-7.51	≤30	Pass

Test Plots:


802.15.4 :





10.5 Band Edge

Requirement(s):

Spec	Item	Requirement	Applicable
§ 15.247 RSS247(5.5)	d)	For non-restricted band, In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB or 30dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, determined by the measurement method on output power to be used. Attenuation below the general limits specified in § 15.209 (a) is not required <input type="checkbox"/> 20 dB down <input checked="" type="checkbox"/> 30 dB down	<input checked="" type="checkbox"/>
Test Setup	 <p>Spectrum Analyzer ————— EUT</p>		
Test Procedure	<p>558074 D01 DTS Meas Guidance v04 <u>Band Edge</u> measurement procedure</p> <ol style="list-style-type: none"> 1. Set the EUT to maximum power setting and enable the EUT transmit continuously. 2. Band edge emissions must be at least 30 dB down from the highest emission level within the authorized band as a measured. The attenuation shall be 30 dB instead of 20 dB when Peak conducted output power procedure is used. 3. Change modulation and channel bandwidth then repeat step 1 to 2. 4. Measured and record the results in the test report. 		
Test Date	08/15/2018	Environmental condition	Temperature 22°C Relative Humidity 46% Atmospheric Pressure 1020mbar
Remark	-		
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail		


Test Data Yes N/A

Test Plot Yes (See below) N/A

Test was done by Rachana Khanduri at RF test site.


Test Plots:

802.15.4:



10.6 Peak Spectral Density

Requirement(s):

Spec	Item	Requirement	Applicable	
§ 15.247(e) RSS247 (5.2.2)	e) f)	DSSS: $\leq 8\text{dBm}/3\text{KHz}$ DSSS in hybrid sys with FH turned off: $\leq 8\text{dBm}/3\text{KHz}$	<input checked="" type="checkbox"/> <input type="checkbox"/>	
Test Setup	 <p>Spectrum Analyzer</p>			
Test Procedure	<p>558074 D01 DTS Meas Guidance v04, 10.2 Method PKPSD (peak PSD)</p> <p><u>Peak spectral density measurement procedure</u></p> <ul style="list-style-type: none"> - Set analyzer center frequency to DTS channel center frequency. - Set the span to 1.5 times the DTS bandwidth. - Set the RBW to: $3\text{ kHz} \leqslant \text{RBW} \leqslant 100\text{ kHz}$. - Set the VBW $\geqslant 3 \times \text{RBW}$. - Detector = Peak - Sweep time = auto couple. - Trace mode = Max Hold - Allow trace to fully stabilize. - Use the peak marker function to determine the maximum amplitude level within the RBW. - If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat. 			
Test Date	08/15/2018	Environmental condition	Temperature Relative Humidity Atmospheric Pressure	22°C 46% 1020mbar
Remark	N/A			
Result	<input checked="" type="checkbox"/> Pass		<input type="checkbox"/> Fail	

Test Data Yes N/A

Test Plot Yes (See below) N/A

Test was done by Rachana Khanduri at RF test site.


PSD measurement results:

802.15.4:


Type	Freq (MHz)	Test mode	CH	Conducted PSD (dBm/3KHz)	Limit (dBm/3KHz)	Result
PSD	2402	Zigbee	Low	3.39	8	Pass
	2440	Zigbee	Mid	2.64	8	Pass
	2480	Zigbee	High	-16.68	8	Pass

Test Plots


802.15.4:



802.15.4-2402MHz




802.15.4-2440MHz



10.7 Radiated Spurious Emissions below 1GHz

Requirement(s):

Spec	Item	Requirement	Applicable										
47CFR§15.247(d) RSS247 (5.5)	a)	<p>Except higher limit as specified elsewhere in other section, the emissions from the low-power radio-frequency devices shall not exceed the field strength levels specified in the following table and the level of any unwanted emissions shall not exceed the level of the fundamental emission. The tighter limit applies at the band edges</p> <table border="1"> <thead> <tr> <th>Frequency range (MHz)</th> <th>Field Strength (uV/m)</th> </tr> </thead> <tbody> <tr> <td>30 - 88</td> <td>100</td> </tr> <tr> <td>88 - 216</td> <td>150</td> </tr> <tr> <td>216 - 960</td> <td>200</td> </tr> <tr> <td>Above 960</td> <td>500</td> </tr> </tbody> </table>	Frequency range (MHz)	Field Strength (uV/m)	30 - 88	100	88 - 216	150	216 - 960	200	Above 960	500	<input checked="" type="checkbox"/>
Frequency range (MHz)	Field Strength (uV/m)												
30 - 88	100												
88 - 216	150												
216 - 960	200												
Above 960	500												
Test Setup													
Procedure	<ol style="list-style-type: none"> 1. The EUT was switched on and allowed to warm up to its normal operating condition. 2. The test was carried out at the selected frequency points obtained from the EUT characterisation. Maximization of the emissions, was carried out by rotating the EUT, changing the antenna polarization, and adjusting the antenna height in the following manner: <ol style="list-style-type: none"> a. Vertical or horizontal polarisation (whichever gave the higher emission level over a full rotation of the EUT) was chosen. b. The EUT was then rotated to the direction that gave the maximum emission. c. Finally, the antenna height was adjusted to the height that gave the maximum emission. 3. A Quasi-peak measurement was then made for that frequency point. 4. Steps 2 and 3 were repeated for the next frequency point, until all selected frequency points were measured. 												
Remark	<p>The EUT was scanned up to 1GHz. Both horizontal and vertical polarities were investigated. The results show only the worst case.</p>												
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail												


Test Data Yes (See below) N/A

Test Plot Yes (See below) N/A

Test was done by Cipher at 10m chamber.

Radiated Emission Test Results (Below 1GHz)

Test specification		Below 1GHz	
Environmental Conditions:	Temp (°C):	26.1	Result
	Humidity (%)	47.5	
	Atmospheric (mbar):	1020	
	Mains Power:	110VAC, 60Hz	
	Tested by:	Cipher	
	Test Date:	08/02/2018	
Remarks:		802.15.4, 2440MHz	Pass




Quasi Max Measurement

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail
105.92	43.89	11.92	-24.41	31.4	Quasi Max	V	104	253	43.5	-12.10	Pass
794.53	19.82	15.48	-14.66	20.64	Quasi Max	V	297	303	46.0	-25.36	Pass
121.56	31.36	12.08	-22.89	20.56	Quasi Max	V	179	280	43.5	-22.94	Pass
30.58	17.29	11.12	-13.43	14.99	Quasi Max	V	201	343	40.0	-25.02	Pass
136.95	18.10	12.19	-23.33	6.96	Quasi Max	V	150	254	43.5	-36.54	Pass
200.92	14.41	12.63	-24.37	2.67	Quasi Max	V	195	220	43.5	-40.83	Pass

Note: Both horizontal and vertical polarities were investigated. The results above show only the worst case.

10.8 Radiated Spurious Emissions between 1GHz – 25GHz

Requirement(s):

Spec	Item	Requirement	Applicable
47CFR§15.247(d), RSS247(A8.5)	a)	For non-restricted band, In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB or 30dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, determined by the measurement method on output power to be used. Attenuation below the general limits specified in § 15.209(a) is not required <input type="checkbox"/> 20 dB down <input checked="" type="checkbox"/> 30 dB down	<input checked="" type="checkbox"/>
Test Setup			
Procedure	1. The EUT was switched on and allowed to warm up to its normal operating condition. 2. The test was carried out at the selected frequency points obtained from the EUT characterisation. Maximization of the emissions, was carried out by rotating the EUT, changing the antenna polarization, and adjusting the antenna height in the following manner: a. Vertical or horizontal polarisation (whichever gave the higher emission level over a full rotation of the EUT) was chosen. b. The EUT was then rotated to the direction that gave the maximum emission. c. Finally, the antenna height was adjusted to the height that gave the maximum emission. An average measurement was then made for that frequency point. 3. Steps 2 and 3 were repeated for the next frequency point, until all selected frequency points were measured.		
Remark	The EUT was scanned up to 40GHz. Both horizontal and vertical polarities were investigated. The results show only the worst case.		
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail		

Test Data Yes (See below) N/A

Test Plot Yes (See below) N/A


Test was done by Cipher at 10m chamber.

Restricted Band Measurement Plots:

802.15.4:



802.15.4-2402MHz



802.15.4-2480MHz

Radiated Emission Test Results (Above 1GHz)

Above 1GHz-25GHz- 802.15.4 - 2402MHz

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail
4804.01	67.32	4.10	-10.91	60.52	Peak Max	H	106	92	74	-13.48	Pass
7204.56	63.02	5.15	-7.73	60.44	Peak Max	H	100	160	74	-13.56	Pass
12007.28	44.81	6.38	-2.30	48.89	Peak Max	V	110	204	74	-25.11	Pass
16128.44	39.93	7.99	0.39	48.31	Peak Max	H	158	64	74	-25.69	Pass
4804.01	50.90	4.10	-10.91	44.10	Average Max	H	106	92	54	-9.90	Pass
7204.56	46.54	5.15	-7.73	43.96	Average Max	H	100	160	54	-10.04	Pass
12007.28	30.04	6.38	-2.30	34.12	Average Max	V	110	204	54	-19.88	Pass
16128.44	28.11	7.99	0.39	36.49	Average Max	H	158	64	54	-17.51	Pass

Above 1GHz-25GHz- 802.15.4 - 2440MHz

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail
4880.04	66.05	4.18	-11.03	59.19	Peak Max	H	101	51	74	-14.81	Pass
7321.55	58.12	5.15	-7.66	55.61	Peak Max	H	103	157	74	-18.39	Pass
12197.28	49.12	6.48	-2.12	53.49	Peak Max	H	100	218	74	-20.51	Pass
14642.96	46.00	7.34	-1.13	52.21	Peak Max	H	101	120	74	-21.79	Pass
4880.04	49.67	4.18	-11.03	42.81	Average Max	H	101	51	54	-11.19	Pass
7321.55	40.58	5.15	-7.66	38.07	Average Max	H	103	157	54	-15.93	Pass
12197.28	32.41	6.48	-2.12	36.78	Average Max	H	100	218	54	-17.22	Pass
14642.96	30.33	7.34	-1.13	36.54	Average Max	H	101	120	54	-17.46	Pass

Above 1GHz-25GHz- 802.15.4 - 2480MHz

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail
4961.20	65.81	4.25	-11.16	58.9	Peak Max	H	102	87	74	-15.10	Pass
7439.99	50.37	5.14	-7.58	47.93	Peak Max	H	113	334	74	-26.07	Pass
12399.86	45.43	6.53	-1.65	50.31	Peak Max	V	153	11	74	-23.69	Pass
16672.22	39.68	8.06	1.77	49.52	Peak Max	H	101	262	74	-24.48	Pass
4961.20	48.54	4.25	-11.16	41.63	Average Max	H	102	87	54	-12.37	Pass
7439.99	34.16	5.14	-7.58	31.73	Average Max	H	113	334	54	-22.28	Pass
12399.86	28.69	6.53	-1.65	33.58	Average Max	V	153	11	54	-20.43	Pass
16672.22	27.85	8.06	1.77	37.69	Average Max	H	101	262	54	-16.31	Pass

Annex A. TEST INSTRUMENT

Instrument	Model	Serial #	Cal Date	Cal Cycle	Cal Due	In use
Conducted Emissions						
R & S Receiver	ESIB 40	100179	06/08/2018	1 Year	06/08/2019	<input checked="" type="checkbox"/>
CHASE LISN	MN2050B	1018	08/16/2017	1 Year	08/16/2018	<input checked="" type="checkbox"/>
Radiated Emissions						
Keysight EXA 44GHz Spectrum Analyzer	N9030B(PXA)	MY57140374	09/06/2017	1 Year	09/06/2018	<input checked="" type="checkbox"/>
Bi-Log antenna (30MHz~2GHz)	JB1	A030702	03/09/2018	2 Year	03/09/2020	<input checked="" type="checkbox"/>
Horn Antenna (1GHz~26GHz)	3115	100059	08/25/2017	1 Year	08/25/2018	<input checked="" type="checkbox"/>
Horn Antenna (26GHz~40GHz)	AH-840	101013	08/28/2017	1 Year	08/28/2018	<input checked="" type="checkbox"/>
Pre-Amp (30MHz~40GHz)	LPA-6-30	11140711	02/10/2018	1 Year	02/10/2019	<input checked="" type="checkbox"/>
RF Conducted Measurement						
Spectrum Analyzer	N9010A	10SL0180	01/18/2018	1 Year	01/18/2019	<input checked="" type="checkbox"/>

Annex B. SIEMIC Accreditation

Accreditations	Document	Scope / Remark
ISO 17025 (A2LA)		Please see the documents for the detailed scope
ISO Guide 65 (A2LA)		Please see the documents for the detailed scope
TCB Designation		A1 , A2 , A3 , A4 , B1 , B2 , B3 , B4 , C
FCC DoC Accreditation		FCC Declaration of Conformity Accreditation
FCC Site Registration		3 meter site
FCC Site Registration		10 meter site
IC Site Registration		3 meter site
IC Site Registration		10 meter site
EU NB		Radio & Telecommunications Terminal Equipment: EN45001 – EN ISO/IEC 17025
		Electromagnetic Compatibility: EN45001 – EN ISO/IEC 17025
Singapore iDA CB(Certification Body)	 	Phase I , Phase II
Vietnam MIC CAB Accreditation		Please see the document for the detailed scope
Hong Kong OFCA		(Phase II) OFCA Foreign Certification Body for Radio and Telecom
		(Phase I) Conformity Assessment Body for Radio and Telecom
Industry Canada CAB		Radio: Scope A – All Radio Standard Specification in Category I
		Telecom: CS-03 Part I, II, V, VI, VII, VIII

Japan Recognized Certification Body Designation		Radio: A1. Terminal equipment for purpose of calling Telecom: B1. Specified radio equipment specified in Article 38-2, Paragraph 1, Item 1 of the Radio Law
Korea CAB Accreditation		EMI: KCC Notice 2008-39, RRL Notice 2008-3: CA Procedures for EMI KN22: Test Method for EMI EMS: KCC Notice 2008-38, RRL Notice 2008-4: CA Procedures for EMS KN24, KN61000-4-2, -4-3, -4-4, -4-5, -4-6, -4-8, -4-11: Test Method for EMS
Taiwan NCC CAB Recognition		Radio: RRL Notice 2008-26, RRL Notice 2008-2, RRL Notice 2008-10, RRL Notice 2007-49, RRL Notice 2007-20, RRL Notice 2007-21, RRL Notice 2007-80, RRL Notice 2004-68 Telecom: President Notice 20664, RRL Notice 2007-30, RRL Notice 2008-7 with attachments 1, 3, 5, 6; President Notice 20664, RRL Notice 2008-7 with attachment 4
Taiwan BSMI CAB Recognition		CNS 13438
Japan VCCI		R-3083: Radiation 3 meter site C-3421: Main Ports Conducted Interference Measurement T-1597: Telecommunication Ports Conducted Interference Measurement
Australia CAB Recognition		EMC: AS/NZS CISPR 11, AS/NZS CISPR 14.1, AS/NZS CISPR22, AS/NZS 61000.6.3, AS/NZS 61000.6.4 Radio communications: AS/NZS 4281, AS/NZS 4268, AS/NZS 4280.1, AS/NZS 4280.2, AS/NZS 4295, AS/NZS 4582, AS/NZS 4583, AS/NZS 4769.1, AS/NZS 4769.2, AS/NZS 4770, AS/NZS 4771 Telecommunications: AS/ACIF S002:05, AS/ACIF S003:06, AS/ACIF S004:06 AS/ACIF S006:01, AS/ACIF S016:01, AS/ACIF S031:01, AS/ACIF S038:01, AS/ACIF S040:01, AS/ACIF S041:05, AS/ACIF S043.2:06, AS/ACIF S60950.1
Australia NATA Recognition		AS/ACIF S002, AS/ACIF S003, AS/ACIF S004, AS/ACIF S006, AS/ACIF S016, AS/ACIF S031, AS/ACIF S038, AS/ACIF S040, AS/ACIF S041, AS/ACIF S043.2