

## RF Exposure Considerations for the Fibar Group S.A. Flood Sensor

### **FCC ID: 2AA9MFGBHFS101**

The FCC requires that the calculated MPE for mobile equipment to be equal to or less than a given limit dependent on frequency at a distance of 20 cm from a device to the body of a user.

The transmitter in the Fibar Group S.A., Flood Sensor covers the 2402-2480MHz frequency band using Bluetooth Low Energy technology.

The following FCC Rule Parts and procedures are applicable:

Part 1.1310 – Radiofrequency radiation exposure limits

Part 2.1091 – Radiofrequency radiation exposure evaluation: mobile devices

KDB447498 D01 v06

Mobile and Portable Devices RF Exposure Procedures and Equipment Authorisation Policies

### **MPE calculation**

$$S = \text{EIRP} / (4 \pi R^2)$$

#### **Where**

S = Power density

EIRP = P x G

P = Maximum transmitter power

G = Antenna gain

R = distance to the centre of radiation of the antenna

---

**Fibar Group S.A.**  
FIBARO System Manufacturer  
ul. Lotnicza 1,  
60-421 Poznań

**KRS** (reg.no): 0000553265  
**NIP**: 7811858097

**Registered capital**: 1 182 100,00 PLN



Good Design  
2013



Founding  
Cedia Member



European Business  
Awards



Quality  
Service



CES Innovation  
Awards

**For the 2.4GHz band (Bluetooth Low Energy):**

**Values**       $S = 1.0 \text{ mW/cm}^2$  for General population uncontrolled exposure  
(FCC Part 1.1310, Table 1(B) Radiofrequency radiation exposure limits)

**$S = 1.0 \text{ mW/cm}^2$**

$P_{\text{max}} = 6.0 \text{ dBm (3.98 mW)}$

$G = 1 \text{ dBi (x1.26)}$

$R = 20 \text{ cm}$

**Calculation:**

$$S = PG/4 \pi R^2$$

$$S = 3.98 \times 1.26 / (12.56 \times (20)^2)$$

$$S = 5.01/5026$$

**$S = 0.0010 \text{ mW/cm}^2$**

**Conclusion**

This confirms compliance to the required FCC Part 1.1310 Radio frequency radiation exposure limit of  $1.0 \text{ mW/cm}^2$  at 20cm operation and, hence, meets the requirements of FCC rule part 2.1091(c) and KDB447498 D01 v06, section 7.1.