

RF Exposure Analysis

FCC ID: 2AA9MFGBHPB101

Analysis for FCC portable use

Standalone SAR test exclusion considerations are defined in KDB 447498 D01, Chapter 4.3.1 where the 1-g head or body and 10-g extremity SAR exclusion threshold is defined by the following formula:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] * [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

For the Fibar Button, the maximum conducted output power is +4.0dBm (2.5mW) including tune-up tolerance at 2.4GHz

Applying the above data using the given KDB 447498 D01 formula, and minimum separation distance of 5mm, the following results:

$$(2.5\text{mW} / 5 \text{ mm}) \times \sqrt{2.4 \text{ GHz}} = 0.77$$

(i.e.: ≤ 3.0 for 1-g SAR and ≤ 7.5 for 10-g extremity SAR)

Conclusion

This demonstrates the Fibar Button meets the criteria for 1-g head / body and 10-g extremity SAR test exemption.

Signature: Ratajczak Date: 03/04/2017

Fibar Group S.A.
ul. Lotnicza 1, 60-421 Poznań
NIP: 781 185 80 97 Regon: 301595664
KRS: 0000553265 (21)

Fibar Group S.A.
FIBARO System Manufacturer
ul. Lotnicza 1,
60-421 Poznań

KRS (REGON): 0000553265
NIP: 7811858097

Registered capital: 1 182 100,00 PLN



Good Design
2013



Founding
Company Member



European Business
Awards



Quality
Service



CES Innovation
Awards