



*Full*

# TEST REPORT

**No. 2014RFW0089**

*For*

**Client : VSN Technologies Inc. d/b/a VSN Mobil**

**Production : WCDMA Digital Mobile Phone**

**Model Name : V.35 / Nextel V.35**

**FCC ID: 2AA9WV1001**

**Model Number: V1001**

**Hardware Version: V01**

**Software Version: V01**

**Issued date: 2014-08-15**

**Note:**

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of ECIT Shanghai.

**Test Laboratory:**

ECIT Shanghai, East China Institute of Telecommunications

Add: 7-8F, G Area, No.668, Beijing East Road, Huangpu District, Shanghai, P. R. China

Tel: (+86)-021-63843300, E-Mail: [welcome@ecit.org.cn](mailto:welcome@ecit.org.cn)

**Revision Version**

<b>Report Number</b>	<b>Revision</b>	<b>Date</b>	<b>Memo</b>
2014RFW0089	00	2014-07-22	Initial creation of test report
2014RFW0089	01	2014-08-08	Second creation of test report
2014RFW0089	02	2014-08-14	Third creation of test report
2014RFW0089	03	2014-08-15	The fourth creation of test report

**CONTENTS**

<b>1.</b>	<b>TEST LABORATORY .....</b>	<b>5</b>
<b>1.1.</b>	<b>TESTING LOCATION .....</b>	<b>5</b>
<b>1.2.</b>	<b>TESTING ENVIRONMENT .....</b>	<b>5</b>
<b>1.3.</b>	<b>PROJECT DATA .....</b>	<b>5</b>
<b>1.4.</b>	<b>SIGNATURE .....</b>	<b>5</b>
<b>2.</b>	<b>CLIENT INFORMATION .....</b>	<b>6</b>
<b>2.1.</b>	<b>APPLICANT INFORMATION .....</b>	<b>6</b>
<b>2.2.</b>	<b>MANUFACTURER INFORMATION .....</b>	<b>6</b>
<b>3.</b>	<b>EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE) .....</b>	<b>7</b>
<b>3.1.</b>	<b>ABOUT EUT .....</b>	<b>7</b>
<b>3.2.</b>	<b>INTERNAL IDENTIFICATION OF EUT USED DURING THE TEST .....</b>	<b>7</b>
<b>3.3.</b>	<b>INTERNAL IDENTIFICATION OF AE USED DURING THE TEST .....</b>	<b>7</b>
<b>4.</b>	<b>REFERENCE DOCUMENTS .....</b>	<b>8</b>
<b>4.1.</b>	<b>REFERENCE DOCUMENTS FOR TESTING .....</b>	<b>8</b>
<b>5.</b>	<b>SUMMARY OF TEST RESULTS .....</b>	<b>9</b>
<b>5.1.</b>	<b>NOTES .....</b>	<b>10</b>
<b>5.2.</b>	<b>STATEMENTS .....</b>	<b>11</b>
<b>6.</b>	<b>TEST RESULT .....</b>	<b>12</b>
<b>6.1.</b>	<b>MAXIMUM OUTPUT POWER .....</b>	<b>12</b>
<b>6.1.1.</b>	<b>MAXIMUM PEAK OUTPUT POWER-CONDUCTED .....</b>	<b>12</b>
<b>6.1.2.</b>	<b>MAXIMUM AVERAGE OUTPUT POWER-CONDUCTED .....</b>	<b>13</b>
<b>6.2.</b>	<b>PEAK POWER SPECTRAL DENSITY .....</b>	<b>14</b>
<b>6.3.</b>	<b>OCCUPIED 6DB BANDWIDTH .....</b>	<b>19</b>
<b>6.4.</b>	<b>BAND EDGES COMPLIANCE .....</b>	<b>25</b>
<b>6.5.</b>	<b>TRANSMITTER SPURIOUS EMISSION-CONDUCTED .....</b>	<b>28</b>



---

6.6.	TRANSMITTER SPURIOUS EMISSION-RADIATED .....	39
7.	TEST EQUIPMENTS AND ANCILLARIES USED FOR TESTS .....	51
8.	TEST ENVIRONMENT .....	52
ANNEX A.	DEVIATIONS FROM PRESCRIBED TEST METHODS .....	54

## 1. Test Laboratory

### 1.1. Testing Location

Company Name:	ECIT Shanghai, East China Institute of Telecommunications
Address:	7-8F, G Area, No. 668, Beijing East Road, Huangpu District, Shanghai, P. R. China
Postal Code:	200001
Telephone:	(+86)-021-63843300
Fax:	(+86)-021-63843301

### 1.2. Testing Environment

Normal Temperature:	15-35°C
Extreme Temperature:	-10/+55°C
Relative Humidity:	20-75%

### 1.3. Project data

Project Leader:	Wangyaqiong
Testing Start Date:	2014-06-01
Testing End Date:	2014-08-14


### 1.4. Signature



**Wang Daming**  
(Prepared this test report)



**Liu Jianquan**  
(Reviewed this test report)



**Zheng Zhongbin**  
Director of the laboratory  
(Approved this test report)

## 2. Client Information

### 2.1. Applicant Information

Company Name: VSN Technologies Inc. d/b/a VSN Mobile  
Address: 1975 E. Sunrise Blvd. Suite 400, Fort Lauderdale FL  
Contact Person: Amit Verma  
Telephone: 954-609-4912  
Postcode: 33304

### 2.2. Manufacturer Information

Company Name: MOBIWIRE MOBILES (NINGBO) CO.,LTD  
Address: No.999,Dacheng East Road,Fenghua City,Zhejiang  
Contact Person: Xu linzhong  
Telephone: 0574 88916450  
Postcode: 315500

### 3. Equipment Under Test (EUT) and Ancillary Equipment (AE)

#### 3.1. About EUT

EUT Description	WCDMA Dual-Mode Digital Mobile Phone
Model name	V.35 / Nextel V.35
WLAN Frequency	2400MHz-2483.5MHz
WLAN Channel	Channel1-Channel11
WLAN type of modulation	802.11b:DSSS 802.11g/n: OFDM
Extreme Temperature	-10/+55°C
Nominal Voltage	3.7V
Extreme High Voltage	4.2V
Extreme Low Voltage	3.5V

Note: Photographs of EUT are shown in ANNEX A of this test report.

#### 3.2. Internal Identification of EUT used during the test

EUT ID*	SN or IMEI	HW Version	SW Version	Date of receipt
N01	354043060003102	V01	V01	2014-06-01

\*EUT ID: is used to identify the test sample in the lab internally.

#### 3.3. Internal Identification of AE used during the test

AE ID*	Description	SN
AE1	RF cable	---
AE2	---	---

\*AE ID: is used to identify the test sample in the lab internally.

## 4. Reference Documents

### 4.1. Reference Documents for testing

The following documents listed in this section are referred for testing.

Reference	Title	Version
FCC Part15	FCC CFR 47, Part 15,Subpart C: 15.205 Restricted bands of operation; 15.209 Radiated emission limits, general requirements; 15.247 Operation within the bands 902-928MHz, 2400-2483.5MHz, and 5725-5850MHz.	2014
ANSI 63.10	Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9KHz to 40GHz	2009

## 5. Summary of Test Results

A brief summary of the tests carried out is shown as following.

Measurement Items	Sub-clause of Part15C	Sub-clause of IC	Verdict
Maximum Peak Output Power	15.247(a)	/	P
Peak Power Spectral Density	15.247(e)	/	P
Occupied 6dB Bandwidth	15.247(d)	/	P
Band Edges Compliance	15.247(b)	/	P
Transmitter Spurious Emission-Conducted	15.247	/	P
Transmitter Spurious Emission-Radiated	15.247,15.209,	/	P
AC Powerline Conducted Emission	15.107,15.207	/	P

Please refer to part 5 for detail.

The measurements are according to ANSI 63.10.

Terms used in Verdict column

P	Pass, the EUT complies with the essential requirements in the standard.
NP	Not Perform, the test was not performed by ECIT.
NA	Not Applicable, the test was not applicable.
F	Fail, the EUT does not comply with the essential requirements in the standard.

## Test Conditions

Tnom	Normal temperature
Tmin	Low Temperature
Tmax	High Temperature
Vnom	Normal Voltage
Vmin	Low Voltage
Vmax	High Voltage
Hnom	Norm Humidity
Anom	Norm Air Pressure

For this report, all the test case listed above are tested under Normal Temperature and Normal Voltage, and also under norm humidity, the specific conditions as following:

Temperature	Tnom	22°C
Voltage	Vnom	3.7V
Humidity	Hnom	32%
Air Pressure	Anom	1010hPa

**5.1. Notes**

All reported tests were carried out on a sample equipment to demonstrate limited compliance with section 3.

The test results of this test report relate exclusively to the item(s) tested as specified in section 5.

The following deviation from, additions to, or exclusions from the test specifications have been made. See section 3.

**5.2. Statements**

The product name V.35 / Nextel V.35, supporting GSM/GPRS /WCDMA/HSDPA/HSUPA/HSPA+/BT/WLAN, manufactured by MOBIWIRE MOBILES (NINGBO) CO.,LTD is a new product for testing.

Note: All tests were carried out while using a fully battery charged.

ECIT has verified that the compliance of the tested device specified in section 5 of this test report is successfully evaluated according to the procedure and test methods as defined in type certification requirement listed in section 5 of this test report.

## 6. Test result

### 6.1. Maximum Output Power

Measurement Limit and method:

Standard	Limit(dBm)
FCC CRF 15.247(b)	< 30

The measurement is according to ANSI 63.10. EUT is operated in continuous transmitting mode.

Measurement Uncertainty:

Measurement Uncertainty	0.75dB
-------------------------	--------

#### 6.1.1. Maximum Peak Output Power-conducted

Measurement Results:

802.11b/g mode

Mode	Data Rate(Mbps)	Test Result(dBm)		
		2412MHz(Ch1)	2437MHz(Ch6)	2462MHz(Ch11)
802.11b	1	7.08	8.26	6.72
	2	6.53	7.98	6.18
	5.5	6.26	7.85	6.70
	11	6.45	7.40	6.59
802.11g	6	9.23	9.35	8.14
	9	9.20	9.41	8.52
	12	8.91	9.15	8.07
	18	8.74	9.51	8.10
	24	9.46	9.89	8.20
	36	9.69	9.99	8.91
	48	9.01	9.38	8.24
	54	9.24	9.32	8.64

The data rate 1Mbps and 36Mbps are selected as worse condition, and the following cases are performed with this condition.

**802.11n mode**

Mode	Data Rate(Index)	Teat Result(dBm)		
		2412MHz(Ch1)	2437MHz(Ch6)	2462MHz(Ch11)
802.11n(20MHz)	MCS0	5.84	5.24	5.76
	MCS1	5.92	5.36	5.17
	MCS2	5.43	6.13	5.08
	MCS3	5.89	6.08	5.02
	MCS4	9.47	9.75	8.97
	MCS5	9.74	10.08	9.07
	MCS6	9.32	9.07	9.00
	MCS7	9.32	9.98	8.94
802.11n(40MHz)	MCS0	/	/	/
	MCS1	/	/	/
	MCS2	/	/	/
	MCS3	/	/	/
	MCS4	/	/	/
	MCS5	/	/	/
	MCS6	/	/	/
	MCS7	/	/	/

The data rate MCS5 is selected as worse condition, and the following case are performed with this condition.

**6.1.2. Maximum Average Output Power-conducted**
**802.11b/g mode**

Mode	Test Result(dBm)		
	2412MHz(Ch1)	2437MHz(Ch6)	2462MHz(Ch11)
802.11b	4.72	4.82	3.65
802.11g	2.71	2.65	1.62

802.11n mode

Mode	Test Result(dBm)		
	2412MHz(Ch1)	2437MHz(Ch6)	2462MHz(Ch11)
802.11n(20MHz)	2.94	2.75	1.79
802.11n(40MHz)	/	/	/

**Conclusion: PASS**

## 6.2. Peak Power Spectral Density

**Measure Limit:**

Standard	Limit
FCC CFR Part 15.247(e)	< 8dBm/3 KHz

The measurement is according to ANSI 63.10 D01 DTS V03.

**Test procedures:**

1. Connect the EUT to spectrum analyzer.
2. Set RBW=3KHz, VBW=10KHz,span more than 1.5 times channel bandwidth.
3. Detector =peak, sweep time=auto couple, trace mode=max hold.

**Measurement Uncertainty:**

Measurement Uncertainty	0.75dB
-------------------------	--------

**Measurement Results:**
**802.11b/g mode**

Mode	Channel	Power Spectral Density(dBm/3kHz)		Conclusion
802.11b	1	Fig.1	-16.55	P
	6	Fig.2	-21.63	P
	11	Fig.3	-22.12	P
802.11g	1	Fig.4	-20.69	P
	6	Fig.5	-20.38	P
	11	Fig.6	-20.70	P


802.11n mode

Mode	Channel	Power Spectral Density(dBm/3kHz)		Conclusion
802.11n(20MHz)	1	Fig.7	-21.98	P
	6	Fig.8	-22.61	P
	11	Fig.9	-22.74	P

802.11g(40MHz)	1	/	/	P
	6	/	/	P
	11	/	/	P


**Conclusion: PASS**

Test graphs as below:




Date: 7.AUG.2014 20:08:26

**Fig.1 Power Spectral Density (802.1b,Ch1)**




Date: 14.AUG.2014 10:59:44

**Fig.2 Power Spectral Density (802.1b,Ch6)**




Date: 14.AUG.2014 11:00:20

**Fig.3 Power Spectral Density (802.1b,Ch11)**




Date: 7.AUG.2014 20:11:42

**Fig.4 Power Spectral Density (802.1g,Ch1)**




Date: 7.AUG.2014 20:12:14

**Fig.5 Power Spectral Density (802.1g,Ch6)**




Date: 7.AUG.2014 20:12:44

**Fig.6 Power Spectral Density (802.1g,Ch11)**




Date: 7.AUG.2014 20:13:24

**Fig.7 Power Spectral Density (802.1n-20MHz,Ch1)**



Date: 7.AUG.2014 20:14:09

**Fig.8 Power Spectral Density (802.1n-20MHz,Ch6)**



Date: 7.AUG.2014 20:14:35

**Fig.9 Power Spectral Density (802.1n-20MHz,Ch11)**

### 6.3. Occupied 6dB Bandwidth

**Measurement Limit:**

Standard	Limit(KHz)
FCC 47 CFR Part 15.247(a)	≥500

The measurement is according to ANSI 63.10.

**Measurement Uncertainty:**

Measurement Uncertainty	60.80Hz
-------------------------	---------

**Test procedures:**

1. Connect the EUT to spectrum analyzer.
2. Set RBW=100KHz, VBW=300KHz,span more than 1.5 times channel bandwidth.
3. Detector =peak, sweep time=auto couple, trace mode=max hold.

**Measurement Result:**
**802.11b/g mode**

Mode	Channel	Occupied 6dB Bandwidth(KHz)		Conclusion
802.11b	1	Fig.10	9.29	P
	6	Fig.11	9.86	P
	11	Fig.12	10.02	P
802.11g	1	Fig.13	16.57	P
	6	Fig.14	16.66	P
	11	Fig.15	16.66	P


**802.11n mode**

Mode	Channel	Occupied 6dB Bandwidth(KHz)		Conclusion
802.11n(20MHz)	1	Fig.16	16.66	P
	6	Fig.17	16.66	P
	11	Fig.18	16.66	P
802.11n(40MHz)	1	/		P
	6	/		P
	11	/		P

**Conclusion: PASS**


**Test graphs as below:**






Date: 4.JUN.2014 16:08:46

**Fig.12 Occupied 6dB Bandwidth (802.11b, Ch11)**




Date: 4.JUN.2014 16:12:44

**Fig.13 Occupied 6dB Bandwidth (802.11g, Ch1)**




Date: 4.JUN.2014 16:15:17

**Fig.14 Occupied 6dB Bandwidth (802.11g, Ch6)**




Date: 4.JUN.2014 16:18:01

**Fig.15 Occupied 6dB Bandwidth (802.11g, Ch11)**




Date: 4.JUN.2014 16:21:17

**Fig.16 Occupied 6dB Bandwidth (802.11n-20MHz, Ch1)**



Date: 4.JUN.2014 16:23:03

**Fig.17 Occupied 6dB Bandwidth (802.11n-20MHz, Ch6)**



Date: 4.JUN.2014 16:24:41

**Fig.18 Occupied 6dB Bandwidth (802.11n-20MHz, Ch11)**

## 6.4. Band Edges Compliance

### Measurement Limit:

Standard	Limited(dBc)
FCC 47 CFR Part 15.247(d)	>20

The measurement is according to ANSI 63.10.

### Measurement Uncertainty:

Measurement Uncertainty	0.75dB
-------------------------	--------

### Test procedures:

1. Connect the EUT to spectrum analyzer.
2. Set RBW=100KHz, VBW=300KHz.
3. Detector =peak, sweep time=auto couple, trace mode=max hold.

### 802.11b/g mode

Mode	Channel	Test Results	Conclusion
802.11b	1	Fig.19	P
	11	Fig.20	P
802.11g	1	Fig.21	P
	11	Fig.22	P


### 802.11n mode

Mode	Channel	Test Results	Conclusion
------	---------	--------------	------------

802.11n(20MHz)	1	Fig.23	P
	11	Fig.24	P
802.11(40MHz)	/	/	/
	/	/	/


**Conclusion: PASS**

**Test graphs as blew:**




Date: 4.JUN.2014 16:30:16

**Fig.19 Band Edges (802.11b, Ch1)**




Date: 4.JUN.2014 16:31:51

**Fig.20 Band Edges (802.11b, Ch11)**




Date: 4.JUN.2014 16:34:04

**Fig.21 Band Edges (802.11g, Ch1)**




Date: 4.JUN.2014 16:35:31

**Fig.22 Band Edges (802.11g, Ch11)**



Date: 4.JUN.2014 16:36:35

**Fig.23 Band Edges (802.11n-20MHz, Ch1)**



Date: 4.JUN.2014 16:37:36

**Fig.24 Band Edges (802.11b-20MHz, Ch11)**

## 6.5. Transmitter Spurious Emission-conducted

### Measurement Limit:

Standard	Limit
FCC 47 CFR Part 15.247(d)	20dB below peak output power in 100KHz bandwidth

This measurement is according to ANSI 63.10.

### Measurement Uncertainty:

Frequency Range	Uncertainty
30MHz ≤ f ≤ 2GHz	0.63
2GHz ≤ f ≤ 3.6GHz	0.82
3.6GHz ≤ f ≤ 8GHz	1.55
8GHz ≤ f ≤ 20GHz	1.86
20GHz ≤ f ≤ 22GHz	1.90
22GHz ≤ f ≤ 26GHz	2.20

**Test procedures:**

1. Connect the EUT to spectrum analyzer.
2. Set RBW=100KHz, VBW=300KHz.
3. Detector =peak, sweep time=auto couple, trace mode=max hold.

**Measurement Result:**

**802.11b/g mode**


Mode	Channel	Frequency Range	Test Results	Conclusion
802.11b	1	2.412GHz	Fig.25	P
		30MHz~26GHz	Fig.26	P
	6	2.437GHz	Fig.27	P
		30MHz~26GHz	Fig.28	P
	11	2.472GHz	Fig.29	P
		30MHz~26GHz	Fig.30	P
802.11g	1	2.412GHz	Fig.31	P
		30MHz~26GHz	Fig.32	P
	6	2.437GHz	Fig.33	P
		30MHz~26GHz	Fig.34	P
	11	2.472GHz	Fig.35	P
		30MHz~26GHz	Fig.36	P

**802.11n mode**

Mode	Channel	Frequency Range	Test Results	Conclusion
802.11n(20MHz)	1	2.412GHz	Fig.37	P
		30MHz~26GHz	Fig.38	P
	6	2.437GHz	Fig.39	P
		30MHz~26GHz	Fig.40	P
	11	2.472GHz	Fig.41	P
		30MHz~26GHz	Fig.42	P
802.11n(40MHz)	1	/	/	/
		/	/	/
	6	/	/	/
		/	/	/
	11	/	/	/
		/	/	/


**Conclusion: PASS**

Test graphs as below:




Date: 24.JUN.2014 14:02:13

**Fig.25 Conducted Spurious Emission (802.11b, Ch1)**




Date: 24.JUN.2014 14:03:27

**Fig.26 Conducted Spurious Emission (802.11b, Ch1, 30MHz~26GHz)**




Date: 24.JUN.2014 14:04:44

**Fig.27 Conducted Spurious Emission (802.11b, Ch6)**




Date: 24.JUN.2014 14:05:14

**Fig.28 Conducted Spurious Emission (802.11b, Ch6, 30MHz~26GHz)**




Date: 24.JUN.2014 14:06:18

**Fig.29 Conducted Spurious Emission (802.11b, Ch11)**




Date: 24.JUN.2014 14:06:53

**Fig.30 Conducted Spurious Emission (802.11b, Ch11, 30MHz~26GHz)**




Date: 24.JUN.2014 14:08:34

**Fig.31 Conducted Spurious Emission (802.11g, Ch1)**




Date: 24.JUN.2014 14:09:57

**Fig.32 Conducted Spurious Emission (802.11g, Ch1, 30MHz~26GHz)**




Date: 24.JUN.2014 14:11:09

**Fig.33 Conducted Spurious Emission (802.11g, Ch6)**




Date: 24.JUN.2014 14:12:09

**Fig.34 Conducted Spurious Emission (802.11g, Ch6, 30MHz~26GHz)**




Date: 24.JUN.2014 14:13:25

**Fig.35 Conducted Spurious Emission (802.11g, Ch11)**




Date: 24.JUN.2014 14:14:22

**Fig.36 Conducted Spurious Emission (802.11g, Ch11, 30MHz~26GHz)**




Date: 24.JUN.2014 14:16:42

**Fig.37 Conducted Spurious Emission (802.11n-20MHz, Ch1)**




Date: 24.JUN.2014 14:17:09

**Fig.38 Conducted Spurious Emission (802.11n-20MHz, Ch1, 30MHz~26GHz)**




Date: 24.JUN.2014 14:19:19

**Fig.39 Conducted Spurious Emission (802.11n-20MHz, Ch6)**




Date: 24.JUN.2014 14:19:39

**Fig.40 Conducted Spurious Emission (802.11n-20MHz, Ch6, 30MHz~26GHz)**



Date: 24.JUN.2014 14:21:06

**Fig.41 Conducted Spurious Emission (802.11n-20MHz, Ch11)**



Date: 24.JUN.2014 14:21:33

**Fig.42 Conducted Spurious Emission (802.11n-20MHz, Ch11, 30MHz~26GHz)**

## 6.6. Transmitter Spurious Emission-Radiated

### Measurement Limit:

Standard	Limit
FCC 47 CFR Part 15.247,15.205,15.209	20dB below peak output power

In addition, radiated emissions which fall in the restricted bands, as defined in 25.205(a), must also comply with the radiated emission limits specified in 15.209(a)(see 15.205(c)). The measurement is according to ANSI 63.10 and KDB558704.

### Limit in restricted band:

Frequency of emission(MHz)	Field strength(uV/m)	Field strength(dBuV/m)
30~88	100	40
88~216	150	43.5
216~960	200	46
Above 960	500	54

### Test condition:

Portable, small, lightweight, or modular devices that may be handheld, worn on the body, or placed on a table during operation shall be positioned on a nonconducting platform, the top of which is 80 cm above the reference ground plane. The preferred area occupied by the EUT arrangement is 1 m by 1.5 m, but it may be larger or smaller to accommodate various sized EUTs. For testing purposes, ceiling- and wall-mounted devices also shall be positioned on a tabletop (see also ANSI 63.10-2009 section 6.3.4 and 6.3.5). In making any tests involving handheld, body-worn, or ceiling-mounted equipment, it is essential to

recognize that the measured levels may be dependent on the orientation (attitude) of the three orthogonal axes of the EUT. Thus, exploratory tests as specified in 8.3.1 shall be carried out for various axes orientations to determine the attitude having maximum or near-maximum emission level.

The EUT was placed on a non-conductive table. The measurement antenna was placed at a distance of 3 meters from the EUT. During testing, the antenna height and the EUT azimuth were varied in order to identify the maximum level of emission from the EUT. This maximization process was repeated with the EUT positioned in each of its three orthogonal orientations.

Frequency of emission (MHz)	RBW/VBW	Sweep Times (s)
30~1000	100KHz/300KHz	5
1000~4000	1MHz/1MHz	15
4000~18000	1MHz/1MHz	40
18000~26500	1MHz/1MHz	20

### 802.11b/g mode

Mode	Channel	Frequency Range	Test Results	Conclusion
802.11b	Power	2.38GHz~2.45GHz	Fig.44	P
	Power	2.45GHz~2.5GHz	Fig.45	P
	1	30MHz~1GHz	Fig.46	P
		1GHz~3GHz	Fig.47	P
		3GHz~18GHz	Fig.48	P
802.11g	Power	2.38GHz~2.45GHz	Fig.49	P
	Power	2.45GHz~2.5GHz	Fig.50	P
	11	30MHz~1GHz	Fig.51	P
		1GHz~3GHz	Fig.52	P
		3GHz~18GHz	Fig.53	P

### 802.11n mode

Mode	Channel	Frequency Range	Test Results	Conclusion
802.11n(20MHz)	Power	2.38GHz~2.45GHz	Fig.54	P

	Power	2.45GHz~2.5GHz	Fig.55	P
	1	30MHz~1GHz	Fig.56	P
		1GHz~3GHz	Fig.57	P
		3GHz~18GHz	Fig.58	P
/	All channels	18GHz~26.5GHz	Fig.59	P

**Conclusion: PASS**

**Note:**

A "reference path loss" is established and  $A_{Rpi}$  is the attenuation of "reference path loss", and including the gain of receive antenna, the gain of the preamplifier, the cable loss.

$P_{Mea}$  is the field strength recorded from the instrument.

The measurement results are obtained as described below:

$$\text{Result} = P_{Mea} + A_{Rpi} = P_{Mea} + \text{Cable Loss} .$$

**802.11b mode**

**Ch1 30MHz~1GHz**

Frequency(MHz)	Result(dBuV/m)	ARpl (dB)	PMea(dBuV/m)	Polarity
34.982704	18	0.73	17.27	V
43.732324	22	0.86	21.14	V
100.659276	12.8	1.83	10.97	H
142.007892	2.7	2.23	0.47	H
199.994144	14.2	2.66	11.54	V

**Ch1 1GHz~3GHz**

Frequency(MHz)	Result(dBuV/m)	ARpl (dB)	PMea(dBuV/m)	Polarity
2692.197	52.1	15.87	36.23	V
2837.5304	52.6	16.66	35.94	H

**Ch1 3GHz~18GHz**

Frequency(MHz)	Result(dBuV/m)	ARpl (dB)	PMea(dBuV/m)	Polarity
10736.08667	45.4	10.42	34.98	V
15217.7654	47.6	13.65	33.95	V
16557.7826	49.3	14.32	34.98	V

802.11g

Ch11 30MHz~1GHz

Frequency(MHz)	Result(dBuV/m)	ARpl (dB)	PMea(dBuV/m)	Polarity
34.343788	17.3	0.73	16.57	V
35.428368	15.2	0.80	14.4	V
44.841476	20.9	0.92	19.98	V
100.272616	12.2	1.84	10.27	H

Ch11 1GHz~3GHz

Frequency(MHz)	Result(dBuV/m)	ARpl (dB)	PMea(dBuV/m)	Polarity
2784.7484	52.1	16.13	35.97	V
2818.3786	52.8	16.66	36.14	H

Ch11 3GHz~18GHz

Frequency(MHz)	Result(dBuV/m)	ARpl (dB)	PMea(dBuV/m)	Polarity
15811.53027	57.67	13.33	44.34	H
16225.6356	59.42	13.6	45.82	H
16278.35487	49.6	14.36	35.24	V

802.11n-20MHz

Ch1 30MHz~1GHz

Frequency(MHz)	Result(dBuV/m)	ARpl (dB)	PMea(dBuV/m)	Polarity
34.169844	10.8	0.73	10.07	V
99.959144	16.7	1.83	14.87	V
125.009556	11	2.00	9.00	V
200.018512	15.2	2.66	12.54	H
249.994512	19.8	3.23	16.57	H

Ch1 1GHz~3GHz

Frequency(MHz)	Result(dBuV/m)	ARpl (dB)	PMea(dBuV/m)	Polarity
2880.7474	53.7	16.58	37.12	V

2936.0168	53.5	16.57	36.93	H
-----------	------	-------	-------	---

### Ch1 3GHz~18GHz

Frequency(MHz)	Result(dBuV/m)	ARpl (dB)	PMea(dBuV/m)	Polarity
16280.48953	63.52	14.36	49.16	V
16948.44827	64.61	13.53	51.08	H
17573.97273	67.08	14.93	52.15	V

### All Ch 18GHz~26.5GHz

Frequency(MHz)	Result(dBuV/m)	ARpl (dB)	PMea(dBuV/m)	Polarity
21179.000000	45.48	6.97	38.51	V
22748.950000	41.63	3.05	38.58	H
23684.800000	41.59	3.05	38.54	H
24633.400000	40.05	3.05	37.00	V
25567.550000	43.01	2.90	40.11	H
26066.500000	42.06	2.90	39.16	V

Test graphs as below:







Fig.44 Radiated emission (Power): 802.11b, low channel



**Fig.45 Radiated emission (Power): 802.11b, high channel**



**Fig.46 Radiated Spurious Emission (802.11b,Ch1,30MHz~1GHz)**



**Fig.47 Radiated Spurious Emission (802.11b,Ch1,1GHz~3GHz)**






Fig.48 Radiated Spurious Emission (802.11b, Ch1, 3GHz~18GHz)




(peak)




(average)

Fig.49 Radiated emission (Power): 802.11g, low channel




**(peak)**




**(average)**


**Fig.50 Radiated emission (Power): 802.11g, high channel**




**Fig.51 Radiated Spurious Emission (802.11g,Ch11,30MHz~1GHz)**




**Fig.52 Radiated Spurious Emission (802.11g,Ch11,1GHz~3GHz)**



**Fig.53 Radiated Spurious Emission (802.11g,Ch11,3GHz~18GHz)**




**(peak)**




(average)


**Fig.54 Radiated emission (Power): 802.11n, low channel**




**Fig.55 Radiated emission (Power): 802.11n, high channel**




**Fig.56 Radiated Spurious Emission (802.11 n-20MHz,Ch1,30MHz~1GHz)**



**Fig.57 Radiated Spurious Emission (802.11 n-20MHz,Ch1,1GHz~3GHz)**



**Fig.58 Radiated Spurious Emission (802.11 n-20MHz,Ch1,3GHz~18GHz)**





## 7. Test Equipments and Ancillaries Used For Tests

The test equipments and ancillaries used are as follows.

### Conducted test system

No.	Equipment	Model	Serial Number	Manufacturer	Calibration Due date
1	Vector Signal Analyzer	FSQ26	101096	R&S	2015-07-06
2	DC Power Supply	ZUP60-14	LOC-220Z006	TDL-Lambda	2015-07-06

### Radiated emission test system

No.	Equipment	Model	Serial Number	Manufacturer	Calibration Due date
1	Universal Radio Communication Tester	CMU200	123126	R&S	2014-08-30
2	Test Receiver	ESCI	101235	R&S	2014-08-30
3	Test Receiver	ESU40	100307	R&S	2014-10-29
4	Trilog Antenna	VULB9163	19-162515	Schwarzbeck	2014-11-11
5	Double Ridged Guide Antenna	ETS-3117	135885	ETS	2017-05-05
6	2-Line V-Network	ENV216	101380	R&S	2014-10-30

7	Single Phase Harmonic & Flicker	DPA500N	V112610998 8	EM Test	2014-10-28
8	Multifunction AC/DC Power Source	Netwave7	V112610998 9	EM Test	2014-10-28
9	Audio Analyzer	UPV	101950	R&S	2014-08-30
10	Power Meter	NRP2	101804	R&S	2014-08-30
11	Signal Generator	SMB 100A	105563	R&S	2014-08-30
12	ESD Test Simulator	Dito	V112610998 2	EM Test	2014-10-31

### Anechoic chamber

Fully anechoic chamber by Frankonia German.

## 8. Test Environment

**Shielding Room1** (6.0 meters×3.0 meters×2.7 meters) did not exceed following limits along the conducted RF performance testing:

Temperature	Min. = 15 °C, Max. = 30 °C
Relative humidity	Min. = 30 %, Max. = 60 %
Shielding effectiveness	> 110 dB
Ground system resistance	< 0.5 Ω
Uniformity of field strength	Between 0 and 6 dB, from 80MHz to 3000 MHz

**Control room** did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 35 °C
Relative humidity	Min. =30 %, Max. = 60 %
Shielding effectiveness	> 110 dB
Electrical insulation	> 10 kΩ
Ground system resistance	< 0.5 Ω

**Fully-anechoic chamber1** (6.8 meters×3.08 meters×3.53 meters) did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 30 °C
Relative humidity	Min. = 30 %, Max. = 60 %
Shielding effectiveness	> 110 dB
Electrical insulation	> 10 kΩ
Ground system resistance	< 0.5 Ω
Uniformity of field strength	Between 0 and 6 dB, from 80MHz to 3000 MHz

**Fully-anechoic chamber2** (Tapered Section: 8.75 meters×3.66 meters×3.66 meters, Rectangular Section: 7.32 meters×3.97 meters×3.66 meters) did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 30 °C
Relative humidity	Min. = 35 %, Max. = 60 %
Shielding effectiveness	> 110 dB
Electrical insulation	> 10 kΩ
Ground system resistance	< 0.5 Ω
Uniformity of field strength	Between 0 and 6 dB, from 30MHz to 40000MHz

**ANNEX A. Deviations from Prescribed Test Methods**

No deviation from Prescribed Test Methods.

**\*\*\*\*\*End The Report\*\*\*\*\***