

Report No.: EED32I00275902 Page 1 of 9

RF Exposure Evaluation Report

Product: Wireless monitor

Trade mark : N/A

Model/Type reference: DXR-6

Serial Number : N/A

Report Number : EED32I00275902 **FCC ID** : 2AAAM-DXR-6BU

Date of Issue : Nov. 30 , 2016

47 CFR Part 1.1307(2015)

Test Standards : 47 CFR Part 1.1310(2015)

KDB447498D01v06

Test result : PASS

Prepared for:

Standard Merit Industrial Limited 2/A Harrison Court Stage 6, 10 Man Wan Road, Kowloon, Hong Kong

Prepared by:

Centre Testing International Group Co., Ltd. Hongwei Industrial Zone, Bao'an 70 District, Shenzhen, Guangdong, China

TEL: +86-755-3368 3668 FAX: +86-755-3368 3385

Tested By:

Tested By:

Reviewed by:

Report Seal Date:

Tom chen (Test Project)

Compiled by:

Kevin lan (Project Engineer)

In Yam Ap

Approved by:

Sheek Luo (Lab supervisor)

Nov. 30, 2016

Kevin yang (Reviewer)

Check No.: 2392185320

Hotline: 400-6788-333 www.cti-cert.com E-mail: info@cti-cert.com Complaint call: 0755-33681700 Complaint E-mail: complaint@cti-cert.com









Page 2 of 9

Report No.: EED32I00275902

2 Version

Version No.	Date	Description				
00	Nov. 30 , 2016	Original				
. /						
	(5)	(6.)	6,			

















































































Page 3 of 9

Report No.: EED32I00275902

Contents 3

	Pa	age
1 COVER PAGE		1
2 VERSION		
3 CONTENTS		3
4 GENERAL INFORMATION		
4.1 CLIENT INFORMATION		4 5 6
5 RF EXPOSURE EVALUATION		
5.1 RF EXPOSURE COMPLIANCE REQUIREMENT		7 7
PHOTOGRAPHS OF EUT CONSTRUCTIONAL DETAILS		<u>e</u>



















































4 General Information

4.1 Client Information

Applicant: Standard Merit Industrial Limited				
Address of Applicant: 2/A Harrison Court Stage 6, 10 Man Wan Road, Kowloon, Hong Kong				
Manufacturer:	Foshan Shunde Alford Electronics Co., Ltd,			
Address of Manufacturer:	Xinjian Industrial Park, Daliang, Shunde, Foshan City, Guangdong Province, China.			

4.2 General Description of EUT

Product Name:	Wireless monitor	
Model No.(EUT):	DXR-6	
Trade Mark:	N/A	
EUT Supports Radios application:	2410.875MHz ~2471.625MHz	(30

4.3 Product Specification subjective to this standard

Operation Frequency:	2410.875MHz ~2471.625MHz					
Modulation Technique:	Frequency Hopping Spread Spectrum(FHSS)					
Modulation Type:	GFSK					
Number of Channel:	19					
Hopping Channel Type:	Adaptive Frequency Hopping systems					
Camera Power Line:	270cm(Unshielded)					
Sample Type:	Mobile production	(20)				
Test Power Grade:	N/A	(0,)				
Test Software of EUT:	N/A					
Antenna Type:	Integral					
Antenna Gain:	0dBi					
Test Voltage:	AC 120V/60Hz, AC 240V/50Hz					
0 1 1 1 1 1 1 1	13.158dBm					
Conducted Peak Power:	The test data refer to the report EED32I00275901					
Sample Received Date:	Oct. 26, 2016	-0-				
Sample tested Date:	Oct. 26, 2016 to Nov. 30, 2016	(4)				
The tested sample and the	e sample information are provided by the client.					



Hotline: 400-6788-333 www.cti-cert.com E-mail: info@cti-cert.com Complaint call: 0755-33681700 Complaint E-mail: complaint@cti-cert.com



Report No.: EED32I00275902 Page 5 of 9

4.4 Test Location

All tests were performed at:

Centre Testing International Group Co., Ltd.

Hongwei Industrial Zone, Bao'an 70 District, Shenzhen, Guangdong, China 518101

Telephone: +86 (0) 755 3368 3668 Fax:+86 (0) 755 3368 3385

No tests were sub-contracted.

4.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

CNAS-Lab Code: L1910

Centre Testing International Group Co., Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC 17025: 2005 General Requirements) for the Competence of Testing and Calibration Laboratories..

A2LA-Lab Cert. No. 3061.01

Centre Testing International Group Co., Ltd. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

FCC-Registration No.: 886427

Centre Testing International Group Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files. Registration 886427.

IC-Registration No.: 7408A-2

The 3m Alternate Test Site of Centre Testing International Group Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for the performance of radiated measurements with Registration No. 7408A-2.

IC-Registration No.: 7408B-1

The 10m Alternate Test Site of Centre Testing International Group Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for the performance of radiated measurements with Registration No. 7408B-1.

NEMKO-Aut. No.: ELA503

Centre Testing International Group Co., Ltd. has been assessed the quality assurance system, the testing facilities, qualifications and testing practices of the relevant parts of the organization. The quality assurance system of the Laboratory has been validated against ISO/IEC 17025 or equivalent. The laboratory also fulfils the conditions described in Nemko Document NLA-10.

VCCI

The Radiation 3 &10 meters site of Centre Testing International Group Co., Ltd. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-4096.

Hotline: 400-6788-333 www.cti-cert.com E-mail: info@cti-cert.com Complaint call: 0755-33681700 Complaint E-mail: complaint@cti-cert.com









Report No.: EED32I00275902

Page 6 of 9

Main Ports Conducted Interference Measurement of Centre Testing International Group Co., Ltd. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: C-4563.

Telecommunication Ports Conducted Disturbance Measurement of Centre Testing International Group Co., Ltd. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: T-2146.

The Radiation 3 meters site of Centre Testing International Group Co., Ltd. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-758

4.6 Deviation from Standards

None.

4.7 Abnormalities from Standard Conditions

None.

4.8 Other Information Requested by the Customer

None.































































Report No.: EED32I00275902 Page 7 of 9

5 RF Exposure Evaluation

5.1 RF Exposure Compliance Requirement

5.1.1 Limits

According to FCC Part1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in part1.1307(b)

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm²)	Averaging time (minutes)						
(A) Limits for Occupational/Controlled Exposures										
0.3–3.0 3.0–30 30–300 300–1500 1500–100,000	614 1842/f 61.4	1.63 4.89/f 0.163	*(100) *(900/f²) 1.0 f/300 5	6 6 6 6 6						
(B) Limits for General Population/Uncontrolled Exposure										
0.3–1.34 1.34–30 30–300 300–1500 1500–100,000	614 824/f 27.5	1.63 2.19/f 0.073	*(100) *(180/f²) 0.2 f/1500 1.0	30 30 30 30						

A rough estimation of the expected exposure in power flux density on a given point can be made with the following equation:

$$S = \frac{P \times G}{4 \times \pi \times R^2}$$

Where:

S = power density

P = power input to the antenna

G = numeric gain of the antenna in the direction of interest relative to an isotropic radiator


R= distance to the centre of radiation of the antenna

EIRP = P*G

The antenna of the product, under normal use condition is at least 20 cm away from the body of the user. Warning statement to the user for keeping at least 20cm separation distance and the prohibition of operating to a person has been printed on the user's manual. Therefore, the S of the device is calculated with R=20cm, and if it is below the limit S, then we can conclude the device complies with the rules.

5.1.2 Test Procedure

Software provided by client enabled the EUT to transmit data at lowest, middle and highest channel individually.











Page 8 of 9

Report No.: EED32I00275902

5.1.3 EUT RF Exposure Evaluation

Antenna Gain: 0dBi

Output Power Into Antenna & RF Exposure Evaluation Distance:

2.0	Channel	Frequency (MHz)	Max Conducted Peak Output Power(dBm)	Gain (dBi)	EIRP (dBm)	EIRP (mW)	R (cm)	S (mW/cm²)	Limit (mW/cm²)	Result
9	Lowest	2410.875	13.158	0	13.158	20.69	20	0.004	1.0	Pass





























Report No.: EED32I00275902 Page 9 of 9

PHOTOGRAPHS OF EUT Constructional Details

Refer to Report No. EED32I00275901 for EUT external and internal photos.

*** End of Report ***

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of CTI, this report can't be reproduced except in full.













































































