

# Radio Exposure Evaluation Report

**FCC ID** : 2AAAS-CM09  
**Equipment** : Vivint Doorbell Camera Pro  
**Brand Name** : Vivint  
**Model Name** : CM09  
**Applicant** : Vivint, Inc.  
4931 N. 300 W., Provo, UT 84604 USA  
**Manufacturer** : Chicony Electronics Co.,Ltd.  
No.69, Sec. 2, Guangfu Rd., Sanchong Dist.  
New Taipei City 241 Taiwan  
**Standard** : 47 CFR FCC Part 2 Subpart J, section 2.1091

The product was received on Dec. 08, 2021, and testing was started from Dec. 29, 2021 and completed on Jan. 03, 2022. We, SPORTON INTERNATIONAL INC. Hsinhua Laboratory, would like to declare that the tested sample has been evaluated in accordance with the procedures given in 47 CFR FCC Part 2 Subpart J, section 2.1091 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. Hsinhua Laboratory, the test report shall not be reproduced except in full.



Approved by: Jackson Tsai

**SPORTON INTERNATIONAL INC. Hsinhua Laboratory**  
No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333411, Taiwan (R.O.C.)



## Table of Contents

**HISTORY OF THIS TEST REPORT .....3**

**1 GENERAL DESCRIPTION .....5**

1.1 Information.....5

1.2 Testing Location .....6

**2 MAXIMUM PERMISSIBLE EXPOSURE .....7**

2.1 Limit of Maximum Permissible Exposure .....7

2.2 MPE Calculation Method .....7

2.3 Calculated Result and Limit.....8

**Photographs of EUT V01**



### History of this test report

Report No.	Version	Description	Issued Date
FA1D0217	01	Initial issue of report	Jan. 25, 2022



### Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
2	-	Exposure evaluation	PASS	-

<b>Declaration of Conformity:</b>
The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.
<b>Comments and Explanations:</b>
None

Reviewed by: Ben Tseng  
Report Producer: Ann Hou



# 1 General Description

## 1.1 Information

### 1.1.1 EUT General Information

RF General Information			
Evaluation Mode	Frequency Range (MHz)	Operating Frequency (MHz)	Modulation Type
2.4GHz WLAN	2400-2483.5	2412-2462	802.11b: DSSS (DBPSK, DQPSK, CCK) 802.11g/n: OFDM (BPSK, QPSK, 16QAM, 64QAM)
5GHz WLAN	5150-5250 5250-5350 5470-5725 5725-5850	5180-5240 5260-5320 5500-5720 5745-5825	802.11a/n: OFDM (BPSK, QPSK, 16QAM, 64QAM) 802.11ac: OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM)
Bluetooth	2400-2483.5	2402-2480	LE: DSSS (GFSK)

### 1.1.2 Antenna Information

Ant.	Brand	Model Name	Antenna Type	Connector
0	Amphenol	CY5765-15-001-C	PIFA	I-PEX
1	Amphenol	CY5765-15-002-C	PIFA	I-PEX

Ant.	Port	Gain (dBi)		
		2.4G	5G	BT
0	0	2.66	4.12	2.66
1	1	0.05	4.41	-

Note 1: The EUT has two antennas.

#### For 2.4GHz function:

For IEEE 802.11 b/g/n mode (2TX/2RX)

Ant. 0 (port 0) and Ant. 1(port 1) could transmit/receive simultaneously.

#### For BT function:

For IEEE 802.15.1 Bluetooth mode (1TX/1RX)

Ant. 0 (port 0) could transmit/receive.

#### For 5GHz function:

For IEEE 802.11 a/n/ac mode (2TX/2RX)

Ant. 0 (port 0) and Ant. 1(port 1) could transmit/receive simultaneously.



## 1.2 Testing Location

<b>Test Lab. : Sporton International Inc. Hsinhua Laboratory</b>		
<input checked="" type="checkbox"/> Hsinhua (TAF: 3785)	<b>ADD:</b> No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333411, Taiwan (R.O.C.)	
	<b>TEL:</b> 886-3-327-3456	<b>FAX:</b> 886-3-327-0973
Test site Designation No. TW3785 with FCC.		
<input type="checkbox"/> Wen 33rd.St. (TAF: 3785)	<b>ADD:</b> No.14-1, Ln. 19, Wen 33rd St., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.)	
	<b>TEL:</b> 886-3-318-0787	<b>FAX:</b> 886-3-318-0287
Test site Designation No. TW0008 with FCC.		

## 2 Maximum Permissible Exposure

### 2.1 Limit of Maximum Permissible Exposure

(A) Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> , H  <sup>2</sup> or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f <sup>2</sup> )*	6
30-300	61.4	0.163	1.0	6
300-1500	-	-	F/300	6
1500-100,000	-	-	5	6

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> , H  <sup>2</sup> or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f <sup>2</sup> )*	30
30-300	27.5	0.073	0.2	30
300-1500	-	-	F/1500	30
1500-100,000	-	-	1.0	30

Note: f = frequency in MHz ; \*Plane-wave equivalent power density

### 2.2 MPE Calculation Method

The MPE was calculated at 20 cm to show compliance with the power density limit. The following formula was used to calculate the Power Density:

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \qquad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

**E** = Electric field (V/m)

**P** = RF output power (W)

**G** = EUT Antenna numeric gain (numeric)

**d** = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$

## 2.3 Calculated Result and Limit

Exposure Environment: General Population / Uncontrolled Exposure

### 2.4GHz WLAN

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up EIRP (dBm)	Tune-up EIRP (W)	Distance (cm)	S (mW/cm <sup>2</sup> )	S Limit (mW/cm <sup>2</sup> )
2.4G;G1D	2.66	22.43	25.09	0.50	25.59	0.36224	20	0.07207	1.00000
2.4G;D1D	2.66	22.15	24.81	0.50	25.31	0.33963	20	0.06757	1.00000

### 5GHz WLAN

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up EIRP (dBm)	Tune-up EIRP (W)	Distance (cm)	S (mW/cm <sup>2</sup> )	S Limit (mW/cm <sup>2</sup> )
5.2G;D1D	4.41	22.39	26.80	0.50	27.30	0.53703	20	0.10684	1.00000
5.3G;D1D	4.41	21.89	26.30	0.50	26.80	0.47863	20	0.09522	1.00000
5.6G;D1D	4.41	20.95	25.36	0.50	25.86	0.38548	20	0.07669	1.00000
5.8G;D1D	4.41	19.63	24.04	0.50	24.54	0.28445	20	0.05659	1.00000

### Bluetooth

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up EIRP (dBm)	Tune-up EIRP (W)	Distance (cm)	S (mW/cm <sup>2</sup> )	S Limit (mW/cm <sup>2</sup> )
2.4G;BT-LE	2.66	8.13	10.79	0.50	11.29	0.01346	20	0.00268	1.00000

—————THE END—————