

RF Exposure Report

Report No.: SABCKS-WTW-P21100725

FCC ID: 2AAAS-DS01

Test Model: DS01

Received Date: Oct. 22, 2021

Date of Evaluation: Dec. 10, 2021

Issued Date: Jan. 13, 2022

Applicant: Vivint, Inc.

Address: 4931 N. 300 W. Provo, UT 84604 USA

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Lin Kou Laboratories

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

Test Location: No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City
33383, TAIWAN

FCC Registration / 788550 / TW0003
Designation Number:



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.

Table of Contents

Release Control Record	3
1 Certificate of Conformity	4
2 RF Exposure	5
2.1 Limits for Maximum Permissible Exposure (MPE)	5
2.2 MPE Calculation Formula	5
2.3 Classification	5
3 Calculation Result of Maximum Conducted Power	6

Release Control Record

Issue No.	Description	Date Issued
SABCKS-WTW-P21100725	Original Release	Jan. 13, 2022

1 Certificate of Conformity

Product: Alarm System Display

Brand: Vivint, Inc.

Test Model: DS01

Sample Status: Engineering Sample

Applicant: Vivint, Inc.

Date of Evaluation: Dec. 10, 2021

Standards: FCC Part 2 (Section 2.1091)

References Test Guidance: KDB 447498 D01 General RF Exposure Guidance v06

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

Prepared by :

Vera Huang

Date: Jan. 13, 2022

Vera Huang / Specialist

Approved by :

Jeremy Lin

Date: Jan. 13, 2022

Jeremy Lin / Project Engineer

2 RF Exposure

2.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
Limits For General Population / Uncontrolled Exposure				
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f ²)*	30
30-300	27.5	0.073	0.2	30
300-1500	f/1500	30
1500-100,000	1.0	30

f = Frequency in MHz; *Plane-wave equivalent power density

2.2 MPE Calculation Formula

$$P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot r^2)$$

where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

r = distance between observation point and center of the radiator in cm

2.3 Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.

3 Calculation Result of Maximum Conducted Power

Band	Max AV Power (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
WLAN 2.4G	28.65	4.2	20	0.383	1
WLAN 5G (5180-5240 MHz)	23.72	4.7	20	0.138	1
WLAN 5G (5260-5320 MHz)	22.47	4.4	20	0.097	1
WLAN 5G (5500-5720 MHz)	22.50	4.2	20	0.093	1
WLAN 5G (5745-5825 MHz)	28.69	4.3	20	0.396	1
BT LE	9.34	4.2	20	0.004	1
DECT	19.32	2.9	20	0.033	1

Note:

- Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.
- The antenna information is listed as below.

Ant. No.	RF Chain No.	Brand	Model	Antenna Net Gain (dBi)	Frequency Range (GHz)	Antenna Type	Connector Type	Cable Length (mm)
1	0	WNC	81XKAB15.G69	3.8	2.4~2.4835	PIFA	ipex(MHF)	47
		WNC	81XKAB15.G69	3.3	5.15~5.25	PIFA	ipex(MHF)	47
		WNC	81XKAB15.G69	3.5	5.25~5.35	PIFA	ipex(MHF)	47
		WNC	81XKAB15.G69	3.6	5.47~5.725	PIFA	ipex(MHF)	47
		WNC	81XKAB15.G69	4.1	5.725~5.85	PIFA	ipex(MHF)	47
2	1	WNC	Display Pro	4.2	2.4~2.4835	PIFA	ipex(MHF)	123.5
		WNC	Display Pro	4.7	5.15~5.25	PIFA	ipex(MHF)	123.5
		WNC	Display Pro	4.4	5.25~5.35	PIFA	ipex(MHF)	123.5
		WNC	Display Pro	4.2	5.47~5.725	PIFA	ipex(MHF)	123.5
		WNC	Display Pro	4.3	5.725~5.85	PIFA	ipex(MHF)	123.5
3	0	WNC	81XKAB15.G70	4.2	2.4~2.4835 (BT)	Monopole	ipex(MHF)	129
4	0	WNC	Display Pro	2.9	1.9 (DECT)	PIFA	None (like solder)	N/A

- The above Antenna information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications, the laboratory shall not be held responsible.

Conclusion:

The formula of calculated the MPE is:

$$CPD1 / LPD1 + CPD2 / LPD2 + \dots \text{etc.} < 1$$

CPD = Calculation power density

LPD = Limit of power density

*WLAN 2.4G and 5G cannot transmit at same time.

*WLAN, BT LE, and DECT technology can transmit at same time.

$$\text{WLAN 2.4GHz} + \text{BT LE} + \text{DECT} = 0.383/1 + 0.004/1 + 0.033/1 = 0.42$$

$$\text{WLAN 5GHz} + \text{BT LE} + \text{DECT} = 0.396/1 + 0.004/1 + 0.033/1 = 0.433$$

Therefore the maximum calculations of above situations are less than the "1" limit.

---END---