

NOTE:

200 grams/mm² paper stock (0.22mm thick),
matte finish

Deliver creased and folded (see diagrams previous page)

SUPPORT INFO- FRONT/ OUTSIDE ARTWORK




JOIN THE COMMUNITY

Visit community.automatic.com to share ideas, issues and questions




REDUCE, REUSE, RECYCLE

This packaging is designed to be a reusable travel cup



PROTECT YOUR BATTERY

Unplug the adapter if you won't drive for more than 2 weeks




REPLACING AN ADAPTER?

Update the Automatic app and visit "Settings" to set up the new adapter

Welcome ▶
let's get started

INSTRUCTIONS - BACK/ INSIDE ARTWORK

TOP/ FRONT PAGE 63002-1 © 2014 Automatic Labs, Inc.



1 RELEASE THE ADAPTER

Press thumb tab on base plate and pull firmly



2 DOWNLOAD THE APP

Search for "Automatic" in the App Store or Google Play



3 LAUNCH THE APP

Do this before plugging the adapter into your car.



4 FOLLOW INSTRUCTIONS

Setup takes just a few minutes, no tools required



5 PLUG IN THE ADAPTER

Do this only when instructed; you'll be ready to go in no time!

63013-A © 2015 Automatic Labs, Inc.

BOTTOM/ BACK PAGE